

MHIPL/MCW/ENV/2020-21/149

25.11.2020

To,

The Additional Principal Chief Conservator of Forest (C),
Ministry of Environment, Forests and Climate Change,
Regional Office (SE Zone), 1st & 2nd Floor, HEPC Building,
No.34, Cathedral Garden Road, Nungambakkam,
CHENNAI-600 034.

Dear Sir,

Sub: Submission of Six Monthly Environmental Clearance Compliance Report of Mellacheruvu Limestone Mine (1.95 MTPA) – Reg.

Ref: EC Letter No. J-11015/113/2013 IA.II (M) dated 22nd July, 2015

With reference to the above subject, please find enclosed herewith Six Monthly Environmental Clearance Compliance status report for the period **April'2020 to September'2020** for our Mellacheruvu Limestone Mine, located at Mellacheruvu (V&M), Suryapet Dist., Telangana state.

Thanking you,

Yours faithfully,
for My Home Industries Private Limited



N. Srinivas Rao
Joint President (Works) - Unit Head

Encl: As above.



HALF-YEARLY ENVIRONMENTAL CLEARANCE COMPLIANCE REPORT (APR'20 - SEPT'20)

MELLACHERUVU LIMESTONE MINE - 1.95 MTPA, 141.644 Ha

EC: Letter No. J-11015/113/2013 IA.II (M) dated 22nd July, 2015

SPECIFIC CONDITIONS		
S.No.	Condition	Compliance Status
i.	The Project will implement and comply with all applicable safeguard measures as provided in OM No. Z-11013/57/2014-IA.II (M) dated 29 th October, 2014.	It is being implemented. Compliance status of the safeguard measures provided in OM No. Z-11013/57/2014-IA.II (M) dated 29 th October, 2014 is attached as Annexure-1 .
ii.	The Project proponent shall obtain Consent to Establish and Consent to Operate from the State Pollution Control Board and effectively implement all the conditions stipulated therein.	Consent to Operate has been obtained from the TSPCB vide order No. TSPCB / NLG / CFO / HO / HO / 2017-607, Dt: 12.05.2017 valid up to 30.06.2021.
iii.	The Mining Operations shall be restricted to above ground water table and it should not intersect the ground water table.	With the present mining operations, we have not encountered with ground water. All possible efforts will be made towards establishing measures to augment groundwater sources.
iv.	The loose solids should be kept separately from flowing water and flow of effluents to nearby areas outside the lease hold shall be prevented. The paved drains along with arrangements for Over Burden Dumps and their drainage may clearly depicted on a contour map of the mining area.	Limestone is out-cropped in the mining lease area and there is no topsoil or Over Burden dump generation.
v.	The project proponent shall ensure that no natural watercourse and /or water resources shall be obstructed due to any mining operations. Adequate measures shall be taken for conservation and protection of the 1 st and 2 nd order streams, emanating or passing through the mine lease during the course of mining operation.	There are no natural water streams that pass through the mine.
vi.	Topsoil, if any shall temporally be stored at earmarked site (s) only and it should not be kept unutilized for long. The topsoil shall be used for land reclamation and plantation.	Limestone is out-cropped in the mining lease area and there is no topsoil.
vii.	Appropriate safeguard measures shall be taken to ensure stability and drainage of dumps so that no solid waste/ debris flow into nallah.	There are no OB dumps in mine lease. However, measures taken to ensure no solid waste/ debris flow into nearby nallah.

SPECIFIC CONDITIONS		
S.No.	Condition	Compliance Status
viii.	The over burden (OB) generated during the mining operation shall be stacked at earmarked dump site(s) only and it should not be kept active for a long period of time and their phase – wise stabilization shall be carried out. Proper terracing of OB dumps(s) shall be carried out. The over burden dumps(s) shall be scientifically vegetated with suitable native species to prevent erosion and surface run off. In critical areas, use of geo textiles shall be undertaken for stabilization of the dumps. Monitoring and management of rehabilitated area should continue until the vegetation becomes self- sustaining. Compliance status should be submitted to the Ministry of Environment, Forest and Climate Change at its Regional Office Chennai on Six monthly basis.	Limestone is outcropped and there is no topsoil available / generated / removed.
ix.	Catch drains and siltation ponds of appropriate size should be constructed working pit. Temporary OB and mineral dumps to arrest flow of silt and sediment directly into adjoining River and other water bodies. The water so collected should be utilized for watering the mine area, roads, green belt development etc. The drains should be regularly desilted particularly after the monsoon and maintained properly.	A bund of 7.5m width is formed all along the lease boundary. The bund act as a barrier to arrest runoff from the mine. Runoff is being collected into mine sump which acts as sedimentation tank. Collected water is being pumped out for watering of mine area, roads, greenbelt development and for captive power plant requirement. The excess water is being pumped to pond located at NE corner of cement plant, which acts as rainwater harvesting pond.
x.	Dimension of retaining wall at toe of OB dump(s) and OB benches within the mine to check run-off and siltation should be based on the rainfall data.	There is no generation of OB in subject mine.
xi.	Plantation shall be raised in an specified area including a 7.5 m wide green belt in the safety Zone around the mining lease, OB Dumps (s), along the roads, etc. by planting the native species in consultation with the local DFO/Agriculture Department. In addition, Plantation shall also be raised in the backfilled and reclaimed area and around water body. The density of the tress should be around 1500 plants per Ha.	- Greenbelt belt is being developed in a phased manner with native plant species. Overall 18.67 Ha developed with greenbelt as on date. - Photographs of greenbelt are presented in Annexure-2.

SPECIFIC CONDITIONS		
S.No.	Condition	Compliance Status
xii.	Effective safeguard measures, such as regular water sprinkling shall be carried out in critical areas prone to air pollution and having high levels of particulate matter such as around crushing and screening plant, loading and unloading point and shall transfer points. Extensive water sprinkling shall be carried out on haul roads. It should be ensured that the Ambient Air Quality parameters conform to the norms prescribed by Central Pollution Control Board In this regard.	- Water spraying arrangement is provided at crusher dump hopper and bag filters are provided at all transfer points to control fugitive emissions. - Crusher is being operated with bag filter. - Water sprinkler system is provided on the haul roads. - Photos showing dust control measures are presented in Annexure – 3.
xiii.	Regular monitoring of water quality upstream and downstream of perennial nallahs falling in the impact zone shall be carried out and record of monitoring data should be maintained and submitted to Ministry of Environment, Forests and Climate Change, its regional office, Chennai, Central Groundwater Authority, Regional Director, Central Groundwater Board, State Pollution Control Board and Central Pollution Control Board.	There is no any perennial nallahs at Mellacheruvu Mine Lease area.
xiv.	Appropriate measures shall be taken for treatment of the upper catchment of the mine lease area.	Mine pit is formed which acts as settling tank.
xv.	The project authority should implement suitable conservation measures to augment ground water resources in the area in consultation with Regional Director, Central Groundwater Board.	Mine sump will help in recharging the ground water.
xvi.	Regular monitoring of ground water level and quality should be carried out in and around mine lease area by establishing a network of existing wells and Installing new piezometers during mining operation. The periodic monitoring [(at least 4 times a year in a year pre-monsoon (April/May), monsoon (August), post-monsoon (November) and winter (January) ; once in each season)]. Shall be carried out in consultation with the State Ground water Board/Central Ground water Authority and the data thus collected may be sent to the regularly to the Ministry of Environment , Forests & Climate Change and its Regional office Chennai, the Central Ground Water Authority and the Regional Director, Central Groundwater Board. If at any stage, it is observed that the groundwater table is getting depleted due to the mining activity; necessary corrective measures shall be carried out.	- Seasonal monitoring of ground water level and quality is being carried out. 9 no's of piezometers were established for ground water quality & levels monitoring. - Data of the same is being submitted to CGWA & CGWB on quarterly basis and also to MoEF&CC, RO, Chennai along with six monthly compliance report. Data of the same is presented in Annexure-4.

SPECIFIC CONDITIONS		
S.No.	Condition	Compliance Status
xvii.	The project proponent shall obtain necessary prior permission of the competent authorities for drawl of requisite quantity of water required for the project.	Necessary prior permission of the competent authorities will be obtained for drawl of water.
xviii.	Suitable rainwater harvesting measures on long term basis shall be planned and implemented in consultation with the Regional Director, Central Groundwater Board.	Mine sump will act as a rain water harvesting structure.
xix.	Appropriate mitigative measures should be taken to prevent pollution of nearby River in consultation with the State Pollution Control Board.	There is no any River near to the Mellacheruvu Limestone Mine lease area. Nearest river is Krishna River at a distance of 15 Kms from mine lease.
xx.	Vehicular emissions should be kept under control and regularly monitored. Measures shall be taken for maintenance of Vehicles used in mining operations and in transportation of mineral. The mineral transportation shall be carried out through the covered trucks only and the vehicles carrying the mineral shall be not be overloaded.	Vehicles are being well maintained. Outside agencies are utilized for maintenance of vehicles. Overloading of vehicles is not entertained.
xxi.	Controlled blasting should be practiced. The mitigative measures for control of ground vibrations and to arrest fly rocks and boulders should be implemented.	Blasting is being done only during day time according to the recommendations of DGMS. Ground vibrations and fly rock are being well controlled by using non-el bottom initiation detonators.
xxii.	Drills shall either be operated with dust extractors or equipped with water injection system.	Wet drilling is being practiced
xxiii.	Mineral handling areas shall be provided with the adequate number of high efficiency dust extraction system. Loading and unloading areas including all the transfer points should also have efficient dust control arrangements. These should be properly maintained and operated.	- Wet drilling is being practiced and water spraying is done on haul roads. Water spraying arrangement is provided at crusher dump hopper, water sprinklers are provided at loading and unloading points to control fugitive emissions. - Fixed water sprinklers are installed along haul roads where vehicular movement is comparatively high to abate dust generated from vehicular movement.
xxiv.	Sewage treatment plant shall be installed for the colony. ETP shall also be provided for the workshop and wastewater generated during the mining operation.	- Sewage Treatment Plant with capacity 400 KLD was installed in colony. - No waste water is generated during mining operations. - Waste water generated from vehicle washings are routed through Oil & Grease separator then followed by sedimentation trap and then to on land for vegetation. - Photographs of STP and vehicle washing system are depicted in Annexure -5

SPECIFIC CONDITIONS		
S.No.	Condition	Compliance Status
xxv.	Pre-placement medical examination and periodical medical examination of the workers engaged in the project shall be carried out and records maintained. For the purpose, schedule of health examination of the workers should be drawn and followed accordingly.	Pre-placement medical examination and periodical occupational health surveillance programme for the workers is being undertaken. Annual medical check-up conducted for 373 employees by third party M/s. Apple Diagnostic & Medical Centre, Hyderabad on 20 th & 21 st December, 2019. Records of the same are being maintained.
xxvi.	Regular monitoring of free silica in the dust will be carried out and records maintained. It shall be ensured that the levels of silica do not exceed the prescribed limits. The workers will be provided with personal protective measures to guard against inhaling silica dust.	Free silica is monitored on the regular basis. Reports are being maintained. Free silica content in the dust is well below the prescribed limits.
xxvii.	Provision shall be made for the housing of construction labour within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, mobile STP, safe drinking water, medical health care, crèche etc. The housing may be in the form of temporary structure to be removed after the completion of the project.	Not applicable. The subject mine is in operation
xxviii.	The project proponent should take all precautionary measures during mining operation for conservation and protection of endangered flora as well as endangered fauna in the study area. Action plan for conservation of flora and fauna shall be prepared and implemented in consultation with the state Forest and Wildlife Department. Necessary allocation of funds for implementation of the conservation plan shall be made and the funds so allocated shall be included in the project cost. Copy of action plan may be submitted to the ministry and its regional office at Chennai within 3 months.	No endangered flora and fauna found in the project area. Details has been submitted letter vide no. MHIL/ENV-HO/2015-16/0022 dated 01-08-2015 along with the certificate issued by the Forest Department, Nalgonda.

SPECIFIC CONDITIONS		
S.No.	Condition	Compliance Status
xxix.	The critical parameters such as RSPM(Particulate matter with size less than 10 micron i.e., PM10) and NOx in the ambient air within the impact zone, peak particle velocity at 300m distance or within the nearest habitation, whichever is closer shall be monitored periodically. Further, quality of discharged water shall also be monitored [(TDS, DO, PH and Total Suspended Solids (TSS))]. The monitored data shall be uploaded on the website of the company as well displayed on a display board at the project site at a suitable location near the main gate of the company in public domain. The Circular No.J-20012/1/2006-IA.II (M) dated 27.05.2009 issued by Ministry of Environment, Forest and Climate Change, which is available on the website of the ministry www.envfor.nic . Install also refer in this regard for its compliance.	All applicable critical parameters, mine sump water quality parameters are being monitored on regular basis and the results are displaying at the board provided at the main gate and in the company website (http://myhomeindustries.com/sustainability/environment/).
xxx.	A Final mine closure Plan along with details of corpus fund should be submitted to the Ministry of Environment, Forest and Climate Change 5 years in advance of final mine closure of approval.	Presently mine is active. Mine decommissioning plan will be submitted to MOEF&CC, 5 years in advance.
xxxi.	The project proponent shall undertake all the commitments made during the public hearing and effectively address the concerns raised by the locals, in the public hearing as well as during consideration of the project, while implementing the project.	Being implemented.

GENERAL CONDITIONS																				
i.	No change in mining technology and scope of working should be made without prior approval of the Ministry of Environment, Forests & Climate Change.	Opencast, Fully mechanized mining method is adopted. Prior approval will be obtained from MOEF&CC if there is any change in mining technology.																		
ii.	No change in the calendar plan including excavation, quantum of mineral and waste should be made	There is no change in the calendar plan. Limestone production details : <table border="1"> <thead> <tr> <th>Year</th><th>Proposed (MT)</th><th>Achieved (MT)</th></tr> </thead> <tbody> <tr> <td>2016 - 17</td><td>19,50,032</td><td>12,17,403</td></tr> <tr> <td>2017 - 18</td><td>19,50,036</td><td>15,72,351</td></tr> <tr> <td>2018 - 19</td><td>19,50,032</td><td>19,49,973</td></tr> <tr> <td>2019 - 20</td><td>19,50,032</td><td>14,90,000</td></tr> <tr> <td>2020-21 (Apr'20-Sept'20)</td><td>19,50,032</td><td>4,53,258*</td></tr> </tbody> </table>	Year	Proposed (MT)	Achieved (MT)	2016 - 17	19,50,032	12,17,403	2017 - 18	19,50,036	15,72,351	2018 - 19	19,50,032	19,49,973	2019 - 20	19,50,032	14,90,000	2020-21 (Apr'20-Sept'20)	19,50,032	4,53,258*
Year	Proposed (MT)	Achieved (MT)																		
2016 - 17	19,50,032	12,17,403																		
2017 - 18	19,50,036	15,72,351																		
2018 - 19	19,50,032	19,49,973																		
2019 - 20	19,50,032	14,90,000																		
2020-21 (Apr'20-Sept'20)	19,50,032	4,53,258*																		
iii.	Four ambient air quality-monitoring stations should be established in the core zone as well as in the buffer zone for RPM (Particulate Matter with size <10 microns i.e., PM ₁₀) and NO _x Monitoring. Location of the stations should be decided based on the meteorological data, topographical features and environmentally and ecologically sensitive targets in consultation with the State Pollution Control Board	8 no's of ambient air quality monitoring stations were established in the core zone as well as buffer zone covering all mine leases based on the meteorological data. - Ambient air quality parameters are getting monitored monthly by MoEF&CC recognized environmental laboratory. - Ambient quality monitoring data for period Apr'20-Sept'20 is presented in Annexure-6.																		
iv.	Data on ambient air RPM (Particulate Matter with size less than 10 microns i.e., PM ₁₀) and NO _x should be regularly submitted to the Ministry of Environment, Forest & Climate Change including its Regional Office at Chennai and the State Pollution Control Board / Central Pollution Control Board once in six months	Ambient air quality monitoring data is being regularly submitted to Regional Office of MOEF&CC along with the half yearly compliance report and monthly to TSPCB.																		
v.	Fugitive dust emissions from all the sources should be controlled regularly. Water spraying arrangement in haul roads, loading and unloading and at transfer points should be provided and properly maintained.	- Wet drilling is being practiced and water spraying is done on haul roads. Crusher is being operated with bag filter. Water spraying arrangement is provided at crusher dump hopper and unit bag filters are also provided at all transfer points of this section to control fugitive emissions. Water sprinkler system is provided on the haul roads. A separate tanker is dedicated for wetting muck pile. - Photos showing dust control measures implemented are presented in Annexure – 3																		

vi.	Measures should be taken for control of noise levels below 85 dBA in the work environment. Workers engaged in blasting and drilling operations, operations of HEMM, etc should be provided with ear plugs / muffs	- Workers exposed to high noise levels are being provided with earplugs and measures are being taken to reduce the ambient noise levels below the standards. - Dump truck cabins and other HEMM cabins are made dust/sound proof. - Below table showing details of noise levels: <table><tr><th rowspan="2">S. No</th><th rowspan="2">Location</th><th colspan="2">dB(A)</th></tr><tr><th>Apr-Jun'20</th><th>Jul-Sept'20</th></tr><tr><td>1.</td><td>LS Apron Feeder</td><td>76.8</td><td>72.4</td></tr><tr><td>2.</td><td>Drilling Point</td><td>80.2</td><td>78.8</td></tr><tr><td>3.</td><td>Showel Point</td><td>71.5</td><td>74.1</td></tr><tr><td>4.</td><td>Dumper Cabin</td><td>68.1</td><td>69.6</td></tr><tr><td>5.</td><td>Loading Area</td><td>75.9</td><td>76.3</td></tr></table>	S. No	Location	dB(A)		Apr-Jun'20	Jul-Sept'20	1.	LS Apron Feeder	76.8	72.4	2.	Drilling Point	80.2	78.8	3.	Showel Point	71.5	74.1	4.	Dumper Cabin	68.1	69.6	5.	Loading Area	75.9	76.3
S. No	Location	dB(A)																										
		Apr-Jun'20	Jul-Sept'20																									
1.	LS Apron Feeder	76.8	72.4																									
2.	Drilling Point	80.2	78.8																									
3.	Showel Point	71.5	74.1																									
4.	Dumper Cabin	68.1	69.6																									
5.	Loading Area	75.9	76.3																									
vii.	Industrial wastewater (workshop and wastewater from the mine) should be properly collected, treated so as to conform to the standards prescribed under GSR 422 (E) dated 19 th May, 1993 and 31 st December, 1993 or as amended from time to time. Oil and grease trap should be installed before discharge of workshop effluents	- There is no any waste water generation in Limestone mining. Waste water generated from vehicle washings are routed through Oil & Grease separator then followed by sedimentation trap and then to on land. For domestic wastewater (toilet wastewater) septic tank and soak pit are provided. - Photographs of vehicle washing system are depicted in Annexure -5.																										
viii.	Personnel working in dusty areas should wear protective respiratory devices and they should also be provided with adequate training and information on safety and health aspects. Occupational health surveillance program of the worker should undertake periodically to observe any contractions due to exposure to dust and take corrective measures, if needed.	- As a company policy all personal workings in Mine site are provided with PPE. Adequate training and information on safety and health aspects are regularly provided. - Annual medical check-up conducted for 373 employees by third party M/s. Apple Diagnostic & Medical Center, Hyderabad on 20th & 21st December, 2019. Records of the same are being maintained. The corrective measures will be taken, if needed.																										
ix.	A separate Environmental Management Cell with suitable qualified personnel should be set up under the control of a Senior Executive, who will report directly to the Head of the Organization	Environmental Management Cell is in place. Organisation structure for environmental management is depicted as Annexure -7																										
x.	The funds earmarked for environmental protection measures should be kept in separate account and should not be diverted for other purpose. Year wise expenditure should be reported to the Ministry of Environment, Forest and Climate Change and its Regional Office located at Chennai.	During the period Apr'20-Sept'20 MHIPL has spent ₹11.19 lakhs as recurring expenditure towards environmental protection measures in Mellacheruvu Mines.																										
xi.	The project authority should inform to the Regional Office located at Chennai regarding date of financial closures and final approval of the project by the concerned authorities and the date of start of land development work.	Duly Noted																										

xii.	The Regional Office of this Ministry located at Chennai shall monitor compliance of the stipulated conditions. The project authorities should extend full cooperation to the officer(s) of the Regional Office by furnishing the requisite data / information / monitoring reports	Requisite data / information / monitoring data are being submitted to Regional Office, MoEF&CC regularly. Full cooperation will be extended to visiting officers.
xiii.	The Project proponent shall submit six monthly reports on the status of compliance of the stipulated Environmental Clearance conditions including results of monitored data (both in hard copy as well as by email) to the Ministry of Environment, Forest & Climate Change, its Regional Office Chennai, the respective Zonal office of Central Pollution control Board the State Pollution Board. The Proponent shall upload the status of compliance of the Environmental Clearance conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the regional Office of the Ministry of Environment, Forest & Climate Change, Chennai, the respective Zonal Office of Central Pollution Control Board and State Pollution Control Board.	Six monthly reports being sent EC compliance status is sent to MoEF&CC RO, Chennai through email. Reports of the same are put in our company website (http://myhomeindustries.com/sustainability/environment/)
xiv.	A copy of clearance letter shall be sent by proponent to concerned Panchayat, Zila Parishad/Municipal Corporation, Urban Local Body and the local NGO, if any, from whom and suggestion / representation, If any, were received while processing the proposal. The clearance letter shall also be put on the website of the company by the proponent.	Submitted to local Panchayat with vide Lr. No. MHIPL / ENV / GEN / 2015 -16 / 4 dated 30 th July 2015.
xv.	The State Pollution Control Board should display a copy of the clearance letter at the Regional Office, District Industry Centre and Collector's Office / Tehsildar's Office for 30 days.	--
xvi.	The environmental statement for each financial year ending 31 st March in form-Vas is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the Environment (Protection) Rules, 1986, as amended subsequently, shall be put on the website of the company along with the status of compliance of Environmental Clearance conditions and shall also be sent to the Regional Office of the Ministry of Environment, Forest & Climate Change, Chennai by e-mail.	Environmental Statement (Form-V) for the year 2019-20 submitted vide letter No. Lr No. MHIPL/MCW/ENV/2020-21/105 dt. 07.09.2020.



My Home Industries Private Limited

Mellacheruvu (V & M)-508246, Suryapet Dist., Telangana State

xvii.	The project authorities should advertise at least in two local newspapers of the District or state widely circulated in which the project is located and one of which shall be in the vernacular language of the locality concerned within seven days of the issue of the clearance letter informing that the project has been accorded environmental clearance and a copy of the clearance letter is available with the State Pollution Control Board and may also be seen at web site of the Ministry of Environment , Forest and Climate Change at http://envfor.nic.in . and a copy of the same should be forwarded to the Regional Office at this Ministry located at Chennai.	Complied. Environment Clearance information was published in “Namaste Telangana” and “The New Indian Express” on 01.08.2015.
-------	--	--

Annexure- 1

Impact of mining activities on Habitations – Issues related to the mining Projects wherein Habitations and villages are the part of mine lease areas or Habitations and villages are surrounded by the mine lease area

No. Z-11013/57/2014-IA.II (M) Dated: 29th October, 2014

S. No.	CONDITION	CURRENT STATUS
A.	The Project Authority shall adopt Best Mining Practice for the given mining conditions. In the mining area, adequate number of check dams, retaining walls/structures, garland drains and settling ponds should be provided to arrest the wash-off with rain water in catchment area.	MHIPL is adopting best mining practices like controlled blasting, Wet drilling, Muck pile wetting, water sprinkling on haul roads and provided retaining walls, garland drains, settling ponds to arrest the wash off with rain water in catchment area wherever required.
B.	The natural water bodies and or streams which are flowing in and around the village should not be disturbed. The Water Table should be nurtured so as not to go down below the pre-mining period. In case of any water scarcity in the area, the Project Authorities have to provide water to the villagers for their use. A provision for regular monitoring of water table in open dug well located in village should be incorporated to ascertain the impact of mining over ground water table.	We have not disturbed any natural water bodies / streams of villages as our mine is located at a distance of more than 1.5 km from nearby village. We are monitoring the ground water level regularly ourselves & also by through MoEF&CC recognized laboratory with piezometers and open wells to ascertain impact on water table.
C.	The illumination and sound at night at project sites disturb the villages in respect of both human and animal population. Consequent sleeping disorders and stress may affect the health in the villages located close to mining operations. Habitations have a right for darkness and minimal noise levels at night. The Project Proponents (PPs) must ensure that the biological clock of the villagers is not disturbed by orienting the floodlights/ masks away from the villages and keeping the noise levels well within the prescribed limits for day/night hours.	The nearby village is about a distance of more than 1.5 kms from our mine lease, so there is no chance to occurrence of Illumination and sound effect to the villagers. Also, we are regularly monitoring the Illumination and sound level (Day/Night) by MoEF&CC recognized environment laboratory and found to be within permissible limits.
D.	The Project Authority shall make necessary alternative arrangements, where required, in consultation with the State Government to provide alternate areas for livestock grazing. In this context, Project Authority should implement the directions of the Hon'ble Supreme Court with regard to acquiring grazing land. The sparse trees on such grazing ground, which provide mid-day shelter from the scorching sun should be scrupulously guarded against felling, lest the cattle abandon the grazing ground or return home by noon.	Not applicable.
E.	Wherever blasting is undertaken as part of mining activity, the Project Authority shall carry out vibration studies well before approaching any such habitats or other buildings to evaluate the zone of influence and impact of blasting on	The nearby villages and hutments or buildings are more than 1.5 kms away from our mine lease, even though we are conducted ground vibration study through external agency and doing controlled blasting technique with shock

S. No.	CONDITION	CURRENT STATUS
	the neighborhood. Within 500 meters of such sites vulnerable to blasting vibrations, avoidance of use of explosives and adoption of alternative means of mineral extraction, such as ripper/dozer combination/rock breakers/surface miners etc. should be seriously considered and practiced wherever practicable. A provision for monitoring of each blast should be made so that the impact of blasting on nearby habitation and dwelling units could be ascertained. The covenant of lease deed under Rule 31 of MCR 1960 provides that no mining operations shall be carried out within 50 meters of public works such as public roads and buildings or inhabited sites except with the prior permission from the Competent Authority.	tube to reduce ground vibration and fly rock and regularly monitoring ground vibration of every blast and is within prescribed limits. No mining activity is carried within 50 meter from public road, buildings or inhabited sites.
F.	Main haulage road in the mine should be provided with permanent water sprinklers and other roads should be regularly wetted with water tankers fitted with sprinklers. Crusher and material transfer points should invariably be provided with Bag filters and or dry fogging system. Belt-conveyors should be fully covered to avoid air borne dust.	We have provided fixed water sprinklers along haul roads and wetting the other roads by water tankers mounted with jet pumps. Bag filters are provided at crusher to avoid the airborne dust and also material transported through closed conveyor belt system.
G.	The Project Authority shall ensure that the productivity of agricultural crops is not affected due to mining operations. Crop Liability Insurance Policy has to be taken by the PP as a precaution to compensate for any crop loss. The impact zone shall be 5km from the boundary of mine lease area for such insurance policy. In case, several mines are located in a cluster, the Associations of owners of the cluster mines, formed inter-alia, to sub-serve such an objective, shall take responsibility for securing such Crop Liability Policy.	We will ensure that the any productivity of agricultural crops is not affected due to our mining operations.
H.	In case any village is located within the mining leasehold which is not likely to be affected due to mining activities during the life of mine, the Expert Appraisal Committee (EAC) should consider the proposal of Environmental Clearance (EC) for reduced mining area. The Mining lease may be executed for the area for which EC is accorded. The mining plan may also be accordingly revised and required stipulations under the MMDR Act, 1957 and MCR, 1960 met.	Not applicable.
I.	Transportation of the minerals by road passing through the village shall not be allowed. A 'bypass' road should be constructed (say, leaving a gap of at least 200 meters) for the purpose of transportation of the minerals so that the impact of sound, dust and accidents	Transportation of mineral is being carried out within lease area. There is no village road is used for transportation.

S. No.	CONDITION	CURRENT STATUS
	could be mitigated. The PP shall bear the cost towards the widening and strengthening of existing public road network in case the same is proposed to be used for the Project. No road movement should be allowed on existing village road network without appropriately increasing the carrying capacity of such roads.	
J.	Likewise, alteration or re-routing of foot paths, pagdandies, cart roads, and village infrastructure/public utilities or roads (for purposes of land acquisition for mining) shall be avoided to the extent possible and in case such acquisition is inevitable, alternative arrangements shall be made first and then only the area acquired. In these types of cases, Inspection Reports by site visit by experts may be insisted upon which should be done through reputed Institutes.	Not Applicable.
K.	As CSR activities by Companies including the Mining Establishments has become mandatory up to 2 % of their financial turn-over, Socio Economic Development of the neighborhood Habitats could also be planned and executed by the PPs more systematically based on the 'Need based door to door survey' by established Social Institutes/Workers on the lines as required under TOR. "R&R Plan/compensation details for the Project Affected People (PAP) should be furnished. While preparing the R&R Plan, the relevant State/National Rehabilitation & Resettlement Policy should be kept in view. In respect of SCs/STs and other weaker sections of the society in the study area, a need based sample survey, famiy-wise, should be undertaken to assess their requirements, and action programs prepared and submitted accordingly, integrating the sectoral programs of line departments of the State Government. It may be clearly brought out whether the village located in the mine lease area will be shifted or not. The issues relating to shifting of Village including their R&R and socio-economic aspects should be discussed in the EIA report."	- During the period Apr'20 – Sept'20, under CSR activities, we have spent ₹. 62.93 Lakh. - R&R is not required as there is no village / habitation was relocated for this project.

Annexure –2

Photos Showing Greenbelt Development



Annexure - 3
Fugitive Dust Emissions Control Measures



Water sprinkling system &
Rubber curtains provided to LS crusher



Mechanical water sprinkling system at Haul roads



Wet Drilling & Personnel with PPEs



Water sprinkling on mine roads



Water sprinkling on muck pile



Water spraying through tankers in the mine roads

Annexure- 4

Piezometers, Ground Water Levels & Quality Monitoring



Piezometers & Ground Water Levels

ML Area	S. No.	Piezometer Location	Meters Below Ground Level	
			27.05.2020	30.08.2020
Choutapalli LSM	1.	Near Corner Pillar No. 2	5.70	3.32
	2.	Near Corner Pillar No. 29	24.82	22.04
	3.	Near SW Corner, At Corner Pillar No. 19	5.00	4.28
	4.	Near Canal 'X' Road	3.56	2.45
Mellacheruvu LSM	5.	Near SW Corner, Opp. to Suvarna Temple	11.00	3.32
	6.	Near SE Corner, Opp. to Suvarna Mine Boundary	7.43	3.93
	7.	In RS Rao Garage	12.34	4.74
Yepalamadhavaram LSM	8.	Beside Mines Office	19.78	15.17
	9.	SW corner (within Neem Plantation)	15.54	13.87

Ground Water Quality Monitoring (Apr'20 - Jun'20) – Piezometer Wells

Sl. No.	Parameter	Loc-1	Loc-2	Loc-3	Loc-4	Loc-5	Loc-6	Loc-7	Loc-8	Loc-9
1.	Color	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0
2.	Turbidity	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
3.	pH @ 25.8°C	7.60	7.52	7.36	7.30	7.69	7.82	7.62	7.66	7.44
4.	Electrical Conductivity	273	703	1458	1032	1234	1012	804	1059	1287
5.	Total Dissolved Solids	666	418	847	605	751	537	465	643	768
6.	Alkalinity as CaCO ₃	313	196	466	352	324	344	243	338	351
7.	Hardness as CaCO ₃	273	165	219	393	453	387	373	422	357
8.	Calcium as Ca	113	60	80	109	109	123	127	136	121
9.	Magnesium as Mg	2.55	3.65	0.02	29.28	43.86	19.32	13.1	19.93	13.24
10.	Chlorides as Cl ⁻	96	73	112	73	125	73	58	81	106
11.	Sulphates as SO ₄	114	45	83	52	102	51	67	50	128
12.	Nitrate as NO ₃	7.43	3.84	13.39	7.62	11.52	7.49	8.39	14.86	8.63
13.	Fluoride as F	1.26	0.98	1.04	0.96	0.89	0.56	0.77	0.91	1.31
14.	Iron as Fe	<0.1	0.12	0.20	<0.1	0.12	0.09	0.18	0.20	0.17
15.	Boron as B	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1
16.	Oil & Grease	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1
17.	Odor	agreeable	agreeable	agreeable	agreeable	agreeable	agreeable	agreeable	agreeable	agreeable
18.	Taste	agreeable	agreeable	agreeable	agreeable	agreeable	agreeable	agreeable	agreeable	agreeable
19.	Manganese as Mn	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.01
20.	Mercury (as Hg)	<0.001	<0.001	<0.001	<0.001	<0.001	<0.001	<0.001	<0.001	<0.001
21.	Nickel as Ni	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
22.	Total Coliform	Absent	Absent	Absent	Absent	Absent	Absent	Absent	Absent	Absent
23.	E-Coli	Absent	Absent	Absent	Absent	Absent	Absent	Absent	Absent	Absent



My Home Industries Private Limited

Mellacheruvu (V & M)-508246, Suryapet Dist., Telangana State

Ground Water Quality Monitoring (Jul'20 - Sept'20) – Piezometer Wells

S. No.	Parameter	Loc-1	Loc-2	Loc-3	Loc-4	Loc-5	Loc-6	Loc-7	Loc-8	Loc-9
1.	Color	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0
2.	Turbidity	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
3.	pH @ 25.8°C	7.93	7.36	7.80	7.68	7.47	7.65	7.28	7.53	7.82
4.	Electrical Conductivity	1032	664	1316	1172	1176	946	932	912	1098
5.	Total Dissolved Solids	599	393	197	684	713	499	566	525	653
6.	Alkalinity as CaCO ₃	282	184	419	398	308	320	297	275	298
7.	Hardness as CaCO ₃	246	155	197	444	430	360	371	421	303
8.	Calcium as Ca	102	56	72	123	104	114	120	144	103
9.	Magnesium as Mg	2.29	3.43	4.15	33.08	41.66	17.96	17.5	14.82	11
10.	Chlorides as Cl ⁻	86	69	101	82	119	68	71	66	90
11.	Sulphates as SO ₄	103	42	75	59	97	47	44	76	109
12.	Nitrate as NO ₃	6.68	3.6	12.05	8.61	10.94	6.96	13.07	9.48	7.10
13.	Fluoride as F	1.12	0.76	0.96	1.12	0.81	0.67	0.79	0.65	1.19
14.	Iron as Fe	<0.1	0.09	0.25	<0.1	0.10	0.13	0.17	0.15	0.21
15.	Boron as B	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1
16.	Oil & Grease	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
17.	Odor	agreeable	agreeable	agreeable	agreeable	agreeable	agreeable	agreeable	agreeable	agreeable
18.	Taste	agreeable	agreeable	agreeable	agreeable	agreeable	agreeable	agreeable	agreeable	agreeable
19.	Manganese as Mn		<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
20.	Mercury (as Hg)	<0.001	<0.001	<0.001	<0.001	<0.001	<0.001	<0.001	<0.001	<0.001
21.	Nickel as Ni	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
22.	Total Coliform	Absent	Absent	Absent	Absent	Absent	Absent	Absent	Absent	Absent
23.	E-Coli	Absent	Absent	Absent	Absent	Absent	Absent	Absent	Absent	Absent

Loc-1: CLM near Corner Pillar No. 29,
Loc-4: MLM South East Corner,
Loc-7: YLM near mine Office

Loc-2: CLM near Corner Pillar No. 2,
Loc-5: MLM near Suvrna Temple,
Loc-8: YLM near neem plantation

Loc-3: CLM near Corner Pillar No. 19
Loc-6: MLM near Lorry Garage
Loc-9: Canal X Road

Annexure -5

Sewage Treatment Plant in colony & Vehicle washing system at Mines



Sewage Treatment Plant at Colony



Vehicle Washing System

Ambient Air Quality

Annexure – 6

PM₁₀, µg/m³

S. No.	Location	Apr'20	May'20	June'20	Jul'20	Aug'20	Sept'20
1.	Mellacheruvu Mine Office	--	65.7	65.9	63.4	60.2	56.8
2.	Choutapalli Village	--	64.2	62.1	66.3	63.6	61.7
3.	Venkatapuram Village	--	59.7	60.5	64.9	59.1	66.3
4.	Raghunathpalem Village	--	56.4	57.9	55.4	58.8	63.6
5.	Mellacheruvu Village	--	67.9	66.1	69.7	67.2	71.4
6.	Yepalamadhavaram Village	--	67.3	63.9	65.7	61.9	58.3
7.	Bakkamanthulagudem Village	--	58.1	57.4	59.5	54.3	51.9
8.	Mallareddygudem Village	--	55.7	53.9	51.2	48.2	53.2

PM_{2.5}, µg/m³

S. No.	Location	Apr'20	May'20	June'20	Jul'20	Aug'20	Sept'20
1.	Mellacheruvu Mine Office	--	21.1	23.4	22.5	21.3	19.4
2.	Choutapalli Village	--	23.7	21.9	24.2	22.6	19.3
3.	Venkatapuram Village	--	18.7	19.5	22.5	19.2	24.7
4.	Raghunathpalem Village	--	16.3	15.9	14.7	16.4	22.9
5.	Mellacheruvu Village	--	26.9	24.8	27.3	25.9	29.1
6.	Yepalamadhavaram Village	--	25.9	22.8	24.1	20.8	18.9
7.	Bakkamanthulagudem Village	--	21.6	20.1	22.4	17.5	15.2
8.	Mallareddygudem Village	--	19.3	17.7	16.3	14.9	16.4

SO₂, µg/m³

S. No.	Location	Apr'20	May'20	June'20	Jul'20	Aug'20	Sept'20
1.	Mellacheruvu Mine Office	--	11.3	8.5	9.6	7.8	9.3
2.	Choutapalli Village	--	9.3	11.4	10.4	9.8	10.7
3.	Venkatapuram Village	--	12.6	9.5	8.2	10.9	8.5
4.	Raghunathpalem Village	--	10.4	8.9	7.8	6.5	7.2
5.	Mellacheruvu Village	--	13.1	12.6	11.4	12.6	11.6
6.	Yepalamadhavaram Village	--	7.7	9.1	11.2	10.1	7.6
7.	Bakkamanthulagudem Village	--	9.3	12.7	9.6	8.4	9.1
8.	Mallareddygudem Village	--	10.5	10.4	7.2	9.6	11.3

NO_x, µg/m³

S.No.	Location	Apr'20	May'20	June'20	Jul'20	Aug'20	Sept'20
1.	Mellacheruvu Mine Office	--	20.6	17.4	19.8	18.2	20.9
2.	Choutapalli Village	--	21.4	22.3	20.5	21.4	24.2
3.	Venkatapuram Village	--	24.9	20.9	17.6	22.6	18.4
4.	Raghunathpalem Village	--	19.1	16.7	15.3	17.9	19.7
5.	Mellacheruvu Village	--	21.5	23.8	21.5	24.7	25.2
6.	Yepalamadhavaram Village	--	23.6	20.9	22.8	19.7	21.8
7.	Bakkamanthulagudem Village	--	20.1	17.4	20.3	18.5	20.7
8.	Mallareddygudem Village	--	17.8	21.8	18.5	20.6	23.2

Annexure – 7

Organizational Setup for Environmental Management

