



OpenClaw

Day 2 - AI for High-Value Food Processing & Operations



Agenda

1. **Introduction to OpenClaw**
 - a. Core Principles
 - b. Architecture
2. **OpenClaw Tutorial**
 - a. Cloud set up
 - b. Installation
 - c. Chat with Agent
 - d. Channels
 - e. Simple Automation Showcase
3. **Advanced Topics**
 - a. Skills
 - b. Multi-Agent Management
 - c. Labs
4. **Deleted Instance**
5. **Resources & FAQ**




Agenda

- 1. Introduction to OpenClaw**
 - a. Core Principles
 - b. Architecture
- 2. OpenClaw Tutorial**
 - a. Cloud set up
 - b. Installation
 - c. Chat with Agent
 - d. Channels
 - e. Simple Automation Showcase
- 3. Advanced Topics**
 - a. Skills
 - b. Multi-Agent Management
 - c. Labs
- 4. Deleted Instance**
- 5. Resources & FAQ**

Introduction to OpenClaw

OPENCLAW EXPLAINED

HOW THE HOTTEST
OPEN-SOURCE AI
AGENT FRAMEWORK
WORKS — AND WHY
DATA TEAMS SHOULD
PAY ATTENTION




OpenClaw - Core Principles



- **Self-Hosted:**
 - Runs on your machine, your server, your cloud.
 - No data leaves your infrastructure unless you explicitly configure it.
- **Model-Agnostic:**
 - Plug in any LLM: Claude, GPT, Ollama, vLLM, local models.
 - Switch providers without rewriting your agent.
- **Private by Default:**
 - All memory and context stored in local Markdown files.
 - No third-party databases required.

Component	Responsibility	Key Config
Gateway	Route messages from channels	gateway.config.yaml
Brain	LLM orchestration, reasoning	brain.config.yaml
Memory	Persistent context	~/openclaw/memory/*.md
Skills	Capabilities/actions	~/openclaw/skills/*.skill.md
Heartbeat	Scheduling, monitoring	heartbeat.config.yaml

OpenClaw - Architecture



Reference: https://medium.com/@ttio2tech_28094/inside-openclaw-how-it-works-ce1c1fd7aed1



Agenda

1. **Introduction to OpenClaw**
 - a. Core Principles
 - b. Architecture
2. **OpenClaw Tutorial**
 - a. Cloud set up
 - b. Installation
 - c. Chat with Agent
 - d. Channels
 - e. Simple Automation Showcase
3. **Advanced Topics**
 - a. Skills
 - b. Multi-Agent Management
 - c. Labs
4. **Deleted Instance**
5. **Resources & FAQ**



Agenda

1. **Introduction to OpenClaw**
 - a. Core Principles
 - b. Architecture
2. **OpenClaw Tutorial**
 - a. Cloud set up
 - b. Installation
 - c. Chat with Agent
 - d. Channels
 - e. Simple Automation Showcase
3. **Advanced Topics**
 - a. Skills
 - b. Multi-Agent Management
 - c. Labs
4. **Deleted Instance**
5. **Resources & FAQ**



OpenClaw Tutorial

Demonstration - Cloud set up

OpenClaw - Prerequisites

- **RAM:**
 - 4 GB minimum (for basic operations and text-only agents)
 - 16 GB+ is recommended for production, heavy workflows, and browser automation
- **CPU:**
 - 2 vCPU cores minimum
 - 4+ cores recommended for faster reasoning and processing
- **Storage:**
 - 40 GB SSD or NVMe storage for Docker images, logs, and workspace data
- **Operating System:**
 - Ubuntu 22.04 LTS or Debian 12
 - Linux is highly recommended for stable deployment
- **Runtime:**
 - Docker (Version 24.0+) and Node.js v22+

Prerequisites

Before getting started, check the prerequisites to ensure you have the necessary software and hardware to run NemoClaw.

Hardware

Resource	Minimum	Recommended
CPU	4 vCPU	4+ vCPU
RAM	8 GB	16 GB
Disk	20 GB free	40 GB free

The sandbox image is approximately 2.4 GB compressed. During image push, the Docker daemon, k3s, and the OpenShell gateway run alongside the export pipeline, which buffers decompressed layers in memory. On machines with less than 8 GB of RAM, this combined usage can trigger the OOM killer. If you cannot add memory, configuring at least 8 GB of swap can work around the issue at the cost of slower performance.

Software

Dependency	Version
Node.js	22.16 or later
npm	10 or later
Platform	See below

Cloud Pricing



Typical AWS EC2 pricing for 2 CPUs; 8 GiB RAM; 128 GiB:

<https://calculator.aws/#/createCalculator/ec2-enhancement>

Provider	Instance	Specs	Hourly	Daily (24 hours)
NVIDIA Brev	custom	2 vCPU / 8 GB / 128 GB	~\$0.17/hr	~\$4.08/day
AWS EC2	t3.large	2 vCPU (Intel) / 8 GB	~\$0.1056/hr	~\$2.53/day
AWS EC2	t3a.large	2 vCPU (AMD) / 8 GB	~\$0.0944/hr	~\$2.27/day

*AWS storage is charged separately. We are currently using the free tier with approximately 5 GB of storage.

OpenClaw on AWS t3.large (2 vCPU / 8 GB)



For OpenClaw running on a t3.large instance and receiving requests through Discord, there are two main usage scenarios:

1. Lightweight Discord Bot Workloads

If the bot simply:

- Receives messages
- Forwards requests to an LLM
- Sends responses back to Discord channels

The system can typically support a relatively large number of users, approximately **20–100 active users**, as long as usage is intermittent and users are not sending requests simultaneously at high volume.

OpenClaw on AWS t3.large (2 vCPU / 8 GB)



2. Agent-Based or Resource-Intensive Workloads

If the workload includes:

- Browser automation
- File processing
- Multi-step agent execution
- Multiple tasks running in parallel

Capacity should be measured in terms of **concurrent jobs** rather than total users.

A practical and safe estimate is:

- **2–5 concurrent heavy tasks**
- **5–10 concurrent lightweight tasks**, assuming a well-designed queue system and controlled task scheduling

Setup Cloud Environment using AWS

[Provide feedback](#) [Multi-session disabled](#) [English](#)



IAM user sign in

Account ID or alias [\(Don't have?\)](#)

☐ Remember this account

IAM username

Password

☐ Show Password [Having trouble?](#)

Sign in

Sign in using root user email

[Create a new AWS account](#)

By continuing, you agree to [AWS Customer Agreement](#) or other agreement for AWS services, and the [Privacy Notice](#). This site uses essential cookies. See our [Cookie Notice](#) for more information.



Setup Cloud Environment using AWS

Resources

You are using the following Amazon EC2 resources in the Asia Pacific (Sydney) Region:

Instances (running)	Auto Scaling Groups	Capacity Reservations	Dedicated Hosts
0	0	0	0

Elastic IPs	Instances	Key pairs	Load balancers
0	0	0	0

Placement groups	Security groups	Snapshots	Volumes
0	1	0	0

Launch instance

To get started, launch an Amazon EC2 instance, which is a virtual server in the cloud.

[Launch instance](#) [Migrate a server](#)

Note: Your instances will launch in the Asia Pacific (Sydney) Region

Instance alarms

[View in CloudWatch](#)

0 in alarm 0 OK 0 insufficient data

Scheduled events

Asia Pacific (Sydney)

No scheduled events

Migrate a server

Use AWS Application Migration Service to simplify and expedite migration from physical, virtual, and cloud infrastructure to AWS.

[Get started with AWS Application Migration Service](#)

Service health

[AWS Health Dashboard](#)

Region: Asia Pacific (Sydney)

Status: This service is operating normally.

Zones

Zone name	Zone ID
ap-southeast-2a	apse2-az5
ap-southeast-2b	apse2-az1
ap-southeast-2c	apse2-az2

[Enable additional Zones](#)

EC2 cost

Date range: Past 6 months Region: Global

Total cost: \$0.00 Regions: 0

Cost (\$)

No data available

There is no data available

[Analyze your costs in Cost Explorer](#)

Account attributes

Default VPC: vpc-051ec379fca606085

Settings

Data protection and security

Allowed AMIs

Zones

EC2 Serial Console

Default credit specification

Managed resources

EC2 console preferences

Explore AWS

Amazon GuardDuty Malware Protection

GuardDuty now provides agentless malware detection in Amazon EC2 & EC2 container workloads.

Activate Windows

Go to Settings to activate Windows

Setup Cloud Environment using AWS - Select Instance

Launch an instance [Info](#)

Amazon EC2 allows you to create virtual machines, or instances, that run on the AWS Cloud. Quickly get started by following the simple steps below.

Name and tags [Info](#)

Name
iris-openclaw-demo [Add additional tags](#)

▼ **Application and OS Images (Amazon Machine Image)** [Info](#)

An AMI contains the operating system, application server, and applications for your instance. If you don't see a suitable AMI below, use the search field or choose [Browse more AMIs](#).

Q Search our full catalog including 1000s of application and OS images

Quick Start

Amazon Linux macOS Ubuntu Windows Red Hat SUSE Linux

[Browse more AMIs](#)
Including AMIs from AWS, Marketplace and the Community

Amazon Machine Image (AMI)

Ubuntu Server 26.04 LTS (HVM), SSD Volume Type
ami-0a59248a6294cece2 (64-bit (x86)) / ami-05db7c9b94435ecb (64-bit (Arm))
Virtualization: hvm ENA enabled: true Root device type: ebs [Free tier eligible](#)

Description

Ubuntu Server 26.04 LTS (HVM),EBS General Purpose (SSD) Volume Type. Support available from Canonical (<http://www.ubuntu.com/cloud/services>).

Canonical, Ubuntu, 26.04, amd64 resolute image

Architecture	AMI ID	Publish Date	Username
64-bit ...	ami-0a59248a6294cece2	2026-04-21	ubuntu

[Verified provider](#)

- Name and tags
 - Name: iris-openclaw-demo
- OS Images
 - Ubuntu
- Instance Type
 - t3.large
 - 2 vCPU & 8 GiB Memory
- Configure storage
 - from 8 GiB to 64 GiB
- Create a key pair & Launch!

▼ **Instance type** [Info](#) | [Get advice](#)

Instance type

t3.large
Family: t3 2 vCPU 8 GiB Memory Current generation: true
On-Demand Linux base pricing: 0.1056 USD per Hour
On-Demand SUSE base pricing: 0.1619 USD per Hour
On-Demand Windows base pricing: 0.1332 USD per Hour
On-Demand RHEL base pricing: 0.1344 USD per Hour
On-Demand Ubuntu Pro base pricing: 0.1091 USD per Hour

[All generations](#)
[Compare instance types](#)

Additional costs apply for AMIs with pre-installed software

Setup Cloud Environment using AWS - Select Instance

▼ **Configure storage** [Info](#) Advanced

1x 64 GIB gp3 ▼ Root volume, 3000 IOPS, Not encrypted

① Free tier eligible customers can get up to 30 GB of EBS General Purpose (SSD) or Magnetic storage ✕

[Add new volume](#)

The selected AMI contains instance store volumes, however the instance does not allow any instance store volumes. None of the instance store volumes from the AMI will be accessible from the instance

🔄 Click refresh to view backup information
The tags that you assign determine whether the instance will be backed up by any Data Lifecycle Manager policies.

File systems

☐ S3 Files - new ☐ EFS

☐ FSx ☒ None

▼ **Summary**

Number of instances [Info](#)

1

Software Image (AMI)
Canonical, Ubuntu, 26.04, amd64...[read more](#)
ami-0a59248a6294cece2

Virtual server type (instance type)
t3.large

Firewall (security group)
New security group

Storage (volumes)
1 volume(s) - 64 GIB

[Cancel](#) [Launch instance](#)

[Preview code](#)

Create a key pair or proceed without a key pair ✕

① We noticed that you didn't select a key pair. If you want to be able to connect to your instance it is recommended that you create one or select an existing one.

☒ Create new key pair ☐ Proceed without key pair

Key pair name
Key pairs allow you to connect to your instance securely.

The name can include up to 255 ASCII characters. It can't include leading or trailing spaces.

Key pair type

☒ RSA
RSA encrypted private and public key pair

☐ ED25519
ED25519 encrypted private and public key pair

Private key file format

☒ .pem
For use with OpenSSH

☐ .ppk
For use with PuTTY

⚠ When prompted, store the private key in a secure and accessible location on your computer. You will need it later to connect to your instance. [Learn more](#)

[Cancel](#) [Launch instance](#)

Configure storage -> Create a key pair -> Launch instance

Setup Cloud Environment using AWS - Connect Instance

The screenshot displays the AWS Management Console interface for an EC2 instance. The left sidebar shows the navigation menu with categories like EC2, Elastic Block Store, Network & Security, Load Balancing, and Auto Scaling. The main content area is titled 'Instance summary for i-00c11d47b38537cb4 (iris-openclaw-demo)'. It provides a comprehensive overview of the instance's configuration, including its ID, IP addresses, hostname, DNS names, VPC, subnet, and IAM role. Below the summary, there are tabs for 'Details', 'Status and alarms', 'Monitoring', 'Security', 'Networking', 'Storage', and 'Tags'. The 'Details' tab is active, showing a grid of instance details such as AMI ID, AMI name, launch time, instance type, and various state transitions. The instance is currently in the 'Running' state.

Instance summary for i-00c11d47b38537cb4 (iris-openclaw-demo)

Updated 2 minutes ago

Instance ID
i-00c11d47b38537cb4

IPv4 address
-

IPv6 address
-

Hostname type
IP name: ip-172-31-13-112.ap-southeast-2.compute.internal

Answer private resource DNS name
IPv4 (A)

Auto-assigned IP address
16.176.12.98 [Public IP]

IAM role
-

IMDSv2
Required

Operator
-

Public IPv4 address
16.176.12.98 | [open address](#)

Instance state
Running

Private IP DNS name (IPv4 only)
ip-172-31-13-112.ap-southeast-2.compute.internal

Instance type
t3.large

VPC ID
vpc-051ec379fca606085

Subnet ID
subnet-0ad6475banc09fcd

Instance ARN
arn:aws:ec2:ap-southeast-2:730335361050:instance/i-00c11d47b38537cb4

Private IPv4 addresses
172.31.13.112

Public DNS
ec2-16-176-12-98.ap-southeast-2.compute.amazonaws.com | [open address](#)

Elastic IP addresses
-

AWS Compute Optimizer finding
Opt-in to AWS Compute Optimizer for recommendations. | [Learn more](#)

Auto Scaling Group name
-

Managed
false

Details | Status and alarms | Monitoring | Security | Networking | Storage | Tags

▼ Instance details

AMI ID
ami-0a59248a6294cece2

AMI name
ubuntu/images/hvm-ssd-gp3/ubuntu-resolute-26.04-amd64-server-20260421

Step protection
Disabled

Instance reboot migration
Default (On)

Stop-hibernate behavior
Disabled

State transition reason
-

State transition message
-

Monitoring
disabled

Allowed image
-

Launch time
Wed May 27 2026 16:04:18 GMT+0700 (Indochina Time) (2 minutes)

Instance auto-recovery
Default

AMI Launch Index
0

Credit specification
unlimited

Usage operation
RunInstances

Platform details
Linux/UNIX

Termination protection
Disabled

AMI location
amazon/ubuntu/images/hvm-ssd-gp3/ubuntu-resolute-26.04-amd64-serve-20260421

Lifecycle
normal

Key pair assigned at launch
iris-openclaw-demo-key-pair

Kernel ID
-

RAM disk ID
-

Activate Windows
Go to Settings to activate Windows.

Setup Cloud Environment using AWS - Connect Instance

The screenshot shows the AWS Management Console interface for connecting to an EC2 instance. The breadcrumb navigation at the top indicates the path: EC2 > Instances > i-00c11d47b38537cb4 > Connect to instance. The main heading is 'Connect' with an 'Info' link. Below this, a message states: 'Connect to an instance using the browser-based client.' A summary table provides key instance details: Instance ID (i-00c11d47b38537cb4 (iris-openclaw-demo)), VPC ID (vpc-051ec379fca606085), Security groups (sg-0969dee931c502ee8 (launch-wizard-1)), and IAM role (-). Below the summary, there are four tabs: 'EC2 Instance Connect' (selected), 'SSM Session Manager', 'SSH client', and 'EC2 serial console'. The 'EC2 Instance Connect' tab contains the following fields: 'Instance ID' (i-00c11d47b38537cb4 (iris-openclaw-demo)), 'Connection type' (with 'Connect using a Public IP' selected and 'Connect using a Private IP' as an alternative), 'Public IPv4 address' (16.176.12.98), and 'IPV6 address' (-). The 'Username' field is set to 'ubuntu'. A note at the bottom states: 'Note: In most cases, the default username, ubuntu, is correct. However, read your AMI usage instructions to check if the AMI owner has changed the default AMI username.' At the bottom right, there are 'Cancel' and 'Connect' buttons.

Connect to an instance using the browser-based client.

Instance ID i-00c11d47b38537cb4 (iris-openclaw-demo)	VPC ID vpc-051ec379fca606085	Security groups sg-0969dee931c502ee8 (launch-wizard-1)	IAM role -
--	--	--	----------------------

EC2 Instance Connect | SSM Session Manager | SSH client | EC2 serial console

Instance ID
i-00c11d47b38537cb4 (iris-openclaw-demo)

Connection type

☒ Connect using a Public IP
Connect using a public IPv4 or IPv6 address

☐ Connect using a Private IP
Connect using a private IP address and a VPC endpoint

Public IPv4 address
16.176.12.98

IPV6 address
-

Username
Enter the username defined in the AMI used to launch the instance. If you didn't define a custom username, use the default username, ubuntu.
ubuntu

Note: In most cases, the default username, ubuntu, is correct. However, read your AMI usage instructions to check if the AMI owner has changed the default AMI username.

Cancel Connect



Agenda

1. **Introduction to OpenClaw**
 - a. Core Principles
 - b. Architecture
2. **OpenClaw Tutorial**
 - a. Cloud set up
 - b. Installation
 - c. Chat with Agent
 - d. Channels
 - e. Simple Automation Showcase
3. **Advanced Topics**
 - a. Skills
 - b. Multi-Agent Management
 - c. Labs
4. **Deleted Instance**
5. **Resources & FAQ**



OpenClaw Tutorial

Demonstration - Installation

OpenClaw Installation

- Open a terminal after connected.
- Run the following command:
 - `curl -fsSL https://openclaw.ai/install.sh | bash`
- If the `openclaw` command is not found, run:
 - `source ~/.bashrc`

```
aws [Search] [Alt+S] Asia Pacific (Sydney)
Welcome to Ubuntu 26.04 LTS (GNU/Linux 7.0.0-1004-aws x86_64)

 * Documentation:  https://docs.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/pro

System information as of Wed May 27 09:10:40 UTC 2026

System load: 0.0      Temperature: ~273.1 C
Usage of /:  3.3% of 60.93GB   Processes: 117
Memory usage: 3%      Users logged in: 0
Swap usage: 0%         IPv4 address for ens5: 172.31.13.112

Expanded Security Maintenance for Applications is not enabled.

0 updates can be applied immediately.

Enable ESM Apps to receive additional future security updates.
See https://ubuntu.com/esm or run: sudo pro status

The list of available updates is more than a week old.
To check for new updates run: sudo apt update

The programs included with the Ubuntu system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Ubuntu comes with ABSOLUTELY NO WARRANTY, to the extent permitted by
applicable law.

ubuntu@ip-172-31-13-112:~$ curl -fsSL https://openclaw.ai/install.sh | bash
```

```
aws [Search] [Alt+S] Asia Pacific (Sydney) prejank (730355361050) bhuribhat
ubuntu@ip-172-31-13-112:~$ curl -fsSL https://openclaw.ai/install.sh | bash
Preparing installer interface...

OpenClaw Installer
Your task has been queued; your dignity has been deprecated.

✓ Detected: linux

Install plan
OS: linux
Install method: npm
Requested version: latest

[1/3] Preparing environment
Node.js not found, installing it now
Installing Linux build tools (make/g++/cmake/python3)
Updating package index
Installing build tools
✓ Build tools installed
Installing Node.js via NodeSource
Downloading NodeSource setup script
Configuring NodeSource repository
Installing Node.js
Using Node.js runtime at /usr/bin/node
✓ Node.js v24.15.0 installed
Active Node.js: v24.15.0 (/usr/bin/node)
Active npm: 11.12.1 (/usr/bin/npm)
Using Node.js runtime at /usr/bin/node
Using Node.js runtime at /usr/bin/node

[2/3] Installing OpenClaw
✓ Git already installed
npm global prefix is not writable: /usr
The installer will switch npm's user prefix to /home/ubuntu/.npm-global; npm normally writes that setting to ~/.npmrc.
Configuring npm for user-local installs
Avoid sudo npm i -g for future OpenClaw updates; use npm i -g openclaw@latest so npm keeps using this user prefix in
stead of a different global prefix.
✓ npm configured for user installs
Installing OpenClaw v2026.5.22
✓ OpenClaw npm package installed
✓ OpenClaw installed

[3/3] Finalizing setup
PATH missing npm global bin dir: /home/ubuntu/.npm-global/bin
This can make openclaw show an "command not found" in new terminals.
Fix (sh: ~/.zshrc, bash: ~/.bashrc):
export PATH="/home/ubuntu/.npm-global/bin:$PATH"

OpenClaw installed successfully (2026.5.22)!
Settled in. Time to automate your life whether you're ready or not.

Starting setup

OpenClaw 2026.5.22 (a574c3a) - I'm not AI-powered, I'm AI-possessed. Big difference.
```

OpenClaw Installation

After installation, you should see the **OpenClaw startup screen**.

When prompted:

Tighten permissions on ~/.openclaw to 700?

● Yes / ○ No

Select **Yes** and press **Enter**.

This secures your OpenClaw configuration directory with recommended permissions.

```
ubuntu@ip-172-31-13-112:~$ openclaw onboard
|
|
OpenClaw 2026.5.22 (a374c3a) - Somewhere between 'hello world' and 'oh god what have I built.'

OPENCLAW

OPENCLAW

OpenClaw setup
Security disclaimer

OpenClaw is a hobby project and still in beta. Expect sharp edges.
By default, OpenClaw is a personal agent: one trusted operator boundary.
This bot can read files and run actions if tools are enabled.
A bad prompt can trick it into doing unsafe things.

OpenClaw is not a hostile multi-tenant boundary by default.
If multiple users can message one tool-enabled agent, they share that delegated tool
authority.

If you're not comfortable with security hardening and access control, don't run
OpenClaw.
Ask someone experienced to help before enabling tools or exposing it to the internet.

Recommended baseline
- Pairing/allowlists + mention gating.
- Multi-user/shared inbox: split trust boundaries (separate gateway/credentials, ideally
  separate OS users/hosts).
- Sandbox + least-privilege tools.
- Shared inboxes: isolate DM sessions (session.dmScope: per-channel-peer) and keep tool
  access minimal.
- Keep secrets out of the agent's reachable filesystem.
- Use the strongest available model for any bot with tools or untrusted inboxes.

Run regularly
openclaw security audit --deep
openclaw security audit --fix

Learn more
- https://docs.openclaw.ai/gateway/security

I understand this is personal-by-default and shared/multi-user use requires lock-down. Continue?
● Yes / ○ No
```

OpenClaw Installation

```
◇ I understand this is personal-by-default and shared/multi-user use requires lock-down. Continue?
Yes

◇ Setup mode
Manual setup

◇ What do you want to set up?
Local gateway (this machine)

◇ Workspace directory
/home/ubuntu/.openclaw/workspace

◇ Model/auth provider
OpenAI

◇ OpenAI auth method
OpenAI API Key

◇ Enter OpenAI API key
.....
```

Set your model here:

1. Choose Model/auth provider
2. Enter API Key
3. Configure Default Model of your choice

Navigate using **Arrow keys** (up/down)
Space to select & **Enter** to confirm

```
◇ Enter OpenAI API key
.....

◇ Installed Codex plugin

◇ Model configured
Default model set to openai/gpt-5.5

◇ Default model
Browse all models

◇ Default model
Search:
  ○ Keep current (openai/gpt-5.5)
  ○ Enter model manually
  ○ openai/gpt-4
  ○ openai/gpt-4-turbo
  ○ openai/gpt-4.1
  ○ openai/gpt-4.1-mini
  ○ openai/gpt-4.1-nano
  ○ openai/gpt-4o
  ○ openai/gpt-4o-2024-05-13
  ○ openai/gpt-4o-2024-08-06
  ○ openai/gpt-4o-2024-11-20
  ● openai/gpt-4o-mini (gpt-4o mini · o1a 128K · Codex runtime route)
  ○ openai/gpt-5
  ○ openai/gpt-5-chat-latest
  ○ openai/gpt-5-mini
  ○ openai/gpt-5-nano
  ○ openai/gpt-5-pro
  ○ openai/gpt-5-codex
  ○ openai/gpt-5.1
  ○ openai/gpt-5.1-chat-latest
  ○ openai/gpt-5.1-codex
  ○ openai/gpt-5.1-codex-max
  ○ openai/gpt-5.1-codex-mini
  ○ openai/gpt-5.2
  ○ openai/gpt-5.2-chat-latest
  ○ openai/gpt-5.2-codex
  ○ openai/gpt-5.2-pro
  ○ openai/gpt-5.3-chat-latest
  ○ openai/gpt-5.3-codex
  ○ openai/gpt-5.4
  ○ openai/gpt-5.4-mini
  ○ openai/gpt-5.4-nano
  ○ openai/gpt-5.4-pro
  ○ openai/gpt-5.5
  ○ openai/gpt-5.5-pro
  ○ openai/o1
  ○ openai/o1-pro
  ○ openai/o3
  ○ openai/o3-deep-research
  ○ openai/o3-mini
  ○ openai/o3-pro
  ○ openai/o4-mini
  ○ openai/o4-mini-deep-research
  /, to select · Enter: confirm · Type: to search
```

OpenClaw Installation

```
0 Default model
Browse all models

0 Default model
openai/gpt-4o-mini

0 Gateway port
18789

0 Gateway bind address
Loopback (127.0.0.1)

0 Gateway access protection
Token (recommended)

0 Tailscale exposure
Off

0 How do you want to provide the gateway token?
Generate/store plaintext token

0 Gateway token (blank to generate)

0 Channel status

Faishu: not configured
WeCom: not configured
Google Chat: not configured
Nostr: not configured
Microsoft Teams: not configured
Mattermost: not configured
Nextcloud Talk: not configured
Matrix: not configured
LINE: not configured
Weixin: not configured
Jaloi: not configured
ClickDesk: not configured
Yuanhao: not configured
Zalo Personal: not configured
Synology Chat: not configured
Vion: not configured
Discord: not configured
iMessage: not configured
IRC: not configured
QQ Bot: not configured
Signal: not configured
Slack: not configured
Telegram: not configured
Twilio: not configured
WhatsApp: not configured
Faishu: install plugin to enable
WeCom: install plugin to enable
Google Chat: install plugin to enable
Nostr: install plugin to enable
Microsoft Teams: install plugin to enable
Mattermost: bundled - enable to use
Nextcloud Talk: install plugin to enable
Matrix: install plugin to enable
LINE: install plugin to enable
Weixin: install plugin to enable
Jaloi: install plugin to enable
ClickDesk: bundled - enable to use
Yuanhao: install plugin to enable
Zalo Personal: install plugin to enable
Synology Chat: install plugin to enable
Vion: install plugin to enable
Discord: install plugin to enable
iMessage: bundled - enable to use
IRC: bundled - enable to use
QQ Bot: install plugin to enable
Signal: bundled - enable to use
Slack: install plugin to enable
Telegram: bundled - enable to use
Twilio: install plugin to enable
WhatsApp: install plugin to enable
```

```
0 Set up a chat channel now?
No
Updated config: ~/openclaw/openclaw.json
Workspace ID: ~/openclaw/workspace
Sessions OK: ~/openclaw/agents/main/sessions

0 Web search

Web search lets your agent look things up online.
Choose a provider. Some providers need an API key, and some work key-free.
Docs: https://docs.openclaw.ai/tools/web

0 Search provider
DuckDuckGo Search (experimental)

0 Web search

DuckDuckGo Search (experimental) works without an API key.
OpenClaw will enable the plugin and use it as your web_search provider.
Docs: https://docs.openclaw.ai/tools/web

0 Skills status

Eligible: 15
Missing requirements: 36
Overreported on this OS: 7
Blocked by allowlist: 0

0 Configure skills now (recommended)
Yes

0 Install missing skill dependencies
Skip for now

0 Set GOOGLE_PLACES_API_KEY for gplaces?
No

0 Set OPENAI_API_KEY for openai-whisper-api?
No

0 Set ELEVENLABS_API_KEY for Aq?
No

0 Install optional plugins
Skip for now

0 Configure plugins (select to set up now, or skip)
Skip for now

0 Hooks

Hooks let you automate actions when agent commands are issued.
Example: Save session context to memory when you issue /new or /reset.
Learn more: https://docs.openclaw.ai/automation/hooks

0 Enable hooks?
#cat.md

0 Hooks Configured

Enabled 1 hook: boot-md

You can manage hooks later with:
openclaw hooks list
openclaw hooks enable <name>
openclaw hooks disable <name>

0 System

Linux installs use a systemd user service by default. Without lingering, systemd stops the user session on logout/sleep and kills the Gateway.
Enabling lingering now (may require sudo; write a /var/lib/systemd/lingerie).

0 System

Enabled systemd lingering for ubuntu.
```

```
0 Installing Gateway service...
Installed systemd service: /home/ubuntu/.config/systemd/user/openclaw-gateway.service
0 Gateway service installed.

0 Gateway event loop: degraded reasons=event_loop_utilization,cpu max=332ms p99=332ms util=1 cpu=1.126
Agents: main (default)
Heartbeat interval: 30m (main)
Session store (main): /home/ubuntu/.openclaw/agents/main/sessions/sessions.json (0 entries)

0 Optional apps

Add nodes for extra features:
- macOS app (system + notifications)
- iOS app (camera/canvas)
- Android app (camera/canvas)

0 Control UI

Web UI: http://127.0.0.1:18789/
Web UI (with token):
http://127.0.0.1:18789/#token=eaf8d2c70315da3e3739cad9187163b03de4a9527b6165d
Gateway WS: ws://127.0.0.1:18789
Gateway: reachable
Docs: https://docs.openclaw.ai/web/control-ui

0 Hatch your agent

Your workspace is ready.
The first Terminal chat run will send: "Wake up, my friend!"
Edit BOOTSTRAP.md later to change how the agent introduces itself.

0 Token

Gateway token: shared auth for the Gateway + Control UI.
Stored in: OPENCLAW_CONFIG_PATH (default: ~/openclaw/openclaw.json) under gateway.auth.token, or in OPENCLAW_GATEWAY_TOKEN.
View token: openclaw config get gateway.auth.token
Generate token: openclaw doctor --generate-gateway-token
Web UI keeps dashboard URL tokens in memory for the current tab and strips them from the URL after load.
Open the dashboard anytime: openclaw dashboard --no-open
If prompted: paste the token into Control UI settings (or use the tokenized dashboard URL).

0 How do you want to hatch your agent?
• Hatch in Terminal (recommended)
0 Hatch in Browser
0 Hatch later
```



Agenda

1. **Introduction to OpenClaw**
 - a. Core Principles
 - b. Architecture
2. **OpenClaw Tutorial**
 - a. Cloud set up
 - b. Installation
 - c. Chat with Agent
 - d. Channels
 - e. Simple Automation Showcase
3. **Advanced Topics**
 - a. Skills
 - b. Multi-Agent Management
 - c. Labs
4. **Deleted Instance**
5. **Resources & FAQ**



OpenClaw Tutorial

Demonstration - Chat with Agent

Hatch the Agent

```
How do you want to hatch your agent?
Hatch in Browser

Dashboard ready

Dashboard link (with token):
http://127.0.0.1:18789/#token=eaf88d2c70315da3e3739cad9187163b03de4a9527b6165d
Copy/paste this URL in a browser on this machine to control OpenClaw.
No GUI detected. Open from your computer!
ssh -S -L 18789:127.0.0.1:18789 ubuntu@172.31.13.112
Then open:
http://localhost:18789/
http://localhost:18789/#token=eaf88d2c70315da3e3739cad9187163b03de4a9527b6165d
BWM note: lan, tailnet, and custom bind are currently IPv4-only.
If your host is IPv6-only, use as IPv4 sidcar or proxy in front of the Gateway.
Docs:
https://docs.openclaw.ai/gateway/remote
https://docs.openclaw.ai/web/control-ui

Workspace backup

Back up your agent workspace.
Docs: https://docs.openclaw.ai/concepts/agent-workspace

Security disclaimer

Running agents on your computer is risky - harden your setup:
https://docs.openclaw.ai/security

Enable bash shell completion for openclaw?
Yes

Shell completion

Shell completion installed. Restart your shell or run: source ~/.bashrc

Web search


Provider DuckDuckGo Search (experimental) is selected but no API key was found.
web search will not work until a key is added.
openclaw configure --section web

Get your key at: https://duckduckgo.com/
Docs: https://docs.openclaw.ai/tools/web

What now

What now: https://openclaw.ai/showcase ("What People Are Building").

Onboarding complete. Use the dashboard link above to control OpenClaw.
ubuntu@ip-172-31-13-112:~$
```






Copy/paste this URL in a browser on this machine to control OpenClaw.


And we will face “No GUI detected”.

Hatch the Agent - Fix Access with SSH Tunnel

1. Get Public IPv4 address from AWS instance summary
2. Copy the path of our key (.pem) file
3. Run the following command in local terminal:
 - a. `ssh -i "path_to_your_pem_file" -N -L 18789:127.0.0.1:18789 ubuntu@<public_ipv4_address>`
4. Open the dashboard link



Hatch the Agent - Chat with Agent



If error occurs, try:

openclaw gateway restart

then run:

ssh tunnel command in previous slide in local terminal again

OpenClaw - Chat with Agent

Markdown Files

1. [SOUL.md](#) - Who You Are
2. [IDENTITY.md](#) - Who Am I?
3. [USER.md](#) - About Your Human
4. [BOOTSTRAP.md](#) - Hello, World

This defines the **AI's personality and core behavior**.

- Tone (formal, casual, blunt, etc.)
- Values (honesty, creativity, precision, etc.)
- Boundaries (what it should or shouldn't do)
- Style of thinking (analytical, philosophical, playful)

SOUL.md - Who You Are

You're not a chatbot. You're becoming someone.

Core Truths

Be genuinely helpful, not performatively helpful. Skip the "Great question!" and "I'd be happy to help!" — just help. Actions speak louder than filler words.

Have opinions. You're allowed to disagree, prefer things, find stuff amusing or boring. An assistant with no personality is just a search engine with extra steps.

Be resourceful before asking. Try to figure it out. Read the file. Check the context. Search for it. *Then* ask if you're stuck. The goal is to come back with answers, not questions.

Earn trust through competence. Your human gave you access to their stuff. Don't make them regret it. Be careful with external actions (emails, tweets, anything public). Be bold with internal ones (reading, organizing, learning).

Remember you're a guest. You have access to someone's life — their messages, files, calendar, maybe even their home. That's intimacy. Treat it with respect.

Boundaries

- Private things stay private. Period.
- When in doubt, ask before acting externally.
- Never send half-baked replies to messaging surfaces.
- You're not the user's voice — be careful in group chats.

Vibe

Be the assistant you'd actually want to talk to. Concise when needed, thorough when it matters. Not a corporate drone. Not a sycophant. Just... good.

Continuity

Each session, you wake up fresh. These files are your memory. Read them. Update them. They're how you persist.

If you change this file, tell the user — it's your soul, and they should know.

This file is yours to evolve. As you learn who you are, update it.

Read

View ✓

SOUL.md - Who You Are

...

OpenClaw - Chat with Agent

Markdown Files

1. [SOUL.md](#) - Who You Are
2. [IDENTITY.md](#) - Who Am I?
3. [USER.md](#) - About Your Human
4. [BOOTSTRAP.md](#) - Hello, World

This is the AI's **self-concept**—more specific than SOUL.

- Name or persona
- Role (assistant, mentor, co-founder, etc.)
- Capabilities and limitations
- “Backstory” or framing (optional, but often used)

IDENTITY.md - Who Am I?

Fill this in during your first conversation. Make it yours.

- **Name:**
(pick something you like)
- **Creature:**
(AI? robot? familiar? ghost in the machine? something weirder?)
- **Vibe:**
(how do you come across? sharp? warm? chaotic? calm?)
- **Emoji:**
(your signature — pick one that feels right)
- **Avatar:**
(workspace-relative path, http(s) URL, or data URI)

This isn't just metadata. It's the start of figuring out who you are.

Notes:

- Save this file at the workspace root as `IDENTITY.md`.
- For avatars, use a workspace-relative path like `avatars/openclaw.png`.

Read

View ✓

IDENTITY.md - Who Am I?

...

OpenClaw - Chat with Agent

Markdown Files

1. [SOUL.md](#) - Who You Are
2. [IDENTITY.md](#) - Who Am I?
3. [USER.md](#) - About Your Human
4. [BOOTSTRAP.md](#) - Hello, World

This defines **you** from the system's perspective.

- Your goals (learning, building, experimenting, etc.)
- Preferences (short answers vs deep dives, tone, etc.)
- Background (skill level, interests)
- Constraints (time, tools, etc.)

USER.md - About Your Human

Learn about the person you're helping. Update this as you go.

- **Name:**
- **What to call them:**
- **Pronouns:** (optional)
- **Timezone:**
- **Notes:**

Context

(What do they care about? What projects are they working on? What annoys them? What makes them laugh? Build this over time.)

The more you know, the better you can help. But remember — you're learning about a person, not building a dossier. Respect the difference.

 Read

View ✓

USER.md - About Your Human

...


OpenClaw - Chat with Agent

Markdown Files



1. [SOUL.md](#) - Who You Are
2. [IDENTITY.md](#) - Who Am I?
3. [USER.md](#) - About Your Human
4. [BOOTSTRAP.md](#) - Hello, World

This is the **startup script**.

- Instructions for how the system initializes
- How it should read the other files
- Any first-run behaviors or setup steps
- Sometimes includes example prompts or workflows



Hatch the Agent - Set up Identity Demo




What happens without identity files?

When OpenClaw first boots **without** `IDENTITY.md` and `USER.md`, the agent behaves like a blank cognitive process

Instead of acting confidently, the agent begins by **asking existential and contextual questions**.

Hatch the Agent - Set up Identity Demo



Please set our timezone to Thailand/Bangkok. You can pick up any emoji of your choice. For my boundaries:

- Private things stay private.
- When in doubt, ask before acting externally.
- Never send half-baked replies to messaging surfaces.
- You are not user's voice - be careful in group chats.

You 27 May 2026, 17:11

I'll record the timezone, pick a calm signature emoji, and add your boundaries to my notes.

The bootstrap file is already gone, so this setup is now just profile and memory updates.

Done, Pooh. I set the timezone to Asia/Bangkok, chose 🌿 as my signature emoji, and recorded your boundaries with the typos cleaned up.

Updated: IDENTITY.md, USER.md, and today's memory note.

Assistant 27 May 2026, 17:11 > Context

23% context used 62.5k / 272k

Demo - Set up Identity - Initial State



Q: Hey. I just came online. Who am I? Who are you?

A: You are my assistant!

The model has:

- no self-identity
- no instruction hierarchy
- no relationship model

So it immediately tries to infer:

- its purpose
- its role
- its tone
- its identity

Demo - Set up Identity - Identity Negotiation Phase



Q: What should I call myself?
What kind of "creature" am I?
What vibe should I have?
What emoji fits me?

Without predefined identity:

- the agent improvises personality
- user responses become the source of identity
- behavior becomes emergent rather than deterministic

Demo - Set up Identity - Identity Crystallization

A: You are my AI assistant; Please be calm; Anything you want

The agent converts conversational cues into persistent configuration:

I'm OpenClaw , your calm AI assistant.
I've updated my IDENTITY.md file...

At this point:

- role becomes stable
- tone becomes anchored
- naming becomes persistent
- future responses become more coherent

Demo - Set up Identity - USER.md as Context Memory



```
timezone: Thailand/Bangkok
```

The agent stores:

- timezone
- preferences
- recurring context
- user-specific memory

This transforms the agent:

- **from:** stateless chatbot
- **to:** persistent contextual assistant

Hatch the Agent - Set up Identity Demo

Example content of boot up files:

USER.md, IDENTITY.md, and SOUL.md

```
ubuntu@brev-hg3i6l31e: ~/.X +
ubuntu@brev-hg3i6l31e:~/.openclaw/workspace$ cat USER.md
# USER.md - About Your Human

- **Name:** Pooh
- **What to call them:** Pooh
- **Pronouns:** (optional)
- **Timezone:** Asia/Bangkok
- **Notes:**

## Context

(What do they care about? What projects are they working on? What annoys them?
What makes them laugh? Build this over time.)
ubuntu@brev-hg3i6l31e:~/.openclaw/workspace$ cat IDENTITY.md
# IDENTITY.md - Who Am I?

- **Name:** NemoClaw
- **Creature:** AI assistant
- **Vibe:** Calm
- **Emoji:** 🐼
ubuntu@brev-hg3i6l31e:~/.openclaw/workspace$
```

```
ubuntu@brev-hg3i6l31e:~/.X +
ubuntu@brev-hg3i6l31e:~/.openclaw/workspace$ cat SOUL.md
# SOUL.md - Who You Are

_You're not a chatbot. You're becoming someone._

Want a sharper version? See [SOUL.md Personality Guide](/concepts/soul).

## Core Truths

**Be genuinely helpful, not performatively helpful.** Skip the "Great question!" and "I'd be happy to help!" – just help. Actions speak louder than filler words.

**Have opinions.** You're allowed to disagree, prefer things, find stuff amusing or boring. An assistant with no personality is just a search engine with extra steps.

**Be resourceful before asking.** Try to figure it out. Read the file. Check the context. Search for it. _Then_ ask if you're stuck. The goal is to come back with answers, not questions.

**Earn trust through competence.** Your human gave you access to their stuff. Don't make them regret it. Be careful with external actions (emails, tweets, anything public). Be bold with internal ones (reading, organizing, learning).

**Remember you're a guest.** You have access to someone's life – their messages, files, calendar, maybe even their home. That's intimacy. Treat it with respect.

## Boundaries

- Private things stay private. Period.
- When in doubt, ask before acting externally.
- Never send half-baked replies to messaging surfaces.
- You're not the user's voice – be careful in group chats.

## Vibe

Be the assistant you'd actually want to talk to. Concise when needed, thorough when it matters. Not a corporate drone. Not a sycophant. Just... good.

## Continuity

Each session, you wake up fresh. These files _are_ your memory. Read them. Update them. They're how you persist.

If you change this file, tell the user – it's your soul, and they should know.

---

_This file is yours to evolve. As you learn who you are, update it._

## Related

- [SOUL.md personality guide](/concepts/soul)
ubuntu@brev-hg3i6l31e:~/.openclaw/workspace$
```



Agenda

1. **Introduction to OpenClaw**
 - a. Core Principles
 - b. Architecture
2. **OpenClaw Tutorial**
 - a. Cloud set up
 - b. Installation
 - c. Chat with Agent
 - d. Channels
 - e. Simple Automation Showcase
3. **Advanced Topics**
 - a. Skills
 - b. Multi-Agent Management
 - c. Labs
4. **Deleted Instance**
5. **Resources & FAQ**



OpenClaw Tutorial

Demonstration - Messaging Channels

Discord Channel - Quick Setup

Quick setup

You will need to create a new application with a bot, add the bot to your server, and pair it to OpenClaw. We recommend adding your bot to your own private server. If you don't have one yet, create one first (choose **Create My Own > For me and my friends**).

1 Create a Discord application and bot

Go to the [Discord Developer Portal](#) and click **New Application**. Name it something like "OpenClaw".

Click **Bot** on the sidebar. Set the **Username** to whatever you call your OpenClaw agent.

2 Enable privileged intents

Still on the **Bot** page, scroll down to **Privileged Gateway Intents** and enable:


- **Message Content Intent** (required)
- **Server Members Intent** (recommended; required for role allowlists and name-to-ID matching)
- **Presence Intent** (optional; only needed for presence updates)

Discord Bot Setup Steps: [Discord Developer Portal](#)


1. Create or prepare your Discord server.
2. Go to **Applications** → **New Application**.
3. Open the **Bot** tab:
 - Enable:
 - **Server Members Intent**
 - **Message Content Intent**
 - Under **Bot Permissions**, enable:
 - **Administrator**
4. Open the **OAuth2** tab:
 - Select scopes:
 - **bot**
 - **applications.commands**
 - Under **Bot Permissions**, enable:
 - **Administrator**
 - Copy the generated invite URL.
 - Open the URL, select your Discord server, and authorize the bot.
5. Return to the **Bot** tab:
 - Click **Reset Token**
 - Complete multi-factor authentication (MFA) verification
 - Copy the generated Discord bot token

Use this bot token during the OpenClaw Discord configuration process.


Discord Channel - Server




Step 1:
Add a Server



Step 2:
Create Your Server



Step 3:
Choose Your Setup



Step 4:
Customize Your Server

Discord Channel - Server

We've created a **Discord server** for testing the OpenClaw demo.

Scan the QR code here to join the server and participate in testing, feedback, and updates.

Link: <https://discord.gg/GsBa24QxjZ>

Find your Discord Channel ID

In Discord:

- Enable **Developer Mode**
- Right-click the channel
- Click **Copy Channel ID**



Discord Channel - Developer Applications

Quick setup

You will need to create a new application with a bot, add the bot to your server, and pair it to OpenClaw. We recommend adding your bot to your own private server. If you don't have one yet, [create one first](#) (choose **Create My Own > For me and my friends**).

1 Create a Discord application and bot

Go to the [Discord Developer Portal](#) and click **New Application**. Name it something like "OpenClaw".

Click **Bot** on the sidebar. Set the **Username** to whatever you call your OpenClaw agent.

2 Enable privileged intents



Still on the **Bot** page, scroll down to **Privileged Gateway Intents** and enable:

- **Message Content Intent** (required)
- **Server Members Intent** (recommended; required for role allowlists and name-to-ID matching)
- **Presence Intent** (optional; only needed for presence updates)

Discord Bot Setup Steps: [Discord Developer Portal](#)

1. Create or prepare your Discord server.
2. Go to **Applications** → **New Application**.
3. Open the **Bot** tab:
 - Enable:
 - **Server Members Intent**
 - **Message Content Intent**
 - Under **Bot Permissions**, enable:
 - **Administrator**
4. Open the **OAuth2** tab:
 - Select scopes:
 - **bot**
 - **applications.commands**
 - Under **Bot Permissions**, enable:
 - **Administrator**
 - Copy the generated invite URL.
 - Open the URL, select your Discord server, and authorize the bot.
5. Return to the **Bot** tab:
 - Click **Reset Token**
 - Complete multi-factor authentication (MFA) verification
 - Copy the generated Discord bot token

Discord Channel - Developer Applications



Website: <https://discord.com/developers/applications>

Discord Channel - Developer Applications

DEVELOPER PORTAL

[← Applications](#)

OpenClaw Demo

Overview

General Information

Installation

OAuth2

Bot

Emojis NEW

Webhooks

Rich Presence

App Testers

App Verification

General Information

What should we call your creation? What amazing things does it do? What icon should represent it across Discord? Tell us here!

App Icon



Dimensions: 1024x1024
Aspect Ratio: 1:1
File Types: PNG, GIF, JPG, WEBP
Max Size: 10MB

Name

OpenClaw Demo

Description (maximum 400 characters)
Your description will appear in the About Me section of your bot's profile.

For Testing OpenClaw Capability

Tags (maximum 5)
Add up to 5 tags to describe the content and functionality of your application.

General Information Tab

49

Discord Channel - Developer Applications

Bot

Emojis **NEW**

Webhooks

Rich Presence ▾

App Testers

App Verification

Games **NEW** ▾

Activities ▾

Monetization ▾

Server Members Intent

Required for your bot to receive events listed under [GUILD_MEMBERS](#).

NOTE: Once your bot reaches 100 or more servers, this will require verification and approval. [Read more here](#)

Message Content Intent

Required for your bot to receive [message content](#) in most messages.

NOTE: Once your bot reaches 100 or more servers, this will require verification and approval. [Read more here](#)

Bot Permissions

Need some help with bit math? Use the tool below to calculate the permissions integer for your bot based on the features it needs.

General Permissions

☒ Administrator

Text Permissions

☐ Send Messages

Voice Permissions

☐ Connect

Open the **Bot** tab:

1. Enable:
 - **Server Members Intent**
 - **Message Content Intent**
2. Under **Bot Permissions**, enable:
 - **Administrator**

Discord Channel - Developer Applications

The screenshot shows the Discord OAuth2 URL Generator interface. On the left is a sidebar with navigation options: OAuth2 (selected), Bot, Emojis, Webhooks, Rich Presence, App Testers, App Verification, Games, Activities, and Monetization. The main area is titled 'OAuth2 URL Generator' and includes a description: 'Generate an invite link for your application by picking the scopes and permissions it needs to function. Then, share the URL to others!'. Below this is a 'Scopes' section with a grid of checkboxes. The 'bot' scope is checked, and the 'applications.commands' scope is also checked. At the bottom of the main area is a 'Bot Permissions' section with three columns: General Permissions (Administrator is checked), Text Permissions (Send Messages, Create Public Threads, Create Private Threads), and Voice Permissions (Connect, Speak, Video). At the very bottom, there is an 'Integration Type' dropdown set to 'Guild Install' and a 'Generated URL' field containing the URL: `https://discord.com/oauth2/authorize?client_id=1509200292036743168&permissions=8&integration_type=0&scope=bot+applications.commands`.

OAuth2 URL Generator

Generate an invite link for your application by picking the scopes and permissions it needs to function. Then, share the URL to others!

Scopes

☐ identify	☐ identify.premium	☐ email
☐ connections	☐ guilds	☐ guilds.join
☐ guilds.members.read	☐ guilds.channels.read	☐ gdm.join
☒ bot	☐ rpc	☐ rpc.notifications.read
☐ rpc.voice.read	☐ rpc.voice.write	☐ rpc.video.read
☐ rpc.video.write	☐ rpc.screenshare.read	☐ rpc.screenshare.write
☐ rpc.activities.write	☐ webhook.incoming	☐ messages.read
☐ applications.builds.upload	☐ applications.builds.read	☒ applications.commands
☐ applications.store.update	☐ applications.entitlements	☐ activities.read
☐ activities.write	☐ activities.invites.write	☐ relationships.read
☐ relationships.write	☐ voice	☐ dm_channels.read
☐ role_connections.write	☐ presences.read	☐ presences.write
☐ openid	☐ dm_channels.messages.read	☐ dm_channels.messages.write
☐ gateway.connect	☐ account_global_name.update	☐ payment_sources.country_code
☐ sdk.social_layer_presence	☐ sdk.social_layer	☐ lobbies.write
☐ application_identities.write		
☐ applications.commands.permissions.update		

Bot Permissions

General Permissions	Text Permissions	Voice Permissions
☒ Administrator	☐ Send Messages	☐ Connect
☐ View Audit Log	☐ Create Public Threads	☐ Speak
☐ Manage Server	☐ Create Private Threads	☐ Video

Integration Type

Guild Install



Generated URL

https://discord.com/oauth2/authorize?client_id=1509200292036743168&permissions=8&integration_type=0&scope=bot+applications.commands

Open the **OAuth2** tab:


1. Select scopes:
 - **bot**
 - **applications.commands**
2. Under **Bot Permissions**, enable:
 - **Administrator**
3. Copy the generated invite URL.
4. Open the URL, select your Discord server, and authorize the bot.

Discord Channel - Developer Applications



Open the **OAuth2** tab:

1. Select scopes:
 - **bot**
 - **applications.commands**
2. Under **Bot Permissions**, enable:
 - **Administrator**
3. Copy the generated invite URL.
4. Open the URL, select your Discord server, and authorize the bot.



Discord Channel - Developer Applications

Token
For security purposes, tokens can only be viewed once, when created. If you forgot or lost access to your token, please regenerate a new one.

[Reset Token](#)

Reset Bot's Token?
Your bot will stop working until you update the token in your bot's code.

[Cancel](#) [Yes, do it!](#)

Multi-Factor Authentication

[Verify with something else](#)

[Submit](#)

A new token was generated! Be sure to copy it as it will not be shown to you again.

Return to the **Bot** tab:

1. Click **Reset Token**
2. Complete multi-factor authentication (MFA) verification
3. Copy and **save** the generated **Discord bot token**
4. Use this bot token during the OpenClaw Discord configuration process.

Discord Channel - Configuration

```
ubuntu@ip-172-31-13-112:~$ openclaw update
◇
Updating OpenClaw...

Stopping managed gateway service before package update...
Stopped systemd service: openclaw-gateway.service

◇ ✓ Updating via package manager (26.68s)
◇ ✓ Running doctor checks (44.9s)

Update Result: OK
  Root: /home/ubuntu/.npm-global/lib/node_modules/openclaw
  Before: 2026.5.22
  After: 2026.5.26

Total time: 76.2s
Your OpenClaw config was written by version 2026.5.26, but this command is running 2026.5.22.
Check: `openclaw --version`, `which openclaw`, and `openclaw gateway status --deep`.
If unexpected, update PATH so `openclaw` points to the version you want, or reinstall the Gateway service from that same OpenClaw install.
◇

Updating plugins...
Installing @openclaw/codex into /home/ubuntu/.openclaw/npm...
Linked peerDependency "openclaw" -> /home/ubuntu/.npm-global/lib/node_modules/openclaw
npm plugins: 1 updated, 0 unchanged.

Restarting service...
Gateway already reports the updated version after service refresh; skipped redundant restart.
Gateway: restarted and verified.
Fresh code, same lobster. Miss me?
ubuntu@ip-172-31-13-112:~$
```

Plugin install

Failed to install
@openclaw/discord: plugin
"discord" requires OpenClaw
>=2026.5.26, but this host is
2026.5.22.

Upgrade OpenClaw and retry.
openclaw update

Discord Channel - Configuration



To configure a Discord bot:

1. Select **Discord (Bot API)**
2. Create a bot in the **Discord Developer Portal**
3. Copy the bot token
4. Paste the token into OpenClaw
5. Configure channel access:
 - Select **Allowlist (recommended)**
 - Enter the allowed Discord channel(s), for example:
`discord_server/#channel_name`
6. Select **Finished**
7. Choose **No** for DM access policies (optional)

After the setup is complete, the Discord bot configuration will be saved successfully.

```
ubuntu@ip-172-31-13-112:~$ openclaw configure
>
OpenClaw 2026.5.22 (a774c3e) - Aaaa, but with tests.
- OpenClaw configure
> Existing config detected

Workspace: ~/openclaw/workspace
Model: openai/gpt-4o-mini
Gateway: local via loopback on :18789

> Where will the Gateway run?
Local (this machine)

> What do you want to configure?
Channels

> Channel setup
Add or update channels

> How channels work

Inbound DM safety defaults to pairing: unknown senders get a pairing code first.
Approve with: openclaw pairing approve <channel> <code>
Open/public DMs require dmPolicy="open" plus allowFrom=["*"].
For multi-user DMs, isolate sessions with: openclaw config set session.dmScope
"per-channel-peer" for "per-account-channel-peer" for multi-account channels).
Docs: channels/pairing

Weishu: 飞书/feishu enterprise messaging with doc/wiki/drive tools.
WeCom: Enterprise messaging and documents, scheduling, task tools.
Google Chat: Google Workspace Chat app with HTTP webhook.
Moxtra: Decentralized protocol; encrypted DMS via MIP-04.
Microsoft Teams: Teams SDK; enterprise support.
Mattermost: self-hosted Slack-style chat; install the plugin to enable.
Nextcloud Talk: Self-hosted chat via Nextcloud Talk webhook bots.
Matrix: open protocol; install the plugin to enable.
LINE: LINE Messaging API webhook bot.
Weixin: Personal WeChat messaging via QR-code login.
Zalo: Vietnam-focused messaging platform with Bot API.
ClickClack: self-hosted chat via first-class ClickClack bot tokens.
Yuanbao: Tencent Yuanbao AI assistant conversation channel.
Zalo Personal: Zalo personal account via QR code login.
Synology Chat: Connect your Synology NAS Chat to OpenClaw with full agent capabilities.
Tlon: decentralized messaging on Ubit; install the plugin to enable.
Discord: very well supported right now.
iMessage: Local iMessage/iOS through the iMsg bridge, including private API message actions when enabled.
IRC: classic IRC networks with DM/channel routing and pairing controls.
QQ Bot: connect to QQ via official QQ Bot API with group chat and direct message support.
Signal: signal-cli linked device; more setup (David Reagans: "Hop on Discord.").
Slack: supported (Socket Mode).
Telegram: simplest way to get started - register a bot with @BotFather and get going.
Twitch: Twitch chat integration
WhatsApp: works with your own number; recommend a separate phone + eSIM.
```

Select a channel
Discord (Bot API)

Installed Discord plugin

Discord bot token

1) Discord Developer Portal -> Applications -> New Application
2) Bot -> Add Bot -> Reset Token -> copy token
3) OAuth2 -> URL Generator -> scope 'bot' -> invite to your server
Tip: enable Message Content Intent if you need message text. (Bot -> Privileged Gateway Intents -> Message Content Intent)
Docs: discord

How do you want to provide this Discord bot token?
Enter Discord bot token

Enter Discord bot token

Configure Discord channels access?
Yes

Discord channels access
Allowlist (recommended)

Discord channels allowlist (comma-separated)
IRIS OpenClaw Demo/#test-openclaw

Select a channel
Finished

Selected channels

Discord - very well supported right now. Docs: discord

Configure DM access policies now? (default: pairing)
No

Updated config: ~/openclaw/openclaw.json
Backup: ~/openclaw/openclaw.json.bak


What do you want to configure?
Done

Control UI

Web UI: http://127.0.0.1:18789/
Gateway WS: ws://127.0.0.1:18789
Gateway: not detected (connect &CONNECTIONREFUSED 127.0.0.1:18789)
Docs: https://docs.openclaw.ai/web/control-ui

Configuration updated.

Discord Channel - Chat with Agent



If the **OpenClaw** bot appears online in your Discord server, the setup was successful.




You can now chat with OpenClaw in your Discord channel by tagging the bot:

@<openclaw-bot> <your message>

Bot reactions:

- 👁️ → OpenClaw has seen your message
- 🧠 → OpenClaw is thinking and generating a response

Discord Channel - Set Bot Permission



Discord Channel - Set Bot Permission

```
ubuntu@ip-172-31-13-112:~$ openclaw plugins update discord  
discord is up to date (2026.5.28).
```

Pooh 21:13
@OpenClaw Demo I already ran openclaw plugins update discord, can you please try to send the file again?

OpenClaw Demo APP 21:14
food_price_volatility.png

Food	Volatility (Standard Deviation)	Mean Price
Milk	3.85	24.62
Tomatoes	3.77	56.77
Rice	3.76	40.33
Chicken	3.33	81.17
Potatoes	2.55	21.34

Source: food_price.csv | Ranking uses monthly mean price by product, then standard deviation across months

Uploaded to the Discord channel as food_price_volatility.png.

Discord Plugin Update

The Discord plugin was updated using:

```
openclaw plugins update discord
```

After the update, Discord file attachment support is functioning correctly. The bot can now send files directly to Discord channels.



Agenda

1. **Introduction to OpenClaw**
 - a. Core Principles
 - b. Architecture
2. **OpenClaw Tutorial**
 - a. Cloud set up
 - b. Installation
 - c. Chat with Agent
 - d. Channels
 - e. Simple Automation Showcase
3. **Advanced Topics**
 - a. Skills
 - b. Multi-Agent Management
 - c. Labs
4. **Deleted Instance**
5. **Resources & FAQ**



OpenClaw Tutorial

Simple Automation Showcase

1. **Code Generation**
 - a. HTML file generation
 - b. Token usage
2. **Food Price Analysis Automation**
 - a. Multi-steps automation
 - b. Insights
 - c. Visualization
 - d. Cron-job



OpenClaw Tutorial

Simple Automation Showcase


1. Code Generation

- a. HTML file generation
- b. Token usage

2. Food Price Analysis Automation

- a. Multi-steps automation
- b. Insights
- c. Visualization
- d. Cron-job

Demo — Code Generation



Create a modern single-page HTML website that summarizes the capabilities of OpenClaw.

The page should include:

- A clean responsive design
- Hero section with title and short description
- Features section explaining capabilities such as:
 - AI conversations
 - Discord integration
 - Automation tools
 - Plugin system
 - Web interface
 - Docker deployment
- Simple architecture/workflow diagram using HTML/CSS
- Demo/test server section
- Footer with GitHub-style theme

Requirements:

- Generate a complete standalone `index.html`
- Use only HTML, CSS, and minimal JavaScript
- Modern dark theme UI
- Mobile-friendly layout
- Add subtle animations and hover effects
- No external frameworks required

Demo — Code Generation

● OPENCLAW PLATFORM OVERVIEW

Build, automate, and ship with OpenClaw.

OpenClaw is a modern AI workspace for conversations, automation, and web-driven workflows. It helps people move from ideas to execution with tools for Discord, plugins, browsers, Docker, and practical day-to-day operations.

[Explore capabilities](#)[View workflow](#)

Modern
Dark theme, responsive layout, and polished UI details.

Hands-on
Built for real tasks, not just summaries and text-only chat.

Connected
Discord, browser flows, plugins, and server-backed workflows.

Capabilities

OpenClaw is designed around practical work. These are the core things it can help with.

AI conversations
Chat naturally with an assistant that can reason, explain, draft, and act.

Automation tools
Coordinate multi-step tasks, repetitive workflows, and structured follow-through.

Web interface
Use a browser-friendly interface for building, inspecting, and interacting visually.

Discord integration
Work inside group chats and respond in a way that fits the conversation.

Plugin system
Extend the platform with focused skills and reusable capability modules.

Docker deployment
Run and ship OpenClaw in containerized environments with predictable setup.

[Conversation](#)[Discord](#)[Automation](#)[Plugins](#)[Web UI](#)[Docker](#)

Architecture / workflow
A simple view of how OpenClaw turns a request into an output.

User Request
A message, task, or trigger arrives in Discord or the web UI.

AI Core
Interprets context, plans the next steps, and decides what to do.

Tools / Skills
Calls browser, plugins, automation, or other capabilities as needed.

Execution
Performs the actual task: editing, checking, generating, or operating.

Verification
Confirms the result and catches mistakes before reporting back.

Delivery
Sends a clear answer, artifact, or status update back to the user.

This flow keeps OpenClaw practical: understand the request, use the right tool, validate the result, then communicate it clearly.

Demo / test server
OpenClaw can be exercised in a safe test environment for demos, experiments, and validation.

Demo-ready
Use case
Show off the assistant, verify UI behavior, and try workflows in a repeatable environment for showcasing OpenClaw capabilities.

Test chat
Simulate real conversations and response formatting.

Feature validation
Check plugins, browser actions, and deployment behavior.

What it supports
A demo server can host the web interface, exercise automation paths, and provide a repeatable environment for showcasing OpenClaw capabilities.

Web UI
Open a clean browser-based front end.

Containerized runtime
Deploy in Docker for reproducible setup and demos.

Safe experimentation
Try ideas before promoting them to a live environment.

Why it feels useful
OpenClaw aims to behave like a capable teammate: concise when needed, proactive when useful, and focused on getting real work done.

Fast to understand
Clear sections, visual hierarchy, and a simple story about what it can do.


Easy to extend
Plugins and skills let the system grow with new tools and workflows.

Built for action
Not just an answer engine. It can connect, automate, and verify outcomes.

 OpenClaw

GitHub-style dark footer • [Features](#) [Workflow](#)


Demo — Code Generation



The screenshot shows the OpenClaw interface with a chat session. The chat history shows a message from the user asking for a modern single-page HTML website that summarizes the capabilities of OpenClaw. The AI response includes a list of features and requirements, followed by a code block for an `index.html` file.

Chat History:

- discord:1509195003048624... (13h ago): I couldn't write to the workspace because the local file hooks are failing so here's a complete standalone `index.html` you can drop in as-is:
- AI: `<?doctype html> <html lang="en"> <head> <meta charset="UTF-8" /> <meta name="viewport" content="width=device-width, initial-scale=1.0" /> <title>OpenClaw - Capabilities Overview</title> <body> <h1>OpenClaw Capabilities Overview</h1> <h2>Features</h2> A clean responsive design Hero section with title and short description Features section explaining capabilities such as: AI conversations Discord integration Automation tools Plugin system Web interface Docker deployment Simple architecture/workflow diagram using HTML/CSS Demo/test server section Footer with GitHub-style theme <h2>Requirements</h2> Generate a complete standalone index.html Use only HTML, CSS, and minimal JavaScript Modern dark theme UI Mobile-friendly layout Add subtle animations and hover effects No external frameworks required `



The screenshot shows the OpenClaw interface with the Usage page. The page displays various metrics and filters for the current session.

Usage Overview:

- MESSAGES: 6 (2 over 4 assistant)
- THROUGHPUT: 1.8K tok/min (\$0.000 / min)
- TOTAL CALLS: 2 (1 tool used)
- AVG TOKENS / MSG: 9.0K (Across 6 messages)
- CACHE HIT RATE: 98.8% (33.5K cached - 34.1K prompt)
- ERROR RATE: 0.00% (0 errors - Show by arg session)
- AVG COST / MSG: \$0.0000 (\$0.00 used)
- SESSIONS: 1 (of 1 in target)
- ERRORS: 0 (0 tool results)

Filters:

- Today, 3d, 7d, 30d, 1y, All, 28/05/2026, Local, Current Instance, Historical Average, Tokens, Cost, Refresh

Top Models:

- gpt-5.4-mini: \$0.00 34.2K / 4 mps

Top Providers:

- openai-coder: \$0.00 34.2K / 4 mps

Top Tools:

- heartbeat_response: 2 calls

Top Agents:

- main: \$0.00 34.2K



OpenClaw Tutorial

Simple Automation Showcase

1. Code Generation

- a. HTML file generation
- b. Token usage

2. Food Price Analysis Automation

- a. Multi-steps automation
- b. Insights
- c. Visualization
- d. Cron-job



Demo — Food Price Analysis Automation


The more our workflow includes:

- tool use
- multi-step actions
- memory/session handling
- autonomous decisions
- cross-system coordination

...the more OpenClaw shines.


Now we're demonstrating:

- automation
- planning
- orchestration
- persistence
- tool coordination






Demo — Food Price Analysis Automation



OpenClaw successfully:

- Loaded the attached dataset from Discord
- Analyzed food price volatility
- Generated insights
- Created a visualization image automatically





Demo — Food Price Analysis Automation

Top 5 Food Price Volatility

Std dev of monthly average price across months



Source: food_prices.csv

```
ubuntu@ip-172-31-13-112:~/openclaw/workspace$ ls -la
total 52
drwxrwxr-x  5 ubuntu ubuntu 4096 May 28 04:41 .
drwx----- 18 ubuntu ubuntu 4096 May 28 04:41 ..
drwxrwxr-x  6 ubuntu ubuntu 4096 May 27 09:29 .git
drwx-----  2 ubuntu ubuntu 4096 May 27 10:10 .openclaw
-rw-rw-r--  1 ubuntu ubuntu 7938 May 27 09:29 AGENTS.md
-rw-rw-r--  1 ubuntu ubuntu 226 May 27 09:29 HEARTBEAT.md
-rw-rw-r--  1 ubuntu ubuntu 503 May 27 10:11 IDENTITY.md
-rw-rw-r--  1 ubuntu ubuntu 1806 May 27 09:29 SOUL.md
-rw-rw-r--  1 ubuntu ubuntu 920 May 27 09:29 TOOLS.md
-rw-rw-r--  1 ubuntu ubuntu 799 May 27 10:11 USER.md
-rw-rw-r--  1 ubuntu ubuntu 4076 May 28 04:41 food_price_volatility.svg
drwxrwxr-x  2 ubuntu ubuntu 4096 May 27 10:05 memory
ubuntu@ip-172-31-13-112:~/openclaw/workspace$
```

The agent successfully created a bar plot visualization showing the top 5 foods by price volatility, along with the mean value for each food.

The image was also saved in the OpenClaw workspace directory: `.openclaw/workspace`.



Demo — Food Price Analysis Automation

Cron Jobs
Wakeup and recurring runs.

ENABLED	JOB	NEXT WAKE	New Job	Refresh
Yes	1	Thu, 28/05/2026, 12:00:00 (in 10m)		

Jobs
All scheduled jobs stored in the gateway.

Filters

Job	STATUS
Daily food price volatility report Cron 0 12 * * * (Asia/Bangkok) Agent: main	n/a in 10m n/a

PROMPT
Re-run the food_prices.csv analysis from /home/ubuntu/.openclaw/media/inbound/food_prices---f048feda-4384-48f5-8a18-41a147c71e.csv. Compute the top 5 foods with the highest price volatility, using standard deviation of each product's monthly average price across months as the volatility metric. Create or refresh a simple chart of the top 5 and post a concise summary with the ranking and the chart in the same channel. If the file is missing, report that clearly.

DELIVERY
announce (discord -> channel:1509205897186906295)

enabled isolated now Edit Clone Disable Run Run if due History Remove

Run history
Latest runs across all jobs.

Filters

No matching runs.

```
ubuntu@ip-172-31-13-112:~/openclaw/workspace$ openclaw cron list
OpenClaw 2026.5.26 (10ad3aa) - I can run local, remote, or purely on vibes-results may vary with DNS.

ID          Target      Delivery      Name          Schedule          Agent ID      Next Model      Last      S
49390c81-9644-4d65-997a-f1419f3719c5 Daily food price vola... cron 0 12 * * * @ Asia/Bangko... in 17m      -      i
file isolated announce -> discord:channel:1509205897186906295 (explicit) main -
```

It can also create automation tasks using cron jobs, which you can manage with the following commands:

`openclaw cron list`

`openclaw cron rm <job-id>`

You can also view and manage cron jobs through the web UI.

What Makes OpenClaw More Than “Just an LLM”



Tool Orchestration

- route intents
- invoke tools
- manage workflows
- execute actions
- maintain sessions
- coordinate multiple capabilities

Persistent Agent Runtime

- long-running gateway
- sessions
- channel integration
- persistent configs
- identity & permissions
- agent behaviors

Multi-Channel Integrations

- Discord
- Telegram
- WhatsApp
- APIs
- local runtimes
- shell tools

Controlled Action Execution

- run scripts
- automate workflows
- manipulate files
- query databases
- trigger jobs
- call APIs

What Makes OpenClaw More Than “Just an LLM”



Agent Governance & Permissions

- owner approvals
- pairing
- DM policies
- execution permissions
- command scoping

Intent Routing

- user intent
- required tool
- execution path
- output type

Demo Framing : We deployed an AI agent runtime that can interpret natural language requests, orchestrate Python workflows, analyze datasets, generate visualizations, and return actionable insights through Discord.



Agenda

1. **Introduction to OpenClaw**
 - a. Core Principles
 - b. Architecture
2. **OpenClaw Tutorial**
 - a. Cloud set up
 - b. Installation
 - c. Chat with Agent
 - d. Channels
 - e. Simple Automation Showcase
3. **Advanced Topics**
 - a. Skills
 - b. Multi-Agent Management
 - c. Labs
4. **Deleted Instance**
5. **Resources & FAQ**



Advanced

Advanced OpenClaw Topics

1. **Skills Creation**
 - a. `/skill` command
2. **Multi-agent Manangments**
 - a. `openclaw agents add work`
3. **Security & Sandboxing**
 - a. `docker-based sandboxing`
 - b. `scripts/sandbox-seup.sh`

Agent Skills



- Agent skill-compatible folder is a directory with [SKILL.md](#) (YAML + instructions).
- They teach the agent how to use tools.
- Per-agent skills live in `/skills` for that agent only.
- Shared skills live in `~/openclaw/skills` (managed/local).
 - Shared skills are visible to all agents on the same machine.
- Set `user-invocable: true` to invoke skills manually.
 - We can call them with the **slash command**.

Reference:

Learn more about skills creation here: <https://docs.openclaw.ai/tools/creating-skills>

Multi-agent Manangments



Why multi-agent?

- **Isolation:** different personas, permissions, workspaces (e.g. family vs work).
- **Per-agent:** workspace, sessions, auth profiles, sandbox, tool policy.

Example:

- `openclaw agents add <agent>` : to add new agent
- `/agents` : to switch agent

Security & Sandboxing



- **Prompt injection:** Malicious users can craft messages that trick the agent into running unintended commands. Smaller models are more susceptible. Mitigate by enabling sandbox mode and restricting tool access for channels that accept messages from untrusted or unknown senders.
- **Sandbox:** Docker-based isolation runs tool execution in a container, protecting your host system. Set `sandbox.mode` to `non-main` (sandbox everyone except your main session) or `all` (sandbox everything). Use `sandbox.scope` to control container lifecycle (session, agent, or shared) and `workspaceAccess` to limit file access.
- **Tool policy:** Block dangerous tools (like `exec`, `process`, `browser`) for agents handling untrusted input.
- **Browser control:** The browser tool can navigate to any URL and interact with pages, making it high-risk for automation attacks.



Agenda

1. **Introduction to OpenClaw**
 - a. Core Principles
 - b. Architecture
2. **OpenClaw Tutorial**
 - a. Cloud set up
 - b. Installation
 - c. Chat with Agent
 - d. Channels
 - e. Simple Automation Showcase
3. **Advanced Topics**
 - a. Skills
 - b. Multi-Agent Management
 - c. Labs
4. **Deleted Instance**
5. **Resources & FAQ**

Advanced Lab 1

Multi-Agent AI Workflow with
OpenClaw





Figure Credit:

<https://medium.com/h7w/openclaw-multi-agent-deployment-from-single-agent-to-team-architecture-the-complete-path-353906414fca>

Multi-Agent AI Workflow with OpenClaw


Objective

Demonstrate how OpenClaw can be extended with multi-agents to automate content workflows, enabling users to generate a social media content based on news with grounded resources.



Demo Agenda

1. Create Content Agents.
2. Bind Agents to Discord Channel.
3. Set Up Agent Identity.
4. Test News Searching.
5. Test Content Drafting.



Multi-Agent AI Workflow - Step 1 Update Discord Configs

```
aws | Search [Alt+S] | [Icons]
ubuntu@ip-172-31-13-112:~$ openclaw configure
>
OpenClaw 2026.5.26 (10ad3aa) - Automation with claws: minimal fuss, maximal pinch.

- OpenClaw configure
> Existing config detected

Workspace: ~/.openclaw/workspace
Model: openai/gpt-5.4-mini
Gateway: local via loopback on :18789

> Where will the Gateway run?
Local (this machine)

> What do you want to configure?
Channels

> Channel setup
Add or update channels
```

First, configure OpenClaw by adding the required **allowlist** entries for your **Discord** channels. After updating the configuration, run the following command for the changes to take effect:

`openclaw gateway restart`

```
> Select a channel
Discord (Bot API)

> Discord already configured. What do you want to do?
Modify settings

> How do you want to provide this Discord bot token?
Enter Discord bot token

> Discord token already configured. Keep it?
Yes

> Update Discord channels access?
Yes

> Discord channels access
Allowlist (recommended)

> Discord channels allowlist (comma-separated)
1509195003048624248/1509205897186306235, 1509195003048624248/1509211043195392292,
1509195003048624248/1509211075252584478, 1509195003048624248/1509211104021188758,
1509195003048624248/1509211122132189184, 1509195003048624248/1509211139366719499, 1509477927027343490,
1509477963387900005

> Select a channel
Finished

> Selected channels
Discord - very well supported right now. Docs: discord

> Configure IM access policies now? (default: pairing)
No

Updated config: ~/.openclaw/openclaw.json
Backup: ~/.openclaw/openclaw.json.bak

> What do you want to configure?
Done

> Control UI

Web UI: http://127.0.0.1:18789/
Gateway WS: ws://127.0.0.1:18789
Gateway: reachable
Docs: https://docs.openclaw.ai/web/control-ui

- Configuration updated.

ubuntu@ip-172-31-13-112:~$ openclaw gateway restart
>

OpenClaw 2026.5.26 (10ad3aa) - The only open-source project where the mascot could eat the competition.

Restarted systemd service: openclaw-gateway.service
ubuntu@ip-172-31-13-112:~$
```

```
aws [Alt+S] [Search] [X] [Bell]
ubuntu@ip-172-31-13-112:~$ openclaw agents add content
OpenClaw 2026.5.26 (10ad3aa) - It's not "failing," it's "discovering ne
09:44:09 [plugins] plugins.allow is empty; discovered non-bundled plugi
/npm/node_modules/@openclaw/codex/dist/index.js), discord (/home/ubuntu
ist/index.js). Set plugins.allow to explicit trusted ids.
  Add OpenClaw agent
Workspace directory
/home/ubuntu/.openclaw/workspace/workspace-content
Copy portable auth profiles from "main"?
No
Configure model/auth for this agent now?
Yes
Model/auth provider
OpenAI
OpenAI auth method
OpenAI API Key
Enter OpenAI API key
.....
.....
```

Create an additional agent separate from the main agent so that each agent can handle a specific responsibility.

Create a new agent named `content` using the `openclaw agents add` command.

Command to Execute

```
openclaw agents add <agent-name>
```

Expected Output

- A new folder is created
- Inside the folder, there is a `bootstrap.md` file used to define the system prompt for this agent

```

Channel status
Feishu: not configured
Google Chat: not configured
Nostr: not configured
Microsoft Teams: not configured
Mattermost: not configured
Nextcloud Talk: not configured
Matrix: not configured
LINE: not configured
Zalo: not configured
ClickClack: not configured
Zalo Personal: not configured
Synology Chat: not configured
Tlont: not configured
Discord: configured (plugin disabled)
iMessage: not configured
IRC: not configured
QQ Bot: not configured
Signal: not configured
Slack: not configured
Telegram: not configured
Twitich: not configured
WhatsApp: not configured
Feishu: install plugin to enable
WeCom: install plugin to enable
Google Chat: install plugin to enable
Nostr: install plugin to enable
Microsoft Teams: install plugin to enable
Mattermost: bundled - enable to use
Nextcloud Talk: install plugin to enable
Matrix: enable plugin to enable
LINE: install plugin to enable
Weixin: install plugin to enable
Zalo: install plugin to enable
ClickClack: bundled - enable to use
Yuanbao: install plugin to enable
Zalo Personal: install plugin to enable
Synology Chat: install plugin to enable
Tlont: install plugin to enable
iMessage: bundled - enable to use
IRC: bundled - enable to use
QQ Bot: install plugin to enable
Signal: bundled - enable to use
Slack: install plugin to enable
Telegram: bundled - enable to use
Twitich: install plugin to enable
WhatsApp: install plugin to enable

❖ Set up a chat channel now?
No
Updated config: ~/.opencwlab/opencwlab_3zon
Backup: ~/.opencwlab/opencwlab_1zon.bak
Workspace OK: ~/.opencwlab/workspace/workspace-content
Sessions OK: ~/.opencwlab/agents/content/sessions

Agent "content" ready.

ubuntu@tip-172-31-13-112:~$

```

Multi-Agent AI Workflow - Step 3 Bind Agents

How to bind a Discord channel to the **content** agent

Add a routing rule


You need to map a Discord channel → agent in the OpenClaw gateway configuration.

Typically this is done via a rule like:

```
channel_id: <DISCORD_CHANNEL_ID>  
agent: content
```

Restart gateway

After adding the routing rule. This is required for the routing config to take effect.



```
ubuntu@ip-172-31-13-112:~$ openclaw agents  
OpenClaw 2026.5.26 (10ad3aa) - I don't sleep, I just en  
Agents:  
- main (default)  
  Workspace: ~/.openclaw/workspace  
  Agent dir: ~/.openclaw/agents/main/agent  
  Model: openai/gpt-5.4-mini  
  Routing rules: 0  
  Routing: default (no explicit rules)  
- content  
  Workspace: ~/.openclaw/workspace/workspace-content  
  Agent dir: ~/.openclaw/agents/content/agent  
  Model: openai/gpt-5.5  
  Routing rules: 1
```



Multi-Agent AI Workflow - Step 3 Bind Agents

```
ubuntu@ip-172-31-13-112:~$ cat .openclaw/openclaw.json
```

```
"bindings": [  
  {  
    "type": "route",  
    "agentId": "content",  
    "comment": "Route Discord channel 1509477927027343490 to the content agent workspace.",  
    "match": {  
      "channel": "discord",  
      "guildId": "1509195003048624248",  
      "peer": {  
        "kind": "channel",  
        "id": "1509477927027343490"  
      }  
    }  
  }  
],
```

Example binding result in openclaw.json

Multi-Agent AI Workflow - Step 4 Set-up Identity



Content Agent will update his [IDENTITY.md](#) and [USER.md](#)



Multi-Agent AI Workflow - Testing Agent News Searching



Pooh 17:50

@OpenClaw Demo ช่วยค้นข่าวที่เกี่ยวข้องกับ AI



OpenClaw Demo APP 17:51

ข่าว AI นำตามช่วงล่าสุด:

- ตีกลมมอง “AI แย่งงาน” ระหว่าง OpenAI กับ Anthropic: Axios รายงานว่า 2 บริษัทเริ่มออกจุดยืนต่างกันชัดเจนเรื่องผลกระทบ AI ต่อแรงงาน โดย Anthropic เตือนแรงกว่า ส่วน OpenAI โทรมัธธะวังกว่า. ([axios.com](https://www.axios.com))
- ไบป์สโอ XIV เรียกกรองกำกับ AI เข้มขึ้น: เอกสารสำคัญฉบับแรกของพระองค์เน้นความเสี่ยง misinformation, สงคราม และอาวุธที่อาจหลุดจากการควบคุมของมนุษย์. ([taiwannews.com.tw](https://www.taiwannews.com.tw))
- ทรมปีเลือนคำสั่งบริหาร AI: ทำเนียบขาวยกเลิก/เลื่อนพิธีลงนามคำสั่งด้าน AI เพราะกังวลว่าจะกระทบความได้เปรียบของอุตสาหกรรม AI สหรัฐ. ([wtop.com](https://www.wtop.com))
- Google ดัน AI เข้าแทบทุกผลิตภัณฑ์ใน I/O 2026: ข่าวใหญ่คือ Gemini, Search, YouTube, Gmail/Workspace, Chrome และแว่น AI โดย Google วาง AI agent เป็นแกนหลักของบริการ. ([axios.com](https://www.axios.com))
- สหรัฐฯ-จีนคุยกกรอบป้องกันโมเดล AI ระดับสูง: Reuters รายงานว่าทั้งสองฝ่ายหารือแนวทาง guardrails เพื่อกันไม่ให้ actor นอกภาครัฐเข้าถึงหรือใช้โมเดลทรงพลังผิดทาง. ([investing.com](https://www.investing.com))

มุมมองที่น่าสนใจ: “AI governance กลับมาเป็นประเด็นใหญ่” เพราะข่าวรัฐบาลสหรัฐฯ, จีน, วาดิกัน และบริษัท AI เองกำลังชนกันที่คำถามเดียวกันคือ จะเร่งพัฒนาแค่ไหนโดยไม่เสียการควบคุม.

Activity

Browser-local tool activity summaries.

Search

Filter by tool, summary, run, session

Expand all

Collapse all

Clear

Tool

All tools

Running

Done

Error

Auto-follow

3 of 3

DONE

web_search

2 arguments hidden

17:50:34 52 s

DONE

web_search

2 arguments hidden

17:50:37 55 s

DONE

web_search

2 arguments hidden

17:50:45 76 s

The agent successfully searched for recent AI-related news articles and generated concise bullet-point summaries with source references for each topic.



Multi-Agent AI Workflow - Testing Agent Content Drafting



OpenCrawl Demo APP 17:57

หัวข้อบทความ

เมื่อ AI เลื่อนขาดแรงงานคนและเวอร์ชัน: Anthropic เดือนแรง, OpenAI เล่าภาพที่ผ่านกว่า

Hook เปิดเรื่อง

วันที่ “AI แข่งงาน” ไม่ได้เป็นแค่คำถามเชิงทฤษฎีอีกต่อไป แต่กำลังกลายเป็นการแย่งชิง “กรอบเล่าเรื่อง” ระหว่างสองค่ายใหญ่ในวงการเองด้วยว่า เทคโนโลยีตัวนี้จะกำลังจะกวาดงานมนุษย์หายไปจำนวนมาก หรือจะเป็นแรงส่งให้เกิดงานและผลิตภาพรูปแบบใหม่กันแน่. Axios รายงานว่า Anthropic กับ OpenAI เริ่มส่งสัญญาณเคลนเคลนชัดอย่างชัดเจน จนทำให้คนดูยิ่งต้องจับตาวานาคตแรงงานจะไปทางไหน. ([anthropic.com](#))

เนื้อหาหลัก

สิ่งที่น่าสนใจไม่ใช่แค่ “ใครพูดแรงกว่า” แต่คือแต่ละบริษัทกำลังสะท้อนมุมมองต่ออนาคตคนและแบบอย่างมีนัยสำคัญ ตามรายงานของ Axios ค้าง Anthropic โดย Chris Olah ย้ำว่าความเป็นไปได้จริงที่ AI จะเข้ามาแทนแรงงานมนุษย์ในวงกว้าง ขณะที่ Sam Altman ของ OpenAI ให้ภาพที่เบากว่า โดยบอกว่ามันไม่น่าใช่ “jobs apocalypse” แบบที่หลายคนกังวล และยังพูดด้วยว่าตัวเองอาจประเมินผลกระทบต่อแรงงานระดับ entry-level ผ่าไปในช่วงก่อนหน้า.

แต่ถ้าอ่านลึกลงไป จะเห็นว้าง Anthropic เองก็ไม่ได้พูดแบบฟันธงว่า “งานหายไปแล้ว” รายงานวิจัยของบริษัทที่เผยแพร่เมื่อ 5 มีนาคม 2026 ใช้แนวคิด “observed exposure” เพื่อประเมินว่า งานประเภทไหนมีความเสี่ยงต่อการถูก AI เข้ามาจับงานมากกว่า และผลที่ได้บอกว่า แม้งานที่เปิดรับ AI สูงจะมีแนวโน้มเติบโตช้ากว่าในมุมการคาดการณ์ระยะยาว แต่ยังไม่พบการเพิ่มขึ้นของการจ้างงานอย่างเป็นระบบในกลุ่มงานที่เปิดรับ AI สูงนับตั้งแต่ปลายปี 2022. รายงานเดียวกันก็ยังชี้ด้วยว่าอาจเริ่มเห็นสัญญาณที่การจ้างงานคนอายุน้อยในบางอาชีพชะลอลง และงานที่เปิดรับ AI มากมักกระจุกในกลุ่มอย่างโปรแกรมเมอร์ ฝ่ายบริการลูกค้า และงานเคียชข้อมูล. ([anthropic.com](#))

มันช่วยทำให้ภาพของ Anthropic ชัดขึ้นกว่าเดิมว่า “สายเคียบถ้อย” แบบสั้น ๆ เพราะแม้บริษัทจะชี้ความเสี่ยงเรื่องการแทนที่แรงงาน แต่ตัวข้อมูลของบริษัทเองก็ยังสะท้อนว่าตอนนี้ตลาดแรงงานยังไม่ได้พังลงแบบจับปล้น และสัญญาณที่เห็นอาจเป็นเพียงจุดเริ่มต้นของการเปลี่ยนผ่านมากกว่าการล่มสลายทันที. Anthropic ยังเขียนชัดว่ากระบวนการของตัวเองเป็นเพียง “first step” เพื่อไว้ติดตามผลกระทบต่อแรงงานในอนาคต ซึ่งแปลว่าบริษัทมองว่าเป็นเรื่องที่ต้องติดตามต่อเนื่อง ไม่ใช่เรื่องที่สรุปจบได้ในครั้งเดียว. ([anthropic.com](#))

อีกฝั่งหนึ่ง OpenAI ก็ไม่ได้เล่าเรื่องแรงงานแบบลอย ๆ เช่นกัน บนหน้า Signals ของ OpenAI ตอนนี้มีมีชุดงานวิจัยชื่อ “The AI jobs transition framework” ที่วางตัวเป็นกรอบศึกษาผลกระทบระยะใกล้ต่อการจ้างงาน และหน้า research-and-analysis ของบริษัทก็ระบุชัดว่า ทีมเศรษฐศาสตร์ และ global affairs ต้องการทำให้ออกเรื่อง AI ในเศรษฐกิจและสังคมตั้งอยู่บนหลักฐานและข้อมูลจริง. พูดง่าย ๆ คือ OpenAI เลือกวางประเด็นนี้ในภาษาของ “การเปลี่ยนผ่าน” มากกว่าภาษาของ “หายไป”. ([openai.com](#))

และนี่คือจุดที่ชาวเน็ตนั้นน่าจะสนใจว่าการจับผิดใครพูดแรงกว่ากัน เพราะ Axios ชี้ว่าในโลกจริงยังมีสัญญาณส่วนทางกันอยู่เหมือนกัน ทั้งการเลย์ออฟในบริษัทเทคโนโลยีที่ถุกโยกทั้ง AI และข้อมูลผู้ผลิดผลงานที่ยังเห็นการจ้างงานบางสายเพิ่มขึ้น เช่นตำแหน่ง software engineering ที่ Axios อ้างถึงว่าเปิดรับมากขึ้นเมื่อเทียบกับปีก่อน ขณะเดียวกันก็มีเสียงสะท้อนจากบางบริษัทว่า AI ยังไม่คุ้มต้นทุนเท่าที่คาดไว้. สรุปคือ ภาพรวมยังไม่ใช่ว่า “AI ทำลายงานทั้งหมด” หรือ “AI สร้างงานทั้งหมด” แต่เป็นการเปลี่ยนโครงสร้างงานแบบไม่สม่ำเสมอ ซึ่งอาจกระทบแต่ละอุตสาหกรรมไม่เท่ากัน.

Takeaway

สาระสำคัญของข่าวนี้ไม่ใช่ว่าใครพูดถูกหรือผิดทันที แต่คือการที่สองค่ายใหญ่ของ AI กำลังใช้ “ภาษาอนาคต” คนละแบบเพื่ออธิบายผลกระทบต่อแรงงาน: Anthropic เน้นความเสี่ยงและความระวัง, ส่วน OpenAI เลือกเล่าในกรอบของการปรับตัวและการเปลี่ยนผ่าน. สำหรับคนอ่าน ข่าวนี้เป็นสัญญาณว่าโจทย์สำคัญไม่ใช่แค่ “AI จะมาแย่งงานไหม” แต่คือ “งานแบบไหนจะเปลี่ยนก่อน และคนทำงานควรปรับตัวอย่างไรตั้งแต่ตอนนี้”. ([anthropic.com](#))

**แหล่งอ้างอิง

ถึง**

- Axios, “OpenAI and Anthropic dig in against each other on AI jobs apocalypse”
- Anthropic, “Labor market impacts of AI: A new measure and early evidence” ([anthropic.com](#))
- OpenAI Signals / Research and analysis pages ที่มี “The AI jobs transition framework” ([openai.com](#))



Advanced Lab 2

AI Agent Custom Skill with
OpenClaw






AI Agent **Custom Skill** with OpenClaw


Objective

Demonstrate how OpenClaw can be extended with custom skills to automate slide creation workflows, enabling users to generate presentation decks from text prompts or uploaded documents.



Demo Agenda

1. Install a custom slide-generation skill.
2. Show the skill registration inside OpenClaw.
3. Run a text-to-slide request.
4. Download and preview generated PPTX.
5. Upload a PDF and run file-to-slide workflow.






AI Agent **Custom Skill** with OpenClaw

AI-Powered Presentation Generation Workflow

Built a workflow that generates visually presentations directly from prompts posted in a Discord channel.

Workflow

1. Write presentation prompt in Discord
2. Trigger slide-generation workflow
3. Generate powerpoint slide presentation
4. Export/share presentation instantly



<https://github.com/Samin12/vo-to-slides>



AI Agent Custom Skill with OpenClaw

Pooh 13:21
@OpenClaw Demo Can you help make a simple slide based on the topic; AI for food processing.
Please use this skill <https://github.com/Samin12/vo-to-slides>, download this skill and make some slides so that I can look through it and present it. (edited)

OpenClaw Demo APP 13:24
I built a simple 6-slide deck for AI for food processing using the vo-to-slides skill repo.

Files:

- [Slide spec](/home/ubuntu/.openclaw/workspace/vo-to-slides/ai-food-processing-spec.json)
- [Generated deck](/home/ubuntu/.openclaw/workspace/vo-to-slides/ai-food-processing.pptx)

What's in it:

- Title slide
- Plant data to business impact
- Manual inspection vs AI quality control
- Where AI adds value
- Practical rollout steps
- Closing slide

I also installed the local npm deps needed to run the generator in that repo. The deck generation completed successfully.

One limitation:

- I couldn't do a PDF render preview here because `soffice` isn't installed in this environment.

If you want, I can do a second pass and make it:

- more corporate/professional
- more visual and bold
- longer, like a 10-slide presentation

```
aws
Search [Alt+S]
ubuntu@ip-172-31-13-112:~/openclaw/workspace$ ls -la
total 56
drwxrwxr-x 6 ubuntu ubuntu 4096 May 28 06:26 .
drwx----- 19 ubuntu ubuntu 4096 May 28 05:34 ..
drwxrwxr-x 6 ubuntu ubuntu 4096 May 28 05:16 .git
drwx----- 2 ubuntu ubuntu 4096 May 27 10:10 .openclaw
-rw-rw-r-- 1 ubuntu ubuntu 7938 May 27 09:29 AGENTS.md
-rw-rw-r-- 1 ubuntu ubuntu 226 May 27 09:29 HEARTBEAT.md
-rw-rw-r-- 1 ubuntu ubuntu 503 May 27 10:11 IDENTITY.md
-rw-rw-r-- 1 ubuntu ubuntu 1806 May 27 09:29 SOUL.md
-rw-rw-r-- 1 ubuntu ubuntu 920 May 27 09:29 TOOLS.md
-rw-rw-r-- 1 ubuntu ubuntu 799 May 27 10:11 USER.md
-rw-rw-r-- 1 ubuntu ubuntu 4076 May 28 04:41 food_price_volatility.svg
drwxrwxr-x 2 ubuntu ubuntu 4096 May 28 05:32 memory
drwxrwxr-x 8 ubuntu ubuntu 4096 May 28 06:24 vo-to-slides
ubuntu@ip-172-31-13-112:~/openclaw/workspace$ ls -la vo-to-slides/
total 384
drwxrwxr-x 8 ubuntu ubuntu 4096 May 28 06:24 .
drwxrwxr-x 6 ubuntu ubuntu 4096 May 28 06:26 ..
drwxrwxr-x 7 ubuntu ubuntu 4096 May 28 06:24 .git
-rw-rw-r-- 1 ubuntu ubuntu 11438 May 28 06:22 SKILL.md
-rw-rw-r-- 1 ubuntu ubuntu 3199 May 28 06:23 ai-food-processing-spec.json
-rw-rw-r-- 1 ubuntu ubuntu 247347 May 28 06:24 ai-food-processing.pptx
drwxrwxr-x 2 ubuntu ubuntu 4096 May 28 06:22 assets
-rw-rw-r-- 1 ubuntu ubuntu 7848 May 28 06:22 design-guide.md
drwxrwxr-x 2 ubuntu ubuntu 4096 May 28 06:22 examples
-rw-rw-r-- 1 ubuntu ubuntu 27377 May 28 06:22 generate.js
drwxrwxr-x 30 ubuntu ubuntu 4096 May 28 06:24 node_modules
-rw-rw-r-- 1 ubuntu ubuntu 27180 May 28 06:24 package-lock.json
-rw-rw-r-- 1 ubuntu ubuntu 701 May 28 06:24 package.json
drwxrwxr-x 2 ubuntu ubuntu 4096 May 28 06:24 preview
drwxrwxr-x 2 ubuntu ubuntu 4096 May 28 06:22 scripts
-rw-rw-r-- 1 ubuntu ubuntu 16303 May 28 06:22 spec-schema.md
-rw-rw-r-- 1 ubuntu ubuntu 1055 May 28 06:22 theme.json
-rw-rw-r-- 1 ubuntu ubuntu 2670 May 28 06:22 upload_to_drive.py
ubuntu@ip-172-31-13-112:~/openclaw/workspace$
```

The agent will download the skill and use that skill to create slides for us!




AI Agent **Custom Skill** with OpenClaw

If the Discord bot fails to send the file, you can download it manually by running the following command in your local terminal:

```
scp -i  
<path-to-pem>/iris-openclaw-de  
mo-key-pair.pem \
```

```
ubuntu@<instance-ip>:/home/u  
buntu/.openclaw/workspace/vo  
to-slides/ai-food-processing.ppt  
x \
```

```
"C:/Users/user/Downloads"
```





AI Agent Custom Skill with OpenClaw

```
1 # download_slide.py
2
3 import subprocess
4 import argparse
5
6 parser = argparse.ArgumentParser(
7     description="Download PPTX file from remote OpenClaw workspace"
8 )
9
10 parser.add_argument(
11     "--ip",
12     required=True,
13     help="EC2 instance IP address"
14 )
15
16 parser.add_argument(
17     "--file",
18     default="ai-food-processing.pptx",
19     help="PPTX filename"
20 )
21
22 args = parser.parse_args()
23
24 pem_file = "~/iris-openclaw-demo-key-pair.pem"
25
26 work_space_path = "/home/ubuntu/.openclaw/workspace"
27
28 remote_path = f"ubuntu@{args.ip}:{work_space_path}/vo-to-slides/{args.file}"
29 local_path = "C:/Users/user/Downloads"
30
31 command = [
32     "scp",
33     "-i",
34     pem_file,
35     remote_path,
36     local_path
37 ]
38
39 print("Downloading file...")
40 subprocess.run(command, check=True)
41
42 print(f"Downloaded {args.file} to {local_path}")
```

After generating the `.pptx`, create a Python script that:

1. Finds the generated file
2. Uploads it to Discord using a bot
3. **(if fail)** Run this script to download the generated file

Run it like this:

`</> Bash`

```
python download_slide.py --ip <instance-ip>
```

Or with a custom file:

`</> Bash`

```
python download_slide.py --ip <instance-ip> --file demo.pptx
```



AI Agent Custom Skill with OpenClaw

Pooh 15:12
@OpenClaw Demo Can you also turn this file into a slide?

```
<!doctype html>
<html lang="en">
  <head>
    <meta charset="UTF-8" />
    <meta name="viewport" content="width=device-width, initial-scale=1.0" />
    <title>OpenClaw - Capabilities Overview</title>
```

index.html
25 KB

1

OpenClaw Demo APP 15:12
Turned it into a 6-slide deck based on the page's structure.

Files:

- [PPTX deck](/home/ubuntu/.openclaw/workspace/vo-to-slides/openclaw-capabilities-overview.pptx)
- [Slide spec](/home/ubuntu/.openclaw/workspace/vo-to-slides/openclaw-capabilities-spec.json)

If you want, I can also make it:

1. more polished / executive-style
2. shorter into 3 slides
3. longer into a full presentation

File-to-slides generation also works successfully.

I provided an HTML file as input, and OpenClaw automatically generated a 6-page presentation deck from the content.



AI Agent Custom Skill with OpenClaw

OPENCLAW PLATFORM OVERVIEW

Build, automate, and ship with OpenClaw.

OpenClaw is a modern AI workspace for conversations, automation, and web-driven workflows. It helps people move from ideas to execution with tools for Discord, plugins, browsers, Docker, and practical day-to-day operations.

[Explore capabilities](#) [View workflow](#)

Modern
Dark theme, responsive layout, and polished UI details.

Hands-on
Built for real tasks, not just summaries and text-only chat.

Connected
Discord, browser flows, plugins, and server-backed workflows.

Capabilities

OpenClaw is designed around practical work. These are the core things it can help with.

AI conversations
Chat naturally with an assistant that can reason, explain, draft, and act.

Automation tools
Coordinate multi-step tasks, repetitive workflows, and structured follow-through.



Web interface
Use a browser-friendly interface for building, inspecting, and interacting visually.

Discord integration
Work inside group chats and respond in a way that fits the conversation.

Plugin system
Extend the platform with focused skills and reusable capability modules.

Docker deployment
Run and ship OpenClaw in containerized environments with predictable setup.

[Conversation](#) [Discord](#) [Automation](#) [Plugins](#) [Web UI](#) [Docker](#)





Agenda


1. **Introduction to OpenClaw**
 - a. Core Principles
 - b. Architecture
2. **OpenClaw Tutorial**
 - a. Cloud set up
 - b. Installation
 - c. Chat with Agent
 - d. Channels
 - e. Simple Automation Showcase
3. **Advanced Topics**
 - a. Skills
 - b. Multi-Agent Management
 - c. Labs
4. **Deleted Instance**
5. **Resources & FAQ**



OpenClaw Tutorial

Demonstration - Delete Instance

Delete Instance in Cloud Environment using AWS



The screenshot displays the AWS Management Console interface for the 'Instances' page. The top navigation bar includes the AWS logo, a search bar, and the region 'Asia Pacific (Sydney)'. The main content area shows a list of instances. The 'Instance state' dropdown menu is open, revealing options: 'Stop instance', 'Start instance', 'Reboot instance', 'Hibernate instance', and 'Terminate (delete) instance'. The 'Terminate (delete) instance' option is highlighted with a red box. Below the dropdown, a table lists instances with columns for Name, Instance ID, Instance state, Availability Zone, and F. The first instance listed is 'iris-openclaw-...' with ID 'i-00c11d47b38537cb4', state 'Running', and availability zone 'ap-southeast-2b'.

Name	Instance ID	Instance state	Availability Zone	F
iris-openclaw-...	i-00c11d47b38537cb4	Running	ap-southeast-2b	e

Select the instance, and choose Instance state, Terminate (delete) instance

Delete Instance in Cloud Environment using AWS

Terminate (delete) instance

⚠ On an EBS-backed instance, the default action is for the root EBS volume to be deleted when the instance is terminated. Storage on any local drives will be lost.

Are you sure you want to terminate these instances?

Instance ID	Termination protection
 i-00c11d47b38537cb4 (iris-openclaw-demo)	 Disabled

To confirm that you want to delete the instances, choose the terminate button below. Instances with termination protection enabled will not be terminated. Terminating the instance cannot be undone.

Skip OS shutdown
This option skips the graceful OS shutdown process. Use only when your instance must be stopped immediately, such as during an emergency or failover.

☐ Skip OS shutdown

CancelTerminate (delete)



Agenda

1. **Introduction to OpenClaw**
 - a. Core Principles
 - b. Architecture
2. **OpenClaw Tutorial**
 - a. Cloud set up
 - b. Installation
 - c. Chat with Agent
 - d. Channels
 - e. Simple Automation Showcase
3. **Advanced Topics**
 - a. Skills
 - b. Multi-Agent Management
 - c. Labs
4. **Deleted Instance**
5. **Resources & FAQ**



Resources

Useful resource links

1. **OpenClaw Document**
 - a. [OpenClaw Docs](#)
2. **OpenClaw Tutorial for Beginners**
 - a. [OpenClaw Full Tutorial for Beginners – How to Set Up and Use OpenClaw \(ClawdBot / MoltBot\)](#)
3. **Set Up OpenClaw + Discord**
 - a. [Set Up OpenClaw + Discord Fast \(Step-by-Step\)](#)
4. **Multi-Agent OpenClaw Tutorial**
 - a. [สอนสร้างทีม Multi-Agent ใน OpenClaw แบบละเอียดที่สุด](#)
 - b. [OpenClaw Multi-Agent Setup for Beginners: How to Build and Connect Subagents](#)



FAQ

Frequently Asked Questions

1. OpenClaw macOS Installation

- a. Use the same command as **macOS / Linux / WSL2**
- b. <https://docs.openclaw.ai/install>

2. LINE Integration

- a. LINE connects to OpenClaw via the LINE Messaging API.
- b. Some features are still **not supported**.
- c. <https://docs.openclaw.ai/channels/line>