Package 'GeoplotRgui'

July 9, 2026

Title Web Interface to GeoplotR

Version 1.0

Date 2026-07-09

Description Front end for GeoplotR rock identification suite

Author Tim Band [aut], Pieter Vermeesch [aut, cre]

Maintainer Pieter Vermeesch <p.vermeesch@ucl.ac.uk>

Depends R (>= 3.0.0)

Imports GeoplotR (>= 0.1), shinylight (>= 1.2)

License GPL-3

URL https://github.com/pvermees/GeoplotRgui/, https://isoplotr.es.ucl.ac.uk/geoplotr/

LazyData true

RoxygenNote 7.3.3

Encoding UTF-8

Contents

GeoplotR 1

Index **3**

`GeoplotR` *Starts the* `GeoplotR` *GUI*

Description

Opens a web-browser with a Graphical User Interface (GUI) for the `GeoplotR` package.

Usage

```
GeoplotR(host = "0.0.0.0", port = NULL, daemonize = FALSE)
```

Arguments

host	IP address to listen on, default is 0.0.0.0 (all interfaces)
port	Internet port of the virtual server. If not defined, a random free port will be chosen and the browser will be opened to show the GUI.
daemonize	If TRUE, keep serving forever without returning. This is useful when called from RScript, to keep

Value

server object, unless daemonize is TRUE.

Examples

```
## Not run:
GeoplotR()

## End(Not run)
## Not run:
GeoplotR(host='127.0.0.1', port=3820, daemonize=TRUE)

## End(Not run)
```

Index

GeoplotR, 1