

Package ‘provenance’

December 5, 2019

Title Statistical Toolbox for Sedimentary Provenance Analysis

Version 2.4

Date 2019-12-05

Description Bundles a number of established statistical methods to facilitate the visual interpretation of large datasets in sedimentary geology. Includes functionality for adaptive kernel density estimation, principal component analysis, correspondence analysis, multidimensional scaling, generalised procrustes analysis and individual differences scaling using a variety of dissimilarity measures. Univariate provenance proxies, such as single-grain ages or (isotopic) compositions are compared with the Kolmogorov-Smirnov, Kuiper or Sircombe-Hazelton L2 distances. Categorical provenance proxies such as chemical compositions are compared with the Aitchison and Bray-Curtis distances, and point-counting data with the chi-square distance. Also included are tools to plot compositional and point-counting data on ternary diagrams and point-counting data on radial plots, to calculate the sample size required for specified levels of statistical precision, and to assess the effects of hydraulic sorting on detrital compositions. Includes an intuitive query-based user interface for users who are not proficient in R.

Author Pieter Vermeesch [aut, cre]

Maintainer Pieter Vermeesch <p.vermeesch@ucl.ac.uk>

Depends R (>= 3.0.0)

Imports MASS, methods, IsoplotR

URL <http://provenance.london-geochron.com>

License GPL-2

LazyData true

RoxygenNote 6.1.1

Encoding UTF-8

R topics documented:

ALR	3
amalgamate	4
as.acomp	5

as.compositional	5
as.counts	6
as.data.frame	7
botev	7
bray.diss	8
CA	9
central	9
CLR	10
combine	11
densities	12
diss	13
endmembers	13
get.f	14
get.n	15
get.p	16
GPA	16
indscal	17
KDE	18
KDEs	19
KS.diss	20
Kuiper.diss	21
lines.ternary	21
MDS	22
minsorting	23
Namib	24
PCA	25
plot.CA	26
plot.compositional	26
plot.distributional	27
plot.GPA	28
plot.INDSCAL	29
plot.KDE	30
plot.KDEs	30
plot.MDS	31
plot.minsorting	32
plot.PCA	33
plot.ternary	34
points.ternary	35
procrustes	35
provenance	36
radialplot	37
read.compositional	38
read.counts	39
read.densities	40
read.distributional	41
restore	42
SH.diss	43
subset	44

<i>ALR</i>	3
summaryplot	45
ternary	46
ternary.ellipse	47
text.ternary	48
Index	49

<i>ALR</i>	<i>Additive logratio transformation</i>
------------	---

Description

Calculates Aitchison’s additive logratio transformation for a dataset of class `compositional` or a compositional data matrix.

Usage

```
ALR(x, ...)  
  
## Default S3 method:  
ALR(x, inverse = FALSE, ...)  
  
## S3 method for class 'compositional'  
ALR(x, ...)
```

Arguments

- `x` an object of class `compositional` OR a matrix of numerical values
- `...` optional arguments
- `inverse` perform the inverse inverse logratio transformation?

Value

a matrix of ALR coordinates OR an object of class `compositional` (if `inverse=TRUE`).

Examples

```
# logratio plot of trace element concentrations:  
data(Namib)  
alr <- ALR(Namib$Trace)  
pairs(alr[,1:5])  
title('log(X/Pb)')
```

amalgamate

Group components of a composition

Description

Adds several components of a composition together into a single component

Usage

```
amalgamate(X, ...)

## Default S3 method:
amalgamate(X, ...)

## S3 method for class 'compositional'
amalgamate(X, ...)

## S3 method for class 'counts'
amalgamate(X, ...)

## S3 method for class 'SRDcorrected'
amalgamate(X, ...)
```

Arguments

X	a compositional dataset
...	a series of new labels assigned to strings or vectors of strings denoting the components that need amalgamating

Value

an object of the same class as X with fewer components

Examples

```
data(Namib)
HMcomponents <- c("Zr", "tm", "rt", "TiOx", "sph", "ap", "ep",
                  "gt", "st", "amp", "cpx", "opx")
am <- amalgamate(Namib$PTHM, feldspars=c("KF", "P"),
                 lithics=c("Lm", "Lv", "Ls"), heavies=HMcomponents)
plot(ternary(am))
```

as.acomp	<i>create an acomp object</i>
----------	-------------------------------

Description

Convert an object of class `compositional` to an object of class `acomp` for use in the `compositions` package

Usage

```
as.acomp(x)
```

Arguments

x	an object of class <code>compositional</code>
---	---

Value

a `data.frame`

Examples

```
data(Namib)
qfl <- ternary(Namib$PT,c('Q'),c('KF','P'),c('Lm','Lv','Ls'))
plot(qfl,type="QFL.dickinson")
qfl.acomp <- as.acomp(qfl)
## uncomment the next two lines to plot an error
## ellipse using the compositions package:
# library(compositions)
# ellipses(mean(qfl.acomp),var(qfl.acomp),r=2)
```

as.compositional	<i>create a compositional object</i>
------------------	--------------------------------------

Description

Convert an object of class `matrix`, `data.frame` or `acomp` to an object of class `compositional`

Usage

```
as.compositional(x, method = NULL, colmap = "rainbow")
```

Arguments

x	an object of class <code>matrix</code> , <code>data.frame</code> or <code>acomp</code>
method	dissimilarity measure, either <code>'aitchison'</code> for Aitchison's CLR-distance or <code>'bray'</code> for the Bray-Curtis distance.
colmap	the colour map to be used in pie charts.

Value

an object of class `compositional`

Examples

```
data(Namib)
PT.acomp <- as.acomp(Namib$PT)
PT.compositional <- as.compositional(PT.acomp)
print(Namib$PT$x - PT.compositional$x)
## uncomment the following lines for an illustration of using this
## function to integrate the provenance package with compositions
# library(compositions)
# data(Glacial)
# a.glac <- acomp(Glacial)
# c.glac <- as.compositional(a.glac)
# summaryplot(c.glac, ncol=8)
```

as.counts	<i>create a counts object</i>
-----------	-------------------------------

Description

Convert an object of class `matrix` or `data.frame` to an object of class `counts`

Usage

```
as.counts(x, method = "chisq", colmap = "rainbow")
```

Arguments

x	an object of class <code>matrix</code> or <code>data.frame</code>
method	either "chisq" (for the chi-square distance) or "bray" (for the Bray-Curtis distance)
colmap	the colour map to be used in pie charts.

Value

an object of class `counts`

Examples

```
X <- matrix(c(0,100,0,30,11,2,94,36,0), nrow=3, ncol=3)
rownames(X) <- 1:3
colnames(X) <- c('a', 'b', 'c')
comp <- as.counts(X)
d <- diss(comp)
```

as.data.frame	<i>create a data.frame object</i>
---------------	-----------------------------------

Description

Convert an object of class `compositional` to a `data.frame` for use in the `robCompositions` package

Usage

```
## S3 method for class 'compositional'  
as.data.frame(x, ...)
```

```
## S3 method for class 'counts'  
as.data.frame(x, ...)
```

Arguments

x	an object of class <code>compositional</code>
...	optional arguments to be passed on to the generic function

Value

a `data.frame`

Examples

```
data(Namib)  
Major.frame <- as.data.frame(Namib$Major)  
## uncomment the next two lines to plot an error  
## ellipse using the robCompositions package:  
# library(robCompositions)  
# plot(pcaCoDa(Major.frame))
```

botev	<i>Compute the optimal kernel bandwidth</i>
-------	---

Description

Uses the diffusion algorithm of Zdravko Botev (2011) to calculate the bandwidth for kernel density estimation

Usage

```
botev(x)
```

Arguments

x a vector of ordinal data

Value

a scalar value with the optimal bandwidth

Author(s)

Dzdravko Botev

References

Botev, Z. I., J. F. Grotowski, and D. P. Kroese. "Kernel density estimation via diffusion." *The Annals of Statistics* 38.5 (2010): 2916-2957.

Examples

```
fname <- system.file("DZ.csv", package="provenance")
bw <- botev(read.distributional(fname)$x$N1)
print(bw)
```

bray.diss	<i>Bray-Curtis dissimilarity</i>
-----------	----------------------------------

Description

Calculates the Bray-Curtis dissimilarity between two samples

Usage

```
bray.diss(x, y)
```

Arguments

x a vector containing the first compositional sample
y a vector of length(x) containing the second compositional sample

Value

a scalar value

Examples

```
data(Namib)
print(bray.diss(Namib$HM$x["N1",], Namib$HM$x["N2",]))
```

CA	<i>Correspondence Analysis</i>
----	--------------------------------

Description

Performs Correspondence Analysis of point-counting data

Usage

```
CA(x, nf = 2, ...)
```

Arguments

x	an object of class counts
nf	number of correspondence factors (dimensions)
...	optional arguments to the corresp function of the MASS package

Value

an object of classes CA, which is synonymous to the MASS packages' correspondence class.

Examples

```
data(Namib)
plot(CA(Namib$PT))
```

central	<i>Calculate central compositions</i>
---------	---------------------------------------

Description

Computes the geometric mean composition of a continuous mixture of point-counting data.

Usage

```
central(x, ...)
```

Arguments

x	an object of class counts
...	optional arguments

Details

The central composition assumes that the observed point-counting distribution is the combination of two sources of scatter: counting uncertainty and true geological dispersion.

Value

an [5 x n] matrix with n being the number of categories and the rows containing:

theta the ‘central’ composition.

err the standard error for the central composition.

sigma the overdispersion parameter, i.e. the coefficient of variation of the underlying logistic normal distribution. `central` computes a continuous mixture model for each component (column) separately. Covariance terms are not reported.

LL the lower limit of a ‘1 sigma’ region for `codetheta`.

UL the upper limit of a ‘1 sigma’ region for `codetheta`.

mswd the mean square of the weighted deviates, a.k.a. reduced chi-square statistic.

p.value the p-value for age homogeneity

CLR

Centred logratio transformation

Description

Calculates Aitchison’s centered logratio transformation for a dataset of class `compositional` or a compositional data matrix.

Usage

```
CLR(x, ...)
```

```
## Default S3 method:
```

```
CLR(x, inverse = FALSE, ...)
```

```
## S3 method for class 'compositional'
```

```
CLR(x, ...)
```

Arguments

x an object of class `compositional` OR a matrix of numerical values

... optional arguments

inverse perform the inverse inverse logratio transformation?

Value

a matrix of CLR coordinates OR an object of class `compositional` (if `inverse=TRUE`)

Examples

```
# The following code shows that applying provenance's PCA function
# to compositional data is equivalent to applying R's built-in
# princomp function to the CLR transformed data.
data(Namib)
plot(PCA(Namib$Major))
dev.new()
clrdat <- CLR(Namib$Major)
biplot(princomp(clrdat))
```

combine

Combine samples of distributional data

Description

Lumps all single grain analyses of several samples together under a new name

Usage

```
combine(X, ...)
```

Arguments

X	a distributional dataset
...	a series of new labels assigned to strings or vectors of strings denoting the samples that need amalgamating

Value

a distributional data object with fewer samples than X

Examples

```
data(Namib)
combined <- combine(Namib$DZ,
  east=c('N3','N4','N5','N6','N7','N8','N9','N10'),
  west=c('N1','N2','N11','N12','T8','T13'))
summaryplot(KDEs(combined))
```

densities

*A list of rock and mineral densities***Description**

List of rock and mineral densities using the following abbreviations: Q (quartz), KF (K-feldspar), P (plagioclase), F (feldspar), Lvf (felsic/porphyritic volcanic rock fragments), Lvm (microlithic / porphyritic / trachitic volcanic rock fragments), Lcc (calcite), Lcd (dolomite), Lp (marl), Lch (chert), Lms (argillaceous / micaceous rock fragments), Lmv (metavolcanics), Lmf (metasediments), Lmb (metabasites), Lv (volcanic rock fragments), Lc (carbonates), Ls (sedimentary rock fragments), Lm (metamorphic rock fragments), Lu (serpentinite), mica, opaques, FeOx (Fe-oxides), turbids, zr (zircon), tm (tourmaline), rt (rutile), TiOx (Ti-oxides), sph (titanite), ap (apatite), mon (monazite), oth (other minerals), ep (epidote), othLgM (prehnite + pumpellyite + lawsonite + carpholite), gt (garnet), ctd (chloritoid), st (staurolite), and (andalusite), ky (kyanite), sil (sillimanite), amp (amphibole), px (pyroxene), cpx (clinopyroxene), opx (orthopyroxene), ol (olivine), spinel and othHM (other heavy minerals).

Author(s)

Alberto Resentini and Pieter Vermeesch

References

Resentini, A, Malusa M G and Garzanti, E. "MinSORTING: An Excel worksheet for modelling mineral grain-size distribution in sediments, with application to detrital geochronology and provenance studies." *Computers & Geosciences* 59 (2013): 90-97.

Garzanti, E, Ando, S and Vezzoli, G. "Settling equivalence of detrital minerals and grain-size dependence of sediment composition." *Earth and Planetary Science Letters* 273.1 (2008): 138-151.

See Also

restore, minsorting

Examples

```
data(Namib,densities)
N8 <- subset(Namib$HM,select="N8")
distribution <- minsorting(N8,densities,phi=2,sigmaphi=1,medium="air",by=0.05)
plot(distribution)
```

diss	<i>Calculate the dissimilarity matrix between two distributional or compositional datasets</i>
------	--

Description

Calculate the dissimilarity matrix between two datasets of class distributional or compositional using the Kolmogorov-Smirnov, Sircombe-Hazelton, Aitchison or Bray Curtis distance

Usage

```
diss(x, method)

## S3 method for class 'distributional'
diss(x, method = NULL)

## S3 method for class 'compositional'
diss(x, method = NULL)

## S3 method for class 'counts'
diss(x, method = NULL)
```

Arguments

x an object of class distributional, compositional or counts
method (optional) either "KS", "Kuiper", "SH", "aitchison", "bray" or "chisq"

Value

an object of class diss

Examples

```
data(Namib)
print(round(100*diss(Namib$DZ)))
```

endmembers	<i>Petrographic end-member compositions</i>
------------	---

Description

A compositional dataset comprising the mineralogical compositions of the following end-members: undissected_magmatic_arc, dissected_magmatic_arc, ophiolite, recycled_clastic, undissected_continental_block, transitional_continental_block, dissected_continental_block, subcreted_axial_belt and subducted_axial_belt

Author(s)

Alberto Resentini and Pieter Vermeesch

References

Resentini, A, Malusa M G and Garzanti, E. "MinSORTING: An Excel worksheet for modelling mineral grain-size distribution in sediments, with application to detrital geochronology and provenance studies." Computers & Geosciences 59 (2013): 90-97.

Garzanti, E, Ando, S and Vezzoli, G. "Settling equivalence of detrital minerals and grain-size dependence of sediment composition." Earth and Planetary Science Letters 273.1 (2008): 138-151.

See Also

minsorting

Examples

```
data(endmembers,densities)
ophiolite <- subset(endmembers,select="ophiolite")
plot(minsorting(ophiolite,densities,by=0.05))
```

get.f

Calculate the largest fraction that is likely to be missed

Description

For a given sample size, returns the largest fraction which has been sampled with $(1-p) \times 100$ % likelihood.

Usage

```
get.f(n, p = 0.05)
```

Arguments

n	the number of grains in the detrital sample
p	the required level of confidence

Value

the largest fraction that is sampled with at least $(1-p) \times 100\%$ certainty

References

Vermeesch, Pieter. "How many grains are needed for a provenance study?." Earth and Planetary Science Letters 224.3 (2004): 441-451.

Examples

```
print(get.f(60))
print(get.f(117))
```

`get.n`

Calculate the number of grains required to achieve a desired level of sampling resolution

Description

Returns the number of grains that need to be analysed to decrease the likelihood of missing any fraction greater than a given size below a given level.

Usage

```
get.n(p = 0.05, f = 0.05)
```

Arguments

<code>p</code>	the probability that all <code>n</code> grains in the sample have missed at least one fraction of size <code>f</code>
<code>f</code>	the size of the smallest resolvable fraction ($0 < f < 1$)
<code>n</code> ,	the number of grains in the sample

Value

the number of grains needed to reduce the chance of missing at least one fraction `f` of the total population to less than `p`

References

Vermeesch, Pieter. "How many grains are needed for a provenance study?." Earth and Planetary Science Letters 224.3 (2004): 441-451.

Examples

```
# number of grains required to be 99% that no fraction greater than 5% was missed:
print(get.n(0.01))
# number of grains required to be 90% that no fraction greater than 10% was missed:
print(get.n(p=0.1, f=0.1))
```

<code>get.p</code>	<i>Calculate the probability of missing a given population fraction</i>
--------------------	---

Description

For a given sample size, returns the likelihood of missing any fraction greater than a given size

Usage

```
get.p(n, f = 0.05)
```

Arguments

<code>n</code>	the number of grains in the detrital sample
<code>f</code>	the size of the smallest resolvable fraction ($0 < f < 1$)

Value

the probability that all `n` grains in the sample have missed at least one fraction of size `f`

References

Vermeesch, Pieter. "How many grains are needed for a provenance study?." *Earth and Planetary Science Letters* 224.3 (2004): 441-451.

Examples

```
print(get.p(60))
print(get.p(117))
```

GPA	<i>Generalised Procrustes Analysis of configurations</i>
-----	--

Description

Given a number of (2D) configurations, this function uses a combination of transformations (reflections, rotations, translations and scaling) to find a 'consensus' configuration which best matches all the component configurations in a least-squares sense.

Usage

```
GPA(X, scale = TRUE)
```

Arguments

<code>X</code>	a list of dissimilarity matrices
<code>scale</code>	boolean flag indicating if the transformation should include the scaling operation

Value

a two column vector with the coordinates of the group configuration

See Also

procrustes

indscal

Individual Differences Scaling of provenance data

Description

Performs 3-way Multidimensional Scaling analysis using Carroll and Chang (1970)'s INdividual Differences SCALing method as implemented using De Leeuw and Mair (2011)'s stress majorization algorithm.

Usage

```
indscal(..., type = "ordinal")
```

Arguments

... a sequence of datasets of class `distributional` or `compositional`
type is either "ratio" or "ordinal"

Value

an object of class `INDSCAL`, i.e. a list containing the following items:

delta: Observed dissimilarities

obsdiss: List of observed dissimilarities, normalized

confdiss: List of configuration dissimilarities

conf: List of matrices of final configurations

gspace: Joint configurations aka group stimulus space

cweights: Configuration weights

stress: Stress-1 value

spp: Stress per point

sps: Stress per subject (matrix)

ndim: Number of dimensions

model: Type of smacof model

niter: Number of iterations

nobj: Number of objects

Author(s)

Jan de Leeuw and Patrick Mair

References

de Leeuw, J., & Mair, P. (2009). Multidimensional scaling using majorization: The R package smacof. Journal of Statistical Software, 31(3), 1-30, < <http://www.jstatsoft.org/v31/i03/>>

Examples

```
data(Namib)
plot(indscal(Namib$DZ,Namib$HM))
```

KDE

Create a kernel density estimate

Description

Turns a vector of numbers into an object of class KDE using a combination of the Botev (2010) bandwidth selector and the Abramson (1982) adaptive kernel bandwidth modifier.

Usage

```
KDE(x, from = NA, to = NA, bw = NA, adaptive = TRUE, log = FALSE,
    n = 512, ...)
```

Arguments

x	a vector of numbers
from	minimum age of the time axis. If NULL, this is set automatically
to	maximum age of the time axis. If NULL, this is set automatically
bw	the bandwidth of the KDE. If NULL, bw will be calculated automatically using <code>botev()</code>
adaptive	boolean flag controlling if the adaptive KDE modifier of Abramson (1982) is used
log	transform the ages to a log scale if TRUE
n	horizontal resolution of the density estimate
...	optional arguments to be passed on to density

Value

an object of class KDE, i.e. a list containing the following items:

x: horizontal plot coordinates

y: vertical plot coordinates

bw: the base bandwidth of the density estimate

ages: the data values from the input to the KDE function

See Also

KDEs

Examples

```
data(Namib)
samp <- Namib$DZ$x[['N1']]
dens <- KDE(samp,0,3000,kernel="epanechnikov")
plot(dens)
```

KDEs

*Generate an object of class KDEs***Description**

Convert a dataset of class distributional into an object of class KDEs for further processing by the summaryplot function.

Usage

```
KDEs(x, from = NA, to = NA, bw = NA, samebandwidth = TRUE,
      adaptive = TRUE, normalise = FALSE, log = FALSE, n = 512, ...)
```

Arguments

x	an object of class distributional
from	minimum limit of the x-axis.
to	maximum limit of the x-axis.
bw	the bandwidth of the kernel density estimates. If bw = NA, the bandwidth will be set automatically using botev()
samebandwidth	boolean flag indicating whether the same bandwidth should be used for all samples. If samebandwidth = TRUE and bw = NULL, then the function will use the median bandwidth of all the samples.
adaptive	boolean flag switching on the adaptive bandwidth modifier of Abramson (1982)
normalise	boolean flag indicating whether or not the KDEs should all integrate to the same value.
log	boolean flag indicating whether the data should be plotted on a logarithmic scale.
n	horizontal resolution of the density estimates
...	optional parameters to be passed on to density

Value

an object of class KDEs, i.e. a list containing the following items:

kdes: a named list with objects of class KDE

from: the beginning of the common time scale

to: the end of the common time scale

themax: the maximum probability density of all the KDEs

pch: the plot symbol to be used by plot.KDEs

xlabel: the x-axis label to be used by plot.KDEs

See Also

KDE

Examples

```
data(Namib)
KDEs <- KDEs(Namib$DZ, 0, 3000, pch=NA)
summaryplot(KDEs, ncol=3)
```

KS.diss

Kolmogorov-Smirnov dissimilarity

Description

Returns the Kolmogorov-Smirnov dissimilarity between two samples

Usage

```
KS.diss(x, y)
```

Arguments

x the first sample as a vector

y the second sample as a vector

Value

a scalar value representing the maximum vertical distance between the two cumulative distributions

Examples

```
data(Namib)
print(KS.diss(Namib$DZ$x[['N1']], Namib$DZ$x[['T8']]))
```

Kuiper.diss	<i>Kuiper dissimilarity</i>
-------------	-----------------------------

Description

Returns the Kuiper dissimilarity between two samples

Usage

```
Kuiper.diss(x, y)
```

Arguments

x	the first sample as a vector
y	the second sample as a vector

Value

a scalar value representing the sum of the maximum vertical distances above and below the cumulative distributions of x and y

Examples

```
data(Namib)
print(Kuiper.diss(Namib$DZ$x[['N1']], Namib$DZ$x[['T8']]))
```

lines.ternary	<i>Ternary line plotting</i>
---------------	------------------------------

Description

Add lines to an existing ternary diagram

Usage

```
## S3 method for class 'ternary'
lines(x, ...)
```

Arguments

x	an object of class ternary, or a three-column data frame or matrix
...	optional arguments to the generic lines function

Examples

```
tern <- ternary(Namib$PT, 'Q', c('KF', 'P'), c('Lm', 'Lv', 'Ls'))
plot(tern, pch=21, bg='red', labels=NULL)
middle <- matrix(c(0.01, 0.49, 0.01, 0.49, 0.98, 0.02), 2, 3)
lines(ternary(middle))
```

MDS

Multidimensional Scaling

Description

Performs classical or nonmetric Multidimensional Scaling analysis of provenance data

Usage

```
MDS(x, ...)

## Default S3 method:
MDS(x, fn, classical = FALSE, k = 2,
    bootstrap = FALSE, nb = 10, ...)

## S3 method for class 'compositional'
MDS(x, classical = FALSE, k = 2,
    bootstrap = FALSE, nb = 10, ...)

## S3 method for class 'counts'
MDS(x, classical = FALSE, k = 2, bootstrap = FALSE,
    nb = 10, ...)

## S3 method for class 'distributional'
MDS(x, classical = FALSE, k = 2,
    bootstrap = FALSE, nb = 10, ...)

## S3 method for class 'diss'
MDS(x, classical = FALSE, k = 2, ...)
```

Arguments

x	an object of class <code>distributional</code> , <code>compositional</code> or <code>diss</code>
...	optional arguments to be passed onto <code>diss</code> (if x is of class <code>compositional</code> or <code>distributional</code>) or onto <code>cmdscale</code> or <code>isoMDS</code> (if x is of class <code>dist</code>).
classical	boolean flag indicating whether classical (TRUE) or nonmetric (FALSE) MDS should be used
k	the desired dimensionality of the solution
bootstrap	resample the data to calculate confidence polygons for the MDS configuration
nb	number of bootstrap resamples

Value

an object of class MDS, i.e. a list containing the following items:

- points: a two column vector of the fitted configuration
- classical: a boolean flag indicating whether the MDS configuration was obtained by classical (TRUE) or nonmetric (FALSE) MDS.
- diss: the dissimilarity matrix used for the MDS analysis
- stress: (only if classical=TRUE) the final stress achieved (in percent)

Examples

```
data(Namib)
plot(MDS(Namib$Major,classical=TRUE))
```

minsorting

Assess settling equivalence of detrital components

Description

Models grain size distribution of minerals and rock fragments of different densities

Usage

```
minsorting(X, dens, sname = NULL, phi = 2, sigmaphi = 1,
  medium = "freshwater", from = -2.25, to = 5.5, by = 0.25)
```

Arguments

X	an object of class compositional
dens	a vector of mineral and rock densities
sname	sample name if unspecified, the first sample of the dataset will be used
phi	the mean grain size of the sample in Krumbein's phi units
sigmaphi	the standard deviation of the grain size distribution, in phi units
medium	the transport medium, one of either "air", "freshwater" or "seawater"
from	the minimum grain size to be evaluated, in phi units
to	the maximum grain size to be evaluated, in phi units
by	the grain size interval of the output table, in phi units

Value

an object of class minsorting, i.e. a list with two tables:

- mfract: the grain size distribution of each mineral (sum of the columns = 1)
- mcomp: the composition of each mineral (sum of the rows = 1)

Author(s)

Alberto Resentini and Pieter Vermeesch

References

Resentini, A, Malusa, M G and Garzanti, E. "MinSORTING: An Excel worksheet for modelling mineral grain-size distribution in sediments, with application to detrital geochronology and provenance studies." *Computers & Geosciences* 59 (2013): 90-97.

Garzanti, E, Ando, S and Vezzoli, G. "Settling equivalence of detrital minerals and grain-size dependence of sediment composition." *Earth and Planetary Science Letters* 273.1 (2008): 138-151.

See Also

restore

Examples

```
data(endmembers,densities)
distribution <- minsorting(endmembers,densities,sname='ophiolite',phi=2,
                           sigmaphi=1,medium="seawater",by=0.05)
plot(distribution,cumulative=FALSE)
```

Namib

An example dataset

Description

A large dataset of provenance data from Namibia comprised of 14 sand samples from the Namib Sand Sea and 2 samples from the Orange River.

Details

Namib is a list containing the following 6 items:

DZ: a distributional dataset containing the zircon U-Pb ages for ca. 100 grains from each sample, as well as their (1-sigma) analytical uncertainties.

PT: a compositional dataset with the bulk petrography of the samples, i.e. the quartz ('Q'), K-feldspar ('KF'), plagioclase ('P'), and lithic fragments of metamorphic ('Lm'), volcanic ('Lv') and sedimentary ('Ls') origin.

HM: a compositional dataset containing the heavy mineral composition of the samples, comprised of zircon ('zr'), tourmaline ('tm'), rutile ('rt'), Ti-oxides ('TiOx'), titanite ('sph'), apatite ('ap'), epidote ('ep'), garnet ('gt'), staurolite ('st'), andalusite ('and'), kyanite ('ky'), sillimanite ('sil'), amphibole ('amp'), clinopyroxene ('cpx') and orthopyroxene ('opx').

PTHM: a compositional dataset combining the variables contained in PT and HM plus 'mica', 'opaques', 'turbids' and 'other' transparent heavy minerals ('LgM'), normalised to 100.

Major: a compositional dataset listing the concentrations (in wt TiO₂, P₂O₅ and MnO).

Trace: a compositional data listing the concentrations (in ppm) of Rb, Sr, Ba, Sc, Y, La, Ce, Pr, Nd, Sm, Gd, Dy, Er, Yb, Th, U, Zr, Hf, V, Nb, Cr, Co, Ni, Cu, Zn, Ga and Pb.

Author(s)

Pieter Vermeesch and Eduardo Garzanti

References

Vermeesch, P. and Garzanti, E., Making geological sense of 'Big Data' in sedimentary provenance analysis, *Chemical Geology* 409 (2015) 20-27

Examples

```
data(Namib)
samp <- Namib$DZ$x[['N1']]
dens <- KDE(samp,0,3000)
plot(dens)
```

PCA

Principal Component Analysis

Description

Performs PCA of compositional data using a centred logratio distance

Usage

```
PCA(x, ...)
```

Arguments

x an object of class `compositional`
 ... optional arguments to R's `princomp` function

Value

an object of classes `PCA`, which is synonymous to the stats packages' `prcomp` class.

Examples

```
data(Namib)
plot(MDS(Namib$Major,classical=TRUE))
dev.new()
plot(PCA(Namib$Major),asp=1)
print("This example demonstrates the equivalence of classical MDS and PCA")
```

plot.CA	<i>Point-counting biplot</i>
---------	------------------------------

Description

Plot the results of a correspondence analysis as a biplot

Usage

```
## S3 method for class 'CA'
plot(x, levels = NULL, labelcol = c("black", "blue"),
      vectorcol = "red", ...)
```

Arguments

x	an object of class CA
levels	a vector of length nrow(dat\$x) with values that are to be used for the colour scale
labelcol	two element vector with the colours that are to be assigned to the labels of the samples corresponding to the minimum and maximum value of levels. If levels==NULL, then the first item of the vector is used for all sample labels.
vectorcol	colour of the vector loadings for the variables
...	optional arguments of the generic biplot function

See Also

CA

Examples

```
data(Namib)
plot(CA(Namib$PT))
```

plot.compositional	<i>Plot a pie chart</i>
--------------------	-------------------------

Description

Plots an object of class compositional as a pie chart

Usage

```
## S3 method for class 'compositional'
plot(x, sname, annotate = TRUE, colmap = NULL,
      ...)
```

Arguments

x	an object of class <code>compositional</code>
sname	the sample name
annotate	a boolean flag controlling if the pies of the pie-chart should be labeled
colmap	an optional string with the name of one of R's built-in colour palettes (e.g., <code>heat.colors</code> , <code>terrain.colors</code> , <code>topo.colors</code> , <code>cm.colors</code>), which are to be used for plotting the data.
...	optional parameters to be passed on to the graphics object

Examples

```
data(Namib)
plot(Namib$Major, 'N1', colmap='heat.colors')
```

plot.distributional	<i>Plot continuous data as histograms or cumulative age distributions</i>
---------------------	---

Description

Plot one or several samples from a `distributional` dataset as a histogram or Cumulative Age Distributions (CAD).

Usage

```
## S3 method for class 'distributional'
plot(x, snames = NULL, annotate = TRUE,
     CAD = FALSE, pch = NA, verticals = TRUE, colmap = NULL, ...)
```

Arguments

x	an object of class <code>distributional</code>
snames	a string or a vector of string with the names of the samples that need plotting if <code>snames</code> is a vector, then the function will default to a CAD.
annotate	boolean flag indicating whether the x- and y-axis should be labeled
CAD	boolean flag indicating whether the data should be plotted as a cumulative age distribution or a histogram. For multi-sample plots, the function will override this value with <code>TRUE</code> .
pch	an optional symbol to mark the sample points along the CAD
verticals	boolean flag indicating if the horizontal lines of the CAD should be connected by vertical lines
colmap	an optional string with the name of one of R's built-in colour palettes (e.g., <code>heat.colors</code> , <code>terrain.colors</code> , <code>topo.colors</code> , <code>cm.colors</code>), which are to be used for plotting the data.
...	optional arguments to the generic plot function

Examples

```
data(Namib)
plot(Namib$DZ,c('N1','N2'))
```

plot.GPA

Plot a Procrustes configuration

Description

Plots the group configuration of a Generalised Procrustes Analysis

Usage

```
## S3 method for class 'GPA'
plot(x, pch = NA, pos = NULL, col = "black",
     bg = "white", cex = 1, ...)
```

Arguments

x	an object of class GPA
pch	plot symbol
pos	position of the sample labels relative to the plot symbols if pch != NA
col	plot colour (may be a vector)
bg	background colour (may be a vector)
cex	relative size of plot symbols
...	optional arguments to the generic plot function

See Also

procrustes

Examples

```
data(Namib)
GPA <- procrustes(Namib$DZ,Namib$HM)
coast <- c('N1','N2','N3','N10','N11','N12','T8','T13')
snames <- names(Namib$DZ)
bgcol <- rep('yellow',length(snames))
bgcol[which(snames %in% coast)] <- 'red'
plot(GPA,pch=21,bg=bgcol)
```

plot.INDSCAL	<i>Plot an INDSCAL group configuration and source weights</i>
--------------	---

Description

Given an object of class INDSCAL, generates two plots: the group configuration and the subject weights. Together, these describe a 3-way MDS model.

Usage

```
## S3 method for class 'INDSCAL'
plot(x, asp = 1, pch = NA, pos = NULL,
     col = "black", bg = "white", cex = 1, xlab = "X", ylab = "Y",
     xaxt = "n", yaxt = "n", ...)
```

Arguments

x	an object of class INDSCAL
asp	the aspect ratio of the plot
pch	plot symbol (may be a vector)
pos	position of the sample labels relative to the plot symbols if pch != NA
col	plot colour (may be a vector)
bg	background colour (may be a vector)
cex	relative size of plot symbols
xlab	a string with the label of the x axis
ylab	a string with the label of the y axis
xaxt	if = 'y', adds ticks to the x axis
yaxt	if = 'y', adds ticks to the y axis
...	optional arguments to the generic plot function

See Also

indscal

Examples

```
data(Namib)
coast <- c('N1','N2','N3','N10','N11','N12','T8','T13')
snames <- names(Namib$DZ)
pch <- rep(21,length(snames))
pch[which(snames %in% coast)] <- 22
plot(indscal(Namib$DZ,Namib$HM),pch=pch)
```

plot.KDE	<i>Plot a kernel density estimate</i>
----------	---------------------------------------

Description

Plots an object of class KDE

Usage

```
## S3 method for class 'KDE'
plot(x, pch = "|", xlab = "age [Ma]", ylab = "", ...)
```

Arguments

x	an object of class KDE
pch	the symbol used to show the samples. May be a vector. Set pch = NA to turn them off.
xlab	the label of the x-axis
ylab	the label of the y-axis
...	optional parameters to be passed on to the graphics object

See Also

KDE

Examples

```
data(Namib)
samp <- Namib$DZ$x[['N1']]
dens <- KDE(samp, from=0, to=3000)
plot(dens)
```

plot.KDEs	<i>Plot one or more kernel density estimates</i>
-----------	--

Description

Plots an object of class KDEs

Usage

```
## S3 method for class 'KDEs'
plot(x, sname = NA, annotate = TRUE, pch = "|", ...)
```

Arguments

x	an object of class KDEs
sname	optional sample name. If sname=NA, all samples are shown on a summary plot
annotate	add a time axis?
pch	symbol to be used to mark the sample points along the x-axis. Change to NA to omit.
...	optional parameters to be passed on to the summaryplot function

See Also

KDEs summaryplot

Examples

```
data(Namib)
kdes <- KDEs(Namib$DZ)
plot(kdes, ncol=2)
```

plot.MDS	<i>Plot an MDS configuration</i>
----------	----------------------------------

Description

Plots the coordinates of a multidimensional scaling analysis as an X-Y scatter plot or 'map' and, if x\$classical = FALSE, a Shepard plot.

Usage

```
## S3 method for class 'MDS'
plot(x, nnlines = FALSE, pch = NA, pos = NULL,
     cex = 1, col = "black", bg = "white", oma = rep(1, 4),
     mar = rep(2, 4), mgp = c(2, 1, 0), xpd = NA, ...)
```

Arguments

x	an object of class MDS
nnlines	if TRUE, draws nearest neighbour lines
pch	plot character (see ?plot for details). May be a vector.
pos	position of the sample labels relative to the plot symbols if pch != NA
cex	relative size of plot symbols (see ?par for details)
col	plot colour (may be a vector)
bg	background colour (may be a vector)
oma	A vector of the form c(bottom, left, top, right) giving the size of the outer margins in lines of text.

mar	A numerical vector of the form <code>c(bottom,left,top,right)</code> that gives the number of lines of margin to be specified on the four sides of the plot.
mgp	The margin line (in mex units) for the axis title, axis labels and axis line. See <code>?par</code> for further details.
xpd	A logical value or NA. See <code>?par</code> for further details.
...	optional arguments to the generic plot function

See Also

MDS

Examples

```
data(Namib)
mds <- MDS(Namib$DZ)
coast <- c('N1','N2','N3','N10','N11','N12','T8','T13')
snames <- names(Namib$DZ)
bgcol <- rep('yellow',length(snames))
bgcol[which(snames %in% coast)] <- 'red'
plot(mds,pch=21,bg=bgcol)
```

plot.minsorting	<i>Plot inferred grain size distributions</i>
-----------------	---

Description

Plot the grain size distributions of the different minerals under consideration

Usage

```
## S3 method for class 'minsoring'
plot(x, cumulative = FALSE, components = NULL,
     ...)
```

Arguments

x	an object of class minsoring
cumulative	boolean flag indicating whether the grain size distribution should be plotted as a density or cumulative probability curve.
components	string or list of strings with the names of a subcomposition that needs plotting
...	optional parameters to be passed on to <code>graphics::matplot</code> (see <code>?par</code> for details)

See Also

minsoring

Examples

```
data(endmembers,densities)
OPH <- subset(endmembers,select="ophiolite")
distribution <- minsorting(OPH,densities,phi=2,sigmaphi=1,
                           medium="air",by=0.05)
plot(distribution,components=c('F','px','opaques'))
```

plot.PCA

*Compositional biplot***Description**

Plot the results of a principal components analysis as a biplot

Usage

```
## S3 method for class 'PCA'
plot(x, levels = NULL, labelcol = c("black", "blue"),
     vectorcol = "red", choices = 1L:2L, scale = 1, pc.biplot = FALSE,
     ...)
```

Arguments

x	an object of class PCA
levels	a vector of length nrow(dat\$x) with values that are to be used for the colour scale
labelcol	two element vector with the colours that are to be assigned to the labels of the samples corresponding to the minimum and maximum value of levels. If levels==NULL, then the first item of the vector is used for all sample labels.
vectorcol	colour of the vector loadings for the variables
choices	see the help pages of the biplot function.
scale	see the help pages of the biplot function.
pc.biplot	see the help pages of the biplot function.
...	optional arguments of the generic biplot function

See Also

PCA

Examples

```
data(Namib)
plot(PCA(Namib$Major))
```

plot.ternary	<i>Plot a ternary diagram</i>
--------------	-------------------------------

Description

Plots triplets of compositional data on a ternary diagram

Usage

```
## S3 method for class 'ternary'
plot(x, type = "grid", pch = NA, pos = NULL,
      labels = names(x), showpath = FALSE, bg = NA,
      col = "cornflowerblue", ticks = seq(0, 1, 0.25), ticklength = 0.02,
      lty = 2, lwd = 1, ...)
```

Arguments

x	an object of class ternary, or a three-column data frame or matrix
type	adds annotations to the ternary diagram, one of either empty, grid, QFL.descriptive, QFL.folk or QFL.dickinson
pch	plot character, see ?par for details (may be a vector)
pos	position of the sample labels relative to the plot symbols if pch != NA
labels	vector of strings to be added to the plot symbols
showpath	if x has class SRDcorrected, and showpath==TRUE, the intermediate values of the SRD correction will be plotted on the ternary diagram as well as the final composition
bg	background colour for the plot symbols (may be a vector)
col	colour to be used for the background lines (if applicable)
ticks	vector of tick values between 0 and 1
ticklength	number between 0 and 1 to mark the length of the ticks
lty	line type for the annotations (see type)
lwd	line thickness for the annotations
...	optional arguments to the generic points function

See Also

ternary

Examples

```
data(Namib)
tern <- ternary(Namib$PT, 'Q', c('KF', 'P'), c('Lm', 'Lv', 'Ls'))
plot(tern, type='QFL.descriptive', pch=21, bg='red', labels=NULL)
```

points.ternary	<i>Ternary point plotting</i>
----------------	-------------------------------

Description

Add points to an existing ternary diagram

Usage

```
## S3 method for class 'ternary'
points(x, ...)
```

Arguments

x	an object of class ternary, or a three-column data frame or matrix
...	optional arguments to the generic points function

Examples

```
tern <- ternary(Namib$PT, 'Q', c('KF', 'P'), c('Lm', 'Lv', 'Ls'))
plot(tern, pch=21, bg='red', labels=NULL)
# add the geometric mean composition as a yellow square:
gmean <- ternary(exp(colMeans(log(tern$x))))
points(gmean, pch=22, bg='yellow')
```

procrustes	<i>Generalised Procrustes Analysis of provenance data</i>
------------	---

Description

Given a number of input datasets, this function performs an MDS analysis on each of these and the feeds the resulting configurations into the GPA() function.

Usage

```
procrustes(...)
```

Arguments

...	a sequence of datasets of classes distributional, n counts and compositional
-----	--

Value

an object of class GPA, i.e. a list containing the following items:
 points: a two column vector with the coordinates of the group configuration
 labels: a list with the sample names

Author(s)

Pieter Vermeesch

References

Gower, J.C. (1975). Generalized Procrustes analysis, *Psychometrika*, 40, 33-50.

See Also

GPA

Examples

```
data(Namib)
gpa <- procrustes(Namib$DZ,Namib$HM)
plot(gpa)
```

provenance

Menu-based interface for provenance

Description

For those less familiar with the syntax of the R programming language, the `provenance()` function provides a user-friendly way to access the most important functionality in the form of a menu-based query interface. Further details and examples are provided on <http://provenance.london-geochron.com>

`provenance` provides statistical tools to interpret large amounts of distributional (single grain analyses) and compositional (mineralogical and bulk chemical) data from the command line, or using a menu-based user interface.

Usage

```
provenance()
```

Details

A list of documented functions may be viewed by typing `help(package='provenance')`. Detailed instructions are provided at <http://provenance.london-geochron.com> and in the *Sedimentary Geology* paper by Vermeesch, Resentini and Garzanti (2016).

Author(s)

Pieter Vermeesch

Maintainer: Pieter Vermeesch <p.vermeesch@ucl.ac.uk>

References

Vermeesch, P., Resentini, A. and Garzanti, E., an R package for statistical provenance analysis, *Sedimentary Geology*, doi:10.1016/j.sedgeo.2016.01.009.

Vermeesch, P., Resentini, A. and Garzanti, E., 2016, An R package for statistical provenance analysis, *Sedimentary Geology*, 336, 14-25.

See Also

<http://provenance.london-geochron.com>

Useful links:

- <http://provenance.london-geochron.com>

radialplot

Visualise point-counting data on a radial plot

Description

Implementation of a graphical device developed by Rex Galbraith to display several estimates of the same quantity that have different standard errors.

Usage

```
radialplot(x, num = 1, den = 2, from = NA, to = NA, t0 = NA,
  sigdig = 2, show.numbers = FALSE, pch = 21, levels = NA,
  clabel = "", bg = c("white", "red"), title = TRUE, ...)
```

Arguments

x	an object of class counts
num	index or name of the numerator variable
den	index or name of the denominator variable
from	minimum limit of the radial scale
to	maximum limit of the radial scale
t0	central value
sigdig	the number of significant digits of the numerical values reported in the title of the graphical output.
show.numbers	boolean flag (TRUE to show sample numbers)
pch	plot character (default is a filled circle)
levels	a vector with additional values to be displayed as different background colours of the plot symbols.
clabel	label of the colour legend

<code>bg</code>	a vector of two background colours for the plot symbols. If <code>levels=NA</code> , then only the first colour is used. If <code>levels</code> is a vector of numbers, then <code>bg</code> is used to construct a colour ramp.
<code>title</code>	add a title to the plot?
<code>...</code>	additional arguments to the generic <code>points</code> function

Details

The radial plot (Galbraith, 1988, 1990) is a graphical device that was specifically designed to display heteroscedastic data, and is constructed as follows. Consider a set of dates $\{t_1, \dots, t_i, \dots, t_n\}$ and uncertainties $\{s[t_1], \dots, s[t_i], \dots, s[t_n]\}$. Define $z_i = z[t_i]$ to be a transformation of t_i (e.g., $z_i = \log[t_i]$), and let $s[z_i]$ be its propagated analytical uncertainty (i.e., $s[z_i] = s[t_i]/t_i$ in the case of a logarithmic transformation). Create a scatterplot of (x_i, y_i) values, where $x_i = 1/s[z_i]$ and $y_i = (z_i - z_o)/s[z_i]$, where z_o is some reference value such as the mean. The slope of a line connecting the origin of this scatterplot with any of the (x_i, y_i) s is proportional to z_i and, hence, the date t_i . These dates can be more easily visualised by drawing a radial scale at some convenient distance from the origin and annotating it with labelled ticks at the appropriate angles. While the angular position of each data point represents the date, its horizontal distance from the origin is proportional to the precision. Imprecise measurements plot on the left hand side of the radial plot, whereas precise age determinations are found further towards the right. Thus, radial plots allow the observer to assess both the magnitude and the precision of quantitative data in one glance.

References

- Galbraith, R.F., 1988. Graphical display of estimates having differing standard errors. *Technometrics*, 30(3), pp.271-281.
- Galbraith, R.F., 1990. The radial plot: graphical assessment of spread in ages. *International Journal of Radiation Applications and Instrumentation. Part D. Nuclear Tracks and Radiation Measurements*, 17(3), pp.207-214.
- Galbraith, R.F. and Laslett, G.M., 1993. Statistical models for mixed fission track ages. *Nuclear Tracks and Radiation Measurements*, 21(4), pp.459-470.

Examples

```
data(Namib)
radialplot(Namib$PT, components=c('Q', 'P'))
```

<code>read.compositional</code>	<i>Read a .csv file with compositional data</i>
---------------------------------	---

Description

Reads a data table containing compositional data (e.g. chemical concentrations)

Usage

```
read.compositional(fname, method = NULL, colmap = "rainbow", ...)
```

Arguments

fname	a string with the path to the .csv file
method	either "bray" (for the Bray-Curtis distance) or "aitchison" (for Aitchison's central logratio distance). If omitted, the function defaults to 'aitchison', unless there are zeros present in the data.
colmap	an optional string with the name of one of R's built-in colour palettes (e.g., heat.colors, terrain.colors, topo.colors, cm.colors), which are to be used for plotting the data.
...	optional arguments to the built-in read.csv function

Value

an object of class `compositional`, i.e. a list with the following items:

`x`: a data frame with the samples as rows and the categories as columns

`method`: either "aitchison" (for Aitchison's centred logratio distance) or "bray" (for the Bray-Curtis distance)

`colmap`: the colour map provided by the input argument

Examples

```
fname <- system.file("Major.csv", package="provenance")
Major <- read.compositional(fname)
plot(PCA(Major))
```

read.counts

Read a .csv file with point-counting data

Description

Reads a data table containing point-counting data (e.g. petrographic, heavy mineral, palaeontological or palynological data)

Usage

```
read.counts(fname, method = "chisq", colmap = "rainbow", ...)
```

Arguments

fname	a string with the path to the .csv file
method	either "chisq" (for the chi-square distance) or "bray" (for the Bray-Curtis distance)
colmap	an optional string with the name of one of R's built-in colour palettes (e.g., heat.colors, terrain.colors, topo.colors, cm.colors), which are to be used for plotting the data.
...	optional arguments to the built-in read.csv function

Value

an object of class `counts`, i.e. a list with the following items:

- `x`: a data frame with the samples as rows and the categories as columns
- `colmap`: the colour map provided by the input argument

Examples

```
fname <- system.file("HM.csv", package="provenance")
Major <- read.counts(fname)
#plot(PCA(HM))
```

<code>read.densities</code>	<i>Read a .csv file with mineral and rock densities</i>
-----------------------------	---

Description

Reads a data table containing densities to be used for hydraulic sorting corrections (minsorting and `srd` functions)

Usage

```
read.densities(fname, ...)
```

Arguments

<code>fname</code>	a string with the path to the .csv file
<code>...</code>	optional arguments to the built-in <code>read.csv</code> function

Value

a vector with mineral and rock densities

Examples

```
data(Namib, densities)
N8 <- subset(Namib$HM, select="N8")
distribution <- minsorting(N8, densities, phi=2, sigmaphi=1, medium="air", by=0.05)
plot(distribution)
```

read.distributional *Read a .csv file with continuous (detrital zircon) data*

Description

Reads a data table containing continuous data (e.g. detrital zircon ages)

Usage

```
read.distributional(fname, errorfile = NA, method = "KS",
  xlab = "age [Ma]", colmap = "rainbow", ...)
```

Arguments

fname	the path of a .csv file with the input data, arranged in columns.
errorfile	the (optional) path of a .csv file with the standard errors of the input data, arranged by column in the same order as fname. Must be specified if the data are to be compared with the Sircombe-Hazelton dissimilarity.
method	an optional string specifying the dissimilarity measure which should be used for comparing this with other datasets. Should be one of either "KS" (for Kolmogorov-Smirnov) or "SH" (for Sircombe and Hazelton). If method = "SH", then errorfile should be specified. If method = "SH" and errorfile is unspecified, then the program will default back to the Kolmogorov-Smirnov dissimilarity.
xlab	an optional string specifying the nature and units of the data. This string is used to label kernel density estimates.
colmap	an optional string with the name of one of R's built-in colour palettes (e.g., heat.colors, terrain.colors, topo.colors, cm.colors), which are to be used for plotting the data.
...	optional arguments to the built-in read.csv function

Value

an object of class `distributional`, i.e. a list with the following items:

x: a named list of vectors containing the numerical data for each sample

err: an (optional) named list of vectors containing the standard errors of x

method: either "KS" (for Kolmogorov-Smirnov), "Kuiper" (for the Kuiper statistic) or "SH" (for Sircombe Hazelton)

breaks: a vector with the locations of the histogram bin edges

xlab: a string containing the label to be given to the x-axis on all plots

colmap: the colour map provided by the input argument

Examples

```
agefile <- system.file("DZ.csv",package="provenance")
errfile <- system.file("DZerr.csv",package="provenance")
DZ <- read.distributional(agefile,errfile)
plot(KDE(DZ$x$N1))
```

restore

Undo the effect of hydraulic sorting

Description

Restore the detrital composition back to a specified source rock density (SRD)

Usage

```
restore(X, dens, target = 2.71)
```

Arguments

X	an object of class <code>compositional</code>
dens	a vector of rock and mineral densities
target	the target density (in g/cm ³)

Value

an object of class `SRDcorrected`, i.e. an object of class `compositional` which is a daughter of class `compositional` containing the restored composition, plus one additional member called `restoration`, containing the intermediate steps of the SRD correction algorithm.

Author(s)

Alberto Resentini and Pieter Vermeesch

References

Garzanti E, Ando, S and Vezzoli, G. "Settling equivalence of detrital minerals and grain-size dependence of sediment composition." *Earth and Planetary Science Letters* 273.1 (2008): 138-151.

See Also

`minsorting`

Examples

```
data(Namib,densities)
rescomp <- restore(Namib$PTHM,densities,2.71)
HMcomp <- c("zr","tm","rt","sph","ap","ep","gt",
            "st","amp","cpx","opx")
amcomp <- amalgamate(rescomp,Plag="P",HM=HMcomp,Opq="opaques")
plot(ternary(amcomp),showpath=TRUE)
```

SH.diss	<i>Sircombe and Hazelton distance</i>
---------	---------------------------------------

Description

Calculates Sircombe and Hazelton's L2 distance between the Kernel Functional Estimates (KFEs, not to be confused with Kernel Density Estimates!) of two samples with specified analytical uncertainties

Usage

```
SH.diss(x, i, j, c.con = 0)
```

Arguments

- x an object of class `distributional`
- i index of the first sample
- j index of the second sample
- c.con smoothing bandwidth of the kernel functional estimate

Value

a scalar value expressing the L2 distance between the KFEs of samples i and j

Author(s)

Keith Sircombe and Martin Hazelton

References

Sircombe, K. N., and M. L. Hazelton. "Comparison of detrital zircon age distributions by kernel functional estimation." *Sedimentary Geology* 171.1 (2004): 91-111.

See Also

KS.diss

Examples

```

datfile <- system.file("DZ.csv",package="provenance")
errfile <- system.file("DZerr.csv",package="provenance")
DZ <- read.distributional(datfile,errfile)
d <- SH.diss(DZ,1,2)
print(d)

```

subset

*Get a subset of provenance data***Description**

Return a subset of provenance data according to some specified indices

Usage

```

## S3 method for class 'distributional'
subset(x, subset = NULL, select = NULL, ...)

## S3 method for class 'compositional'
subset(x, subset = NULL, components = NULL,
       select = NULL, ...)

## S3 method for class 'counts'
subset(x, subset = NULL, components = NULL,
       select = NULL, ...)

```

Arguments

x	an object of class distributional
subset	logical expression indicating elements or rows to keep: missing values are taken as false.
select	a vector of sample names
...	optional arguments for the generic subset function
components	categories to keep

Value

an object of class distributional

See Also

read.distributional

Examples

```
data(Namib)
coast <- c("N1","N2","T8","T13","N12","N13")
ZTRcoast <- subset(Namib$HM,select=coast,components=c('gt','cpx','ep'))
DZcoast <- subset(Namib$DZ,select=coast)
summaryplot(ZTRcoast,KDEs(DZcoast),ncol=2)
```

summaryplot	<i>Joint plot of several provenance datasets</i>
-------------	--

Description

Arranges kernel density estimates and pie charts in a grid format

Usage

```
summaryplot(..., ncol = 1, pch = NA)
```

Arguments

- ... a sequence of datasets of class compositional, KDEs, or distributional
- ncol the number of columns
- pch (optional) symbol to be used to mark the sample points along the x-axis of the KDEs (if appropriate).

Value

a summary plot of all the data comprised of KDEs for the datasets of class KDEs, pie charts for those of class compositional and histograms for those of class distributional.

See Also

KDEs

Examples

```
data(Namib)
KDEs <- KDEs(Namib$DZ,0,3000)
summaryplot(KDEs,Namib$HM,Namib$PT,ncol=2)
```

ternary	<i>Define a ternary composition</i>
---------	-------------------------------------

Description

Create an object of class ternary

Usage

```
ternary(X, x = 1, y = 2, z = 3)
```

Arguments

X	an object of class compositional OR a matrix or data frame with numerical data
x	string/number or a vector of strings/numbers indicating the variables/indices making up the first subcomposition of the ternary system.
y	second (set of) variables
z	third (set of) variables

Value

an object of class ternary, i.e. a list containing:

x: a three column matrix (or vector) of ternary compositions.

and (if X is of class SRDcorrected)

restoration: a list of intermediate ternary compositions inherited from the SRD correction

See Also

restore

Examples

```
data(Namib)
tern <- ternary(Namib$PT,c('Q'),c('KF','P'),c('Lm','Lv','Ls'))
plot(tern,type="QFL")
```

ternary.ellipse	<i>Ternary confidence ellipse</i>
-----------------	-----------------------------------

Description

plot a $100(1 - \alpha)\%$ confidence region around the data or around its mean.

Usage

```
ternary.ellipse(x, ...)  
  
## Default S3 method:  
ternary.ellipse(x, alpha = 0.05, population = TRUE,  
  ...)  
  
## S3 method for class 'compositional'  
ternary.ellipse(x, alpha = 0.05,  
  population = TRUE, ...)  
  
## S3 method for class 'counts'  
ternary.ellipse(x, alpha = 0.05, population = TRUE,  
  ...)
```

Arguments

x	an object of class ternary
...	optional formatting arguments
alpha	cutoff level for the confidence ellipse
population	show the standard deviation of the entire population or the standard error of the mean?

Examples

```
data(Namib)  
tern <- ternary(Namib$Major, 'CaO', 'Na2O', 'K2O')  
plot(tern)  
ternary.ellipse(tern)
```

text.ternary	<i>Ternary text plotting</i>
--------------	------------------------------

Description

Add text an existing ternary diagram

Usage

```
## S3 method for class 'ternary'
text(x, labels = 1:nrow(x$x), ...)
```

Arguments

x	an object of class ternary, or a three-column data frame or matrix
labels	a character vector or expression specifying the text to be written
...	optional arguments to the generic text function

Examples

```
data(Namib)
tern <- ternary(Namib$Major, 'CaO', 'Na2O', 'K2O')
plot(tern, pch=21, bg='red', labels=NULL)
# add the geometric mean composition as a text label:
gmean <- ternary(exp(colMeans(log(tern$x))))
text(gmean, labels='geometric mean')
```


Index

`_PACKAGE` (provenance), 36

ALR, 3

`amalgamate`, 4

`as.acomp`, 5

`as.compositional`, 5

`as.counts`, 6

`as.data.frame`, 7

`biplot`, 26, 33

`botev`, 7

`bray.diss`, 8

CA, 9

`central`, 9

CLR, 10

`combine`, 11

`densities`, 12

`diss`, 13

`endmembers`, 13

`get.f`, 14

`get.n`, 15

`get.p`, 16

GPA, 16

`indscal`, 17

KDE, 18

KDEs, 19

`KS.diss`, 20

`Kuiper.diss`, 21

`lines` (`points.ternary`), 35

`lines.ternary`, 21

MDS, 22

`minsorting`, 23

Namib, 24

PCA, 25

`plot.CA`, 26

`plot.compositional`, 26

`plot.distributional`, 27

`plot.GPA`, 28

`plot.INDSCAL`, 29

`plot.KDE`, 30

`plot.KDEs`, 30

`plot.MDS`, 31

`plot.minsorting`, 32

`plot.PCA`, 33

`plot.ternary`, 34

`points.ternary`, 35

`procrustes`, 35

provenance, 36

`provenance-package` (provenance), 36

`radialplot`, 37

`read.compositional`, 38

`read.counts`, 39

`read.densities`, 40

`read.distributional`, 41

`restore`, 42

SH.diss, 43

`subset`, 44

`summaryplot`, 45

ternary, 46

`ternary.ellipse`, 47

`text` (`points.ternary`), 35

`text.ternary`, 48