Momentum-based Optimization Techniques in Machine Learning

Pham Viet Hung



Pham Viet Hung Presentation 1 / 16

Content

- Overview
 - ► Estimation/Learning vs. Pure Optimization
 - ► Gradient-Based Optimization
- ► Momentum-based methods
 - Vanila SGD
 - ► SGD with Polyak Momentum
 - SGD with Nesterov Momentum

Pham Viet Hung Presentation 2 / 16

But before digging into the topic...

https://www.youtube.com/watch?v=dQ4jUFmp7hQ

Pham Viet Hung Presentation 3 / 16

Overview

Pham Viet Hung Presentation 4 / 16

Estimation/Learning vs. Pure Optimization

- ▶ Stats: Estimation; CS: Learning Meaning: using data to estimate an unknown quantity (Wasserman, 2004)
- ▶ In ML/DL, optimization is a tool to achieve the best possible P (some performance metric) defined w.r.t the test set; hard to track it \Longrightarrow optimize P indirectly through a cost function $J(\theta)$.
- ▶ In pure optimization, care about only $J(\theta)$
- ▶ Cost Function: $J(\theta) = \mathbb{E}_{(x,y) \sim \hat{p}_{\mathsf{data}}} [L(f(x;\theta),y)]; \quad \hat{p}_{\mathsf{data}}$: empirical distro
- Empirical Risk Minimization (ERM):

$$\mathbb{E}_{(x,y) \sim \hat{p}_{\mathsf{data}}} \left[L(f(x;\theta), y) \right] = \frac{1}{n} \sum_{i=1}^{n} L(f(x^{(i)}; \theta), y^{(i)}) \tag{1}$$

Pham Viet Hung Presentation 5 / 16

Gradient-based Optimization

- ► First-order optimization algorithms: Using variants of gradient-only algorithm. Mostly some variants of gradient descent algorithms.
- ➤ Second-order optimization algorithms: Algorithms that make use of Hessian matrix (a.k.a second derivatives). *Problem*: Poor conditioning of the Hessian matrix.
- ► The above-mentioned optimization techniques are mostly used in convex optimization. In Deep Learning, mostly as a subroutine of some Deep Learning algorithms.
- ▶ Usually variants of Stochastic Gradient Descent optimization (usually with minibatch) is used in Machine Learning (ML) and Deep Learning (DL).

Vanila SGD SGD with Polyak Momentum SGD with Nesterov Momentum

Momentum-based methods

Pham Viet Hung Presentation 7 / 16

Vanila SGD (1)

- SGD (with minibatch) and its flavours are the most used optimization methods for ML problem.
- ▶ The step length/learning rate is defined as fixed in SGD, but in practice we need a gradually decreasing values \Longrightarrow denote it as ϵ_k
- ► The two sufficient conditions to guarantee convergence of SGD:

$$\sum_{k=1}^{\infty} \epsilon_k = \infty \tag{2}$$

$$\sum_{k=1}^{\infty} \epsilon_k^2 \le \infty \tag{3}$$

Vanila SGD (2)

Algorithm 8.1 Stochastic gradient descent (SGD) update at training iteration k

```
Require: Learning rate \epsilon_k

Require: Initial parameter \boldsymbol{\theta}

while stopping criterion not met do

Sample a minibatch of m examples from the training set \{\boldsymbol{x}^{(1)}, \dots, \boldsymbol{x}^{(m)}\} with corresponding targets \boldsymbol{y}^{(i)}.

Compute gradient estimate: \hat{\boldsymbol{g}} \leftarrow +\frac{1}{m} \nabla_{\boldsymbol{\theta}} \sum_{i} L(f(\boldsymbol{x}^{(i)}; \boldsymbol{\theta}), \boldsymbol{y}^{(i)}).

Apply update: \boldsymbol{\theta} \leftarrow \boldsymbol{\theta} - \epsilon \hat{\boldsymbol{g}}.

end while
```

Figure: Algorithm of Vanila SGD (Goodfellow et al., 2016)

Pham Viet Hung Presentation 9 / 16

SGD with Polyak Momentum (1)

- Sometimes learning with SGD is slow.
- ▶ Polyak (1964) proposes a method to accelerate learning in a high curvature, small and consistent/noisy gradient environment.
- ▶ The key driver is the **velocity** variable *v*

Pham Viet Hung Presentation 10 / 16

SGD with Polyak Momentum (2)

Algorithm 8.2 Stochastic gradient descent (SGD) with momentum

Require: Learning rate ϵ , momentum parameter α

Require: Initial parameter θ , initial velocity v

while stopping criterion not met do

Sample a minibatch of m examples from the training set $\{x^{(1)}, \dots, x^{(m)}\}$ with corresponding targets $y^{(i)}$.

Compute gradient estimate: $\mathbf{g} \leftarrow \frac{1}{m} \nabla_{\boldsymbol{\theta}} \sum_{i} L(f(\mathbf{x}^{(i)}; \boldsymbol{\theta}), \mathbf{y}^{(i)}).$

Compute velocity update: $\mathbf{v} \leftarrow \alpha \mathbf{v} - \epsilon \mathbf{g}$.

Apply update: $\theta \leftarrow \theta + v$.

end while

Figure: Algorithm of SGD w/ Polyak momentum (Goodfellow et al., 2016)

Pham Viet Hung Presentation 11 / 16

SGD with Nesterov Momentum (1)

- ▶ Based on Nesterov's (1983, 2004) accelerated method, Sutskever (2013) in his PhD thesis proposed a variant of momentum-based SGD optimization technique
- ▶ Difference between Nesterov and Polyak momentum is the evaluation point of the gradient.
- With Nesterov momentum, the evaluation of the the gradient occurs after the current velovity is applied.

Pham Viet Hung Presentation 12 / 16

SGD with Nesterov Momentum (2)

```
Algorithm 8.3 Stochastic gradient descent (SGD) with Nesterov momentum
```

Require: Learning rate ϵ , momentum parameter α

Require: Initial parameter θ , initial velocity v

while stopping criterion not met do

Sample a minibatch of m examples from the training set $\{x^{(1)}, \dots, x^{(m)}\}$ with corresponding labels $y^{(i)}$.

Apply interim update: $\tilde{\theta} \leftarrow \theta + \alpha v$.

Compute gradient (at interim point): $\mathbf{g} \leftarrow \frac{1}{m} \nabla_{\tilde{\boldsymbol{\theta}}} \sum_{i} L(f(\mathbf{x}^{(i)}; \tilde{\boldsymbol{\theta}}), \mathbf{y}^{(i)}).$

Compute velocity update: $\mathbf{v} \leftarrow \alpha \mathbf{v} - \epsilon \mathbf{g}$.

Apply update: $\theta \leftarrow \theta + v$.

end while

Figure: Algorithm of SGD w/ Nesterov momentum (Goodfellow et al., 2016)

Pham Viet Hung Presentation 13 / 16

Vanila SGD SGD with Polyak Momentum SGD with Nesterov Momentum

Thank you very much for your attention!

Pham Viet Hung Presentation 14 / 16

References 1

- Wasserman, L. (2004). All of statistics: a concise course in statistical inference (Vol. 26). New York: Springer.
- Goodfellow, I., Bengio, Y., Courville, A. (2016). Deep Learning. MIT Press.
- Melville, J. (2016). *Nesterov Accelerated Gradient and Momentum*. https://jlmelville.github.io/mize/nesterov.html#Sutskever_Nesterov_Momentum

Pham Viet Hung Presentation 15 / 16

References 2

- Polyak, B. T. (1964). Some methods of speeding up the convergence of iteration methods. USSR Computational Mathematics and Mathematical Physics, 4(5), 1–17.
- Nesterov, Y. (1983). A method of solving a convex programming problem with convergence rate $O(1/k^2)$. Soviet Mathematics Doklady, 27(2):372–376
- Nesterov, Y. (2004). *Introductory lectures on convex optimization: A basic course*. Kluwer Academic Publishers
- Sutskever, I. (2013). *Training Recurrent Neural Networks*. University of Toronto. https://tspace.library.utoronto.ca/bitstream/1807/36012/6/Ilya_Sutskever_201306 PhD thesis.pdf

Pham Viet Hung Presentation 16 / 16