

Software Version	2.06.10
User Name:	System Administrator

Experiment File Path:	
Protocol File Path:	DB:\Protocols\hackathon_singleread.prt

Plate Number	Plate 6
Date	7/25/2026
Time	5:41:51 PM
Reader Type:	ELx808
Reader Serial Number:	Unknown
Reading Type	Reader

Procedure Details

Plate Type	96 WELL PLATE
Read	Absorbance Endpoint
	Full Plate
	Wavelengths: 450, 490, 630
	Read Speed: Normal

Actual Temperature:	28.2
---------------------	------

Actual Temperature:	28.2
---------------------	------

Actual Temperature:	28.2
---------------------	------

Results

	1	2	3	4	5	6	7	8	9	10	11	12	
A	0.040	0.039	0.032	0.033	0.037	0.033	0.610	0.035	0.340	0.045	0.037	0.060	450
	0.040	0.039	0.032	0.034	0.037	0.034	0.560	0.035	0.310	0.044	0.037	0.063	490
	0.041	0.040	0.035	0.035	0.038	0.035	0.520	0.036	0.289	0.044	0.038	0.067	630
B	0.040	0.045	0.057	0.038	0.040	0.034	0.043	0.036	0.035	0.038	0.039	0.037	450
	0.039	0.044	0.060	0.038	0.041	0.034	0.043	0.036	0.036	0.039	0.040	0.039	490
	0.045	0.050	0.070	0.044	0.046	0.035	0.045	0.039	0.042	0.043	0.042	0.043	630
C	0.045	0.049	0.038	0.045	0.036	0.045	0.039	0.051	0.045	0.049	0.058	0.042	450
	0.045	0.048	0.039	0.046	0.038	0.045	0.040	0.051	0.045	0.050	0.056	0.041	490
	0.043	0.045	0.036	0.043	0.034	0.043	0.040	0.046	0.044	0.048	0.052	0.041	630
D	0.043	0.038	0.038	0.048	0.051	0.042	0.045	0.042	0.041	0.040	0.045	0.044	450
	0.046	0.040	0.038	0.050	0.052	0.043	0.046	0.044	0.042	0.041	0.046	0.045	490
	0.045	0.040	0.039	0.050	0.053	0.043	0.043	0.043	0.042	0.043	0.045	0.042	630
E	0.044	0.037	0.035	0.038	0.040	0.038	0.036	0.040	0.044	0.046	0.041	0.040	450
	0.047	0.040	0.041	0.039	0.043	0.042	0.043	0.046	0.044	0.049	0.047	0.042	490
	0.043	0.038	0.036	0.038	0.040	0.037	0.037	0.038	0.040	0.043	0.038	0.036	630
F	0.041	0.045	0.035	0.048	0.119	0.043	0.043	0.041	0.045	0.042	0.042	0.044	450
	0.043	0.048	0.042	0.054	0.113	0.051	0.047	0.042	0.048	0.045	0.044	0.047	490
	0.043	0.045	0.039	0.046	0.107	0.044	0.038	0.039	0.042	0.039	0.039	0.042	630
G	0.041	0.049	0.040	0.050	0.039	0.039	0.045	0.041	0.040	0.039	0.038	0.041	450
	0.043	0.049	0.039	0.052	0.039	0.041	0.046	0.041	0.040	0.038	0.040	0.041	490
	0.045	0.050	0.043	0.051	0.041	0.041	0.045	0.042	0.038	0.038	0.042	0.044	630
H	0.040	0.043	0.042	0.040	0.043	0.096	0.036	0.043	0.036	0.041	0.042	0.040	450
	0.041	0.044	0.044	0.042	0.041	0.099	0.038	0.047	0.038	0.040	0.043	0.041	490
	0.042	0.045	0.045	0.044	0.041	0.101	0.039	0.046	0.039	0.044	0.043	0.042	630