

# Understanding GANs

# What we will be covering in this module?

- Introduction to Image Generation
- What are Generative Models?
- Understanding Generative Adversarial Networks
- Project on Texture Generation using GANs
  - Simple Implementation
  - Better GAN Architectures
- What's Next?

# Understanding GANs with an example



# Understanding GANs with an example

Forger


Create fraudulent imitations of original paintings



# Understanding GANs with an example

Art Investigator

Identify the Real and Fake paintings



# Understanding GANs with an example

Forger

Create fraudulent imitations of original paintings

Art Investigator

Identify the Real and Fake paintings

Analytics  
Vidhya

# Understanding GANs with an example

Forger

Create fraudulent imitations of original paintings

Art Investigator

Identify the Real and Fake paintings

Analytics  
Vidhya

# How do GANs work?


Image Generation is the task of generating completely new realistic images which does not belong to the training dataset, but resembles them






# How do GANs work?

Image Generation is the task of generating completely new realistic images which does not belong to the training dataset, but resembles them




# How do GANs work?

Image Generation is the task of generating completely new realistic images which does not belong to the training dataset, but resembles them



# How do GANs work?

Image Generation is the task of generating completely new realistic images which does not belong to the training dataset, but resembles them




# How do GANs work?

Image Generation is the task of generating completely new realistic images which does not belong to the training dataset, but resembles them

$$\min_G \max_D V(D, G)$$

$$V(D, G) = \mathbb{E}_{x \sim p_{data}(x)} [\log D(x)] + \mathbb{E}_{z \sim p_z(z)} [\log(1 - D(G(z)))]$$




# How do GANs work?

Image Generation is the task of generating completely new realistic images which does not belong to the training dataset, but resembles them

$$\min_G \max_D V(D, G)$$

$$V(D, G) = \mathbb{E}_{x \sim p_{data}(x)} [\log D(x)] + \mathbb{E}_{z \sim p_z(z)} [\log(1 - D(G(z)))]$$




# How do GANs work?

Image Generation is the task of generating completely new realistic images which does not belong to the training dataset, but resembles them

$$\min_G \max_D V(D, G)$$

$$V(D, G) = \mathbb{E}_{x \sim p_{data}(x)} [\log D(x)] + \mathbb{E}_{z \sim p_z(z)} [\log(1 - D(G(z)))]$$




# How do GANs work?

Image Generation is the task of generating completely new realistic images which does not belong to the training dataset, but resembles them

$$\min_G \max_D V(D, G)$$

$$V(D, G) = \mathbb{E}_{x \sim p_{data}(x)} [\log D(x)] + \mathbb{E}_{z \sim p_z(z)} [\log(1 - D(G(z)))]$$

- where,
  - $p_{data}(x)$  -> the distribution of real data
  - $x$  -> sample from  $p_{data}(x)$




# How do GANs work?

Image Generation is the task of generating completely new realistic images which does not belong to the training dataset, but resembles them

$$\min_G \max_D V(D, G)$$

$$V(D, G) = \mathbb{E}_{x \sim p_{data}(x)} [\log D(x)] + \mathbb{E}_{z \sim p_z(z)} [\log(1 - D(G(z)))]$$

- where,
  - $p_{data}(x)$  -> the distribution of real data
  - $x$  -> sample from  $p_{data}(x)$
  - $p(z)$  -> distribution of fake data
  - $z$  -> sample from  $p(z)$






# How do GANs work?

Image Generation is the task of generating completely new realistic images which does not belong to the training dataset, but resembles them


$$\min_G \max_D V(D, G)$$
$$V(D, G) = \mathbb{E}_{x \sim p_{data}(x)} [\log D(x)] + \mathbb{E}_{z \sim p_z(z)} [\log(1 - D(G(z)))]$$

- where,
  - $p_{data}(x)$  -> the distribution of real data
  - $x$  -> sample from  $p_{data}(x)$
  - $p(z)$  -> distribution of fake data
  - $z$  -> sample from  $p(z)$
  - $G(z)$  -> Generator Network
  - $D(x)$  -> Discriminator Network




# Deep Learning Architecture of simple GANs

- Broadly a GAN architecture has two main subparts
  - Generator Network (MLP network)
  - Discriminator Network (MLP network)





# Deep Learning Architecture of GANs

Pass 1: Train discriminator and freeze generator



# Deep Learning Architecture of GANs

Pass 2: Train generator and freeze discriminator




Pass 2:


$D(x)$  -> Get output (dont update)

$G(x)$  -> Update

# Deep Learning Architecture of GANs



# Deep Learning Architecture of GANs



What is a GAN?

# Formal Training Methodology of GANs



# Formal Training Methodology of GANs

- **Step 1:** Define architecture of Discriminator





# Formal Training Methodology of GANs

- **Step 1:** Define architecture of Discriminator
- **Step 2:** Define architecture of Generator



# Formal Training Methodology of GANs

- **Step 1:** Define architecture of Discriminator
- **Step 2:** Define architecture of Generator
- **Step 3:** Train Discriminator



# Formal Training Methodology of GANs

- **Step 1:** Define architecture of Discriminator
- **Step 2:** Define architecture of Generator
- **Step 3:** Train Discriminator
  - **Step 3.1:** Take samples from real data



# Formal Training Methodology of GANs

- **Step 1:** Define architecture of Discriminator
- **Step 2:** Define architecture of Generator
- **Step 3:** Train Discriminator
  - **Step 3.1:** Take samples from real data
  - **Step 3.2:** Generate fake data from Generator

# Formal Training Methodology of GANs

- **Step 1:** Define architecture of Discriminator
- **Step 2:** Define architecture of Generator
- **Step 3:** Train Discriminator
  - **Step 3.1:** Take samples from real data
  - **Step 3.2:** Generate fake data from Generator
  - **Step 3.3:** Update the parameters of Discriminator on the combined batch

# Formal Training Methodology of GANs

- **Step 1:** Define architecture of Discriminator
- **Step 2:** Define architecture of Generator
- **Step 3:** Train Discriminator (for one or more iterations)
  - **Step 3.1:** Take samples from real data
  - **Step 3.2:** Generate fake data from Generator
  - **Step 3.3:** Update the parameters of Discriminator on the combined batch

# Formal Training Methodology of GANs

- **Step 1:** Define architecture of Discriminator
- **Step 2:** Define architecture of Generator
- **Step 3:** Train Discriminator (for one or more iterations)
  - **Step 3.1:** Take samples from real data
  - **Step 3.2:** Generate fake data from Generator
  - **Step 3.3:** Update the parameters of Discriminator on the combined batch
- **Step 4:** Train generator

# Formal Training Methodology of GANs

- **Step 1:** Define architecture of Discriminator
- **Step 2:** Define architecture of Generator
- **Step 3:** Train Discriminator (for one or more iterations)
  - **Step 3.1:** Take samples from real data
  - **Step 3.2:** Generate fake data from Generator
  - **Step 3.3:** Update the parameters of Discriminator on the combined batch
- **Step 4:** Train generator
  - **Step 4.1:** Generate fake data from Generator



# Formal Training Methodology of GANs

- **Step 1:** Define architecture of Discriminator
- **Step 2:** Define architecture of Generator
- **Step 3:** Train Discriminator (for one or more iterations)
  - **Step 3.1:** Take samples from real data
  - **Step 3.2:** Generate fake data from Generator
  - **Step 3.3:** Update the parameters of Discriminator on the combined batch
- **Step 4:** Train generator
  - **Step 4.1:** Generate fake data from Generator
  - **Step 4.2:** Update the parameters of Generator on how well the Discriminator is fooled

# Formal Training Methodology of GANs

- **Step 1:** Define architecture of Discriminator
- **Step 2:** Define architecture of Generator
- **Step 3:** Train Discriminator (for one or more iterations)
  - **Step 3.1:** Take samples from real data
  - **Step 3.2:** Generate fake data from Generator
  - **Step 3.3:** Update the parameters of Discriminator on the combined batch
- **Step 4:** Train generator
  - **Step 4.1:** Generate fake data from Generator
  - **Step 4.2:** Update the parameters of Generator on how well the Discriminator is fooled
- **Step 5:** (Optional) Check if the fake data visually if it seems legit. If yes, stop training, else go to Step 3

