

Forth Golfscript Interpreter

Golfscript

Golfth

Code Golf

- ▶ shortest possible source code that implements an algorithm
- ▶ solving problems (holes) in as few keystrokes as possible

Golforth

Code Golf

- ▶ shortest possible source code that implements an algorithm
- ▶ solving problems (holes) in as few keystrokes as possible

Golfscript

- ▶ stack oriented, variables exist
- ▶ single symbols represent high level operations
- ▶ strong typed
- ▶ heavy use of operator overloading and type coercion

Golforth

Golfscript Types

- ▶ Integer: 1 2
- ▶ Arrays: [1 2 3] [3]
- ▶ Strings: "one two three"
- ▶ Blocks: {1+}

Golforth

Golfscript Types

- ▶ Integer: 1 2
- ▶ Arrays: [1 2 3] [3]
- ▶ Strings: "one two three"
- ▶ Blocks: {1+}

Golfscript Operator Example

- ▶ 12 3 * -> 36
- ▶ [50 51 52]' '* -> "50 51 52"
- ▶ [1 2 3]{1+}/ -> 2 3 4
- ▶ {.@\%.}do; (n1 n2 -- gcd)

Forth Implementation

Typesystem

- ▶ Values as scalar references on stack
- ▶ Anonymous functions
 - ▶ `: anon_int { u -- typext }`
`:noname u POSTPONE LITERAL POSTPONE typeno_int POSTPONE ; ;`

`12 anon_int s" foo" anon_str`



2 elements on stack (12 and 'foo')

Golforth

Parser

- ▶ translates golfscript to forth execution tokens
- ▶ based on regular expression of reference implementation
- ▶ Responsible for:
 - ▶ infer initial type from syntax
 - ▶ symbol table for variable tracking
 - ▶ note that every value can be a variable!

12 'foo':x



(creating x in symbol table)



12 anon_int s" foo" anon_str dup x !

Arrays

- ▶ Construction similar to postscript.
- ▶ `[` marks stack size, `]` collects back to marked size.
- ▶ Mark moves when stack becomes smaller:

`1 2 [\] -> [2 1]`

Type Coercion and Overloading

- ▶ Typeorder for Coercion
- ▶ Coercion according to highest order type
- ▶ Heavy operator overloading results in wide range of functionality

Golforth

Implementation Status in Percentage

Complex Overloaded ¹		Stack Operators		Loops & Conditionals		Math		Output	
!	100	@	100	until	100	abs	100	'	0
=	100	\	100	while	100	base	100	print	100
~	100	;	100	do	100	rand	0	puts	100
\$	100	.	100	if	100			p	0
+	100								
-	100								
*	100								
/	100								
%	100								
,	75								
?	75								
(75								
)	75								
	50								
&	50								
^	50								
<	100								
>	100								
and or xor	0								
zip	100								

Testsuite covering 130 golfscript programs.

¹ Introspection based features for Blocks have not been implemented.

Cutbacks

- ▶ Error Handling differs
- ▶ Introspective Block operations not implemented

Usage of Idiomatic Forth

- ▶ Stack paradigm mapped to typed language
- ▶ Wordlists for variable tracking
- ▶ Macros & anonym functions for
 - ▶ language implementation
 - ▶ operator implementation