

# **Next Door League**

# **Technische Dokumentation Ausbildung Techniker – Informatik**

Titel: Next Door League

Bereich: Webdesign Autor: Huberty Tom

Klasse: T3IFAN

Schule: Lycée technique des Arts et Métiers

Abgabe: Luxemburg, 25 Februar 2014

## Inhaltsverzeichnis

1.Einleitung.	5
1.1.Vorwort	5
1.2.Idee	5
1.3.Software	5
1.4.Kompatibilität	5
1.5.Zugangsdaten	
2.Bedienungsanleitung.	
2.1.Benutzergruppen	
2.2.Matchsystem.	
2.3.Streams	
2.4. Sicherheit.	
3.Entwicklung	
3.1.Grundaufbau des Designs - FrontEnd	
3.2.Grundaufbau des Design – BackEnd	
3.3. Wichtige Variablen	
3.5.Datenbank CiviL	
3.6.Ordnerstruktur	
3.6.1 /	
3.6.2 /cms	
3.6.3 /cms/ckeditor	
3.6.4 /cms/img	
3.6.5 /cms/include.	
3.6.6 /img	
3.6.7 /img/news	
3.6.8 /img/partners	
3.6.9 /img/smedia	15
3.6.10/img/teams	16
3.6.11/img/users	16
3.6.12/include	
3.6.13/include/league	
3.6.14/include/news.	
3.6.15/include/profile	
3.6.16/include/register	
3.6.17/include/streams	
3.6.18/include/teams	
3.6.19/stylesheets	
3.7. Stylesheets	
3.7.1 /cms/style.css	
3.8.PHP	
3.8.1 /cms/index.php.	
3.8.2 /cms/include/login.php.	
3.8.3 /cms/include/status.php	
3.8.4 /cms/include/news.php.	
3.8.5 /cms/include/teams.php.	
3.8.6 /cms/include/users.php.	
1 1	

4.2.2.17./include/league/view.php	119
4.2.2.18./include/league/comment.php	
4.2.2.19./include/news/index.php	
4.2.2.20./include/profile/index.php	
4.2.2.21./include/profile/view.php	
4.2.2.22./include/profile/edit.php	
4.2.2.23./include/register/index.php	
4.2.2.24./include/register/captcha.php	
4.2.2.25./include/streams/index.php	157
4.2.2.26./include/teams/index.php	
4.2.2.27./include/teams/view.php.	
4.2.2.28./include/teams/edit.php.	170
4.2.2.29.include/teams/create.php.	176
4.2.2.30./include/teams/join.php.	
4.2.3Javascript	181
4 2 3 1 /include/bg_set_php	181

## 1. Einleitung

### 1.1. Vorwort

Folgende Dokumentation enthält jegliche benötigten Informationen zur Weiterentwicklung der Webapplikation. Dem Leser wird vermittelt wie die Applikation aufgebaut ist, technische Details werden auch erklärt.

### 1.2. Idee

Die Idee von "Next Door League" besteht darin, Benutzern die Möglichkeit zu geben ein eigenes Team zu formen und zu verwalten. Mit diesem Team kann man in einer Liga teilnehmen um somit gegen andere Teams anzutreten um somit Punkte zu gewinnen ggf. verlieren. Benutzer können ausserdem ihren Stream-Account von <u>www.twitch.tv</u> angeben um somit in einer List angezeigt zu werden welche jeden Streamer der Applikation anzeigt. Ausserdem werden durch Neuigkeiten, Besucher und Benutzer auf dem Laufendem von der Gaming-Szene gehalten.

### 1.3. Software

Folgende Tabelle zeigt die Software an die bei der Realisierung der Applikation verwendet wurde:

Software	Version	URL
PHP5	5	http://php.net/
HTML	5	http://www.w3schools.com/html/
CSS	3	http://www.w3schools.com/css/
MySQL	5.1.49-3	http://www.mysql.com/
CKEditor	4	http://ckeditor.com/
Kryogenix sorttable		http://www.kryogenix.org/code/browser/sort table/

## 1.4. Kompatibilität

Da in der Webapplikation HTML5 und CSS3 verwendet wird, ist es empfehlenswert einen aktuellen Browser zu verwenden um Darstellungsfehler zu verhindern. Javascript soll ausserdem im Browser aktiviert werden.

Huberty Tom 5/182

## 1.5. Zugangsdaten

### **SFTP:**

IP: foxi.ltam.lu

Username: hubto133 Passwort: qwer1337

### mySQL:

IP: foxi.ltam.lu

Username: hubto133 Passwort: 19921106133

### **Content-Managment-System:**

IP:hubto133.foxi.lu/cms

**Admin:** 

Username: adminitam Passwort: testitam

**Moderator:** 

Username: moderatorItam

Passwort: testItam

### **ND-League Owner of Team1:**

Username: teamowner1

Passwort: testItam

### **ND-League Owner of Team2:**

Username: teamowner2

Passwort: testItam

Huberty Tom 6/182

## 2. Bedienungsanleitung

### 2.1. Benutzergruppen

Es gibt 3 verschieden Benutzergruppen:

#### Admin:

Ein Admin kann sich im Content-Managment-System anmelden und somit Benutzerkonten aktivieren/deaktivieren, bearbeiten und löschen. Weiterhin kann er Teams bearbeiten oder löschen und Neuigkeiten erstellen, bearbeiten und löschen. Das Managen der Matches in der Liga ist nicht benötigt im CMS da sich alles selbst bearbeitet via PHP.

Im Front-End Bereich wird ein Admin als normaler Benutzer dargestellt. Er hat also somit nur die Möglichkeit im CMS selbst Benutzer, Teams oder Neuigkeiten zu verwalten.

#### **Moderator:**

Ein Moderator kann sich im Content-Managment-System anmelden und kann dort nur Neuigkeiten erstellen, bearbeiten und löschen.

Im Front-End Bereich wird auch der Moderator als normaler Benutzer dargestellt. Somit hat er keine Möglichkeit Neuigkeiten zu bearbeiten, nur wenn er ins CMS geht.

#### Benutzer:

Ein normaler Benutzer hat die Möglichkeit seine Benutzerinformationen zu verändern. Dazu gehört auch das hochladen eines neuen Avatars, welcher den gestellten Kriterien entsprechen muss. Benutzer können unter die Neuigkeiten Kommentare erstellen und löschen, somit können kleine Diskussion mit Anderen über die Neuigkeit geführt werden.

Der Benutzer kann einem Team beitreten mit einem Passwort, selbst ein Team erstellen oder aus einem Team austreten. Der Besitzer eines Teams kann dies in die Liga einschreiben, sobald dieses mindestens 5 Mitglider hat, und wieder ausschreiben. Er hat ausserdem die Möglichkeit ein neues Logo hochzuladen welches den Kriterien entspricht. Ein Teambesitzer kann das Team löschen jedoch nicht verlassen ausser er übergibt die Besitzerrechte an ein anderes Mitglied des Teams. Nur ein Teambesitzer kann andere Teams in der Liga herausforderen und die Matchdaten und Resultate eintragen.

Mitglieder eines Teams welches in einem **offenen** Match ist können unter den Matchinformationen kommentieren um somit mit dem gegnerischen Team Informationen auszutauschen.

Huberty Tom 7/182

### 2.2. Matchsystem

In der Liga wird das ELO-System (<a href="http://en.wikipedia.org/wiki/Elo\_rating\_system">http://en.wikipedia.org/wiki/Elo\_rating\_system</a>) um die Punkte zu berechnen, welche vergeben werden nachdem ein Team gegen ein Anderes gespielt hat, angewand. Somit erhält jedes Team wenn es erstellt wird automatisch 1000 Punkte um somit faire Punktevergabe zu versichern.

Formel des winround-winloss Elo-Systems:

$$R_{new} = R_{old} + CI * (W - E)$$

Rnew = Neues Ranking des Teams

Rold = Altes Ranking des Teams

C1 = Konstante (50 in diesem Fall)

W = Prozentpunkte (Gewonnen = 1, Verloren = 0)

E = Erwartete Prozentpunkte ( Siehe unten)

### **Erwartete Prozentpunkte- Berechnung:**

$$E = \frac{1}{1 + 10^{(R-Rother)}}$$

$$C2$$

R = Ranking des eigenen Teams

Rother = Ranking des Gegners

C2 = Konstante (400)

Diese Berechnung trifft auf beide Teams zu um jeweils die Punkte zu berechnen welche vergeben werden.

Bei der Matcherstellung wird diese Formel direkt angewendet um somit dem Herausforderer sofort anzuzeigen wieviel Punkte das eigene Team verlieren bzw. verdienen kann. Die Berechneten Punkte werden ausserdem bei der Matcherstellung in den Datenbankeintrag mit gesichert um somit keine neue Berechnung durchführen zu müssen.

Eine E-Mail, mit dem Link zum Match wird dem gegnerischem Teambesitzer gesendet um diesen somit über das Match zu informieren.

Falls der Gegner das Match ablehnen will muss der Teambesitzer auf "Decline Match" drücken somit wird das Match geschlossen und dem Team, welches aufgegeben hat, werden 5 Punkte entzogen. Das somit gewonnene Team erhällt jedoch keine zusätzlichen Punkte.

Die Teamresultate können erst eingegeben werden wenn beide Teams die gleichen Datums und Uhrzeiten angegeben haben. Hat ein Team das Resultat eingegeben kann das Datum und die Uhrzeit nicht mehr geändert werden. Das Aufgeben bzw Ablehnen des Matches ist auch nicht mehr möglich.

Huberty Tom 8/182

Wenn beide Teams die Resultate des Matches eingetragen haben wird überprüft ob beide auch gleich sind. Sind die Resultate nicht gleich müssen die Teams erneut die Resultate eingeben, damit kein Missverständnis zwischen den Teams entsteht welches gewonnen hat. Wenn die Überprüfung der Resultate erfolgreich ist wird das Match geschlossen und die Punkte werden vergeben.

Das Kommentieren unter den Matchinformationen wird somit auch ausgeschaltet.

### 2.3. Streams

Bei den Streams wird die sogenannte Twitch APIv3 (<a href="https://github.com/justintv/Twitch-API/blob/master/v3\_resources/streams.md">https://github.com/justintv/Twitch-API/blob/master/v3\_resources/streams.md</a>) benutzt. Falls ein Benutzer also in seinem Profil die TwitchID seines <a href="https://www.twitch.tv">www.twitch.tv</a> Accounts angibt, wird diese in die Auswertung der Streams mit einbezogen.

Der Server beantragt jede Anfrage der API neu an die api.twitch.tv Server. Somit dauert die komplette Auswertung aller Daten (Vieweranzahl und Spieltitel), länger als bei normalen Anfragen auf den Server. Dieses Problem wird jedoch in der Weiterentwicklung des Projektes behoben.

Nachdem die Informationen ausgewertet wurden, wird eine Tabelle angezeigt mit den Streams der Benutzer, wo man dann erkennen kann wieviel Viewer der Stream gerade hat und welches Spiel der Streamer gerade live streamt. Indem man auf Online klickt wird der Stream dann auch in die Applikation integriet und man kann den Live-Stream verfolgen.

### 2.4. Sicherheit

Um Sicherheitslücken per mySQL-Injections in Eingabefeldern zu vermeiden wird die Funktion mysql\_real\_escape\_string() benutzt somit werden keine ungewollten Daten ausgegeben die einem Angreifer nützen könnten.

Durch htmlspecialchars werden Angriffe via XSS (Cross-Site-Scripting) bei der Ausgabe in ein HTML-Gerüst verhindert.

#### Passwörter:

Passwörter welche bei den Benutzern und Teams genutzt werden sin mit SHA1 codiert, somit ist hier auch wiederum eine Sicherheit eingebaut.

Huberty Tom 9/182

Header

## 3. Entwicklung


## 3.1. Grundaufbau des Designs - FrontEnd



Das ganze Design ist in einem "Wrapper"-Div eingespeist, somit wird das Design auf 1000px gehalten.

**Huberty Tom** 10/182

## 3.2. Grundaufbau des Design – BackEnd



- Navigation
- Content

Im Content-Managment-System wurde am Design gespart da nur das notwendigste hier benötigt wird.

Das Design wird durch ein "Container"-Div in Form gehalten, dieses Div hat minimal eine Breite von 500px und maximal 80% des Browsers.

Huberty Tom 11/182

## 3.3. Wichtige Variablen

### \$\_SESSION['loggedIN']

Bestimmt ob der Benutzer eingeloggt ist oder nicht. True = eingeloggt.

### \$\_SESSION['username']

Beinhaltet den Benutzernamen des Users wenn eingeloggt.

### \$\_SESSION['is\_admin']

Sagt aus ob der Benutzer Admin ist, oder nicht. True = Admin.

### \$\_SESSION['is\_moderator']


Sagt aus ob der Benutzer Moderator ist. True = Moderator.

### \$\_SESSION['team\_id']

Beinhaltet die team\_id des Benutzers um somit Zugriff auf das Team zu überprüfen

Huberty Tom 12/182

## 3.4. Datenbank UML



Huberty Tom 13/182

## 3.5. Datenbank Erläuterungen

### users:

### active

- 0: Benutzer ist deaktiviert.
- 1: Benutzer ist aktiviert.

### · is\_admin

- 0: Benutzer is kein Admin
- 1: Benutzer is Admin

### is\_moderator

- 0: Benutzer is kein Moderator
- 1: Benutzer ist Moderator

### fgpw\_code

Wird benutzt zum zurücksetzen des Passwortes. (fgpw = forgot password)

### matches:

### status

- 0: Match ist geschlossen.
- 1: Match ist offen.
- 2: Team 1 hat Match abgelehnt.
- 3: Team 2 hat Match abgelehnt.

Huberty Tom 14/182

### 3.6. Ordnerstruktur

### 3.6.1

Dies ist der Stammordner, hier befinden sich alle notwendigen Dateien für die Webapplikation.

### 3.6.2 /cms

Dieser Unterordner beinhaltet das Content-Managment-System.

## 3.6.3 /cms/ckeditor

Hier befinden sich die Dateien welche vom CKEditor benötigt werden um korrekt ausgeführt und angezeigt zu werden.

### 3.6.4 /cms/img

Hier befinden sich die im CMS angewendeten Bilder.

## 3.6.5 /cms/include

Hier befinden sich die PHP-Dateien welche zur Verwaltung der Benutzer, Teams und Neuigkeiten verwendet werden.

## 3.6.6 /img

Dier Ordner beinhaltet alles Bilder welche in der Applikation selbst verwendet werden.

## 3.6.7 /img/news

In diesem Unterordner von /img werden die Bilder der Neuigkeiten gespeichert. Bilder werden per SFTP-Zugang hier hochgeladen um als Verlinkung verwendet zu werden.

## 3.6.8 /img/partners

Hier werden die Bilder der Partner der Applikation gespeichert. Bilder werden per SFTP-Zugang hier hochgeladen.

## 3.6.9 /img/smedia

Hier befinden sich die "Social Media"-Icons, wie Facebook oder Twitter. Bilder werden per SFTP-Zugang hier hochgeladen um genutzt zu werden.

Huberty Tom 15/182

#### 3.6.10 /img/teams

In diesem Ordner werden die Teamlogos der Teams gespeichert. Es werden Schreibrechte hier benötigt.

#### 3.6.11 /img/users

In diesem Ordner werden die Avatare der Benutzer gespeichert. Es werden Schreibrechte hier benötigt.

#### 3.6.12 /include

Hier befinden sich jegliche verwendete PHP-Dateien die zur Darstellung der Applikation benötigt werden.

#### 3.6.13 /include/league

Hier werden die PHP-Dateien gespeichert welche zur Verwaltung und Darstellung der Liga bzw. der Matches benötigt werden.

#### 3.6.14 /include/news

Hier liegt die Datei welche genutzt wird um die News korrekt anzuzeigen.

#### /include/profile 3.6.15

Hier werden die Dateien gespeichert welche benötigt werden zur Bearbeitung und Darstellung der Benutzer.

#### 3.6.16 /include/register

Wird benötigt damit Benutzer sich registrieren können.

#### 3.6.17 /include/streams

Hier werden die Dateien für die Darstellung der Streams gespeichert.

#### 3.6.18 /include/teams

In diesem Ordner liegen die Dateien welche zur Erstellung, Verwaltung und Darstellung der Teams benötigt werden.

#### 3.6.19 /stylesheets

Hier werden die drei benötigten CSS-Dateien gespeichert.

16/182 **Huberty Tom** 

### 3.7. Stylesheets

## 3.7.1 /cms/style.css

Definiert das Design des Content-Managment-Systems.

### 3.7.2 /stylesheets

### blue style.css:

Wird genutzt wenn Cookie nd\_league\_design\_color = blue\_style.

### orange style.css:

Wird genutzt wenn Cookie nd\_league\_design\_color = orange\_style.

#### standard.css:

Wird als Standart-Stylesheet genutzt. Wenn man also zum ersten mal die Applikation besucht oder kein anderes Design ausgewählt hat.

### 3.8. PHP

## 3.8.1 /cms/index.php

- Beinhaltet das HTML-Gerüst vom CMS
- Die CSS-Datei vom CMS wird geladen
- Laden der angefragten Seiten des Admins/Moderators
- Authentifizierung des Benutzers ob dieser angemeldet ist und Admin/Moderator ist

## 3.8.2 /cms/include/login.php

Authentifizierung des Benutzers und setzen der wichtigen \$ SESSION-Variablen.

## 3.8.3 /cms/include/status.php

Wird genutzt um erneut zu überprüfen ob der User noch immer aktiviert ist.

## 3.8.4 /cms/include/news.php

Wird gebraucht zur Verwaltung der Neuigkeiten.

## 3.8.5 /cms/include/teams.php

Wird gebraucht um die Teams zu verwalten.

Huberty Tom 17/182

## 3.8.6 /cms/include/users.php

Hiermit wird die Verwaltung der Benutzer gehandhabt.

### 3.8.7 /index.php

- Beinhaltet das HTML-Gerüst
- CSS-Dateien werden geladen
- Laden der angefragten Seiten des Benutzers
- Authentifizierung des Benutzers ob dieser angemeldet ist

## 3.8.8 /include/about.php

Mit dieser Datei wird dem Benutzer Informationen über Next Door League angezeigt.

## 3.8.9 /include/bg\_set.php

Obwohl die Datei nur ein Javascript enthält wird sie per include() in die Index-Datei geladen.

Hier wird per Javascript überprüft ob der Browser ein Cookie namens "nd\_league\_design\_color" gesetzt hat. Ist dies nicht der Fall so wird ein Cookie gesetzt mit dem Wert "standard" um somit die CSS-Datei auszuwählen welche genutzt wird.

Indem man auf der Applikation oben links im Header eine Farbe auswählt, kann man die Cookies und somit die CSS-Datei ändern welche geladen wird.

## 3.8.10 /include/config.php

Mit dieser Datei wird die Datenbankverbindung hergestellt.

## 3.8.11 /include/contact.php

Mit dieser Datei wird das Kontaktformular aufgerufen. Hier kann ein Besucher/Benutzer eine Email an <a href="mailto:nextdoorleague@gmail.com">nextdoorleague@gmail.com</a> schicken im somit Kontakt mit dem Besitzer/Verwalter der Seite aufzunehmen bezüglich Fragen oder anderem.

## 3.8.12 /include/forgotpw.php

Diese Datei wird genutzt um das Passwort eines Benutzers zurückzusetzen.

### **Vorgang:**

- 1) Benutzer gibt E-Mail-Adresse an.
- 2) Email mit Confirmation-code (Zufallsgenerierter MD5 Code) wird an die Email gesendet. Gleichzeitig wird dem Account der entsprechenden Email der Confirmation in die Datenbank geschrieben.

Huberty Tom 18/182

- 3) Wird nun auf den Link zugegriffen welcher per Mail versendet wurde, wird überprüft op der Code mit der Email-Adresse übereinstimmt.
- 4) Ist dies der Fall so wird das Reset-Password Formular angezeigt und der Benutzer kann nun das Passwort zurücksetzen.
- 5) Ist die Zurücksetzung erfolgreich wird der Code aus der Datenbank entfernt damit ein anderer Benutzer nicht die Möglichkeit erhält selbst den Code zu benutzen. (was eher unwahrscheinlech ist.)

## 3.8.13 /include/login.php

Diese Datei wird genutzt zur Authentifizierung des Benutzer ob der Benutzername und das Passwort übereinstimmen. Hier werden ausserdem auch die wichtigen \$\_SESSION-Variablen gesetzt.

## 3.8.14 /include/status.php

Wird genutzt zur kontinuierlichen Überprüfung ob der Benutzer noch aktiviert ist und ob sich das Team des Benutzers geändert hat. Ist die der Fall so wird die \$\_SESSION['team\_id'] neu gesetzt.

## 3.8.15 /include/league/challenge.php

In dieser Datei wird zunächst überprüft ob der Benutzer welche diese Seite aufruft ein Teambesitzer ist oder nicht. Diese Seite wird zur Matcherstellung gegen ein anderes Teambenötigt.

Teambesitzer können nur andere Teams und nicht ihr eigenes Team herausforderen. Die Team-ID welche für das zu herausfordernde Team benötigt wird, wird über die \$\_GET['teamid']-Variable ausgelesen.

Ausserdem werden hier die ELO-Punkte welche dann zur Auswertung des Matches im nachinein einbezogen werden.

Der Herausforderer muss ein späteres Datum eingeben als der Tag an dem er ein anderes Team herausfordert, sonst erhält er eine Fehlermeldung.

Sind die Voraussetzungen eingehalten worden wird ein offenes Match erstellt und der herausgeforderte Teambesitzer erhält per Email eine Meldung das dieser herausgefordert wurde und dazu ein Link zum erstellten Match.

## 3.8.16 /include/league/comment.php

Wird benötigt um zu überprüfen ob ein Benutzer Mitglied eines Teams in einem offenen Matches ist. Ist dies der Fall kann der Benutzer im offenen Match noch eigene Kommentare hinzufügen bzw. löschen.

Ist das Match geschlossen (Status 0,2,3) so kann kein Benutzer mehr kommentare hinzufügen, nur die Kommentare welche schon erstellt wurden werden angezeigt.

Huberty Tom 19/182

## 3.8.17 /include/league/index.php

Hier werden drei Tabellen angezeigt:

### Teams in League:

Hier werden die Teams, deren Wins, deren Loses und die momentane Punkteanzahl angezeigt. Ausserdem kann man mit Hilfe des "Challenge-Buttons" das Team herausforderen.

### Open Matches:

Hier werden die offenen Matches, mit den zwei Teams welches das Match eröffnet haben, angezeigt. Per View Match kann man dann auch auf die Matchseite kommen um mehr Informationen zu bekommen.

#### Closed Matches:

Hier werden die geschlossenen Matches, mit den Teams, angezeigt. Hier ist auch wieder die Möglichkeit die Matchinfomationen zu schauen indem man auf View Match klickt.

Ausserdem kann ein Benutzer sein Team, wenn er Teambesitzer ist und das Team mindestens 5 Mitglieder hat, hier in die Liga ein/ausschreiben.

### 3.8.18 /include/league/view.php

Diese Datei ermöglicht es Benutzern die Matchinformationen und Kommentare zu sehen.

Ein Teambesitzer der beiden Teams welche das Match erstellt haben, kann hier auch das Datum und die Uhrzeit änderen des Matches änderen. Teambesitzer können ausserdem auch ein Match ablehnen dies kann jedoch nur gemacht werden solange keines der beiden Teams ein Resultat eingeben hat. Das Team welches das Match ablehnt erhält 5 Minuspunkte. Wenn Teambesitzer des Teams welches herausgefordert hat ablehnt so wird der Status des Matches auf 2 gesetzt und somit geschlossen. Beim herausgeforderten Team wird der Status 3 und das Match wird geschlossen.

Nachdem beide Teams ein Datum und eine Uhrzeit vereinbart haben kann der Teambesitzer das Matchresultat eintragen. Sind beide Resultate gleich wird das Match geschlossen und die Punkte vergeben. Falls nicht müssen die Teams die Resulate neu eintragen.

## 3.8.19 /include/news/index.php

Hier werden alle erstellten Neuigkeiten angezeigt. Jeweils fünf Neuigkeiten werden pro Seite angezeigt welche man entweder unten auswählen kann oder man gibt der \$\_GET['list']-Variable einen Wert.

## 3.8.20 /include/profile/edit.php

Hier wird überprüft ob der Benutzer welcher die Edit-Seite angewählt hat auch wirklich der Benutzer des durch \$\_GET['username'] angegebenen Benutzers ist. Ist dies nicht der Fall

Huberty Tom 20/182

wird eine Fehlermeldung angezeigt.

Wenn der Benutzer richtig ist so erhält er die Möglichkeit fast alle Daten seine Profile zu ändern. Ein Benutzer kann seinen Benutzernamen nicht ändern.

Falls der Benutzer in einem Team ist kann er auch von hier aus aus dem Team treten.Ist der Benutzer ein Teambesitzer ist dies jedoch nicht möglich, dieser muss zuerst die Rechte weitergeben oder er löscht das Team.

Der Benutzer kann ausserdem einen Avatar hochladen welcher jedoch den Kriterien her passen muss.

Ist eine Änderung gemacht worden wird eine Meldung angezeigt das der Benutzer "updated" wurde.

## 3.8.21 /include/profile/index.php

Hier wird überprüft welche \$\_GET['action'] gesetzt wurde. Je nach Wert wird view oder edit.php aufgerufen.

### 3.8.22 /include/profile/view.php

Hier wird das Profil des jeweiligen Benutzers angezeigt mit all seinen Informationen und dem Team in welchem dieser gerade ist.

Falls der Benutzer sein eigenes Profil anwählt so kann er über "Edit Profile" auf die edit.php zugreifen und somit sein Profil ändern.

## 3.8.23 /include/captcha.php

Mit dieser Datei wird ein Captcha-Code erstellt welches benötigt wird zur Registrierung neuer Benutzer.

## 3.8.24 /include/index.php

Hiermit wird das Registrierungsformular aufgerufen. Gleichzeitig wird captcha.php geladen um somit ein neues Captcha zu erstellen damit auch verifiziert ist das kein Spam-bot Registrierungen durchführen kann.

Es wird überprüft ob der Username und die Email-Adresse schon vergeben sind. Ist dies der Fall so erhält man eine Fehlermeldung. Wenn diese nicht vergeben sind wird noch überprüft ob beide einzugebenden Passwörter gleich sind und ob das Captcha richtig eingegeben wurde.

Falls man den Captcha-Code nicht erkennen kann, kann man per Javascript klickt auf "Reload Captcha" klicken und die Datei captcha.php wird neu aufgerufen und es wird somit ein neues Captcha-Bild erzeugt.

Ist die Registrierung erfolgreich, erhält man eine Meldung das man nun registriert sei. Man kann sich nun einloggen.

Huberty Tom 21/182

## 3.8.25 /include/streams/index.php

Mit dieser Datei werden alle Streams der Benutzer, welche eine Twitch-ID angegeben haben, angezeigt. Die Informationen werden durch die JSON-API von twitch.tv erworben. Da zurzeit nur per file\_get\_contents() die Informationen für jeden einzelnen Benutzer aufgerufen und ausgewertet werden, benötigt die Seite längere Zeit um alles anzuzeigen.

Ist die Seite geladen so erhält man Informationen über den Stream eines Benutzers, man sieht wieviel Viewer dieser momentan hat und was er für ein Spieltitel spielt, wenn dieser dann auch online ist.

Man kann ausserdem den twitch-Namen per Suche aussuchen, somit kann man die angezeigten Benutzer verringern.

Indem man auf Online klickt wird man zum Stream weitergeleitet welcher und die Applikationen eingebettet wurde.

### 3.8.26 /include/teams/create.php

Mit dieser Datei wird überprüft ob der Benutzer schon in einem Team ist oder nicht. Fall ja so wird eine Fehlermeldung angezeigt.

Ist der Benutzer in keinem Team so kann er ein neues Team erstellen. Ein Create Team Formular wird angezeigt. Ist der Teamname schon vergeben erhält man eine Fehlermeldung. Man muss dem Team ausserdem ein Passwort geben welches dann benötigt wird um in das Team zu gelangen.

Sind beide Passwörter gleich so wird keine Fehlermeldung ausgegeben und das Team wird erstellt.

Der Benutzer welches das Team erstellt hat ist somit Teambesitzer.

## 3.8.27 /include/teams/edit.php

Diese Datei funktioniert ähnlich wie die edit.php beim Benutzer, jedoch kann man hier die Informationen des Teams bearbeiten.

Löschen des Teams kann man auch beantragen, das Team wird jedoch nicht gelöscht, es wird nur deaktiviert so wird vermieden das einfach ein neues Team erstellt wird mit gleichem Namen.

Der Teambesitzer kann auch ein Logo des Teams hochladen welches jedoch den vorgeschriebenen Kriterien treu sein muss. Falls dies nicht der Fall ist erhält man eine Fehlermeldung.

Passwortänderung kann auch vorgenommen werden.

Huberty Tom 22/182

### 3.8.28 /include/teams/index.php

Hier werden jegliche Teaminformationen angezeigt so wie auch die Mitglieder des Teams. Wenn man Teammitglied ist erhält man die Option das Team zu leaven. Man wird dann nochmal gefragt ob man sicher sei, dann wird man aus dem Team gelöscht. Als Teambesitzer kann man das Team nicht verlassen man muss zuerst seine Besitzerrechte im edit.php weitergeben.

Als Teambesitzer hat man die Möglichkeit Teammitglieder aus dem Team zu kicken, dies wird durch ein X-Button in der Tabelle der Benutzer vereinfacht, und wird mit zusätzlicher Anfrage ausgeführt.

## 3.8.29 /include/team/join.php

Durch diese Datei hat ein Benutzer welche in keinem Team ist die Möglichkeit einem Team beizutreten. Es muss den genauen Namen des Teams eingeben sonst erhält der Benutzer eine Fehlermeldung dass das Team nicht gefunden wurde.

Ausserdem muss der Benutzer das Passwort des Teams kennen um somit dem Team beitzutreten.

Hat der Benutzer beide Informationen richtig eingeben so ist er Mitglied des angegebenen Teams.

### 3.9. Javascript

## 3.9.1 /include/sorttable.js

Diese Javascript-Datei ermöglicht es Tabellen durch klicken des Titels zu sortieren.

Dies wurde bei fast alles Tabellen der Applikation angewendet.

Diese Javascript wurde von kryogenix.org entnommen.

http://www.kryogenix.org/code/browser/sorttable/

Huberty Tom 23/182

## 4. Anhang

## 4.1. Copyright Hinweise

Die standard.png Bilder in jeweils dem /img/teams und /img/users-Ordner, und die challenge.png in /img stammen von der Seite www.iconfinder.com .

Die Bilder aus dem Ordner /img/smedia Stammen aus einem Freebies Gesamtpaket von <a href="http://www.onextrapixel.com/2014/01/24/freebie-24-free-circular-flat-social-media-icons/">http://www.onextrapixel.com/2014/01/24/freebie-24-free-circular-flat-social-media-icons/</a>

Die Bilder aus dem Ordner /img/partners wurden zur Verfügung gestellt von <u>www.welivegames.com</u> und <u>www.videogames.lu</u> Das dead\_link.png enthält keine zuverlässige Originalquelle (<u>www.reddit.com</u>).

Das Logo von Next Door League wurde von Tom Huberty erstellt.

### 4.2. Source Code

## 4.2.1 Stylesheets

### 4.2.1.1. /cms/style.css

```
/* CSS for the CMS of NextDoor League */
html{
                background-color:#83d8d5;
                font-family:"Calibri";
```

Huberty Tom 24/182

```
color:black;
        width:100%;
       height:100%;
#container{
       background-position:initial;
       background-repeat:initial;
       margin:0 auto;
       max-width:80%;
       min-width:500px;
       height:99%;
/* LOGIN SECTION START */
img.login logo{
        top:30%;
       left:45%;
       position:fixed;
canvas.cms login{
        top:30%;
       left:39.7%;
       position:fixed;
       height:300px;
       width: 300px;
       border-radius:150px;
       background:#FFF;
input.cms login{
       padding-left:2px;
       border:groove 1px #000;
       border-radius:3px;
table.cms login button{
        width: 99%;
       border:1px black solid;
```

Huberty Tom 25/182

```
border-radius:3px;
       cursor:pointer;
table.cms login{
       margin-left:auto;
       margin-right:auto;
       top:32.3%;
       left:41.55%;
       max-width:200px;
       position:fixed;
table.cms login tr{
       height:15px !important;
table.cms login td{
       height:15px !important;
/*LOGIN SECTION END */
/*NAVIGATION SECTION START */
div.cms navigation{
       width:100%;
div.cms navigation button{
       border:none;
       background:#000;
       color:white;
       width:100px;
       height:100px;
       border-radius:50px;
```

Huberty Tom 26/182

```
cursor:pointer;
div.cms navigation button:hover{
      background:rgba(0,0,0,0.2);
button.cms logout{
      width: 70px;
      height: 70px;
      border-radius:35px;
      background:;
/*NAVIGATION SECTION END */
/*MAIN SECTION START */
div.content{
      margin-top:10px;
      width:100%;
      min-height:500px;
      /*background:#0F9;*/
      background: rgba (250, 250, 250, 0.8);
table.news search td{
      margin-left:100px;
/*MAIN SECTION END */
/*ERROR BACKGROUNDFIELD */
input.error{
      background-color:#FF9999;
```

Huberty Tom 27/182

```
table.content{
    padding:0px;
    margin:0px;
    width:100%;
}
textarea.content{
    padding:0px;
    margin:0px;
    min-width:90%;
    width:99%;
}
```

### 4.2.1.2. /stylesheets/standard.css

```
* {
        margin: 0;
        padding: 0;
html {
      /* only the Background-color is changed in each css file(standard.css,blue style.css and orange style.css)
        background-color:#E0E0E0;
        height: 100%;
header, nav, section, article, aside, footer {
        display: block;
body {
        font-family:"Calibri Light";
        width: 100%;
        height: 100%;
        background-repeat:no-repeat;
        background-attachment:fixed;
a {
        color: blue;
```

Huberty Tom 28/182

```
outline: none;
        text-decoration: underline;
a:hover {
        text-decoration: none;
img {
        border: none;
input {
        vertical-align: middle;
#wrapper {
        width: 1000px;
        margin: 0 auto;
        min-height: 100%;
        height: auto !important;
        height: 100%;
/* Header
#filler{
        width: 20%;
        height:100%;
        float:left;
#login{
        width:20%;
        float:right;
        height:100%;
        margin-top:-10px;
        text-align:center;
#login{
```

Huberty Tom

```
float:right;
        height:100%;
        font-family:"Calibri";
.login{
        border:solid grey 1px;
        border-radius:2px;
        padding:2px;
        font-size:16px;
        font-family: "Calibri Light";
.standardbutton{
        font-family:"Calibri Light";
        margin-top:4px;
        margin-right:2%;
        width: 37.8%;
        font-size:15px;
        font-weight:400;
        background:none;
        border:solid black 1px;
        border-radius:2px;
    cursor:pointer;
        background-color:#FFF;
        white-space:nowrap;
.standardbutton:hover{
        transition-duration:0.1s;
        background:#dcdcdc;
#header {
        position:relative;
        height: 165px;
        text-align:center;
```

Huberty Tom 30/182

```
width:100%;
/* CMS */
#panel button{
      width:100%;
      height:20%;
      color:#FFF;
      background-color:black;
       border:none;
      border-radius:4px;
/*Navigation
-----*/
#navigation{
       width: 100%;
      padding-bottom:15px;
      padding-left:3px;
      font-family:Calibri Light;
a.navbutton {
      background-color:black;
      display:inline-block;
      color:#ffffff;
      height:30px;
       width:19.6%;
       -webkit-transform: skew(20deg);
   -moz-transform: skew(20deg);
   -o-transform: skew(20deg);
       cursor:pointer;
      border:none;
       text-decoration:none;
a.navbutton p{
```

Huberty Tom 31/182

```
-webkit-transform: skew(-20deg);
   -moz-transform: skew(-20deg);
   -o-transform: skew(-20deg);
       background:none;
       font-size:16px;
       color:white;
       text-decoration:none;
       text-align:center;
       line-height:30px;
       text-indent:0px;
a.navbutton:hover{
       background-color: rgba(0,0,0,0.2);
/* Middle
          ._____*/
#middle {
       width: 100%;
       padding: 0 0 100px;
       min-height:790px;
       top:auto;
       /*border:1px solid #666;*/
#middle:after {
       content: '';
       clear: both;
       display: table;
#container {
```

Huberty Tom

```
div.news{
       background-color:rgba(255,255,255,0.7);
div.news content{
       margin-left:5px;
       margin-right:5px;
div.news content img{
       margin-left:-5px;
       margin-right:-5px;
table.comments{
       break-inside:auto;
        break-before:auto;
#content {
       background-color:rgba(255,255,255,0.7);
        width: 73%;
        height:100%;
       float: left;
       break-inside:auto;
        break-before:auto;
table.infoedit{
       width:100%;
table.infoedit tr{
        width:100%;
table.infoedit td{
       width:135px;
table.infoview tr{
        width:100%;
```

```
table.infoview td{
        width:135px;
table.stats{
       width:100%;
       border-collapse:collapse;
table.stats tr{
       background: rgba(0,0,0,0.1);
table.stats td{
       border:1px black solid;
table.stats tbody tr:nth-child(2n) td {
 background: rgba(0,0,0,0.1);
table.stats tbody tr:nth-child(2n+1) td {
 background: rgba(255,255,255,0.1);
input.standardinput{
       border:solid grey 1px;
       border-radius:2px;
       padding:2px;
        width: 90%;
        font-size:14px;
        font-family:"Calibri Light";
a.actionbutton{
        font-family:"Calibri Light";
       font-size:15px;
       padding-left:10px;
       padding-right:10px;
        width:auto;
        text-decoration:none;
        color:black;
       background:none;
```

Huberty Tom 34/182

```
border: solid black 1px;
      border-radius:2px;
   cursor:pointer;
      background-color:#FFF;
a.actionbutton:hover{
      transition-duration:0.1s;
      background:#dcdcdc;
.search{
      margin:10px;
      border:solid grey 1px;
      border-radius:2px;
      padding:2px;
      font-family:"Calibri Light";
/* Sidebar Right
   */
#sideRight {
      background-color:rgba(255,255,255,0.5);
      float:right;
      border-radius:3px;
      color:white;
      width: 25%;
      height:auto;
/* Footer
 #footer {
      width: 100.2%;
      height: 150px;
      border-top:#999 1px solid;
      float:left;
```

Huberty Tom 35/182

```
table.footer info{
      width:100%;
table.footer info th{
      background: rgba (0,0,0,0.2);
       width:33.33%;
       text-align:center;
table.footer info td{
       text-align:center;
div.foot list a{
       text-decoration: none;
       color:black;
div.foot list a:hover{
       text-decoration:underline;
/* Registration
, negrotation .....*/
table.td registerform{
      width: 400px;
/* CKEditor Content CSS is needed to show news properly
```

# 4.2.2 PHP

# 4.2.2.1. /cms/index.php

```
<?php
//CONNECT WITH DATABASE
include("../include/config.php");
//CHECK IF USER IS IN DATABASE
include("./include/login.php");
//CHECK IF USER IN DATABASE AND ACTIVATED
if($ SESSION['loggedIN'] == true){
        include("./include/status.php");
//VARIABLES
if(!isset($ SESSION['navigation'])){
        $ SESSION['navigation'] = 'include/news.php';
//CHECK WHICH CONTENT SHOULD BE DISPLAYED
if(isset($ POST['navigation'])){
        $ SESSION['navigation'] = 'include/'.$ POST['navigation'].'.php';
        if ($ POST['navigation'] == 'news') {
                unset($ SESSION['news action']);
        if ($ POST['navigation'] == 'users') {
                unset($ SESSION['user action']);
        if($ POST['navigation'] == 'teams'){
                unset($ SESSION['team action']);
        if($ POST['navigation'] == 'matches') {
```

Huberty Tom 37/182

```
unset($ SESSION['matches action']);
//echo $ SESSION['navigation'];
?>
<!DOCTYPE html>
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
<link href="style.css" rel="stylesheet" type="text/css">
<script src="./ckeditor/ckeditor.js"></script><!-- TEXT EDITOR BY http://ckeditor.com -->
<meta http-equiv="refresh" content="URL=index.php">
<meta http-equiv="Content-Type" content="text/html; charset=utf-8" />
<link rel="SHORTCUT ICON" href="img/ND Logo 250px.png">
<title>ND-League-CMS</title>
</head>
<body>
<!-- LOGIN SECTION BEGIN-->
<form method="post" action="<?=$ SERVER['SCRIPT NAME']?>" id="cms login">
</form>
<?php
      if($ SESSION['loggedIN']==false){?>
<canvas class="cms login"></canvas>
<tr>
   <img src="./img/ND Logo 250px.png" width="75px" ></img>
 <tr>
   Content Managment System
 <?php
             if($errorlogin!==''){ ?>
 <tr>
```

Huberty Tom 38/182

```
<td colspan="3" align="center" style="word-break:break-strict !important; font-size:12.2px; color: #FA6A5A; font-
weight:bold;"><?=$errorlogin?>
 <? }
       if ($ SESSION['loggedIN'] == false) {
 ?>
 Username:
   <input type="text" name="data username" class="cms login" required form="cms login" autofocus >
     </input>
 Password:
   <input type="password" name="data password" class="cms login" required form="cms login" >
     </input>
 >
   <button type="submit" name="BTN logIN" form="cms login" value="Login"> Login </button>
   <a href=".../?page=ForgotPassword"><button type="button" name="BTN rs password">Forgot Password?</button></a>
 <!-- LOGIN SECTION END-->
<? }
} elseif($ SESSION['loggedIN'] == true && ($ SESSION['is admin'] == true || $ SESSION['is moderator'] == true)){?>
<form method="post" action="<?=$ SERVER['SCRIPT NAME']?>" name="cms navigation">
 <div id="container">
   <div name="navigation" class="cms navigation">
     style="<?=($ SESSION['navigation']=='include/news.php'?'background-color:#FF962D;':'');?>">News</button>
     <?php
              if($ SESSION['is admin']==true){?>
     <button type="submit" name="navigation" value="users"</pre>
style="<?=($ SESSION['navigation']=='include/users.php'?'background-color:#FF962D;':'');?>">Users</button>
     <button type="submit" name="navigation" value="teams"</pre>
style="<?=($ SESSION['navigation']=='include/teams.php'?'background-color:#FF962D;':'');?>">Teams</button>
     <? } ?>
```

Huberty Tom 39/182

```
<button type="submit" name="BTN logOUT" class="cms logout">Logout/button>
</form>
    </div>
    <div class="content">
   <form method="post" action="<?=$ SERVER['SCRIPT NAME']?>" name="cms content">
    <input type="text" id="cms action" name="cms action" hidden=""/>
      <?php
                        include($ SESSION['navigation']);
                        //echo $ SESSION['navigation'];
                ?>
    </form>
    </div>
 </div>
<? } ?>
</body>
</html>
```

#### 4.2.2.2. /cms/include

Huberty Tom 40/182

```
//Check if login button is pressed
if (isset($ POST['BTN logIN'])) {
    //Check if user matches the password
    $checkquery = mysql query("SELECT * FROM users WHERE id username ='" .
mysql real escape string($ POST['data username']) . "' and password='" . sha1($ POST['data password']) . "'");
    $check = mysql num rows($checkquery);
    if ($check == 1) {
        $status = mysql result($checkquery, 0, 'active');
    //If not give out error message
    if ($check !== 1) {
        $errorlogin = 'Username or password is wrong.';
        $ SESSION['username'] = '';
       //if user is inactive set error message
    } elseif ($status == 0) {
       $errorlogin = 'Useraccount is inactive.';
        $ SESSION['username'] = '';
    } else {
        //Set session variables according to the user
        $checkquery moderator = mysql query("SELECT * FROM users WHERE id username ='" . $ POST['data username'] . "' AND
is moderator = true");
        $check moderator = mysql num rows($checkquery moderator);
        $checkquery admin = mysql query("SELECT * FROM `users` WHERE `id username` = '" . $ POST['data username'] . "'
AND is admin = true ");
        $check admin = mysql num rows($checkquery admin);
        //Check if the user is admin or moderator to get into the Content Managment System of nextdoorleague
        if ($check admin == 1) {
            $ SESSION['username'] = $ POST['data username'];
            $\frac{1}{2} \text{SESSION['loggedIN']}
                                   = true;
            $ SESSION['is admin']
                                   = true;
            $ SESSION['navigation'] = 'include/news.php';
            $\secondstar \text{SESSION['team id']} = \text{mysql result($checkquery, 0, 'fi team');}
```

Huberty Tom 41/182

```
} elseif ($check moderator == 1) {
                                  $ SESSION['username']
                                                                                                   = $ POST['data username'];
                                  $ SESSION['loggedIN'] = true;
                                  $ SESSION['is moderator'] = true;
                                  $\secondstar \secondstar \seco
                                  $ SESSION['team id'] = mysql result($checkquery, 0, 'fi team');
                                  //if no rights to view cms show error message and unset the user session
                       } else {
                                   $ SESSION['username'] = '';
                       //$ SESSION['menu'] = 'Include/news.php';
//LOGIN END
//LOGOUT
if (isset($ POST['BTN logOUT'])) {
           $ SESSION['loggedIN'] = false;
           $\text{SESSION['is admin']} = \text{false;}
           $ SESSION['team id'] = 0;
           unset($ SESSION['navigation']);
           unset($ SESSION['news action']);
           session destroy();
//LOGOUT END
//GET GET VARIABLES + REDIRECT
function pre page()
                                             = $ SERVER['HTTP REFERER'];
           $url
           $store gets = array();
           parse str(parse url($url, PHP URL QUERY), $store gets);
           $store get key = array keys($store gets);
           //print r($store get key);
           $get GETS = '';
           for (\$i = 0; \$i \le \text{count}(\$store \text{ get key}) - 1; \$i++)
```

Huberty Tom 42/182

## 4.2.2.3. /cms/include/news.php

### <?php //VARIABLES if (!isset(\$ SESSION['news action'])) { \$ SESSION['news action'] = 'search'; \$month = array( '--Month--', 'January', 'February', 'March', 'April', 'May', 'June', 'July', 'August', 'September', 'October',

Huberty Tom 43/182

```
'November',
    'December'
);
//SOL OUERY TO GET NEWS
$news sql = "SELECT * FROM news ORDER BY news.id news DESC";
//CHECK WHICH ACTION IS TAKEN BY THE USER
if (isset($ POST['BTN addnews'])) {
    $ SESSION['news action'] = 'add';
} elseif (isset($ POST['BTN editnews'])) {
   $ SESSION['news action'] = 'edit';
//ADDING A NEWS TO THE DATABASE
if (isset($ POST['news confirmAdd']) && $ SESSION['news action'] == 'add') {
    $date
           = date('d.m.Y');
   $news title = $ POST['news title'];
   $news genre = $ POST['news genre'];
   $news content = $ POST['news editor'];
   $news creator = $ SESSION['username'];
   mysql query("INSERT INTO news(fi username, date, title, text, genre) VALUES ('" . $news creator . "','" . $date .
"','" . $news title . "','" . $news content . "','" . $news genre . "')");
    $ SESSION['news action'] = 'search';
    echo "<meta http-equiv='refresh' content='URL=index.php'>";
//EDITING A NEWS IN THE DATABASE
if (isset($ POST['BTN editnews'])) {
    //echo $ POST['select news'];
   $ SESSION['news action'] = 'edit';
   $news editsql = "SELECT * FROM news WHERE id news = '" . $ POST['select news'] . "' LIMIT 1";
   $news editquery = mysql query($news editsql, $con);
```

Huberty Tom 44/182

```
$news id = mysql result($news editquery, 0, 'id news');
   $news title = mysql result($news editquery, 0, 'title');
   $news genre = mysql result($news editquery, 0, 'genre');
   $news content = mysql result($news editquery, 0, 'text');
//Check if confirmation of news is pressed
if (isset($ POST['news confirmEdit']) && $ SESSION['news action'] == 'edit') {
   $news id = $ POST['news id'];
   $news title = $ POST['news title'];
   $news genre = $ POST['news genre'];
   $news content = $ POST['news editor'];
   mysql query("UPDATE `news` SET title='" . $news title . "',text='" . $news content . "',genre='" . $news genre . "'
WHERE id news=" . $news id . "");
   $ SESSION['news action'] = 'search';
//DELETING NEWS
if (isset($ POST['BTN deletenews'])) {
   mysql query("DELETE FROM news WHERE id news=" . $ POST['select news'] . "");
   $ SESSION['news action'] = 'search';
//EXECUTING THE SEARCH FUNCTION (CHANGING SQL QUERY)
if (isset($ POST['BTN search'])) {
   if ($ POST['search by'] == 0) {
       if (($ POST['select day'] && $ POST['select month'] && $ POST['select year']) > 0) {
           if ($ POST['select day'] < 10) {</pre>
               $ POST['select day'] = "0" . $ POST['select day'];
           if ($ POST['select month'] < 10) {</pre>
               $ POST['select month'] = "0" . $ POST['select month'];
```

Huberty Tom 45/182

```
$ $\text{State} = $\text{POST['select day']} . "." . $\text{POST['select month']} . "." . $\text{POST['select year']};
            $news sql = "SELECT * FROM news WHERE date LIKE '" . $date . "'";
    } elseif ($ POST['search by'] == 1 && $ POST['news search'] !== '') {
        $news sql = "SELECT * FROM news WHERE title REGEXP '" . $ POST['news search'] . "'";
    $ SESSION['news action'] = 'search';
//EXECUTING THE NEWS QUERY AND GETTING NUMBERS OF NEWS
$news result = mysql query($news sql, $con);
$news rows = mysql num rows($news result);
//print r(htmlentities(mysql result($news result, 2, 'text')));
>>
<!--
-->
<?php
if ($ SESSION['news action'] == 'search') {
?>
Search:
  <select name="select day" required>
    <option value="0">--Day--</option>
    <?php
    for ($i = 1; $i <= 31; $i++) {
        echo "<option value='" . $i . "'>" . $i . "</option>";
?>
  </select>
  <select name="select month">
   <?php
   for ($i = 0; $i <= 12; $i++) {
```

Huberty Tom 46/182

```
echo "<option value='" . $i . "'>" . $month[$i] . "</option>";
?>
 </select>
 <select name="select year">
   <option value="0">--Year--
   <?php
   $i = date('Y');
   while ($i >= 1980) {
      echo "<option value='" . $i . "'>" . $i . "</option>";
       $i--;
>>
 </select>
 <input type="text" id="news search" name="news search" hidden=""/>
 <button type="submit" id="BTN search" name="BTN search" role="search">Go !/button>
<input type="radio" name="search by" value="0" checked="checked" onclick="change search(this.value)">
by Date
</input>
<br />
<input type="radio" name="search by" value="1" onclick="change search(this.value)">
by Title
</input>
<p>
 <button name="BTN addnews" type="submit">Add News/button>
 <button name="BTN editnews" type="submit" id="BTN edit" disabled>Edit News/button>
 <button name="BTN deletenews" type="submit" id="BTN delete" onclick="return confirm('Do you really want to delete this</pre>
news?');" disabled>Delete News</button>
Title:
   Date:
   Username:
```

Huberty Tom 47/182

```
Genre:
 < select size="10" name="select news"
style=";height:100px;width:100%;border:none;" onchange="get newsinfo();enable buttons();">
       <?
   $i = 0;
   while ($i < $news rows) {</pre>
       $optionname = htmlentities(mysql result($news result, $i, 'title'));
       $optionid = htmlentities(mysql result($news result, $i, 'id news'));
       echo "<option value='" . $optionid . "'>" . $optionname . "</option>";
       $i++;
?>
     </select>
   <select size="1" name="select newsdate" hidden="true" >
       <?
   \dot{s}_i = 0:
   while ($i < $news rows) {</pre>
       $optionname = htmlentities(mysql result($news result, $i, 'date'));
       echo "<option value='" . $optionname . "'>" . $optionname . "</option>";
       $i++;
?>
     </select>
     <label id="news date">/</label>
   <select size="1" name="select newsuser" hidden="true" >
       <?
   $i = 0;
   while ($i < $news rows) {</pre>
       $optionname = htmlentities(mysql result($news result, $i, 'fi username'));
       echo "<option value='" . $optionname . "'>" . $optionname . "</option>";
       $i++;
?>
```

Huberty Tom 48/182

```
</select>
    <label id="news username">/</label>
   <select size="1" name="select newsgenre" hidden="true" >
   $i = 0;
   while ($i < $news rows) {</pre>
      $optionname = htmlentities(mysql result($news result, $i, 'genre'));
      echo "<option value='" . $optionname . "'>" . $optionname . "</option>";
      $i++;
?>
     </select>
     <label id="news genre">/</label>
 <?
} elseif ($ SESSION['news action'] == 'add') {
<h1>Add News</h1>
>
   Title: 
   <input type="text" name="news title" required="required"/>
     <br />
 >
   Genre:
   <select size="1" name="news genre">
      <option value="Gaming">Gaming</option>
      <option value="Hardware">Hardware
      <option value="Software">Software
     </select>
     <br />
 <textarea id="news editor" name="news editor" >
```

Huberty Tom 49/182

```
Enter your news here...
       </textarea>
<br />
<button type="submit" name="news confirmAdd">Post</button>
} elseif ($ SESSION['news action'] == 'edit') {
<h1>Edit News</h1>
<input type="text" name="news id" hidden="" value="<?= $news id ?>" />
<t.r>
   Title: 
   <input type="text" name="news title" value="<?=htmlspecialchars($news title),ENT QUOTES)?>" required="required"/>
     <br />
 >
   Genre:
   <select size="1" name="news genre">
       <option value="Gaming">Gaming</option>
       <option value="Hardware">Hardware
       <option value="Software">Software
     </select>
     <br />
 <textarea id="news editor" name="news editor"><<?= htmlspecialchars($news content),ENT QUOTES) ?>
</textarea>
<br />
<button type="submit" name="news confirmEdit">Edit</button>
} elseif ($ SESSION['news action'] == 'delete') {
?>
<h1>Delete News</h1>
<?
?>
<script>
```

Huberty Tom 50/182

```
// Replace the <textarea id="news editor"> with a CKEditor
        // instance, using default configuration.
        CKEDITOR.replace( 'news editor');
        // Enabled Edit and Delete Button for News/User/Teams
    function enable buttons(){
                document.getElementById('BTN edit').disabled=false;
                        document.getElementById('BTN delete').disabled=false;
        function get newsinfo() {
                document.getElementsByName('select newsdate').item(0).selectedIndex =
document.getElementsByName('select news').item(0).selectedIndex;
                document.getElementsByName('select newsuser').item(0).selectedIndex =
document.getElementsByName('select news').item(0).selectedIndex;
                document.getElementsByName('select newsgenre').item(0).selectedIndex =
document.getElementsByName('select news').item(0).selectedIndex;
                document.getElementById('news date').innerHTML =
document.getElementsByName('select newsdate').item(0).value;
                document.getElementById('news username').innerHTML =
document.getElementsByName('select newsuser').item(0).value;
                document.getElementById('news genre').innerHTML =
document.getElementsByName('select newsgenre').item(0).value;
        function change search(radio value) {
                if(radio value==0){
                        document.getElementsByName('select day').item(0).hidden='';
                        document.getElementsByName('select month').item(0).hidden='';
                        document.getElementsByName('select year').item(0).hidden='';
                        document.getElementById('news search').hidden = 'hidden';
                if(radio value==1) {
                        document.getElementsByName('select day').item(0).hidden='hidden';
                        document.getElementsByName('select month').item(0).hidden='hidden';
                        document.getElementsByName('select year').item(0).hidden='hidden';
                        document.getElementById('news search').hidden = '';
```

Huberty Tom 51/182

```
} </script>
```

#### 4.2.2.4. /cms/include/status.php

```
//Does the user exist? If not unset session.
$check_user_status_q = mysql_query("SELECT * FROM users WHERE id_username = '" . $_SESSION['username'] . "'");
$check_user_exist = mysql_num_rows($check_user_status_q);

if ($check_user_exist == 1) {

    //Check if user is active else unset session.
    $check_status = mysql_result($check_user_status_q, 0, 'active');
    if ($check_status == 0) {
        $_SESSION['loggedIN'] == false;
    }
} else {
    $_SESSION['loggedIN'] == false;
}
}
```

### 4.2.2.5. /cms/include/teams.php

```
<?php
//VARIABLES
if (!isset($_SESSION['team_action'])) {
    $_SESSION['team_action'] = 'search';
}
$email_msg = '';
$errorteamname = 0;
$teamname msg = '';</pre>
```

Huberty Tom

```
$password msq = '';
//echo $ SESSION['team action'];
//SOL OUERY TO GET NEWS
$teams sql = "SELECT * FROM teams ORDER BY teams.teamname ASC ";
//CHECK WHICH ACTION IS TAKEN BY THE USER
if (isset($ POST['BTN addteam'])) {
  $ SESSION['team action'] = 'add';
  $new teamname
  $new website
                   = '';
  $new leader
                    = '';
  $new descr
                    = '';
  $new logo
} elseif (isset($ POST['BTN editteam'])) {
  $ SESSION['team action'] = 'edit';
if (isset($ POST['team confirmAdd']) && $ SESSION['team action'] == 'add') {
  $ SESSION['team action'] = 'search';
  = 1\overline{1};
  $new logo
  //CHECK teamname
               = $ POST['teamname'];
  $new teamname
  $new teamname nospace = str replace(' ', '', $new teamname);
  $checkteam q1 = mysql query("SELECT * FROM teams WHERE teamname = '" . $new teamname . "'");
  $checkteam1 = mysql num rows($checkteam q1);
```

Huberty Tom 53/182

```
$check allTeams = mysql query("SELECT * FROM teams");
    $check numTeams = mysql num rows($check allTeams);
                = 0:
    checkteam2 = 0;
   while ($i < $check numTeams && $checkteam2 == 0) {</pre>
        if (strtolower(str replace(' ', '', mysql result($check allTeams, $i, 'teamname'))) == strtolower($new teamname))
            checkteam2 = 1;
        if (strtolower(str replace(' ', '', mysql result($check allTeams, $i, 'teamname')))) ==
strtolower($new teamname nospace)) {
            $checkteam2 = 1;
        $i++;
    //echo $checkteam;
    if ($checkteam1 !== 0 || $checkteam2 !== 0) {
        $errorteamname = 1;
        $teamname msg = 'Teamname already exists!';
    //CHECK IF PASSWORDS ARE CORRECT
    //PASSWORD
   if ($ POST['new password1'] == $ POST['new password2']) {
        $check pw
                     = true;
       $new password = shal($ POST['new password1']);
    } else {
        $check pw
                     = false;
        $password msg = 'Both passwords have to be the same!';
```

Huberty Tom 54/182

```
if ($errorteamname == 0 && $check pw == true) {
      //CHECK NEW teams RIGHTS
      mysql query("INSERT INTO teams(teamname, fi username, password, website, logo, description) VALUES ('".
$new teamname . "','" . $new leader . "','" . $new password . "','" . $new website . "','" . $new descr . "')");
      $id teamsql = "SELECT * FROM teams WHERE teamname = '" . $new teamname . "' LIMIT 1";
      $id teamquery = mysql query($id teamsql, $con);
      $id team
                  = mysql result($id teamquery, 0, 'id team');
      mysql query("UPDATE users SET fi team = '" . $id team . "' WHERE id username = '" . $new leader . "'");
      $ SESSION['team action'] = 'search';
   } else {
      $ SESSION['team action'] = 'add';
//////////// EDITING A TEAM IN THE
if (isset($ POST['BTN editteam'])) {
   $ SESSION['team action'] = 'edit';
   //GET INFORMATION OF DATABASE
   $team editsql
                       = "SELECT * FROM teams WHERE id team = '" . $ POST['select teams'] . "' LIMIT 1";
                     = mysql query($team editsql, $con);
   $team editquery
                       = mysql result($team editquery, 0, 'teamname');
   Steamname
   $old teamname
                       = $teamname;
   $team id
                       = mysql result($team editquery, 0, 'id team');
   $team leader
                      = mysql result($team editquery, 0, 'fi username');
                       = htmlspecialchars(mysql result($team editquery, 0, 'website'), ENT QUOTES);
   $team website
                       = htmlspecialchars(mysql result($team editquery, 0, 'description'), ENT QUOTES);
   $team descr
                        = mysql result($team editquery, 0, 'logo');
   $new logo
```

Huberty Tom 55/182

```
//echo $user rights;
if (isset($ POST['team confirmEdit']) && $ SESSION['team action'] == 'edit') {
    $old teamname = $ POST['old teamname'];
    $team id = $ POST['team id'];
    $teamname = $ POST['teamname'];
    $team website = $ POST['website'];
    $team descr = $ POST['descr'];
    $team leader = $ POST['team leader'];
    //CHECK Teamname
   if ($teamname !== $ POST['old teamname']) {
       $checkteam q = mysql query("SELECT * FROM teams WHERE teamname = '" . $teamname . "'");
        $checkteam = mysql num rows($checkteam q);
        if ($checkteam >= 1) {
           $errorteamname = 1;
           $teamname msg = 'Teamname already exists!';
    //CHECK TEAMLEADER
   if ($ POST['ch leader'] == 1) {
       $team leader = $ POST['sel leader'];
    //CHECK IF PASSWORDS ARE CORRECT
   if (($ POST['new password1'] || $ POST['new password2']) !== '') {
       $pass change = 1;
       if ($ POST['new password1'] == $ POST['new password2']) {
           $check pw = true;
           $new password = shal($ POST['new password1']);
        } else {
            $check pw = false;
           $password msg = 'Both passwords have to be the same!';
```

Huberty Tom 56/182

```
} else {
      pass change = 0;
   if ($errorteamname == 0 && $pass change == 1 && $check pw == true) {
      //CHECK NEW teams RIGHTS
      mysql query("UPDATE teams SET teamname='" . $teamname . "',fi username='" . $team leader . "',password='" .
$new password . "', website='" . $team website . "', logo='', description='" . $team descr . "' WHERE id team ='" . $team id
$ SESSION['team action'] = 'search';
   } elseif ($errorteamname == 0 && $pass change == 0) {
      mysql query("UPDATE teams SET teamname='" . $teamname . "',fi username='" . $team leader . "',website='" .
$team website . "',logo='',description='" . $team descr . "' WHERE id team ='" . $team id . "'");
      $ SESSION['team action'] = 'search';
///////////////// DELETING A TEAM TO THE DATABASE +
if (isset($ POST['BTN deleteteam'])) {
   //SET FI TEAM OF MEMBERS TO 0
   $members sql = "SELECT * FROM users WHERE fi team = '" . $ POST['select teams'] . "'";
   $members result = mysql query($members sql, $con);
   $members rows = mysql num rows($members result);
   for ($i = 0; $i <= $members rows - 1; $i++) {
      $membername = mysql result($members result, $i, 'id username');
      mysql query("UPDATE users SET fi team = 0 WHERE id username = '" . $membername . "'");
   //DELETING TEAM
```

Huberty Tom 57/182

```
mysql query("DELETE FROM teams WHERE id team = '" . $ POST['select teams'] . "'");
  $ SESSION['team action'] = 'search';
//EXECUTING THE SEARCH FUNCTION (CHANGING SQL QUERY)
if (isset($ POST['BTN search'])) {
  if ($ POST['team search'] !== '') {
     if ($ POST['search by'] == 0) {
        $teams sql = "SELECT * FROM teams WHERE teamname REGEXP '" . $ POST['team search'] . "'";
     } elseif ($ POST['search by'] == 1) {
        $teams sql = "SELECT * FROM teams WHERE fi username REGEXP '" . $ POST['team search'] . "'";
  $ SESSION['team action'] = 'search';
//EXECUTING THE teams QUERY AND GETTING NUMBERS OF teams
$teams result = mysql query($teams sql, $con);
$teams rows = mysql num rows($teams result);
//print r(htmlentities(mysql result($teams result, 2, 'text')));
?>
<!--
-->
<?php
```

Huberty Tom 58/182

```
if ($ SESSION['team action'] == 'search') {
2>
Search:
 <input type="text" id="team search" name="team search"/>
 <button type="submit" id="BTN search" name="BTN search" role="search">Go !/button>
<input type="radio" name="search by" value="0" checked="checked">
by Teamname
</input>
<br />
<input type="radio" name="search by" value="1">
by Leader
</input>
</p>
<q>
 <button name="BTN addteam" type="submit">Add Team/button>
 <button name="BTN editteam" type="submit" id="BTN edit" disabled >Edit Team/button>
 delete this team?');">Delete Team</button>
<a>
Teamname:
   Website:
   Leader:
 >
   <select size="10" name="select teams"
style=";height:100px;width:100%;border:none;" onchange="get userinfo();enable buttons();">
      <?
   \dot{s}_i = 0:
   while ($i < $teams rows) {</pre>
      $optionname = htmlentities(mysql result($teams result, $i, 'teamname'));
      $optionid = htmlentities(mysql result($teams result, $i, 'id team'));
      echo "<option value='" . $optionid . "'>" . $optionname . "</option>";
      $i++;
```

Huberty Tom 59/182

```
2>
     </select>
   <select size="1" name="select teamwebsite" hidden="true" >
   $i = 0;
   while ($i < $teams rows) {</pre>
       if (mysql result($teams result, $i, 'website') !== '') {
          $optionname = htmlentities(mysql result($teams result, $i, 'website'));
       } else {
          $optionname = '/';
       echo "<option value='" . $optionname . "'>" . $optionname . "</option>";
       $i++;
?>
     </select>
     <label id="teams website">/</label>
   <select size="1" name="select teamleader" hidden="true" >
       <?
   $i = 0;
   while ($i < $teams rows) {</pre>
       $optionname = mysql result($teams result, $i, 'fi username');
      echo "<option value='" . $optionname . "'>" . $optionname . "</option>";
       $i++;
?>
     </select>
     <label id="teams leader">/</label>
 } elseif ($ SESSION['team action'] == 'add') {
<h1>Add Team</h1>
```

Huberty Tom 60/182

```
>
   Teamname*: 
   <input type="text" name="teamname" maxlength="20" pattern="^[A-Za-z0-9] {1,20}$" title="Only a-z,A-Z, ,0-9.</pre>
Minimum 1 character." value="<?= $new teamname ?>" required="required"/>
   <?= $teamname msq ?>
 >
   Website: 
   <input type="text" name="website" value="<?=htmlspecialchars($new website),ENT QUOTES)?>"
          autocomplete="off"/>
 >
   Leader: 
   <td>
   <select size="1" name="leader" style="width:150px">
   <?php
   $members sql = "SELECT * FROM users WHERE fi team = 0";
   $members result = mysql query($members sql, $con);
   $members rows = mysql num rows($members result);
   for ($i = 0; $i <= $members rows - 1; $i++) {</pre>
       $membername = mysql result($members result, $i, 'id username');
       echo "<option value="" . $membername . "'>" . $membername . "</option>";
?>
   </select>
   >
   Password*:
   <input pattern=".{7,}" title="7 characters minimum." type="password" name="new password1" required</pre>
autocomplete="off" />
   <?= $password msq ?>
 >
   Repeat Password*:
   <input pattern=".{7,}" title="7 characters minimum." type="password" name="new password2" required />
```

Huberty Tom 61/182

```
>
   Description: 
   <textarea name="descr"><?= htmlspecialchars($new descr,ENT QUOTES) ?></textarea>
 <br />
<button type="submit" name="team confirmAdd">Add Team/button>
} elseif ($ SESSION['team action'] == 'edit') {
>>
<h1>Edit Team</h1>
>
   Teamname: 
   <input type="text" name="old teamname" hidden="" value="<?= $old teamname ?>"/><input type="text" name="team id"
hidden="" value="<?= $team id ?>" />
     <input type="text" name="teamname" pattern="^[A-Za-z0-9 ]{1,20}$" title="Only a-z,A-Z, ,0-9. Minimum 1 character."</pre>
value="<?= $teamname ?>" required="required"/>
   <?= $teamname msq ?>
 >
   Website: 
   <input type="text" name="website" value="<?= $team website ?>"/>
 >
   Leader: 
   <td>
   <input type="text" name="ch leader" value="0" hidden="" />
   <input type="text" name="team leader" id="show leader" readonly="readonly" value="<?= $team leader ?>" />
   <button type="button" onclick="change leader();" id="change">Change</putton>
   <select size="1" name="sel leader" style="width:150px" hidden="">
   <?php
   $members sql
                 = "SELECT * FROM users WHERE fi team = '" . $team id . "'";
   $members result = mysql query($members sql, $con);
   $members rows = mysql num rows($members result);
   for ($i = 0; $i <= $members rows - 1; $i++) {
       $membername = mysql result($members result, $i, 'id username');
```

Huberty Tom 62/182

```
echo "<option value='" . $membername . "'>" . $membername . "</option>";
?>
   </select>
   >
   Password*:
   <input pattern="{7,}" title="7 characters minimum." type="password" name="new password1" />
   <?= $password msq ?>
 <tr>
   Repeat Password*:
   <input pattern=".{7,}" title="7 characters minimum." type="password" name="new password2" />
 >
   Description: 
   <textarea name="descr"><?= $team descr ?></textarea>
 >
    Logo: 
   <input type="file" accept="image/*" name="logo" />
 </tr>
<br />
<button type="submit" name="team confirmEdit">Edit Team/button>
<?
} elseif ($ SESSION['team action'] == 'delete') {
?>
<h1>Delete Team</h1>
<?
}
?>
<script>
      // Replace the <textarea id="news editor"> with a CKEditor
      // instance, using default configuration.
      CKEDITOR.replace( 'news editor');
```

Huberty Tom 63/182

```
// Enabled Edit and Delete Button for News/User/Teams
    function enable buttons() {
                document.getElementById('BTN edit').disabled=false;
                        document.getElementById('BTN delete').disabled=false;
        // Update user information according to the user selected
        function get userinfo(){
                document.getElementsByName('select teamwebsite').item(0).selectedIndex =
document.getElementsByName('select teams').item(0).selectedIndex;
                document.getElementsByName('select teamleader').item(0).selectedIndex =
document.getElementsByName('select teams').item(0).selectedIndex;
                document.getElementById('teams website').innerHTML =
document.getElementsByName('select teamwebsite').item(0).value;
                document.getElementById('teams leader').innerHTML =
document.getElementsByName('select teamleader').item(0).value;
        //show members to to change the leader of a team
        function change leader() {
                if (document.getElementById('show leader').hidden==false) {
                document.getElementById('show leader').hidden=true;
                document.getElementsByName('sel leader').item(0).hidden=false;
                document.getElementsByName('ch leader').item(0).value=1;
                document.getElementById('change').innerHTML = "Don't Change";
                }else{
                document.getElementById('show leader').hidden=false;
                document.getElementsByName('sel leader').item(0).hidden=true;
                document.getElementsByName('ch leader').item(0).value=0;
                document.getElementById('change').innerHTML = "Change";
</script>
```

Huberty Tom 64/182

### 4.2.2.6. /cms/include/users.php

```
<?php
//VARIABLES
if (!isset($ SESSION['user action'])) {
   $ SESSION['user action'] = 'search';
\$erroremail = 0:
$email msq = '';
$errorusername = 0;
$username msg = '';
$password msg = '';
//echo $ SESSION['user action'];
//SQL QUERY TO GET NEWS
$users sql = "SELECT * FROM users ORDER BY users.id username ASC ";
//CHECK WHICH ACTION IS TAKEN BY THE USER
if (isset($ POST['BTN adduser'])) {
   $ SESSION['user action'] = 'add';
   $new username
                     = '';
   $new firstname = '';
  $new_lastname
$new_email
$new_skypeid
$new_steamid
$new_lolid
                     = '';
                     = '';
  $new streamid
                     = 11;
   $user avatar
                     = '';
} elseif (isset($ POST['BTN edituser'])) {
   $ SESSION['user action'] = 'edit';
```

Huberty Tom 65/182

```
if (isset($ POST['user confirmAdd']) && $ SESSION['user action'] == 'add') {
    $new firstname = utf8 decode(mysql real escape string($ POST['firstname']));
   $new lastname = utf8 decode(mysql real escape string($ POST['lastname']));
   $new skypeid = utf8 decode(mysgl real escape string($ POST['skypeID']));
   $new steamid = utf8 decode(mysql real escape string($ POST['steamID']));
                 = utf8 decode(mysql real escape string($ POST['lolID']));
    $new lolid
   $new streamid = utf8 decode(mysql real escape string($ POST['streamID']));
   //CHECK USERNAME
    $new username = $ POST['username'];
   $checkuser q = mysql query("SELECT * FROM users WHERE id username = '" . $new username . "'");
   $checkuser = mysql num rows($checkuser q);
   if (\$checkuser >= 1) {}
       $errorusername = 1;
       $username msq = 'Username already exists!';
   //CHECK EMAIL IF ALREADY IN USE
   $new email = $ POST['email'];
   $checkemail q = mysql query("SELECT * FROM users WHERE email = '" . $new email . "'");
    $checkemail = mysql num rows($checkemail q);
   if ($checkemail >= 1) {
       $erroremail = 1;
       $email msg = 'Email is already in use!';
   //CHECK IF PASSWORDS ARE CORRECT
   //PASSWORD
   if ($ POST['new password1'] == $ POST['new password2']) {
       $check pw = true;
       $new password = shal($ POST['new password1']);
    } else {
       $check pw
                     = false;
       $password msg = 'Both passwords have to be the same!';
```

Huberty Tom 66/182

```
}
   if ($errorusername == 0 && $erroremail == 0 && $check pw == true) {
       //CHECK NEW USERS RIGHTS
       if ($ POST['user rights'] == 0) {
          echo 'exe1';
          mysql query("INSERT INTO users (id username, is admin, is moderator, fi team, email, password,
firstname, lastname, skypeid, steamid, lolid, stream, avatar) VALUES ('" . $new username . "','0','0','','" . $new email .
"','" . $new password . "','" . $new firstname . "','" . $new lastname . "','" . $new skypeid . "','" . $new steamid .
"','" . $new lolid . "','" . $new streamid . "','standard.png')");
      } elseif ($ POST['user rights'] == 1) {
          echo 'exe2';
          mysql query("INSERT INTO users (id username, is admin, is moderator, fi team, email, password,
firstname, lastname, skypeid, steamid, lolid, stream, avatar) VALUES ('". Snew username. "','0','1',''". Snew email.
"','" . $new password . "','" . $new firstname . "','" . $new lastname . "','" . $new skypeid . "','" . $new steamid .
"','" . $new lolid . "','" . $new streamid . "','standard.png')");
       } elseif ($ POST['user rights'] == 2) {
          echo 'exe3';
          mysql query("INSERT INTO users (id username, is admin, is moderator, fi team, email, password,
firstname, lastname, skypeid, steamid, lolid, stream, avatar) VALUES ('" . $new username . "','1','0','','" . $new email .
"','" . $new password . "','" . $new firstname . "','" . $new lastname . "','" . $new skypeid . "','" . $new steamid .
"','" . $new lolid . "','" . $new streamid . "','standard.png')");
       $ SESSION['user action'] = 'search';
}
if (isset($ POST['BTN edituser'])) {
   $ SESSION['user action'] = 'edit';
```

Huberty Tom 67/182

```
//GET INFORMATION OF DATABASE
                            = "SELECT * FROM users WHERE id username = '" . $ POST['select users'] . "' LIMIT 1";
    $user editsql
    $user editquery
                            = mysql query($user editsql, $con);
    $username
                            = mysql result($user editquery, 0, 'id username');
                            = $username;
    $old username
                            = mvsql result($user editquery, 0, 'active');
   $user active
                            = mysql result($user editquery, 0, 'is admin');
   $user isAdmin
                            = mysql result($user editquery, 0, 'is moderator');
    $user_isModerator
                            = mysql result($user editquery, 0, 'fi team');
    $user team
    $user firstname
                            = htmlspecialchars(mysql result($user editquery, 0, 'firstname'),ENT QUOTES);
                            = htmlspecialchars(mysql result($user editquery, 0, 'lastname'), ENT QUOTES);
    $user lastname
                            = mysql result($user editquery, 0, 'email');
   $user email
                            = $user email;
    $old email
                            = htmlspecialchars(mysql result($user editquery, 0, 'skypeid'),ENT QUOTES);
    $user skypeid
    $user steamid
                            = htmlspecialchars(mysql result($user editquery, 0, 'steamid'),ENT QUOTES);
                            = htmlspecialchars(mysql result($user editquery, 0, 'lolid'), ENT QUOTES);
    $user lolid
                            = mysql result($user editquery, 0, 'stream');
    $user streamid
    $user avatar
                            = mysql result($user editquery, 0, 'avatar');
    //CHECK WHICH RIGHTS THE USER HAS
   if ($user isModerator == 1) {
       $user rights = 1;
   } elseif ($user isAdmin == 1) {
       $user rights = 2;
    } else {
       suser rights = 0;
   //echo $user rights;
//Check is status will be changed for a user
if (isset($ POST['BTN statuschange']) && $ SESSION['user action'] == 'edit') {
    $old username = $ POST['old username'];
   $old email = $ POST['old email'];
   $username
                   = $ POST['username'];
   $user active
                   = $ POST['status'];
```

Huberty Tom 68/182

```
$user email = $ POST['email'];
   $user rights = $ POST['user rights'];
    $user firstname = utf8 decode(mysql real escape string($ POST['firstname']));
    $user lastname = utf8 decode(mysql real escape string($ POST['lastname']));
   $user skypeid = utf8 decode(mysql real escape string($ POST['skypeID']));
   $user steamid = utf8 decode(mysql real escape string($ POST['steamID']));
   $user lolid = utf8 decode(mysql real escape string($ POST['lolID']));
   $user streamid = utf8 decode(mysgl real escape string($ POST['streamID']));
   // update user to active or inactive
   if ($user active == 'Activated') {
       mysql query("UPDATE users SET active = 0 WHERE id username = '" . $old username . "'");
   } else {
       mysql query("UPDATE users SET active = 1 WHERE id username = '" . $old username . "'");
    $ SESSION['user action'] = 'search';
//Check if a user will be edited
if (isset($ POST['user confirmEdit']) && $ SESSION['user action'] == 'edit') {
    $old username = $ POST['old username'];
   $old email = $ POST['old email'];
    $username = $ POST['username'];
   $user email = $ POST['email'];
   $user rights = $ POST['user rights'];
   $user firstname = utf8 decode(mysql real escape string($ POST['firstname']));
    $user lastname = utf8 decode(mysql real escape string($ POST['lastname']));
   $user skypeid = utf8 decode(mysql real escape string($ POST['skypeID']));
   $user steamid = utf8 decode(mysgl real escape string($ POST['steamID']));
   $user lolid
                   = utf8 decode(mysql real escape string($ POST['lolID']));
   $user streamid = utf8 decode(mysql real escape string($ POST['streamID']));
   //CHECK USERNAME
   if ($username !== $ POST['old username']) {
       $checkuser q = mysql query("SELECT * FROM users WHERE id username = '" . $username . "'");
       $checkuser = mysql num rows($checkuser q);
       //echo $checkuser;
```

Huberty Tom 69/182

```
if ($checkuser >= 1) {
            $errorusername = 1;
            $username msg = 'Username already exists!';
    //CHECK EMAIL IF ALREADY IN USE
    if ($user email !== $ POST['old email']) {
        $checkemail q = mysql query("SELECT * FROM users WHERE email = '" . $user email . "'");
        $checkemail = mysql num rows($checkemail q);
        //echo $checkemail;
        if ($checkemail >= 1) {
            $erroremail = 1;
            $email msq = 'Email is already in use!';
    //CHECK IF PASSWORDS ARE CORRECT
    if ($ POST['new password1'] == '' && $ POST['new password2'] == '') {
        pass change = 0;
    } else {
        $pass change = 1;
        if ($ POST['new password1'] == $ POST['new password2']) {
            $check pw = true;
            $new password = shal($ POST['new password1']);
       } else {
            $check pw
                         = false;
            $password msg = 'Both passwords have to be the same!';
    //echo 'passchange '.$pass change.'';
    if ($errorusername == 0 && $erroremail == 0 && $pass change == 1 && $check pw == true) {
        //CHECK NEW USERS RIGHTS
        if ($ POST['user rights'] == 0) {
           mysql query("UPDATE users SET id username='" . $username . "', is admin='0', is moderator='0', email='" .
$user email . "',password='" . $new password . "',firstname='" . $user firstname . "',lastname='" . $user lastname .
"', skypeid='" . $user skypeid . "', steamid='" . $user steamid . "', lolid='" . $user lolid . "', stream='" . $user streamid
```

Huberty Tom 70/182

```
. "' WHERE id username='" . $old username . "'");
       } elseif ($ POST['user rights'] == 1) {
           mysql query("UPDATE users SET id username='" . $username . "', is admin='0', is moderator='1', email='" .
$user email . "',password='" . $new password . "',firstname='" . $user firstname . "',lastname='" . $user lastname .
"', skypeid='" . $user skypeid . "', steamid='" . $user steamid . "', lolid='" . $user lolid . "', stream='" . $user streamid
. "' WHERE id username='" . $old username . "'");
       } elseif ($ POST['user rights'] == 2) {
           mysql query("UPDATE users SET id username='" . $username . "', is admin='1', is moderator='0'', email='" .
Suser email . "', password='" . Snew password . "', firstname='" . Suser firstname . "', lastname='" . Suser lastname .
"', skypeid='" . $user skypeid . "', steamid='" . $user steamid . "', lolid='" . $user lolid . "', stream='" . $user streamid
. "' WHERE id username='" . $old username . "'");
       $ SESSION['user action'] = 'search';
   } elseif ($errorusername == 0 && $erroremail == 0 && $pass change == 0) {
       if ($ POST['user rights'] == 0) {
           mysql query("UPDATE users SET id username='" . $username . "', is admin='0', is moderator='0', email='" .
Suser email . "', firstname='" . Suser firstname . "', lastname='" . Suser lastname . "', skypeid='" . Suser skypeid .
"', steamid='" . $user steamid . "', lolid='" . $user lolid . "', stream='" . $user streamid . "' WHERE id username='" .
$old username . "'");
       } elseif ($ POST['user rights'] == 1) {
           mysql query("UPDATE users SET id username='" . $username . "', is admin='0', is moderator='1', email='" .
Suser email . "', firstname='" . Suser firstname . "', lastname='" . Suser lastname . "', skypeid='" . Suser skypeid .
"', steamid='" . $user steamid . "', lolid='" . $user lolid . "', stream='" . $user streamid . "' WHERE id username='" .
$old username . "'");
       } elseif ($ POST['user rights'] == 2) {
           mysql query("UPDATE users SET id username='" . $username . "',is admin='1',is moderator='0',email='" .
$user email . "', firstname='" . $user firstname . "', lastname='" . $user lastname . "', skypeid='" . $user skypeid .
"', steamid='" . $user steamid . "', lolid='" . $user lolid . "', stream='" . $user streamid . "' WHERE id username='" .
$old username . "'");
       $ SESSION['user action'] = 'search';
```

Huberty Tom 71/182

```
if (isset($ POST['BTN deleteuser'])) {
  mysql query("DELETE FROM users WHERE id username = '" . $ POST['select users'] . "'");
  $ SESSION['user action'] = 'search';
//EXECUTING THE SEARCH FUNCTION (CHANGING SQL QUERY)
if (isset($ POST['BTN search'])) {
  if ($ POST['user search'] !== '') {
     if ($ POST['search by'] == 0) {
       $users sql = "SELECT * FROM users WHERE id username REGEXP '" . $ POST['user search'] . "'";
     } elseif ($ POST['search by'] == 1) {
       $users sql = "SELECT * FROM users WHERE email REGEXP '" . $ POST['user search'] . "'";
  $ SESSION['user action'] = 'search';
//EXECUTING THE USERS QUERY AND GETTING NUMBERS OF USERS
$users result = mysql query($users sql, $con);
$users rows = mysql num rows($users result);
//print r(htmlentities(mysql result($users result, 2, 'text')));
?>
<!--
```

Huberty Tom 72/182

```
-->
<?php
if ($ SESSION['user action'] == 'search') {
Search:
 <input type="text" id="user search" name="user search"/>
 <button type="submit" id="BTN search" name="BTN search" role="search">Go !/button>
<a>
<input type="radio" name="search by" value="0" checked="checked">
by Username
</input>
<br />
<input type="radio" name="search by" value="1">
by Email
</input>
<button name="BTN adduser" type="submit">Add User/button>
 <button name="BTN edituser" type="submit" id="BTN edit" disabled>Edit User
 user?');" disabled>Delete User</button>
</p>
Username:
  Firstname:
  Lastname:
  E-mail:
  Rights:
 <tr>
  <select size="10" name="select users" style=";height:100px;width:100%;border:none;"
onchange="get userinfo();enable buttons();">
     <?
  $i = 0;
  while ($i < $users rows) {</pre>
```

Huberty Tom 73/182

```
$optionname = htmlentities(mysql result($users result, $i, 'id username'));
       echo "<option value='" . $optionname . "'>" . $optionname . "</option>";
       $i++;
?>
     </select>
   <select size="1" name="select usersfirstname" hidden="true" >
   $i = 0;
   while ($i < $users rows) {</pre>
       if (mysgl result($users result, $i, 'firstname') !== '') {
           $optionname = htmlentities(mysql result($users result, $i, 'firstname'));
       } else {
           $optionname = '/';
       echo "<option value='" . $optionname . "'>" . $optionname . "</option>";
       $i++;
?>
     </select>
     <label id="users firstname">/</label>
   <select size="1" name="select userslastname" hidden="true" >
       <?
   $i = 0;
   while ($i < $users rows) {</pre>
       if (mysql result($users result, $i, 'lastname') !== '') {
           $optionname = htmlentities(mysql result($users result, $i, 'lastname'));
       } else {
           $optionname = '/';
       echo "<option value='" . $optionname . "'>" . $optionname . "</option>";
       $i++;
?>
     </select>
```

Huberty Tom 74/182

```
<label id="users lastname">/</label>
   <select size="1" name="select usersemail" hidden="true" >
       <?
   $i = 0;
   while ($i < $users rows) {</pre>
       $optionname = htmlentities(mysql result($users result, $i, 'email'));
       echo "<option value='" . $optionname . "'>" . $optionname . "</option>";
       $i++;
?>
     </select>
     <label id="users email">/</label>
 <select name="show rights" hidden="">
       <?
   $i = 0;
   while ($i < $users rows) {</pre>
       $ch admin = htmlentities(mysql result($users result, $i, 'is admin'));
       $ch mod = htmlentities(mysql result($users result, $i, 'is moderator'));
       if (\$ch admin == 0 \& \& \$ch mod == 1) {
          $optionname = 'Moderator';
       } elseif ($ch admin == 1 && $ch mod == 0) {
          $optionname = 'Administrator';
       } else {
           $optionname = 'Standard';
       echo "<option value='" . $optionname . "'>" . $optionname . "</option>";
       $i++;
>>
   </select>
   <label id="user rights">/</label>
```

Huberty Tom 75/182

```
< >
} elseif ($ SESSION['user action'] == 'add') {
<h1>Add User</h1>
>
   Username*: 
   <input type="text" name="username" maxlength="20" pattern="^[A-Za-z0-9] {1,20}$" title="Only a-z,A-Z, ,0-9.
Minimum 1 character." value="<?= $new username ?>" required="required"/>
   <?= $username msq ?>
 >
   Firstname: 
   <input type="text" name="firstname" value="<?= $new firstname ?>"/>
 >
   Lastname: 
   <input type="text" name="lastname" value="<?= $new lastname ?>"/>
 >
   E-Mail*: 
   <input type="email" name="email" value="<?= $new email ?>" required="required" autocomplete="off" />
   <?= $email msq ?>
 >
   Password*:
   <input pattern="{7,}" title="7 characters minimum." type="password" name="new password1" required</pre>
autocomplete="off" />
   <?= $password msg ?>
 >
   Repeat Password*:
   <input pattern=".{7,}" title="7 characters minimum." type="password" name="new password2" required</pre>
autocomplete="off" />
 <tr>
```

Huberty Tom 76/182

```
Skype ID: 
  <input type="text" name="skypeID" value="<?= $new skypeid ?>"/>
 >
  Steam ID: 
  <input type="text" name="steamID" value="<?= $new steamid ?>"/>
 >
   LoL ID: 
  <input type="text" name="lolID" value="<?= $new lolid ?>"/>
 <tr>
   Twitch ID: 
  <input type="text" name="streamID" value="<?= $new steamid ?>"/>
 <tr>
  Standard:
  <input type="radio" name="user rights" value="0" checked="checked"/>
 >
  Moderator: 
  <input type="radio" name="user rights" value="1" />
 >
  Admin: 
  <input type="radio" name="user rights" value="2"/>
 <br />
<button type="submit" name="user confirmAdd">Add User</button>
< >
} elseif ($ SESSION['user action'] == 'edit') {
<h1>Edit User</h1>
>
   Username:
```

Huberty Tom 77/182

```
<input type="text" name="old username" hidden="" value="<?= $old username ?>"/>
     <input type="text" name="username" maxlength="20" pattern="^[A-Za-Z0-9] {1,20}$" title="Only a-z,A-Z, ,0-9. Minimum</pre>
1 character." value="<?= $username ?>" required="required"/>
   <?= $username msq ?>
 >
       Active:
   <input type="text" readonly="readonly" name="status" value="<?= ($user active == 1 ? 'Activated' :</pre>
'Deactivated'); ?>" />
   <button type="submit" name="BTN statuschange" onclick="return confirm('Do you want to <?= ($user active == 1 ?
'deactivate' : 'activate'); ?> this user?')"><?= ($user active == 1 ? 'Deactivate?' : 'Activate?'); ?></button>
 >
   Firstname: 
   <input type="text" name="firstname" value="<?= $user firstname ?>"/>
 >
   Lastname: 
   <input type="text" name="lastname" value="<?= $user lastname ?>"/>
 >
   E-Mail: 
   <input type="text" name="old email" hidden="" value="<?= $old email ?>" autocomplete="off"/>
     <input type="text" name="email" value="<?= $user email ?>" required="required" />
   <?= $email msg ?>
 >
   Password*:
   <input pattern="{7,}" title="7 characters minimum." type="password" name="new password1" autocomplete="off"</pre>
/></td>
   <?= $password msq ?>
 >
   Repeat Password*:
   <input pattern=".{7,}" title="7 characters minimum." type="password" name="new password2" autocomplete="off"</pre>
/></td>
```

Huberty Tom 78/182

```
>
   Skype ID: 
   <input type="text" name="skypeID" value="<?= $user skypeid ?>"/>
 >
   Steam ID: 
  <input type="text" name="steamID" value="<?= $user steamid ?>"/>
 >
  Lol ID: 
  <input type="text" name="lolID" value="<?= $user lolid ?>"/>
 >
   Twitch ID: 
  <input type="text" name="streamID" value="<?= $user streamid ?>"/>
 >
   Standard:
  <input type="radio" name="user rights" value="0" <?= ($user rights == 0 ? "checked='checked'" : ''); ?>/>
 >
   Moderator: 
  <input type="radio" name="user rights" value="1" <?= ($user rights == 1 ? "checked='checked'" : ''); ?>/>
 >
  Admin: 
  <input type="radio" name="user rights" value="2" <?= ($user rights == 2 ? "checked='checked'" : ''); ?>/>
 <br />
<button type="submit" name="user confirmEdit">Edit User/button>
} elseif ($ SESSION['user action'] == 'delete') {
>>
<h1>Delete User</h1>
<?
```

Huberty Tom 79/182

```
?>
<script>
        // Replace the <textarea id="news editor"> with a CKEditor
        // instance, using default configuration.
        CKEDITOR.replace( 'news editor');
        // Enabled Edit and Delete Button for News/User/Teams
    function enable buttons() {
                document.getElementById('BTN edit').disabled=false;
                        document.getElementById('BTN delete').disabled=false;
        function get userinfo() {
                document.getElementsByName('select usersfirstname').item(0).selectedIndex =
document.getElementsByName('select users').item(0).selectedIndex;
                document.getElementsByName('select userslastname').item(0).selectedIndex =
document.getElementsByName('select users').item(0).selectedIndex;
                document.getElementsByName('select usersemail').item(0).selectedIndex =
document.getElementsByName('select users').item(0).selectedIndex;
                document.getElementsByName('show rights').item(0).selectedIndex =
document.getElementsByName('select users').item(0).selectedIndex;
                document.getElementById('users firstname').innerHTML =
document.getElementsByName('select usersfirstname').item(0).value;
                document.getElementById('users lastname').innerHTML =
document.getElementsByName('select userslastname').item(0).value;
                document.getElementById('users email').innerHTML =
document.getElementsByName('select usersemail').item(0).value;
                document.getElementById('user rights').innerHTML =
document.getElementsByName('show rights').item(0).value;
</script>
```

Huberty Tom 80/182

# 4.2.2.7. /index.php

```
<?
session start();
//DATABASE CONNECT
include("include/config.php");
//DATABASE END
//LOGIN
include("include/login.php");
//CHECK IF USER IN DATABASE IS Activated else loggedIN = false
//+ check if user in a team if not update session team id
if ($ SESSION['loggedIN'] == true) {
   include("./include/status.php");
//ARRAY OF PAGES
$pages array = array(
    "Home",
    "News".
    "Teams",
    "League",
    "Streams",
   "Profile",
   "Register",
    "About",
    "Contact",
    "ForgotPassword"
);
//REGISTER
if (isset($ POST['BTN register'])) {
   $ SESSION['before'] = pre page();
   header('Location:' . $ SERVER['SCRIPT NAME'] . '?page=Register', true, 302);
```

Huberty Tom 81/182

```
}
//If no page is set then Home
if (!isset($ GET['page'])) {
    $ GET['page'] = 'Home';
//Check if GET page exists
if (in array($ GET['page'], $pages array)) {
    $head title = $ GET['page'];
} else {
    $head title = "Page not found";
// Get the title of the news into the webtitle
if ($ GET['page'] == 'News' && isset($ GET['id'])) {
    $checknews exist header = mysql query("SELECT * FROM news WHERE id news = '" . $ GET['id'] . "'");
   $newserror header = mysql num rows($checknews exist header);
   if ($newserror header !== 0) {
        $title output = mysql query("SELECT * FROM news WHERE id news = '" . $ GET['id'] . "'");
       $news title = mysql fetch object($title output);
        $head title = $news title->title;
// To prevent reposting a comment when reloading the page.//
if (isset($ POST['BTN comment']) && isset($ POST['comment txt'])) {
    Susername
                 = $ SESSION['username'];
                 = utf8 decode(mysql real escape string($ POST['comment txt']));
   $comment date = date('d.m.Y@H:i');
   //Check if it is a news or match comments
   if ($ GET['page'] == 'News') {
       $news id = $ GET['id'];
       mysql query("INSERT INTO news comments (fi username, fi news, text, date) VALUES ('" . $username . "','" .
$news id . "','" . $comment . "','" . $comment date . "')");
    } elseif ($ GET['page'] == 'League') {
       $match id = $ GET['matchid'];
```

Huberty Tom 82/182

```
mysql query("INSERT INTO match comments (fi username, fi match, text, date) VALUES ('" . $username . "','" .
$match id . "','" . $comment . "','" . $comment date . "')");
    pre page();
?>
<!DOCTYPE html>
<html xmlns="http://www.w3.org/1999/xhtml">
<head>
<meta name="author" content="Huberty Tom">
<meta charset="utf-8" />
<!--[if IE]><script src="http://html5shiv.googlecode.com/svn/trunk/html5.js"></script><![endif]-->
<title><?= $head title ?></title>
<meta name="keywords" content="gaming,luxembourg,league of legends,nextdoor,streams" />
<meta name="description" content="" />
<meta property="og:title" content="<?= $head title ?>" />
<script src="./include/sorttable.js"></script>
<link rel="stylesheet" href="./stylesheets/standard.css" type="text/css" media="screen, projection" />
<link rel="SHORTCUT ICON" href="img/nd logo 250px.png">
</head>
<body>
<div id="fb-root"></div>
include("include/bg set.php");
<script>
(function(d, s, id) {
  var js, fjs = d.getElementsByTagName(s)[0];
  if (d.getElementById(id)) return;
  js = d.createElement(s); js.id = id;
  js.src = "//connect.facebook.net/en US/all.js#xfbml=1&appId=248506615199544";
  fis.parentNode.insertBefore(is, fis);
```

Huberty Tom 83/182

```
}(document, 'script', 'facebook-jssdk'));
!function(d,s,id){
var js,fjs=d.getElementsByTagName(s)[0],p=/^http:/.test(d.location)?'http':'https';
if(!d.getElementBvId(id)){
               is=d.createElement(s);
               is.id=id;is.src=p+'://platform.twitter.com/widgets.is';
               fis.parentNode.insertBefore(is,fis);
} (document, 'script', 'twitter-wjs');
</script>
 <div id="wrapper">
<form action="<?= $ SERVER['SCRIPT NAME'] ?>" method="post" >
 <div id="header">
   <div id="filler">
       <button type="button" name="design blue" style="background:#0CF;width:30px;height:20px;border:1px black solid;"</pre>
onClick="changeCSS('blue style',0)"></button>
       <button type="button" name="design orange" style="background:#FF9D3C;width:30px;height:20px;border:1px black</pre>
solid;" onClick="changeCSS('orange style',0)"></button>
       <button type="button" name="design white" style="backgroudn:#C0C0C0; width:30px; height:20px; border:1px black</pre>
solid;" onClick="changeCSS('standard',0)"></button>
   </div>
   <div id="login">
     <?php
if ($ SESSION['loggedIN'] == true) {
   $qetuser avatar q = mysql query("SELECT * FROM users WHERE id username = '" . $ SESSION['username'] . "'");
   $get avatar
                    = mysql result($getuser avatar q, 0, 'avatar');
?>
     <tr>
         Hello,
           <?= $ SESSION['username'] ?>
       >
         <img src="./img/users/<?= $get avatar ?>" width="75px" alt="User Avatar">
       <tr>
```

Huberty Tom 84/182

```
<!-- <input class="standardbutton" style="width:100%;" type="submit" name="BTN profile" value="Profile"
disabled/> -->
         <input class="standardbutton" style="width:100%;" type="submit" name="BTN profile" value="Profile"
formaction="<?= $ SERVER['SCRIPT NAME'] ?>?page=Profile&amp;action=view&amp;user=<?= $ SESSION['username'] ?>"
formmethod="post"/>
         <input class="standardbutton" style="width:100%;" type="submit" name="BTN logOUT" value="Logout" />
       <?
} else {
?>
     <fieldset style="border:none;" title="Login Area">
       <br />
       Username:
       <input class="login" type="text" name="data username" style="width:100%" />
       <br />
       Password:
       <input class="login" type="password" name="data password" style="width:100%" />
       <input class="standardbutton" style="width:47%" type="submit" name="BTN logIN" autofocus value="Login" />
       <input class="standardbutton" style="width:47%" type="submit" name="BTN register" value="Register" />
       <a href="?page=ForgotPassword"><button type="button" class="standardbutton" style="width:100%" >Forgot password?
</button></a>
     </fieldset>
     <?
?>
   </div>
   <!--#login-->
    <img src="img/nd logo 250px.png" alt="NDLogo" style="height:120px;margin:0" >
    <strong>Next Door League</strong> </div>
</form>
<!--#header-->
<form method="get" action="<?= $ SERVER['SCRIPT NAME'] ?>" name="menu">
 <div id="navigation"> <a href="?page=Home" class="navbutton">
    Home
   </a> <a href="?page=News" class="navbutton">
```

Huberty Tom 85/182

```
News
   </a> <a href="?page=Teams" class="navbutton">
    Teams
   </a> <a href="?page=League" class="navbutton">
   League
   </a> <a href="?page=Streams" class="navbutton">
   Streams
   </a> </div>
</form>
<div id="middle">
<?php
//CHANGE PAGE
if (in array($ GET['page'], $pages array)) {
    switch ($ GET['page']) {
       case "Home":
           include("./include/home.php");
           break;
       case "News":
           include("./include/news/index.php");
           break:
       case "Teams":
           include("./include/teams/index.php");
           break;
       case "League":
           include("./include/league/index.php");
           break:
       case "Streams":
           include("./include/streams/index.php");
           break:
       case "Register":
           include("./include/register/index.php");
```

Huberty Tom 86/182

```
break:
       case "About":
           include("./include/about.php");
           break;
       case "Contact":
           include("./include/contact.php");
           break:
       case "Profile":
           include("./include/profile/index.php");
           break:
       case "ForgotPassword":
           include("./include/forgotpw.php");
           break;
       default:
           include("./include/home.php");
?>
<div id="sideRight">
<caption style="color:black; font-weight:bold; background: rqba(255, 255, 255, 0.4); font-size:14px">Open
Matches:
       <?php
   $matches lookup q = mysql query("SELECT * FROM matches WHERE status=1 ORDER BY id match DESC LIMIT 3");
   $match lookup count = mysql num rows($matches lookup q);
   if (\$match lookup count != \overline{0}) {
       for (\$i = 0; \$i < \$match lookup count; \$i++) {
           $match lookup id = mysql result($matches lookup q, $i, 'id match');
           $match lookup team1 = mysql result($matches lookup q, $i, 'fi team1');
                             = mysql result(mysql query("SELECT * FROM teams WHERE id team='" . $match lookup team1 .
           $team1 teamname
"'"), 0, 'teamname');
           $match lookup team2 = mysql result($matches lookup q, $i, 'fi team2');
                             = mysql result(mysql query("SELECT * FROM teams WHERE id team='" . $match lookup team2 .
           $team2 teamname
"'"), 0, 'teamname');
           >
               <?= $team1 teamname ?>
               <td style="text-align:center;border:none; font-weight:bold; width:2%; padding-left:2px; padding-
```

Huberty Tom 87/182

```
right:2px">vs
             <?= $team2 teamname ?>
          <tr>
             <a href="<?= $ SERVER['SCRIPT NAME'] ?>?
page=League&action=view&matchid=<?= $match lookup id ?>" class="standardbutton" style="text-
decoration:none; color:black; padding-left:3px; padding-right:3px" target=" self">View Match</a>
          <?
     else |
             >
             No open matches found.
      <?
?>
<caption style="color:black;font-weight:bold;background:rgba(255,255,0.4);font-size:14px">Closed
Matches:
      <?php
   $matches lookup q = mysql query("SELECT * FROM matches WHERE status=0 OR status=2 OR status=3 ORDER BY id match
DESC LIMIT 3");
   $match lookup count = mysql num rows($matches lookup q);
   if (\$match lookup count != 0) {
      for (\$i = 0; \$i < \$match lookup count; \$i++) {
          $match lookup id = mysql result($matches lookup q, $i, 'id match');
          $match lookup team1 = mysql result($matches lookup q, $i, 'fi team1');
          $team1 teamname
                          = mysql result(mysql query("SELECT * FROM teams WHERE id team='" . $match lookup team1 .
"'"), 0, 'teamname');
          $match lookup team2 = mysql result($matches lookup q, $i, 'fi team2');
          $team2 teamname
                          = mysql result(mysql query("SELECT * FROM teams WHERE id team='" . $match lookup team2 .
"'"), 0, 'teamname');
?>
```

Huberty Tom 88/182

```
<tr>
           <?= $team1 teamname ?>
           <td style="text-align:center;border:none;font-weight:bold;width:2%;padding-left:2px;padding-
right:2px">vs
           <?= $team2 teamname ?>
        <tr>
           <a href="<?= $ SERVER['SCRIPT NAME'] ?>?
page=League&action=view&matchid=<?= $match lookup id ?>" class="standardbutton" style="text-
decoration:none; color:black; padding-left:3px; padding-right:3px" target=" self">View Match</a>
        <?
   } else {
?>
           >
           No closed matches found.
     <?
?>
</div>
<?
} else {
?>
     <div id="content" style="width:100%;background:none">
     >
           <h3 style="padding-left:5px">0ops, you have found a dead link!</h3>
     >
           <h4 style="padding-left:5px">Maybe you mistyped the link or followed a bad
one.</h4>
     <tr>
```

Huberty Tom 89/182

```
<img src="./img/dead link.png" alt="dead link">
       </div>
<?
?>
</div>
<!-- #middle-->
<footer id="footer">
       <tr>
              Social Media
              Partners
              About Us
       <tr>
              >
                     <div class="foot list"><a href="http://facebook.com" target="new"><imq</pre>
src="./img/smedia/facebook-64.png" style="width:32px" alt="Facebook"/></a></div>
          <div class="foot list"><a href="http://twitter.com" target="new"><img src="./img/smedia/twitter-64.png"
style="width:32px" alt="Twitter"/></a></div>
              <td>
              <div class="foot list"><a href="http://videogames.lu" target="new"><img</pre>
src="./img/partners/videogames logo.png" style="width:90px" alt="Videogames.lu" /></a></div>
                     <div class="foot list"><a href="http://welivegames.com" target="new"><img</pre>
src="./img/partners/welivegames logo.png" style="width:100px" alt="WeLiveGames" /></a></div>
              <td>
                     <div class="foot list"><a href="<?= $ SERVER['SCRIPT NAME'] ?>?page=About">About</a></div>
                     <div class="foot list"><a href="<?= $ SERVER['SCRIPT NAME'] ?>?page=Contact">Contact</a></div>
```

Huberty Tom 90/182

# 4.2.2.8. /include/about.php

```
<!-- Show information about NextDoor League -->
<div id="content" style="background:rgba(255,255,255,0.7);padding-left:5px;padding-right:5px;">
<caption style="text-align:center;font-weight:bold">About</caption>
      <img src="./img/nd logo 250px.png" alt="nd logo" width="70" />
   </t.r>
   <b>NextDoor League</b>
   <t:r>
      <td>
      The sole purpose of NextDoor League, is to create a friendly yet entertaining Userplattform. Users should
             be able to view recent news about Gaming (mostly League of Legends), Hardware and Software. With the
cooperation of our
          partners we will even give more news about what is happening in the luxembourgish e-sports-scene, and how it
is evolving more and more.
      On the other hand NextDoor League wants to provide a League-System, like ESL, for a smaller community. A user
```

Huberty Tom 91/182

# 4.2.2.9. /include/config.php

# <?

```
//Connect to database
    $host = "localhost";
    $user = "hubto133";
    $pass = "19921106133";
    $db = "hubto133";

$con = mysql_connect($host, $user, $pass);
    mysql_select_db($db);
?>
```

Huberty Tom 92/182

#### 4.2.2.10. /include/contact.php

```
<div id="content" style="background:rgba(255,255,255,0.7);">
<?
herefore $check text = 0;
        = 0;
$send
//Check if send email is pressed
// if yes then send email to nextdoorleague@gmail.com else give out error message
if (isset($ POST['BTN sendmail'])) {
   if ($ POST['message'] != '') {
      \stackrel{-}{\text{Ssend}} = 1:
      $from = $ POST['email'];
      $to = 'nextdoorleague@gmail.com';
      $name = $ POST['name'];
      $subject = $ POST['subject'];
      $message = utf8 decode('Name: ' . $name . chr(10) . $ POST['message']);
      mail($to, $subject, $message, $from);
   } else {
      check text = 1;
      $error text = 'Text-field needs to be filled out.';
if ($send == 0) {
?>
<form action="<?= $ SERVER['SCRIPT NAME'] ?>?page=Contact" method="post" autocomplete="off">
align:left"><h3><b>//Contact Form:</b></h3>
      <tr>
      <td>Name*:</td>
   <tr>
```

Huberty Tom 93/182

```
<input type="text" class="standardinput" style="width:250px" name="name" required="required" />
   >
      Email*:
   >
      <input type="email" class="standardinput" style="width:250px" name="email" required="required"/>
   <tr>
      Subject*:
   <tr>
      <input type="text" class="standardinput" style="width:400px" name="subject" required="required" />
   <tr>
      Message*:
   if (isset($ POST['BTN sendmail']) && $check text == 1) {
?>
      <tr>
             <span style="color:red"><?= $error text ?></span>
      <?
?>
      <tr>
      <textarea class="standardinput" style="max-height:200px;min-height:200px;max-width:700px;min-width:400px"
maxlength="500" name="message" ></textarea>
   </tr>
   >
      <button type="submit" class="standardbutton" name="BTN sendmail">Send mail</button>
   </form>
<?
} else {
```

Huberty Tom 94/182

```
//error message
echo "<h3 style='padding-left:5px'>An email will be send, notifying NextDoor League.</h3>";
}
?>
</div>
```

# 4.2.2.11. /include/forgotpw.php

```
<?
$error email
               = '';
$error password = '';
$reset
               = 0;
$reset password = 0;
//Check if button to reset password is pushed.
if (isset($ POST['BTN rs pw'])) {
   //Check if both passwords are the same, if yes update userprofiles password
   if ($ POST['reset password1'] == $ POST['reset password2']) {
        $reset password = 1;
        $new password = mysql real escape string(shal($ POST['reset password1']));
       mysql query("UPDATE users SET password = '" . $new password . "', fgpw code='' WHERE email = '" . $ GET['email'] .
    } else {
       //Set error message
       $reset password = 0;
       $error password = 'Both passwords need to be the same.';
//Check if a request is send to reset the password
if (isset($ POST['BTN rs link'])) {
    $check email q = mysql query("SELECT * FROM users WHERE email = '" . $ POST['email'] . "'");
    $check email = mysql num rows($check email q);
   //If submitted email exists then send email and generate activation code
    if ($check email == 1) {
       $activationcode = substr(md5(rand(1000, 9999999)), 0, 9);
       mysql query("UPDATE users SET fgpw code = '" . $activationcode . "' WHERE email = '" . $ POST['email'] . "'");
       //Email variables
```

Huberty Tom 95/182

```
$from = 'MIME-Version: 1.0' . "\r\n";
       $from .= 'Content-type: text/plain; charset=ISO-8859-1' . "\r\n";
       $from .= 'From: nextdoorleague@gmail.com';
              = $ POST['email'];
       $to
       $message = "Your password has been requested to change, if you are aware of this please click the link below. If
not please ignore this email." . chr(10) . "Link to reset password: http://" . $ SERVER['SERVER NAME'] . "?
page=ForgotPassword&email=" . $ POST['email'] . "&activation=" . $activationcode;
       //Send email to user whom password should be reseted
       mail($to, 'NextDoor League - Forgotten Password ', $message, $from);
       \$reset = 1;
   } else {
       reset = 0;
       $error email = 'No user with give email-adress found.';
?>
<div id="content">
if (!isset($ GET['email']) && !isset($ GET['activation'])) {
   if ($reset == 0) {
?>
       <form method="post" action="<?= $ SERVER['SCRIPT NAME'] ?>?page=ForgotPassword">
         <h3><b>//Forgotten password</b></h3>
             >
               Email:
               <input type="email" class="standardinput" style="width:100%" name="email" required>
             if (isset($ POST['BTN rs link']) && $reset == 0) {
?>
                     <tr>
                            <span style="color:red"><?= $error email ?></span>
```

Huberty Tom 96/182

```
<?
?>
                    <tr>
                           <button type="submit" class="standardbutton" style="width:100%" name="BTN rs link">Send
Resetlink</button>
                    </form>
<?
   } else {
      echo "<h3 style='padding-left:5px'>A confirmation email has been sent, please check your emails.</h3>";
   //If email and activation gets are set.
} elseif (isset($ GET['email']) && isset($ GET['activation'])) {
   //Check if the email matches the activation code, if not give out error message, if true then show reset password
form
   $check request q = mysql query("SELECT * FROM users WHERE email = '" . $ GET['email'] . "' AND fgpw code = '" .
$ GET['activation'] . "'");
   $check request = mysql num rows($check request q);
   if ($check request == 1 && $reset password == 0) {
?>
             <form method="post" action="<?= $ SERVER['SCRIPT NAME'] ?>?page=ForgotPassword&amp;email=<?=</pre>
$ GET['email'] ?>&activation=<?= $ GET['activation'] ?>">
       >
                    <h3><b>//Reset
password:</b></h3>
      >
             Password:
          <input pattern=".{7,}" title="7 characters minimum." type="password" name="reset password1" required
class="standardinput" />
      <tr>
```

Huberty Tom 97/182

```
Re-Enter Password:
          <input pattern=".{7,}" title="7 characters minimum." type="password" name="reset password2" required
class="standardinput" />
       if (isset($ POST['BTN rs pw']) && $reset password == 0) {
?>
                     <tr>
                            <span style="color:red"><?= $error password ?></span>
                     <?
?>
                     <tr>
       >
              <button type="submit" class="standardbutton" style="width:100%" name="BTN rs pw">Reset
Password</button>
       </form>
   } elseif ($reset password == 1 && $check request == 0) {
       echo "<h3 style='padding-left:5px'>Your password has been successfully reseted.</h3>";
       echo "<h3 style='padding-left:5px'>No passwordreset was requested for this email.</h3>";
?>
</div>
```

#### 4.2.2.12. /include/login.php

<?

//LOGIN START

```
if (!isset($ SESSION['loggedIN'])) {
    $ SESSION['loggedIN'] = false;
    $\subseteq \text{SESSION['is admin']} = \text{false;}
    $\subseteq \text{SESSION['is moderator'] = false;}
//Check if log in button is pressed
if (isset($ POST['BTN logIN'])) {
    //Check if username and password match each other
   $checkquery = mysql query("SELECT * FROM users WHERE id username ='" .
mysql real escape string($ POST['data username']) . "' and password='" . shal($ POST['data password']) . "' AND active =
1");
    $check = mysql num rows($checkquery);
    //If the query can't find a match then set error message
    if ($check !== 1) {
        $errorlogin = 'Username or password is wrong.';
        $ SESSION['username'] = '';
       pre page();
    } else {
        //If match is found then log in.
        $ SESSION['username'] = $ POST['data username'];
        $ SESSION['loggedIN'] = true;
        //Function pre page() is used here, to get back to the previous page and not back to the home page.
        pre page();
        //Set session variables
        $checkquery admin = mysql query("SELECT * FROM `users` WHERE `id username` = '" . $ SESSION['username'] . "' AND
is admin = true ");
        $check admin = mysql num rows($checkquery admin);
        if (\$check admin == 1) {
           $ SESSION['is admin'] = true;
        $checkquery moderator = mysql query("SELECT * FROM `users` WHERE `id username` = '" . $ SESSION['username'] . "'
AND is moderator = true ");
        $check moderator
                           = mysql num rows($checkquery moderator);
        if ($check moderator == 1) {
           $ SESSION['is moderator'] = true;
```

Huberty Tom 99/182

```
$checkquery team = mysql query("SELECT * FROM users WHERE id username = '" . $ SESSION['username'] . "'");
                        = mysql result($checkquery team, 0, 'fi team');
       $check team
       $ SESSION['team id'] = $check team;
//LOGIN END
//LOGOUT
if (isset($ POST['BTN logOUT'])) {
    $ SESSION['loggedIN']
                         = false;
    $ SESSION['is admin']
                             = false;
    $ SESSION['is moderator'] = false;
   $ SESSION['team id']
                         = 0;
   session destroy();
   pre page();
//LOGOUT END
//Function to get GET VARIABLES + REDIRECT
function pre page()
               = $ SERVER['HTTP REFERER'];
   $url
    $store gets = array();
   parse str(parse url($url, PHP URL QUERY), $store gets);
   $store get key = array keys($store gets);
   //print r($store get key);
   $get GETS = '';
   for ($i = 0; $i <= count($store get key) - 1; $i++) {
       if ($i == 0) {
           $get GETS = '?';
                = $store get key[$i];
       $key
       $key value = $store gets[$key];
       $get GETS = $get GETS . $key . '=' . $key value;
```

Huberty Tom 100/182

```
if ($i < count($store_get_key) - 1) {
         $get_GETS = $get_GETS . '&';
    }
}
header('Location:' . $_SERVER['SCRIPT_NAME'] . $get_GETS, true, 302);
return ($_SERVER['SCRIPT_NAME'] . $get_GETS);
}
</pre>
```

#### 4.2.2.13. /include/home.php

```
<div id="content">
    <?php
//Output of news limit is set to 3 news.
$limit = 3;
//Select all news, max 3
$news output = mysql query("SELECT * FROM news ORDER BY id news DESC LIMIT $limit");
//loop to write the news
while ($row = mysql fetch object($news output)) {
   $ID news = $row->id news;
   $Date = $row->date;
   $Title = $row->title;
   $User = $row->fi username;
   $Content = $row->text;
   $Genre = $row->genre;
?>
    <div class="news">
      <h2 style="background:rgba(0,0,0,0.18);">
       <a style="text-decoration:none;cursor:pointer;color:black;padding:5px;" href="<?= $ SERVER['SCRIPT NAME'] ?>?
page=News&id=<?= $ID news ?>">
        <?= htmlspecialchars($Title,ENT QUOTES) ?>
        <br />
        </a>
        <small style="font-size:13px;padding:5px;">posted by <?= $User ?>, on <?= $Date ?>
    </small></h2>
      <div class="news content">
```

Huberty Tom 101/182

```
<?= htmlspecialchars decode($Content,ENT QUOTES) ?>
       >
              >
                     <div class="fb-share-button" data-href="<?= $ SERVER['SCRIPT NAME'] ?>?page=News&amp;id=<?=</pre>
$ID news ?>" data-type="button"></div>
              <?
   if (!isset($ GET['id'])) {
?>
              <a href="<?= $ SERVER['SCRIPT NAME'] ?>?page=News&amp;id=<?= $ID news ?>" class="standardbutton"
style="width:100px;text-decoration:none;color:black;padding-left:10px;padding-right:10px;">Comment?</a>
          <?
?>
       </div>
   </div>
   <hr style="margin:5px;color:#999999;" />
?>
 </div>
```

# 4.2.2.14. /include/status.php

```
<?
//Is used to check if the user is still active and update the team session
//Does the user exist? If not unset session.
$check_user_status_q = mysql_query("SELECT * FROM users WHERE id_username = '" . $_SESSION['username'] . "'");
$check_user_exist = mysql_num_rows($check_user_status_q);</pre>
```

Huberty Tom 102/182

```
if ($check_user_exist == 1) {
    //Check if user is active else unset session.
    $check_status = mysql_result($check_user_status_q, 0, 'active');
    if ($check_status == 0) {
        $_SESSION['loggedIN'] = false;
    }
    //Check if user is still in a team and update SESSION['team_id']
    $check_user_inteam = mysql_result($check_user_status_q, 0, 'fi_team');
    if ($check_user_inteam != 0) {
        $_SESSION['team_id'] = $check_user_inteam;
    } else {
        $_SESSION['team_id'] = 0;
    }
} else {
        $_SESSION['loggedIN'] = false;
}
//Check if user is still in a team
?>
```

#### 4.2.2.15. /include/league.index.php

```
//Variables initialisation
$user_teamowner = 0;

//Register team of user in league
if (isset($_POST['BTN_regi_team'])) {
    mysql_query("UPDATE teams SET league = 1 WHERE id_team = '" . $_SESSION['team_id'] . "'");
}

if (isset($_POST['BTN_unsub_team'])) {
    mysql_query("UPDATE teams SET league = 0, points = 1000 WHERE id_team = '" . $_SESSION['team_id'] . "'");
}

//Check if the user is logged in.
```

Huberty Tom 103/182

```
if ($ SESSION['loggedIN'] == true) {
   //Check if users current team is in league and user is owner of the team to join the league
   if ($ SESSION['team id'] != 0) {
      $check user owner g = mysgl query("SELECT * FROM teams WHERE id team = '" . $ SESSION['team id'] . "'");
      $check user owner = mysql result($check user owner q, 0, 'fi username');
      $check team league = mysql result($check user owner q, 0, 'league');
      if ($ SESSION['username'] == $check user owner) {
         $user teamowner = 1;
      if ($check team league == 0) {
         //Check if the team has minimum 5 members to enter league
         $check member number q = mysql query("SELECT * FROM users WHERE fi team ='" . $ SESSION['team id'] . "'");
         $check member number = mysql num rows($check member number q);
         if ($check member number >= 5) {
            $enter = true;
         } else {
            $enter = false;
}
?>
<div id="content">
<?
if (!isset($ GET['action'])) {
?>
      <h3 style="font-
weight:bold;width:100%;background:rqba(255,255,0.5);">League:</h3>
            <?
   if ($user teamowner == 1 && $check team league == 0) {
?>
```

Huberty Tom 104/182

```
//Register your team:
            >
            <td>
            <form method="post" action="<?= $ SERVER['SCRIPT NAME'] ?>?page=League">
                  <button type="submit" name="BTN regi team" <?= ($enter == false ? 'disabled' : ''); ?>
class="standardbutton" onclick="return confirm('Do you want to join the league with your team?')" >Register your team!
</button>
            </form>
            <tr>
            < >
      if ($enter == false) {
?>
                  >
                  radius:2px;padding:3px;width:30%"><h5>Your team needs to have atleast 5 members to enter the league.</h5>
            <?
   } elseif ($user teamowner == 1 && $check team league == 1) {
?>
            >
            <td>
            <form method="post" action="<?= $ SERVER['SCRIPT NAME'] ?>?page=League">
                  <button type="submit" name="BTN unsub team" class="standardbutton" onclick="return confirm('Do</pre>
you really want to unsubscribe your team? Points will be resetted.')" >Unsubscribe your team from league</button>
            </form>
            <?
```

Huberty Tom 105/182

```
?>
           //Teams in League:
           >
                 Teamname:
           Wins:
           Loses:
           Points:
           Challenge:
           <?php
   //Select all team who are in the league and give out team information in a table
   $league teams q
                 = mysql query("SELECT * FROM teams WHERE league = 1 ORDER BY points DESC");
   $league teams count = mysql num rows($league teams q);
   if ($league teams count !== 0) {
     for (\$i = 0; \$i < \$league teams count; \$i++) {
        $team logo = mysql result($league teams q, $i, 'logo');
                 = mysql result($league teams q, $i, 'id team');
         $team id
        $team teamname = mysql result($league teams q, $i, 'teamname');
        $team wins = mysql result($league teams q, $i, 'wins');
        $team loses = mysql result($league teams q, $i, 'loses');
        $team points = mysql result($league teams q, $i, 'points');
>>
           <tr>
                 <img src="./img/teams/<?= $team logo ?>" width="20" alt="Team Logo"
/></td>
                 <a href="<?= $ SERVER['SCRIPT NAME'] ?>?
page=Teams&action=view&teamid=<?= $team id ?>" target=" self"><?= htmlentities($team teamname) ?></a>
                 <?= $team wins ?>
```

Huberty Tom 106/182

```
<?= $team loses ?>
               <?= $team points ?>
               <a href="<?= $ SERVER['SCRIPT NAME'] ?>?
page=League&action=challenge&teamid=<?= $team id ?>" target=" self"><img src="./img/challenge.png" width="20"
alt="Challenge"/></a>
          <?
  } else {
?>
          >
          There are no teams in the league registered yet.
     <?
2>
<br />
<h3 style="font-
weight:bold;width:100%;background:rgba(255,255,255,0.5);">Open Matches:</hd>
     >
      Challenger Team
     Matchinfo
  <?php
  //Give out open matches (status -> 1) and information of it
  $matches lookup q = mysql query("SELECT * FROM matches WHERE status=1 ORDER BY id match DESC");
  $match lookup count = mysql num rows($matches lookup q);
  if (\$match lookup count != \overline{0}) {
     for (\$i = 0; \$i < \$match lookup count; \$i++) {
       $match lookup id = mysql result($matches lookup q, $i, 'id match');
```

Huberty Tom 107/182

```
$match lookup team1 = mysql result($matches lookup q, $i, 'fi team1');
         $team1 teamname
                        = mysql result(mysql query("SELECT * FROM teams WHERE id team='" . $match lookup team1 .
"'"), 0, 'teamname');
         $team1 logo
                        = mysql result(mysql query("SELECT * FROM teams WHERE id team='" . $match lookup team1 .
"'"), 0, 'logo');
         $match lookup team2 = mysql result($matches lookup q, $i, 'fi team2');
         Steam2 teamname
                       = mysql result(mysql query("SELECT * FROM teams WHERE id team='" . $match lookup team2 .
"'"), 0, 'teamname');
         $team2 logo
                        = mysql result(mysql query("SELECT * FROM teams WHERE id team='" . $match lookup team2 .
"'"), 0, 'logo');
>>
         >
            <img src="./img/teams/<?= $team1 logo ?>" width="18" alt="Team Logo"
/></td>
            <?= $team1 teamname ?>
            <imq src="./imq/teams/<?= $team2 logo ?>" width="18" alt="Team Logo"
/></td>
            <?= $team2 teamname ?>
            <a href="<?= $ SERVER['SCRIPT NAME'] ?>?
page=League&action=view&matchid=<?= $match lookup id ?>" class="standardbutton" style="text-
decoration:none;color:black;padding-left:3px;padding-right:3px" target=" self">View Match</a>
         <?
    else |
?>
            >
            No open matches found.
      <?
?>
<br />
```

Huberty Tom 108/182

```
<h3 style="font-
weight:bold;width:100%;background:rgba(255,255,255,0.5);">Closed Matches:</hd>
      >
       Challenger Team
       Challenged Team
      Matchinfo
   <?php
   //Give out closed matches (status -> 0 ) and information about it
   $matches lookup q = mysql query("SELECT * FROM matches WHERE status=0 OR status=2 OR status=3 ORDER BY id match
DESC");
   $match lookup count = mysql num rows($matches lookup q);
   if (\$match lookup count != 0) {
      for ($i = 0; $i < $match lookup count; $i++) {}
          $match lookup id = mysql result($matches lookup q, $i, 'id match');
          $match lookup team1 = mysql result($matches lookup q, $i, 'fi team1');
                          = mysql result(mysql query("SELECT * FROM teams WHERE id team='" . $match lookup team1 .
          $team1 teamname
"'"), 0, 'teamname');
          $team1 logo
                          = mysql result(mysql query("SELECT * FROM teams WHERE id team='" . $match lookup team1 .
"'"), 0, 'logo');
          $match lookup team2 = mysql result($matches lookup q, $i, 'fi team2');
          $team2 teamname
                          = mysql result(mysql query("SELECT * FROM teams WHERE id team='" . $match lookup team2 .
"'"), 0, 'teamname');
          $team2 logo
                          = mysql result(mysql query("SELECT * FROM teams WHERE id team='" . $match lookup team2 .
"'"), 0, 'logo');
          >
             <img src="./img/teams/<?= $team1 logo ?>" width="18" alt="Team Logo"
/></td>
             <?= $team1 teamname ?>
             <imq src="./imq/teams/<?= $team2 logo ?>" width="18" alt="Team Logo"
/></td>
             <?= $team2 teamname ?>
             <a href="<?= $ SERVER['SCRIPT NAME'] ?>?
```

Huberty Tom 109/182

```
page=League&action=view&matchid=<?= $match lookup id ?>" class="standardbutton" style="text-
decoration:none;color:black;padding-left:3px;padding-right:3px" target=" self">View Match</a>
           <?
    } else {
?>
              <tr>
              No open matches found.
       <?
?>
< >
   //Check which action is taken, if action = challenge challenge.php will be loaded else if action = view then view.php
will be included
} elseif ($ GET['action'] == 'challenge') {
   include('challenge.php');
} elseif ($ GET['action'] == 'view') {
   include('view.php');
?>
</div>
```

# 4.2.2.16. /include/league/challenge.php

```
<?
if (isset($_GET['teamid'])) {
   if ($_SESSION['loggedIN'] == true) {
     $challenge_created = 0;
     //Check if user is owner of a team</pre>
```

**Huberty Tom** 

```
$check owner q = mysql query("SELECT * FROM teams WHERE fi username = '" .
$ SESSION['username'] . "'");
     $check owner = mysql num rows($check owner q);
     if (\$check owner != 0) {
        //Check if users team is in the league
        $check user team = mysql result($check owner q, 0, 'league');
        if ($check user team == 1) {
          //Check if the given teamid exists
          $check team2 q = mysql query("SELECT * FROM teams WHERE id team = '" .
$ GET['teamid'] . "' AND league = 1");
          $check team2 = mysql num rows($check team2 q);
          if (\$check\ team2\ !==\ 0) {
             if ($ GET['teamid'] !== $ SESSION['team id']) {
                //Get information about team 2
                $team2 id = mysql result($check team2 q, 0, 'id team');
                $team2 teamname = mysql result($check team2 q, 0, 'teamname');
               //Get email of challenged team leader
                $get email team2 q = mysql query("SELECT * FROM users WHERE
id username = '" . $team2 leader . "'");
                $get email team2 = mysql result($get email team2 q, 0, 'email');
                //Get information about own team
```

Huberty Tom 111/182

```
$check team1 q
                                = mysql query("SELECT * FROM teams WHERE id team = '"
. $ SESSION['team id'] . "'");
                $team1 id
                                = mysql result($check team1 q, 0, 'id team');
                $team1 teamname = mysql result($check team1 q, 0, 'teamname');
                $team1 logo = mysql result($check team1 q, 0, 'logo');
                $team1 points = mysql result($check team1 q, 0, 'points');
                //Calculate win/lose points to show how many points the team can make
(Elo-System: oneround-winloss)
                = 1 / (1 + pow(10, (-(steam1 points - steam2 points)))
/ 400));
                //Points which will be calculated with current points
                points winlose = round(50 * (1 - perpected));
                \$error \overline{d}ate = '';
                $error_time = '';
                $error exists = '';
                if (isset($ POST['BTN confirmchallenge'])) {
                   //Check if given date is not greater than today
                   $today = strtotime(date('d.m.Y'));
                   $date string = $ POST['date'];
                   $date = strtotime($ POST['date']);
                   $date array = explode('.', $ POST['date']);
                   if (checkdate($date array[1], $date array[0], $date array[2])) {
                      if ($date > $today) {
```

Huberty Tom 112/182

```
check date = 1;
                       } else {
                          check date = 0;
                          $error date = 'Date needs to be later than today.';
                    } else {
                       check date = 0;
                       $error date = 'Date is not valid.';
                    //Check if given time is valid
                    if (intval($ POST['time hours']) <= 24 &&</pre>
intval($ POST['time minutes']) <= 59) {</pre>
                       check time = 1;
                       $time string = $ POST['time hours'] . ':' .
$ POST['time minutes'];
                    } else {
                       check time = 0;
                       $error time = 'Time given is not valid.';
                    //Check if a match with the same teams already exists on that day
                    $check match already exists q1 = mysql query("SELECT * FROM
matches WHERE fi team1 = " . $team1 id . " 'AND fi team2 = " . $team2 id . " 'AND
date1='" . $date string . "'");
                    $check match already exists q2 = mysql query("SELECT * FROM
matches WHERE fi team1 = " . $team2 id . " 'AND fi team2 = " . $team1 id . " 'AND
date1='" . $date string . "'");
```

Huberty Tom 113/182

```
$check match already exists1
mysql num rows ($check match already exists q1);
                    $check match already exists2
mysql num rows ($check match already exists q2);
                    if ($check match already exists1 == 0 &&
$check match already exists2 == 0) {
                      $exists = 0;
                    } else {
                     \hat{S}exists = 1:
                     $error exists = "You cant' play against a team two times a day.";
                   //If date and time are correct create match
                    if ($check date == 1 && $check time == 1 && $exists == 0) {
                      mysql query("INSERT INTO matches
(fi team1, fi team2, points1, points2, gain points, date1, time1) VALUES (" . $team1 id .
"," . $team2 id . "," . $team1 points . "," . $team2 points . "," . $points winlose .
",'" . $date string . "','" . $time string . "')");
                      //Get match id for email
                      $qet match id q = mysql query("SELECT * FROM matches WHERE
fi team1 = '" . $team1 id . "' AND fi team2 = "" . $team2 id . "' AND date1 = '" .
$date string . "'");
                       $get match id = mysql result($get match id q, 0, 'id match');
                       //Email variables
                       = 'MIME-Version: 1.0' . "\r\n";
                       $from .= 'Content-type: text/plain; charset=ISO-8859-1' .
```

Huberty Tom 114/182

```
"\r\n";
                   $from .= 'From: nextdoorleague@gmail.com';
                   $to = $get email team2;
                   $message = "Your team $team2 teamname has been challenged." .
chr(10) . "Link to your match: " . $ SERVER['SERVER NAME'] . "?
page=League&action=view&matchid=" . $get match id;
                   //Send email to challenged team leader
                   mail ($to, 'NextDoor League - Challenged by ' . $team1 teamname,
$message, $from);
                   $challenge created = 1;
              if ($challenge created == 0) {
?>
         <table style="border-collapse:collapse; width:100%; margin-bottom:5px"
class="infoview">
              bottom:1px rgba(0,0,0,0.2) solid;">
              <h3 style="font-
weight:bold; width:100%; background:rgba(255, 255, 255, 0.5); ">Challenge:</h3>
              >
         <br/>
<br/>
style="padding-right:25px"><?= $team1 teamname ?></b><br/>
/>
            <img src="./img/teams/<?= $team1 logo ?>" width="100" alt="Team1 Logo"
```

Huberty Tom 115/182

```
><br />
           Current Points: <?= $team1 points ?><br />
        \langle \mathbf{b} \rangle \forall \mathbf{s} \cdot \langle \mathbf{b} \rangle
        <br/>
<br/>
style="padding-left:25px"><?= $team2 teamname ?></b><br/>
/>
           <img src="./img/teams/<?= $team2 logo ?>" width="100" alt="Team2 Logo"
><br />
           Current Points: <?= $team2 points ?><br />
        >
         Possible Point-Addition:
        <t.r>
        <br/>
<br/>
span style="color:#EB7965"><?= - ($points winlose) ?></span>/<span
style="color:green">+<?= ($points winlose) ?></span></b>
        <form method="post" action="<?= $ SERVER['SCRIPT NAME'] ?>?
```

Huberty Tom 116/182

```
page=League&action=challenge&teamid=<?= $ GET['teamid'] ?>">
    solid" colspan="4"> //Time & amp; Date: 
      <t.r>
        Date:
        <input type="text" name="date" required="required" maxlength="10"
title="DD.MM.YYYY" class="standardinput" style="width:100%" pattern="(0[1-9]|1[0-9]|
2[0-9]|3[01])[\.](0[1-9]|1[012])[\.][0-9]{4}" placeholder="DD.MM.YYYY" />
        <?= $error date ?>
      <t.r>
        <span style="color:red"><?= $error exists ?></span>
        >
        Time:
        <input type="text" name="time hours" class="standardinput"
style="width:40px" pattern="[\d+]{2,}" maxlength="2" placeholder="hh"
required="required" /> :
             <input type="text" name="time minutes" class="standardinput"</pre>
style="width:40px" pattern="[\d+]{2,}" maxlength="2" placeholder="mm"
required="required" />
        <?= $error time ?>
```

Huberty Tom 117/182

```
>
          <button type="submit" name="BTN confirmchallenge"
class="standardbutton" style="width:100%" >Challenge!</button>
        <t.r>
          <a href="<?= $ SERVER['SCRIPT NAME'] ?>?page=League"><button
type="button" class="standardbutton" style="width:100%" >Cancel</button></a>
        </form>
      <?
                } else {
                  //Challenge created
?>
     <h3 style='padding-left:5px'>Challenge has been created.<a class="actionbutton"
href="<?= $ SERVER['SCRIPT NAME'] ?>?page=League&amp;action=view&amp;matchid=<?=</pre>
$get_match_id ?>" target="_self">View Match</a></h3>
     <?
               //Every error message for challenging a team
             } else {
                echo "<h3 style='padding-left:5px'>You can't challenge your own team!
</h3>";
```

Huberty Tom

```
} else {
              echo "<h3 style='padding-left:5px'>No team was found. Please be sure to
check if the given team is registered in the league!</h3>";
        } else {
           echo "<h3 style='padding-left:5px'>Your team has to be registered in the
league.</h3>";
     } else {
        echo "<h3 style='padding-left:5px'>You have to be the owner of a team!</h3>";
   } else {
     echo "<h3 style='padding-left:5px'>You have to be logged in to challenge a team!
</h3>";
} else {
  echo "<h3 style='padding-left:5px'>No team was given to challenge!</h3>";
>>
```

#### 4.2.2.17. /include/league/view.php

```
<?php
if (isset($_GET['matchid'])) {
    //Check if the matchid exists
    $check_matchid_exist_q = mysql_query("SELECT * FROM matches WHERE id_match = '" . $_GET['matchid'] . "'");
    $check_matchid = mysql_num_rows($check_matchid_exist_q);</pre>
```

Huberty Tom

```
if ($check matchid !== 0) {
   //Initialisation of variables
   check date = 0;
                       = '';
   $error date
   $check time
                      = 0:
   $error time
                      = '';
   $check result
                     = 0:
   $error result
                      = '';
   $enter result
                       = 0:
                        = ''';
   $error match
   check match results = 0;
   $decline
                        = 0:
                       = 11;
   $decline msq
   //Get win/losing points
   $points winlose
                        = mysql result($check matchid exist q, 0, 'gain points');
   //Get teams ids
                        = mysql result($check matchid exist q, 0, 'fi team1');
   $team1 id
   $team2 id
                        = mysql result($check matchid exist q, 0, 'fi team2');
   //Get Team1 infos
                        = mysql query("SELECT * FROM teams WHERE id team = '" . $team1 id . "'");
   $get info team1 q
   $team1 teamname
                       = mysql result($get info team1 q, 0, 'teamname');
                       = mysql result($get info team1 q, 0, 'logo');
   $team1 logo
                       = mysql result($get info team1 q, 0, 'fi username');
   $team1 leader
   //Get Team2 infos
   $get info team2 q = mysql query("SELECT * FROM teams WHERE id team = '" . $team2 id . """);
   $team2 teamname = mysql result($get info team2 q, 0, 'teamname');
   $team2 logo = mysql result($get info team2 q, 0, 'logo');
   $team2 leader = mysql result($get info team2 q, 0, 'fi username');
   //Change the proposed date
   if (isset($ POST['prop date'])) {
       //Check if given date is not greater than today
                = strtotime(date('d.m.Y'));
       $today
       $date string = $ POST['date'];
       $date = strtotime($ POST['date']);
       $date array = explode('.', $ POST['date']);
```

Huberty Tom 120/182

```
if (checkdate($date array[1], $date array[0], $date array[2])) {
                if ($date > $today) {
                    $check date = 1;
                } else {
                    check date = 0;
                    $error date = 'Date needs to be later than today.';
            } else {
                check date = 0;
               $error date = 'Date is not valid.';
            if ($check date == 1) {
                if ($ SESSION['username'] == $team1 leader) {
                    mysql query("UPDATE matches SET date1 = '" . $date string . "' WHERE id match = '" . $ GET['matchid']
. "'");
                } elseif ($ SESSION['username'] == $team2 leader) {
                    mysql query("UPDATE matches SET date2 = '" . $date string . "' WHERE id match = '" . $ GET['matchid']
. "'");
       //Change the proposed time
       if (isset($ POST['prop time'])) {
            //Check if given time is valid
           if (intval($ POST['time hours']) <= 24 && intval($ POST['time minutes']) <= 59) {</pre>
               check time = 1;
               $time string = $ POST['time hours'] . ':' . $ POST['time minutes'];
            } else {
                check time = 0;
                $error time = 'Time given is not valid.';
            if ($check time == 1) {
               if ($ SESSION['username'] == $team1_leader) {
```

Huberty Tom 121/182

```
mysql query("UPDATE matches SET time1 = '" . $time string . "' WHERE id match = '" . $ GET['matchid']
. "'");
                } elseif ($ SESSION['username'] == $team2 leader) {
                   mysql query("UPDATE matches SET time2 = '" . $time string . "' WHERE id match = '" . $ GET['matchid']
. "'");
        //Enter results
        if (isset($ POST['result'])) {
            if ($ POST['team1 result'] != $ POST['team2 result']) {
                check result = 1;
                $result string = $ POST['team1 result'] . ':' . $ POST['team2 result'];
               if ($ SESSION['username'] == $team1 leader) {
                   mysql query("UPDATE matches SET result1 = '" . $result string . "' WHERE id match = '" .
$ GET['matchid'] . "'");
                } elseif ($ SESSION['username'] == $team2 leader) {
                   mysql query("UPDATE matches SET result2 = '" . $result string . "' WHERE id match = '" .
$ GET['matchid'] . "'");
                //check if both results are the same if true then update status to closed + Updating team points
                $match results g = mysgl guery("SELECT * FROM matches WHERE id match = '" . $ GET['matchid'] . "'");
                $check result1 = mysql result($match results q, 0, 'result1');
                $check result2 = mysql result($match results q, 0, 'result2');
               $fi team1
                                = mysql result($match results q, 0, 'fi team1');
                $fi team2
                                = mysql result($match results q, 0, 'fi team2');
                                = mysql result($match results q, 0, 'gain points');
                $elo
                if ($check result1 == $check result2) {
                    mysql query("UPDATE matches SET status = 0 WHERE id match = '" . $ GET['matchid'] . "'");
                    $calc result = explode(':', $check result1);
                    if ($calc result[0] > $calc result[1]) {
                       mysql query("UPDATE teams SET points=points+" . $elo . ",wins=wins+1 WHERE id team = '" .
$fi team1 . "'");
                       mysql query("UPDATE teams SET points=points-" . $elo . ",loses=loses+1 WHERE id team = '" .
$fi team2 . "'");
                    } else {
```

Huberty Tom 122/182

```
mysql query("UPDATE teams SET points=points-" . $elo . ",loses=loses+1 WHERE id team = '" .
$fi team1 . "'");
                        mysql query("UPDATE teams SET points=points+" . $elo . ",wins=wins+1 WHERE id team = '" .
$fi team2 . "'");
            } else {
               // Initiate error message when 1:1 or 0:0
                \hat{s} check result = 0;
               $error result = 'Only one may win/lose.';
        //Check if decline button was chosen then make status of match 2 or 3 according to which teamowner declined the
match
        //The team which declined the match will get 5 penality points.
        if (isset($ POST['BTN decline'])) {
            $decline = 1;
            if ($ SESSION['username'] == $team1 leader) {
                mysql query("UPDATE matches SET status = 2 WHERE id match = '" . $ GET['matchid'] . "'");
               mysql query("UPDATE teams SET points=points-5 WHERE id team = '" . $team1 id . "'");
                $decline msg = 'Team ' . $team1 teamname . ' will lose 5 points for declining the match.';
            } elseif ($ SESSION['username'] == $team2 leader) {
               mysql query("UPDATE matches SET status = 3 WHERE id match = '" . $ GET['matchid'] . "'");
               mysql query("UPDATE teams SET points=points-5 WHERE id team = '" . $team2 id . "'");
        $check match q = mysql query("SELECT * FROM matches WHERE id match = '" . $ GET['matchid'] . "'");
        //Get results of the match
        $match result1 = mysql result($check match q, 0, 'result1');
        $match result2 = mysql result($check match q, 0, 'result2');
       if ($match result1 != '' && $match result2 != '') {
            if ($match result1 != $match result2) {
                $error match
                                    = 'Given results are not the same, please re-enter results.';
                $check match results = 1;
```

Huberty Tom 123/182

?>

```
//Get status of match (open/close)
$match status = mysql result($check match q, 0, 'status');
//if closed then check who won
if ($match status == 0) {
   $results = explode(':', $match result1);
   $team1 result = $results[0];
   $team2 result = $results[1];
} elseif ($\status == 2) {
   $decline msg = 'Team ' . $team1 teamname . ' lost 5 points for declining the match.';
} elseif ($match status == 3) {
   $decline msg = 'Team ' . $team2 teamname . ' lost 5 points for declining the match.';
//Get points from teams at current match
$team1 points = mysql result($check match q, 0, 'points1');
$team2 points = mysql result($check match q, 0, 'points2');
//Get proposed match dates and times
$match date1 = mysql result($check match q, 0, 'date1');
$match date2 = mysql result($check match q, 0, 'date2');
$match time1 = mysql result($check match q, 0, 'time1');
$match time2 = mysql result($check match q, 0, 'time2');
//Check if times and dates are the same for both teams so teamowner can enter the results
if ($match date1 == $match date2 && $match time1 == $match time2) {
   $enter result = 1;
       Contestants:
       Matchinfo:
   <tr>
```

Huberty Tom 124/182

```
>
                        <img src="./img/teams/<?= $team1 logo ?>" width="100" alt="Team1 Logo" ><br />
                         <br/>
<br/>
<br/>
a href="<?= $ SERVER['SCRIPT NAME'] ?>?page=Teams&amp;action=view&amp;teamid=<?=
$team1 id ?>" style="text-decoration:none;color:black" target=" self"><?= $team1 teamname ?></a></b><br/>/>
                     \langle \mathbf{b} \rangle \forall \mathbf{s} \cdot \langle \mathbf{b} \rangle
                               <img src="./img/teams/<?= $team2 logo ?>" width="100" alt="Team2 Logo" ><br />
                        <b><a href="<?= $ SERVER['SCRIPT NAME'] ?>?page=Teams&amp;action=view&amp;teamid=<?=
$team2 id ?>" style="text-decoration:none;color:black" target=" self"><?= $team2 teamname ?></a></b><br/>/>
                     <tr>
                         <br/>
style="color:rgba(0,0,0,0.5);font-weight:bold;font-size:larger">Status:
                                                 <span style="color:<?= ($match status == 1 ? 'green' :</pre>
'red'); ?>">
                                                        <?= ($match status == 1 ? 'open' : 'closed'); ?>
                         </span>
                        </b>
                      <?
      if ($match date1 == $match date2) {
?>
                  >
                         <td>Date:</td>
                      <?= $match date1 ?>
```

Huberty Tom 125/182

```
<?
   } else {
?>
          Proposed dates:
          by <?= $team1 teamname ?>:
            <?= $match date1 ?>
          by <?= $team2 teamname ?>:
            <?= $match date2 ?>
          <?
   if ($match time1 == $match time2) {
?>
          >
              Time:
            <?= $match time1 ?>
          <?
   } else {
?>
          Proposed times:
          by <?= $team1 teamname ?>:
            <?= $match time1 ?>
          by <?= $team2 teamname ?>:
            <?= $match time2 ?>
          <?
```

Huberty Tom 126/182

```
?>
         Result:
       <?
   if (isset($ SESSION['username']) && $match status == 1) {
     if ($ SESSION['username'] == $team1 leader || $ SESSION['username'] == $team2 leader) {
?>
               Leaderoptions:
            <?
?>
     <tr>
   if ($match status != 2 && $match status != 3) {
?>
       >
           if ($match status == 0) {
       if ($decline == 0) {
?>
           <tr>
               <?=
$team1 result ?>
             :
               <?=
$team2 result ?>
           <tr>
           <tr>
               <?= ($team1 result > $team2 result ?
```

Huberty Tom 127/182

```
$team1 teamname: $team2 teamname); ?> won the match.
              >
                    Points earned/lost:
              >
                   <span style="color:<?= ($team1 result > $team2 result ? 'green' : 'red'); ?>"><?=</pre>
($team1 result > $team2 result ? '+' : '-'); ?><?= $points winlose ?></span>
                 :
                   <span style="color:<?= ($team1 result > $team2 result ? 'red' : 'green'); ?>"><?=</pre>
($team1 result > $team2 result ? '-' : '+'); ?><?= $points winlose ?></span>
                 <?
        else {
?>
              >
                   <b><?= ($match result1 == '' ? 'No results entered yet' :</pre>
'Results entered'); ?></b>
                   :
                   <b><?= ($match result2 == '' ? 'No results entered yet' :</pre>
'Results entered'); ?></b>
                 >
            <?
         if ($check match results == 1) {
?>
                         <tr>
                         <td colspan="3" style="background:rgba(255,255,255,0.7;border:1px black
```

Huberty Tom 128/182

```
solid; text-align:center">
                             <span style="color:red"><?= $error match ?></span>
                          <?
?>
                } else {
?>
                                <?= $decline msg ?>
                <?
      //Only show Leaderoptions when match open and user logged in
      if (isset($ SESSION['username']) && $match status == 1) {
         //Check if user is a teamleader
         if ($ SESSION['username'] == $team1 leader || $ SESSION['username'] == $team2 leader) {
?>
             <td>
                   <? //Only change time and date when no results are given
             if ($match result1 == '' && $match result2 == '') {
?>
                   <tr>
                          <form method="post" action="<?= $ SERVER['SCRIPT NAME'] ?>?
page=League&action=view&matchid=<?= $ GET['matchid'] ?>">
                          <button type="submit" name="BTN decline"
class="standardbutton" onclick="return confirm('You will lose 5 points if you decline this match. Are you sure?')"
>Decline Match</button>
                      </form>
                   <tr>
```

Huberty Tom 129/182

```
New Date:
                   >
                          <form method="post" action="<?= $ SERVER['SCRIPT NAME'] ?>?
page=League&action=view&matchid=<?= $ GET['matchid'] ?>">
                          <input type="text" name="date" required="required"
maxlength="10" title="DD.MM.YYYY" class="standardinput" style="width:100px" pattern="(0[1-9]|1[0-9]|2[0-9]|3[01])[\.]
(0[1-9]|1[012])[\.][0-9]{4}" placeholder="DD.MM.YYYY" />
                       <button type="submit" name="prop date" class="standardbutton" style="margin-</pre>
bottom:3px;width:auto;padding-left:3px;padding-right:3px">Propose Date</button>
                       </form>
                   < >
                if ($check date == 0) {
?>
                          <tr>
                          <h5><?= $error date ?></h5>
                       <?
?>
                   <tr>
                          New Time:
                   >
                          <form method="post" action="<?= $ SERVER['SCRIPT NAME'] ?>?
page=League&action=view&matchid=<?= $ GET['matchid'] ?>">
                          <input type="text" name="time hours" class="standardinput"
style="width:40px" pattern="[\d+]{2,}" maxlength="2" placeholder="hh" required="required" />:
                   <input type="text" name="time minutes" class="standardinput" style="width:40px" pattern="[\d+]</pre>
{2,}" maxlength="2" placeholder="mm" required="required" />
                       <
                          <button type="submit" name="prop time" class="standardbutton" style="margin-</pre>
bottom: 3px; width: auto; padding-left: 3px; padding-right: 3px">Propose Time</button>
```

Huberty Tom 130/182

```
</form>
                <?
             if ($check time == 0) {
?>
                      <h5><?= $error time ?></h5>
                   <?
           if ($enter result == 1) {
?>
                <tr>
                      Results:
                <form method="post" action="<?= $ SERVER['SCRIPT NAME'] ?>?page=League&action=view&amp;matchid=<?</pre>
= $ GET['matchid'] ?>">
                <tr>
                      <?= $team1 teamname ?><br />
                      <input type="text" maxlength="1" pattern="[01]" name="team1 result" title="Only 1(win) or</pre>
0(lose)." class="standardinput" style="width:20px" required >
                      <b>:</b>
                   <?= $team2 teamname ?><br />
                      <input type="text" maxlength="1" pattern="[01]" name="team2 result" title="Only 1(win) or</pre>
0(lose)." class="standardinput" style="width:20px" required >
                   <?
             if ($check result == 0) {
?>
                      <tr>
                      <h5><?= $error result ?></h5>
```

Huberty Tom 131/182

```
<?
?>
                   >
                         <button type="submit" name="result"</pre>
class="standardbutton">Enter Results</button>
                   </form>
                 <?
?>
                <?
?>
         <?
      include('comment.php');
      echo "<h3 style='padding-left:5px'>No match was found. Please be sure to give a matchid which exists!</h3>";
} else {
   echo "<h3 style='padding-left:5px'>No match was given to view!</h3>";
?>
```

# 4.2.2.18. /include/league/comment.php

//Delete comments from match\_comments

```
if (isset($ POST['del comment'])) {
   $comment id = $ POST['del comment'];
   mysql query("DELETE FROM match comments WHERE id comment = '" . $comment id . "'");
/*----*/
echo "<h3 style='background:rgba(0,0,0,0.3);padding-left:5px;margin-bottom:10px'><strong>//Comments:</strong></h3>";
$comment output = mysql query("SELECT * FROM match comments WHERE fi match = '" . $ GET['matchid'] . "' ORDER BY
id comment DESC");
if (mysql num rows($comment output) !== 0) {
   while ($row = mysql fetch object($comment output)) {
      $ID comment = $row->id comment;
                    = $row->date;
      $comment date
      $comment author = $row->fi username;
      $comment content = $row->text;
      $avatar q = mysql query("SELECT * FROM users WHERE id username = '" . $comment author . "'");
      $avatar
                   = mysql result($avatar q, 0, 'avatar');
?>
             <form method="post" action="<?= $ SERVER['SCRIPT NAME'] ?>?page=League&amp;action=view&amp;matchid=<?=</pre>
$ GET['matchid'] ?>">
             >
                          <img src="./img/users/<?= $avatar ?>" width="20" style="margin-top:3px" alt="User
Avatar" />
                                <?= $comment author ?><br />
                                <?= $comment date ?>
                          <?php
      if (isset($ SESSION['username']) && $ SESSION['username'] == $comment author) {
?>
                                [ button type="submit" formmethod="post" formaction=""
style="border: none; cursor: pointer; background: none" onclick="return confirm('Do you really want to delete this
comment?'); " name="del comment" value="<?= $ID comment ?>"><span style="color:red;font-weight:bold;font-
```

Huberty Tom 133/182

```
size:10px">X</span></button>]
                                       <?
?>
                               <?= htmlspecialchars($comment content,ENT QUOTES) ?>
                               </form>
<?
else
   echo "Be the first to comment!<br />";
//check if user is logged in and in one of both teams to comment in the match section
if ($ SESSION['loggedIN'] == true) {
   if ($ SESSION['team id'] == $team1 id || $ SESSION['team id'] == $team2 id) {
       if ($match status == 1) {
?>
               <form method="post" action="<?= $ SERVER['SCRIPT NAME'] ?>?page=League&amp;action=view&amp;matchid=<?=</pre>
$ GET['matchid'] ?>" name="comments">
               <fieldset style="border:none">
                       <textarea style='min-width:500px;max-width:720px;min-height:100px;margin-top:10px;'
name='comment txt' required="required"></textarea><br />
                       <button class='standardbutton' name="BTN comment" style='width:100px'>Comment
               </fieldset>
               </form>
<?
       } elseif ($match status == 0 || $match status == 2 || $match status == 3) {
           echo "<h4>Match is closed. Comments disabled.</h4>";
    } else {
       echo "<h4>You need to be a member of one of the competing teams to comment.</h4>";
} else {
    echo "<h4>You have to be logged in to comment.</h4>";
```

Huberty Tom 134/182

}
?>

#### 4.2.2.19. /include/news/index.php

```
<?php
// GET NEWS
if (!isset($ GET['list'])) {
   $ GET['list'] = 1;
$news query = mysql query("SELECT * FROM news"); //get newstable
           = mysql num rows ($news query); //count news
if (isset($ POST['BTN getpage']) || isset($ POST['pagenumber'])) {
   $ GET['list'] = $ POST['pagenumber'];
if (isset($ POST['del comment'])) {
    $comment id = $ POST['del comment'];
   mysql query("DELETE FROM news comments WHERE id comment = '" . $comment id . "'");
  <div id="content">
 <?
/* Output limit Page */
$page = mysql real escape string($ GET['list']);
$limit page = 3;
newserror = 0;
$start = ($page * $limit page) - $limit page;
if (!isset($ GET['id'])) {
   $news output = mysql query("SELECT * FROM news ORDER BY id news DESC LIMIT $start , $limit page");
} else {
                 = mysql query("SELECT * FROM news WHERE id news = '" . $ GET['id'] . "'");
   $checknews exist = mysql num rows($news output);
   if ($checknews exist == 0) {
       newserror = 1:
```

Huberty Tom 135/182

```
if ($newserror == 0) {
   while ($row = mysql fetch object($news output)) {
       $ID news = $row->id news;
                    = $row->date;
       $news date
       $news title = htmlspecialchars($row->title,ENT QUOTES);
       $news author = $row->fi username;
       $news content = $row->text;
       $news genre = $row->genre;
?><div class="news">
                   <h2 style="background:rgba(0,0,0,0.18);">
                       <a style="text-decoration:none;cursor:pointer;color:black;padding:5px;" href="<?=</pre>
$ SERVER['SCRIPT NAME'] ?>?page=News&id=<?= $ID news ?>"><?= $news title ?></a>
                                      <small style="font-size:13px;padding:5px;">posted by <?= $news author ?>, on <?=</pre>
$news date ?></small>
               </h2>
               <div class="news content">
                                      <?= $news content ?>
                   >
                       >
                              <div class="fb-share-button" data-href="<?= $ SERVER['SCRIPT NAME'] ?>?
page=News&id=<?= $ID news ?>" data-type="button"></div>
                       if (!isset($ GET['id'])) {
?>
                       >
                           <a href="<?= $ SERVER['SCRIPT NAME'] ?>?page=News&amp;id=<?= $ID news ?>"
class="standardbutton" style="width:100px; text-decoration:none; color:black; padding-left:10px; padding-
right:10px;">Comment?</a>
                       <?
?>
```

Huberty Tom 136/182

```
</div>
            </div>
                        <hr style="margin:5px;color:#999999;" />
   if (!isset($ GET['id'])) {
       /*----*/
       $countlinks = 1:
       echo "<h3 style='text-align:center'>Page: ";
       for ($i = 1; $i < $count; $i++) {</pre>
           if ($i % $limit page == 0) {
              $countlinks++;
       for ($j = 1; $j <= $countlinks; $j++) {</pre>
           echo "<a href='" . $ SERVER['SCRIPT NAME'] . "?page=News&amp;list=$j'>" . $j . "</a>";
           if ($j <> $countlinks) {
              echo ",";
       $pattern = '[1-' . $countlinks . ']';
       echo "</h3>";
   } else {
       /*----*/
       echo "<h3 style='background:rqba(0,0,0,0.3);padding-left:5px;marqin-</pre>
bottom:10px'><strong>Comments:</strong></h3>";
       $comment output = mysql query("SELECT * FROM news comments WHERE fi news ='" . $ GET['id'] . "' ORDER BY
id comment DESC");
       if (mysql num rows($comment output) !== 0) {
           while ($row = mysql fetch object($comment output)) {
              $ID comment = $row->id comment;
              $comment date = $row->date;
              $comment author = $row->fi username;
              $comment content = $row->text;
              $avatar q = mysql query("SELECT * FROM users WHERE id username = '" . $comment author . "'");
                           = mysql result($avatar q, 0, 'avatar');
              $avatar
```

Huberty Tom 137/182

```
?>
               <form method="post" action="<?= $ SERVER['SCRIPT NAME'] ?>?page=News&amp;id=<?= $ GET['id'] ?>">
                               <tr>
                         <img src="./img/users/<?= $avatar ?>" width="20px" style="margin-top:3px" alt="User
Avatar" />
                                                  <?= $comment author ?><br />
                               <?= $comment date ?>
                         <?php
            if (isset($ SESSION['username']) && $ SESSION['username'] == $comment author) {
?>
                                                  size:10px">
                         [<button type="submit" formmethod="post" formaction=""</pre>
style="border:none; cursor:pointer; background:none" onclick="return confirm('Do you really want to delete this
comment?');" name="del comment" value="<?= $ID comment ?>"><span style="color:red;font-weight:bold;font-
size:10px">X</span></button>]
                         </p>
                                                  <?
?>
                                                  <?= htmlspecialchars($comment content,ENT QUOTES) ?>
                      </form>
                  <?
         echo "Be the first to comment!<br />";
   //Check if user is logged in , if yes show comment box if no don't show the comment box
   if ($ SESSION['loggedIN'] == true && isset($ GET['id'])) {
```

Huberty Tom 138/182

```
?>
              <form method="post" action="<?= $ SERVER['SCRIPT NAME'] ?>?page=News&amp;id=<?= $ GET['id'] ?>"
name="comments">
              <fieldset style="border:none">
                                     <textarea style='min-width:500px;max-width:720px;min-height:100px;margin-
top:10px;' name='comment txt' required="required"></textarea><br />
                                     style='width:100px'>Comment</button>
              </fieldset>
              </form>
   } elseif (isset($ GET['id'])) {
       echo "You have to be logged in to comment.";
} else {
   echo "<h3 style='padding-left:5px'>There is no news relating to the given ID!</h3>";
?>
 </div>
```

### 4.2.2.20. /include/profile/index.php

```
<?php
?>
<div id="content">
<?php
//Check which content will be displayed according to the action variable
if (isset($_GET['action'])) {
    if ($_GET['action'] == 'view') {
        include('view.php');
    } elseif ($_GET['action'] == 'edit') {
        include('edit.php');
    }
}</pre>
```

Huberty Tom 139/182

```
?>
</div>
```

#### 4.2.2.21. /include/profile/view.php

```
<?
//Get if user exists
$getuser q = mysql query("SELECT * FROM users WHERE id username='" . $ GET['user'] . "' AND active = 1");
$check user = mysql num rows($getuser q);
//If user exists give out information
if ($check user == 1) {
   $qetuser team q = mysql query("SELECT * FROM teams WHERE id team = '" . mysql result($qetuser q, 0, 'fi team') .
""");
   $qetuser team check = mysql num rows ($qetuser team q);
   $user username = mysql result($getuser q, 0, 'id username');
   $user_firstname = mysql_result($getuser_q, 0, 'firstname');
$user_lastname = mysql_result($getuser_q, 0, 'lastname');
   if ($\frac{9}{2}etuser team check !== 0) {
      $user teamid = mysql result($getuser team q, 0, 'id team');
      $user team = mysql result($qetuser team q, 0, 'teamname');
   } else {
      suser teamid = 0;
      $user_team = '/';
   $user email = mysql result($qetuser q, 0, 'email');
   $user skypeid = mysql result($getuser q, 0, 'skypeid');
   $user steamid = mysql result($getuser q, 0, 'steamid');
   $user lolid = mysql result($getuser q, 0, 'lolid');
   $user stream = mysql result($getuser q, 0, 'stream');
   $user avatar = mysql result($getuser q, 0, 'avatar');
?>
<?= $user username ?>
       <?php
```

Huberty Tom 140/182

```
//Check if logged in user is the user which profile is shown right now
  if (isset($ SESSION['username'])) {
     if ($user username == $ SESSION['username']) {
?>
                 <a class="actionbutton" href="<?=
$ SERVER['SCRIPT NAME'] ?>?page=Profile&action=edit&user=<?= $ SESSION['username'] ?>">Edit Profile</a>
     <?
?>
     <img src="./img/users/<?= $user avatar ?>" width="100px" alt="User Avatar"/>
   //User 
  <tr>
     Firstname: 
     <?= htmlspecialchars(($user firstname !== '' ? $user firstname : '/'),ENT QUOTES); ?>
  >
     Lastname: 
     <?= htmlspecialchars(($user lastname !== '' ? $user lastname : '/'),ENT QUOTES); ?>
  >
      Team: 
     <?php
  if ($user teamid !== 0) {
?>
       >
           <a href="<?= $ SERVER['SCRIPT NAME'] ?>?page=Teams&amp;action=view&amp;teamid=<?= $user teamid ?>"
style="color:black" target=" self">
        <?= $user team ?>
        </a>
       <?
```

Huberty Tom 141/182

```
} else {
2>
       /
2>
    //Contactinformation 
  >
     E-Mail: 
     <?= $user email ?>
  >
     Skype ID: 
     <?= htmlspecialchars(($user skypeid !== '' ? $user skypeid : '/'), ENT QUOTES); ?>
   >
     Steam ID: 
     <?= htmlspecialchars(($user steamid !== '' ? $user steamid : '/'), ENT QUOTES); ?>
   >
     LoL ID: 
     <?= htmlspecialchars(($user lolid !== '' ? $user lolid : '/'), ENT QUOTES); ?>
   >
     Twitch ID: 
     <?= ($user stream !== '' ? "<a href='" . $ SERVER['SCRIPT NAME'] . "?page=Streams&amp;watch=" . $user stream</pre>
. "' target='new' style='color:black'>" . $user stream . "</a>" : '/'); ?>
     </tr>
<?
} else
  //Give out this message if the user was not found
  echo "<h3 style='padding-left:5px'>The user you want to view does not exist, or is deactivated!</h3>";
```

Huberty Tom 142/182

### 4.2.2.22. /include/profile/edit.php

```
<?
error reporting(E ERROR | E PARSE);
//VARIABLES
suser updated = 0;
\$erroremail = 0;
$change avatar = 0;
$erroravatar = '';
= '';
$password msq = '';
//User wants to delete/deactivate account
if (isset($ POST['BTN del user'])) {
   mysql query("UPDATE users SET fi team = 0,active = 0 WHERE id username = '" . $ SESSION['username'] . "'");
// USER WANTS TO LEAVE TEAM
if (isset($ POST['team leave'])) {
   mysql query("UPDATE users SET fi team = 0 WHERE id username = '" . $ POST['username'] . "'");
   $user updated
   $ SESSION['team id'] = 0;
//USER UPDATE PROFILE
if (isset($ POST['BTN updateuser'])) {
   $user email = mysql real escape string($ POST['email']);
   $user firstname = utf8 decode(mysql real escape string($ POST['firstname']));
   $user lastname = utf8 decode(mysql real escape string($ POST['lastname']));
   $user skypeid = utf8 decode(mysql real escape string($ POST['skypeid']));
   $user steamid = utf8 decode(mysql real escape string($ POST['steamid']));
   $user lolid = utf8 decode(mysql real escape string($ POST['lolid']));
   $user streamid = utf8 decode(mysql real escape string($ POST['stream']));
   //CHECK EMAIL IF ALREADY IN USE
   if ($ POST['email'] !== $ POST['oldemail']) {
       $user email = mysql real escape string($ POST['email']);
       $check email q = mysql query("SELECT * FROM users WHERE email = '" . $user email . "'");
       $check email = mysql num rows($check email q);
       if ($check email >= 1) {
           $erroremail = 1;
```

Huberty Tom 143/182

```
$email msg = 'Email is already in use!';
    //CHANGE PASSWORD
    if ($ POST['password1'] !== '' || $ POST['password2'] !== '') {
        $password change = 1;
        if ($ POST['password1'] == $ POST['password2']) {
            \frac{1}{2} $check password = 1;
            $new password = mysql real escape string($ POST['password1']);
        } else {
            $check password = 0;
            $password msq = 'Both passwords have to be the same.';
    } else {
        $password change = 0;
    //CHECK IF PASSWORD WAS CHANGED OR NOT
    if ($password change == 1 && $erroremail == 0) {
        $user updated = 1;
        //Update password
        mysql query("UPDATE users SET email='" . $user email . "',password='" . sha1($ POST['password1']) .
"',firstname="" . $user firstname . "',lastname='" . $user lastname . "',skypeid='" . $user skypeid . "',steamid='" .
$user_steamid . "',lolid='" . $user lolid . "',stream='" . $user streamid . "' WHERE id username = '" .
$ SESSION['username'] . "'");
    elseif ($password change == 0 && $erroremail == 0) {
        $user updated = 1;
        mysql query("UPDATE users SET email='" . $user email . "', firstname='" . $user firstname . "', lastname='" .
Suser lastname . "', skypeid='" . Suser skypeid . "', steamid='" . Suser steamid . "', lolid='" . Suser lolid . "', stream='"
. Suser streamid . "' WHERE id username = '" . S SESSION['username'] . """);
    //CHECK IF AVATAR IS CHANGED
    if (!empty($ FILES['avatar']['name'])) {
        if (isset($ FILES['avatar'])) {
            $change avatar = 1;
            $allowed
                           = array(
                "aif",
                "ipea",
```

Huberty Tom 144/182

```
"jpa",
               "png"
           );
                      = explode(".", $ FILES['avatar']['name']);
           $tempname
           $extension = end($tempname);
           if ((($ FILES["avatar"]["type"] == "image/gif") || ($ FILES["avatar"]["type"] == "image/jpeg") ||
($ FILES["avatar"]["type"] == "image/jpg") || ($ FILES["avatar"]["type"] == "image/pjpeg") || ($ FILES["avatar"]["type"]
== "image/x-png") || ($ FILES["avatar"]["type"] == "image/png")) && ($ FILES["avatar"]["size"] <= 204800) &&
in array($extension, $allowed)) {
               // CHECK IF IMAGE IS SQUARE
               list($width, $height) = getimagesize($ FILES['avatar']['tmp name']);
               if ($width == $height) {
                   $lookupavatar q = mysql query("SELECT avatar FROM users WHERE id username = '" .
$ SESSION['username'] . "'");
                   $lookupavatar = mysql result($lookupavatar q, 0, 'avatar');
                   $old tempname = explode(".", $lookupavatar);
                   $old extension = end($old tempname);
                   unlink('./img/users/' . $lookupavatar);
                   move uploaded file($ FILES["avatar"]["tmp name"], "./imq/users/" . $ SESSION['username'] . '.' .
$extension);
                   //UPDATE AVATAR IN DATABASE OF USER
                   $newavatar = $ SESSION['username'] . '.' . $extension;
                   mvsql query("UPDATE users SET avatar='" . $newayatar . "' WHERE id username = '" .
$ SESSION['username']. """);
               } else {
                   $erroravatar = 'Image need to be square(128x128,250x250,etc..).';
           } else {
               $erroravatar = 'Invalid File, see conditions.';
    } else {
       $change avatar = 0;
```

Huberty Tom 145/182

```
//CHECK IF USER IS LOGGED IN
if (isset($ SESSION['username']) && !isset($ POST['BTN del user'])) {
   // OUERY FOR USERINFORMATION
   $aetuser q
                         = mysql query("SELECT * FROM users WHERE id username='" . $ GET['user'] . "'");
   // OUERY FOR TEAMINFORMATION ABOUT USER
   $getuser team q
                         = mysql query("SELECT * FROM teams WHERE id team = '" . mysql result($qetuser q, 0,
'fi team') . "'");
   $getuser team check = mysql num rows($getuser team q);
   //CHECK IF THE USER IS THE LEADER OF HIS TEAM
   $check user teamleader g = mysgl query("SELECT * FROM teams WHERE fi username = '" . $ SESSION['username'] . "'");
   $check user teamleader = mysql num rows($check user teamleader q);
   if ($check user teamleader !== 1) {
       $user teamleader = 0;
   } else {
       $user teamleader = 1;
   //INFORMATION ABOUT USER
   $user username = mysql result($qetuser q, 0, 'id username');
   $user firstname = htmlspecialchars(mysql result($getuser q, 0, 'firstname'),ENT QUOTES);
   $user lastname = htmlspecialchars(mysql result($qetuser q, 0, 'lastname'),ENT QUOTES);
   if ($getuser team check !== 0) {
       $user teamid = mysql result($getuser team q, 0, 'id team');
       $user team = mysql result($qetuser team q, 0, 'teamname');
   } else {
       suser teamid = 0;
       suser team = '/';
   $user email = mysql result($getuser q, 0, 'email');
   $user skypeid = htmlspecialchars(mysql result($getuser q, 0, 'skypeid'),ENT QUOTES);
   $user steamid = htmlspecialchars(mysql result($getuser q, 0, 'steamid'),ENT QUOTES);
   $user lolid = htmlspecialchars(mysql result($getuser q, 0, 'lolid'),ENT QUOTES);
   $user stream = mysql result($qetuser q, 0, 'stream');
   $user avatar = mysql result($getuser q, 0, 'avatar');
   if ($ GET['user'] == $ SESSION['username']) {
?>
```

Huberty Tom 146/182

```
Edit Profile:
            <a class="actionbutton" href="<?= $ SERVER['SCRIPT NAME'] ?>?
page=Profile&action=view&user=<?= $ SESSION['username'] ?>">View Profile</a>
            >
                  <td>
                  <form method="post" action="<?= $ SERVER['SCRIPT NAME'] ?>?
page=Profile&action=edit&user=<?= $ SESSION['username'] ?>">
                  <button type="submit" name="BTN del user" class="standardbutton" onclick="return confirm('Do</pre>
really want to delete/desactivate your account?')" >Delete Account</button>
                  </form>
                  <?php
      //If user was updated show message
      if ($user updated == 1) {
?>
            <h4 align="center" style="background:rgba(255,255,255,0.5);border-radius:4px;border:1px rgba(0,0,0.8)
solid; margin-bottom: 4px; ">The user has been updated. </h4>
>>
         <form method="post" action="<?= $ SERVER['SCRIPT NAME'] ?>?page=Profile&amp;action=edit&amp;user=<?=</pre>
$user username ?>" enctype="multipart/form-data">
         //Avatar
            <imq src="./imq/users/<?= $user avatar ?>" width="100px" alt="User Avatar"/>
            >
                  <input type="file" name="avatar" class="standardinput" accept="image/jpeg, image/png"</pre>
style="background:rgba(255,255,255,0.6);" />
```

Huberty Tom 147/182

```
<?= ($change avatar == 1 ? $erroravatar : ''); ?>
             >
                    <td style="background:rgba(255,255,255,0.8);border:1px rgba(0,0,0,0.7) solid;border-
radius:2px;padding:2px;">
                    <h5>Only jpeq,jpq,pnq and gif allowed. Must be under 200kbytes.</h5>
                   <h5>Picture needs to be square (128x128,250x250,...).</h5>
                <br />
                    //User
             >
                          Username: 
                          <input type="text" name="username" class="standardinput" maxlength="20" pattern="^[A-
Za-z0-9 | {1,20}$" title="Only a-z,A-Z, ,0-9. Minimum 1 character." style="background:rgba(255,255,255,0.5)" value="<?=
$user username ?>" readonly="readonly" />
                          <tr>
                     Team: 
                <input type="text" name="team" class="standardinput" style="background:rgba(255,255,255,0.5)"
value="<?= $user team ?>" readonly="readonly" />
                    <?php
      if ($user teamid !== 0) {
?>
                <button type="submit" class="standardbutton" style="width:100%; margin:0; name="team leave"
onclick="return confirm('Do you really want to leave <?= $user team ?> ?');" <?= ($user teamleader == 1 ? 'disabled=""' :
''); ?> >Leave Team?</button>
                   <?
?>
             <?php
      if ($user teamleader == 1) {
```

Huberty Tom 148/182

```
?>
           >
                <td style="background:rqba(255,255,255,0.8);border:1px rqba(0,0,0,0.7) solid;border-
radius:2px;padding:2px;" colspan="2">
                first!</h5>
             <?
?>
                      >
                      Firstname: 
                      <input type="text" name="firstname" class="standardinput" value="<?= $user firstname
?>" />
                      >
                      Lastname: 
                      <input type="text" name="lastname" class="standardinput" value="<?= $user lastname ?</pre>
>" />
                      //Password
           <tr>
                      Password: 
                      <input type="password" name="password1" class="standardinput" />
             <h5><?= $password msg ?></h5>
                      <tr>
                <td style="background:rqba(255,255,255,0.8);border:1px rqba(0,0,0,0.7) solid;border-
radius:2px;padding:2px;" colspan="2">
                   <h5>Leave empty, if you don't want to change your current password.</h5>
```

Huberty Tom 149/182

```
Re-Enter Password: 
                       <input type="password" name="password2" class="standardinput" />
                       >
                 <td style="background:rqba(255,255,255,0.8);border:1px rqba(0,0,0,0.7) solid;border-
radius:2px;padding:2px;" colspan="2">
                    <h5>Re-Enter password, if you want to change your current password.</h5>
              //Contactinformation
           >
                        E-Mail: 
                       <input type="email" name="email" class="standardinput" value="<?= $user email ?>"
required />
              <?= $email msq ?>
              <input type="email" hidden="" name="oldemail" value="<?= $user email ?>" />
                       >
                 Skype ID: 
                 <input type="text" name="skypeid" class="standardinput" value="<?= $user skypeid ?>" />
           >
                 Steam ID: 
                 <input type="text" name="steamid" class="standardinput" value="<?= $user steamid ?>" />
           LoL ID: 
                 <input type="text" name="lolid" maxlength="16" class="standardinput" value="<?= $user lolid ?</pre>
>" />
           >
              Twitch ID:
```

Huberty Tom 150/182

```
<input type="text" name="stream" class="standardinput" maxlength="25" pattern="^[A-Za-z0-9]
{4,25}$" title="Only a-z,A-Z, ,0-9. Minimum 4 characters." value="<?= $user stream ?>" />
               <tr>
                      <button type="submit" name="BTN updateuser" class="standardbutton" style="width:100%">Update
User</button>
               </form>
          <?
   } else {
       echo "<h3 style='padding-left:5px'>You can't edit another user!</h3>";
} elseif (isset($ SESSION['username']) && isset($ POST['BTN del user'])) {
   echo "<h3 style='padding-left:5px'>You have deleted/deactivated your account!</h3>";
} else {
   echo "<h3 style='padding-left:5px'>You have to be logged in to edit!</h3>";
```

### 4.2.2.23. /include/register/index.php

```
<?php
//VARIABLES
$new username = NULL;
$username msg = NULL;
$new email = NULL;
$email msq
              = NULL;
\$erroremail = 0;
$new password = NULL;
$password msg = NULL;
$new firstname = NULL;
$new lastname = NULL;
$captcha msg = NULL;
$user added
              = false;
if (!isset($ POST['old captcha'])) {
```

Huberty Tom 151/182

```
$ POST['old captcha'] = '';
if (!isset($ POST['regi captcha'])) {
    $ POST['regi captcha'] = '';
if (!isset($ POST['regi email'])) {
   $ POST['regi email'] = '';
if (!isset($ POST['regi username'])) {
   $ POST['regi username'] = '';
if (!isset($ POST['regi password1'])) {
   $ POST['regi password1'] = '';
if (!isset($ POST['regi password2'])) {
   $ POST['regi password2'] = '';
//VARIABLES END
//CHECK INFORMATION
if (isset($ POST['BTN GOregister'])) {
   $new firstname = htmlspecialchars($ POST['regi firstname'],ENT QUOTES);
   $new lastname = htmlspecialchars($ POST['regi lastname'], ENT QUOTES);
   //USERNAME
    $new username = $ POST['regi username'];
    $checkuser g = mysql query("SELECT * FROM users WHERE id username = '" . $new username . "'");
   $checkuser = mysql num rows($checkuser q);
   if ($checkuser == 1) {
       $check username = false;
       $username msg = 'Username already exists!';
   } else {
       $check username = true;
   //CHECK EMAIL IF ALREADY IN USE
    $new email = $ POST['regi email'];
   $check email q = mysql query("SELECT * FROM users WHERE email = '" . $new email . "'");
   $check email = mysql num rows($check email q);
    //echo $checkemail;
```

Huberty Tom 152/182

```
if ($check email >= 1) {
       $erroremail = 1;
       $email msg = 'Email is already in use!';
   //PASSWORD
   if ($ POST['regi password1'] == $ POST['regi password2']) {
       $check pw
                    = true;
       $new password = shal($ POST['regi password1']);
   } else {
       $check pw
                    = false;
       $password msg = 'Passwords need to be the same!';
   //CAPTCHA
   if ($ POST['regi captcha'] == $ SESSION['captchastring']) {
       $check captcha = true;
   } else {
       $check captcha = false;
       $captcha msg = 'Captcha was not correct!';
   // echo $ SESSION['before regi'];
   //ADD USER
   if ($check username == true && $erroremail == 0 && $check pw == true && $check captcha == true) {
       $new email = $ POST['regi email'];
       $new firstname = utf8 decode(mysql real escape string($ POST['regi firstname']));
       $new lastname = utf8 decode(mysql real escape string($ POST['regi lastname']));
       $user added = true;
       //echo $ SERVER['SCRIPT NAME'].$ SESSION['before regi'];
       $prev url = $ SERVER['SERVER NAME'] . $ SESSION['before'];
       $url prefix = substr($ SERVER['HTTP REFERER'], 0, strpos($ SERVER['HTTP REFERER'], $ SERVER['SERVER NAME']));
       //echo $url prefix.$prev url;
       mysql query("INSERT INTO `users`(`id username`, `email`, `password`, `firstname`, `lastname`, avatar) VALUES
('$new username','$new email','$new password','$new firstname','$new lastname','standard.png')");
       header("Refresh:3; url=" . $url prefix . $prev url, true, 303);
//CHECK END
```

Huberty Tom 153/182

```
<script>
   //Javascript is being used to reload the captcha in the registration form
       function reloadCaptcha()
               var d=new Date();
               img = document.getElementById('captcha');
               img.src = './include/register/captcha.php?a='+d.getDate();
 </script>
       <form action="<?= $ SERVER['SCRIPT NAME'] ?>?page=Register" method="post" autocomplete="off">
  <div id="content" style="background:rgba(255,255,255,0.7);">
    <?php
//Check if a user is already logged in. If yes show message if not show registerform
if ($ SESSION['loggedIN']) {
?>
               You are already logged in. <a href="<?= $ SERVER['SCRIPT NAME'] ?>">Back Home</a>
} elseif ($user added == false) {
?>
       <lequend style="font-weight:bold; font-size:24px; width:100%; background:rgba(0, 0, 0, 0.25); ">Register</lequend>
       <fieldset name="registerform" style="border:none;" id="standardinput" >
       >
           Username*:
           <input type="text" autocomplete="on" maxlength="20" pattern="^[A-Za-z0-9 ]{1,20}$" title="Only a-z,A-
Z, ,0-9. Minimum 1 character." name="regi username" required class="standardinput" value="<?= $new username ?>" />
           <:td><:= $username msg ?>
         <tr>
```

Huberty Tom 154/182

```
Firstname:
          <input type="text" name="regi firstname" class="standardinput" value="<?=$new firstname ?>" />
        Lastname:
         <input type="text" name="regi lastname" class="standardinput" value="<?= $new lastname ?>" />
        >
          Email Address*:
         <input type="email" name="reqi email" placeholder="example@ndleaque.lu" required class="standardinput"</pre>
value="<?= $new email ?>"/>
         <;= $email msq ?>
        >
         Password*:
         <input pattern=".{7,}" title="7 characters minimum." type="password" name="regi password1" required
class="standardinput" />
          <?= $password msg ?>
        <t.r>
          Repeat Password*:
         <input pattern=".{7,}" title="7 characters minimum." type="password" name="regi password2" required
class="standardinput" />
        <imq id="captcha" name="captcha imq" src="./include/register/captcha.php"></imq></br><a
onClick="reloadCaptcha();">Reload Captcha!</a>
          <input type="text" name="regi captcha" required class="standardinput" />
          <?= $captcha msg ?>
        <t.r>
          <input class="standardbutton" style="width:100%;" type="submit" name="BTN GOregister"
value="Register">
        </fieldset>
      <?
```

Huberty Tom 155/182

## 4.2.2.24. /include/register/captcha.php

```
<?php
session start();
$countcaptcha = 0;
$kevstring
               = 'abcdefghijklmnopgrstuvwxvz023456789';
$captchastring = '';
$rotdegree
               = 0;
$heightchar
               = 0;
               = imagecreatetruecolor(100, 40);
$im
              = imagecolorallocate($im, 0, 0, 0);
$black
              = imagecolorallocate($im, 255, 255, 255);
Swhite
$red
               = imagecolorallocate($im, 236, 69, 88);
$arev
               = imagecolorallocate($im, 128, 128, 128);
imagefill($im, 0, 0, $white);
putenv('GDFONTPATH=' . realpath('.'));
$captchafont = 'anson-regular-webfont.ttf';
for ($countcaptcha = 1; $countcaptcha <= 30; $countcaptcha++) {</pre>
    imagettftext($im, 15, rand(-90, 90), rand(10, 100), rand(1, 40), $grey, $captchafont, '.');
for ($countcaptcha = 1; $countcaptcha <= 10; $countcaptcha++) {</pre>
    imagettftext($im, 15, rand(-90, 90), rand(10, 100), rand(1, 40), $black, $captchafont, '|');
for ($countcaptcha = 1; $countcaptcha <= 6; $countcaptcha++) {</pre>
    $captchastring = $captchastring . substr($keystring, rand(1, 35), 1);
```

Huberty Tom 156/182

# 4.2.2.25. /include/streams/index.php

```
<?php
//VARIABLES
 \$status = 0;
//STREAM SELECTION
if(isset($ GET['action'])){
        if($ GET['action'] == 'search') {
   $search q=mysql query("SELECT * FROM users WHERE stream REGEXP '".$ GET['search']."'");
        $search num=mysql num rows($search q);
        //echo $search num;
        if ($search num >0) {
         $stream array=mysql fetch all($search q);
         //print r($stream array);
}else{
        $search q=mysql query("SELECT * FROM users WHERE stream <>''");
        $search num=mysql num rows ($search q);
        if($search num >0){
          $stream array=mysql fetch all($search q);
```

Huberty Tom 157/182

```
//STREAM SELECTION END
//FUNCTION FETCH ARRAY
function mysql fetch all($result) {
      global $search q;
      $all = array();
      while ($all[] = mysql fetch array($search q)) {}
            return $all;
?>
<div id="content">
<?php
      //If get of watch is set show the stream selected
      if(!isset($ GET['watch'])){ ?>
      <h3 style="font-weight:bold; width:100%; background:rgba(255,255,255,0.5); ">Search:</h3>
             <form action="<?=$ SERVER['SCRIPT NAME']?>" method="GET">
                   <fieldset style="border:none">
                         <input type="hidden" name="page" value="<?=$ GET['page']?>" />
             <input type="hidden" name="action" value="search" />
                         <input class="search" type="text" required="" name="search" />
                         <input class="search" type="submit" />
                   </fieldset>
            </form>
      <h3 style="font-weight:bold;width:100%;background:rgba(255,255,255,0.5);">Streams:</h3>
      <!-- HEI GEET TABELL UN
      <a style="text-decoration:none; cursor:pointer; color:black; ">Username</a>
             <a style="text-decoration:none; cursor:pointer; color:black; ">Twitch</a>
            <a style="text-decoration:none; cursor:pointer; color:black; ">Status</a>
```

Huberty Tom 158/182

```
<?php
         if($search num!==0)
               for($i=0;$i<=$search num-1;$i++)</pre>
                       $stream stats = "https://api.twitch.tv/kraken/streams/".htmlentities($stream array[$i]
['stream']);
                       $json = file get contents($stream stats, true);
                       $decode = json decode($json, true);
                       if ($decode['stream'] !==null) {
                             $status=1;
                             $viewers = $decode['stream']['viewers'];
                             $game = $decode['stream']['game'];
                       } else {
                             $status=0;
                             $viewers = '';
                             $game = '';
               ?>
     <?=$stream array[$i]['id username']?>
       <?=$stream array[$i]['stream'];?>
       <?=$viewers;?>
       <; = $qame; ?>
       <?php if($status==1)
                               {?>
                                     <a href="<?=$ SERVER['SCRIPT NAME']?>?page=Streams&amp;watch=<?=$stream array[$i]</pre>
['stream']?>" target=" self">Online</a>
                               <?} else {?>
                                 <a >OFFLINE</a>
                               <? } ?>
                               <?
```

Huberty Tom 159/182

## 4.2.2.26. /include/teams/index.php

```
<?php
//VARIABLES
                       = '';
$join teamname
$teampassword msg
                       = '';
$teamname msg
                       = '';
$team join
                       = false;
$errorteamname
                       = 0:
$errorlogo
                       = '';
$check user team owner = 0;
$confirm edit
                      = 0;
$password msq
                      = '';
//TEAM SELECTION
$search q
                       = mysql query("SELECT id team, teamname, website, fi username, points FROM teams WHERE fi username
<>''');
                       = mysql num rows($search q);
$search num
if ($search num > 0) {
    $teams array = mysql fetch all($search q);
```

Huberty Tom 160/182

```
} else {
    echo 'fail';
//TEAM SELECTION END
//IS USER IN TEAM?
if ($ SESSION['loggedIN'] == true) {
    $check user team q
                            = mysql query("SELECT fi team FROM users WHERE id username = '" . $ SESSION['username'] .
""");
    $check user team object = mysql fetch object($check user team q);
    $check user team
                            = $check user team object->fi team;
//
//FUNCTION FETCH ARRAY
//mysql fetch all to insert every team into one array
function mysql fetch all($result)
    global $search q;
    $all = array();
    while ($all[] = mysql fetch array($search g)) {
    return $all;
?>
<script>
        //Javascript is used here to show teammembers if a teamowner wants to change the leader.
        function change leader() {
                if (document.getElementById('show leader').hidden==false) {
                document.getElementById('show leader').hidden=true;
                document.getElementsByName('sel leader').item(0).hidden=false;
                document.getElementsByName('ch leader').item(0).value=1;
                document.getElementById('change').innerHTML = "Don't Change";
                }else{
                document.getElementById('show leader').hidden=false;
                document.getElementsByName('sel leader').item(0).hidden=true;
                document.getElementsByName('ch leader').item(0).value=0;
                document.getElementById('change').innerHTML = "Change";
```

Huberty Tom 161/182

```
</script>
<div id="content">
      >
             <?php
if ($ SESSION['loggedIN'] == true && $check user team <> 0 && !isset($ GET['action'])) {
>>
             <a class="actionbutton" href="<?= $ SERVER['SCRIPT NAME'] ?>?page=Teams&amp;action=view&amp;teamid=<?
= $check user team ?>">View Team</a>
   $check user team owner q = mysql query("SELECT * FROM teams WHERE id team = '" . $ SESSION['team id'] . "' AND
fi username = '" . $ SESSION['username'] . "'");
   $check user team owner = mysql num rows($check user team owner q);
   if ($check user team owner == 1) {
?>
                          <a class="actionbutton" href="<?= $ SERVER['SCRIPT NAME'] ?>?
<?
} elseif ($ SESSION['loggedIN'] == true && $check user team == 0 && !isset($ GET['action'])) {
>>
                    <a class="actionbutton" href="<?= $ SERVER['SCRIPT NAME'] ?>?
<a class="actionbutton" href="<?= $ SERVER['SCRIPT NAME'] ?>?page=Teams&amp;action=join">Join
a Team</a>
?>
             <?php
if (isset($ GET['action'])) {
   if ($ GET['action'] == 'join' && $ SESSION['loggedIN'] && $ SESSION['team id'] == 0) {
```

162/182

Huberty Tom

```
include('join.php');
   } elseif ($ GET['action'] == 'join' && $ SESSION['loggedIN'] == false) {
?>
               <h3 style="padding-left:5px">You have to be logged in to join a team!</h3>
       < >
    } elseif ($ GET['action'] == 'join' && $ SESSION['loggedIN'] && $ SESSION['team id'] !== 0) {
?>
               <h3 style="padding-left:5px">You have to leave your current team to join a new one!</h3>
               <h4 style="padding-left:5px">You can leave your team by going onto the teams profile (<a href="<?=
$ SERVER['SCRIPT NAME'] ?>?page=Teams&action=view&teamid=<?= $ SESSION['team id'] ?>">Click here</a>) and then
choose to leave. </h4>
       <?
       //check which action is taken. Include the according file to it.
   } elseif ($ GET['action'] == 'edit') {
       include('edit.php');
   } elseif ($ GET['action'] == 'view') {
       include('view.php');
   } elseif ($ GET['action'] == 'create') {
       include('create.php');
} else {
?>
       <h3 style="font-weight:bold;width:100%;background:rgba(255,255,255,0.5);">Teams:</h3>
   <h5 style="background:rgba(255,255,255,0.5); padding-bottom:5px">Sort the table by clicking on the titles.</h5>
       Team
              Website
              Leader
              Points
              Members
       <?php
   for ($i = 0; $i <= $search num - 1; $i++) {</pre>
       $teamid = $teams array[$i]['id team'];
       $teamname = $teams array[$i]['teamname'];
       $website = htmlspecialchars($teams array[$i]['website'],ENT QUOTES);
```

Huberty Tom 163/182

```
= $teams array[$i]['fi username'];
      $leader
      $points
             = $teams array[$i]['points'];
>>
      <tr >
            <a href="<?= $ SERVER['SCRIPT NAME'] ?>?
page=Teams&action=view&teamid=<?= $teamid ?>" style="text-decoration:none;color:black;font-weight:bold">
                   <?= $teamname ?>
      </a>
            <a href="http://<?= $website; ?>" target="new">
                   <?= $website ?>
                   </a>
            <?= $leader ?>
            <?= $points ?>
            <?php
      //Show how many members a team has.
      $check team members = mysql query("SELECT * FROM users WHERE fi team = '" . $teamid . "'");
      echo mysql num rows ($check team members);
?>
         <?
?>
      <?
?>
</div>
```

# 4.2.2.27. /include/teams/view.php

```
<?
//Initiate is_owner
$is_owner = 0;</pre>
```

Huberty Tom

```
//Leave team
if(isset($ POST['btn leave'])){
      mysql query("UPDATE users SET fi team = 0 WHERE id username = '".$ SESSION['username']."'");
      $ SESSION['team id'] = 0;
if(isset($ POST['BTN kick'])){
      mysql query("UPDATE users SET fi team = 0 WHERE id username = '".$ POST['BTN kick']."'");
      //Email variables
      $from = 'MIME-Version: 1.0' . "\r\n";
      $from .= 'Content-type: text/plain; charset=ISO-8859-1' . "\r\n";
      $from .= 'From: nextdoorleague@gmail.com';
             = $ POST['email'];
      $t.o
      $message = "You have been kicked from ".$ POST['teamname'].".";
      //Send email to challenged team leader
      mail($to , 'NextDoor League - Kicked of team' , $message , $from );
//GET TEAM INFORMATION
$qetteam q=mysql query("SELECT * FROM teams WHERE id team='".$ GET['teamid']."' AND fi username <>''");
$check team = mysql num rows($getteam q);
if($check team == 1 && !isset($ POST['btn leave'])){
      $team id = mysql result($getteam q,0,'id team');
      $team teamname = mysql result($getteam q,0,'teamname');
      $team leader = mysql result($getteam q,0,'fi username');
      $team points = mysql result($getteam q,0,'points');
      $team website = mysql result($getteam q,0,'website');
      $team logo = mysql result($getteam q, 0, 'logo');
      $team descr = mysql result($getteam q,0,'description');
?>
<?=$team teamname?>
```

Huberty Tom 165/182

```
<?php
              //check if user is logged in and is in the viewed team
              if($ SESSION['loggedIN'] == true    && $ SESSION['team id']!=0) {
                     if($team id == $ SESSION['team id'] && $team leader != $ SESSION['username']) {
                             sis owner = 0;
                      }elseif($team id == $ SESSION['team id'] && $team leader == $ SESSION['username']) {
                             \sin \sin \theta = 1;
                     //if user is team owner he can not leave, else he can leave
                     if($is owner == 0){ ?>
              <form method="post" action="<?=$ SERVER['SCRIPT NAME']?>?page=Teams&amp;action=view&teamid=<?=$team id?</pre>
>">
                             <button type="submit" class="standardbutton" style="width:auto;padding-left:3px;padding-</pre>
right: 3px; margin-bottom: 3px; margin-right: 5px" name="btn leave" onclick="return confirm('Do you really want to leave your
team?')">Leave Team?</button>
              </form>
              <? }elseif($is owner == 1){ ?>
                             <button type="button" class="standardbutton" style="width:auto;padding-left:3px;padding-</pre>
right: 3px; margin-bottom: 3px; margin-right: 5px" onclick="return alert('You can not leave your team while being the
leader.')">Leave Team?</button>
              <?
                     if(isset($ SESSION['username'])){
                             if($team leader == $ SESSION['username']){ ?>
                             <a class="actionbutton" href="<?=$ SERVER['SCRIPT NAME']?>?
page=Teams&action=edit&teamid=<?=$team id?>">Edit Team</a>
                  <?
              }?>
```

Huberty Tom 166/182

```
>
       <imq src="./imq/teams/<?=$team logo?>" width="100" alt="Team Logo"/>
   <tr >
   //Teaminfo
   >
       Leader: 
       <a href="<?=$ SERVER['SCRIPT NAME']?>?page=Profile&amp;action=view&amp;user=<?=$team leader?>"
target=" self"><?= htmlentities($team leader) ?></a>
   >
       Points: 
       <?= htmlentities($team points) ?>
   <tr >
   //Contact
   >
       Website: 
   <a href="<?=$team website?>" target="new"><?= htmlspecialchars($team website,ENT QUOTES) ?></a>
   <tr >
   //Description
   >
     <?=htmlspecialchars($team descr,ENT QUOTES) ?>
   <tr >
```

Huberty Tom 167/182

```
//Members
      <tr>
             Avatar
      Username
      Email
      LoL-ID
      <?
             //If teamowner then show kick column
             if($ SESSION['loggedIN'] == true && $ SESSION['team id']!=0){
                   if($team id == $ SESSION['team id'] && $team leader != $ SESSION['username']){
                          \overline{\$} is owner = 0;
                    }elseif($team id == $ SESSION['team id'] && $team leader == $ SESSION['username']) {
                          sis owner = 1;
                    if($is owner ==1) {
                          echo "Kick";
             ?>
   <?php
//List all members of the team
      $membercount q = mysql query("SELECT * FROM users WHERE fi team = '".$team id."'");
      $membercount = mysql num rows($membercount q);
      for (\$i = 0; \$i < \$membercount; \$i++) {
             $member username = mysql result($membercount q,$i,'id username');
             $member email = mysql result($membercount q,$i,'email');
             $member lolid = htmlspecialchars(mysql result($membercount q,$i,'lolid'),ENT QUOTES);
             $member avatar = mysql result($membercount q,$i,'avatar');
      ?>
```

Huberty Tom 168/182

```
>
       <img src="./img/users/<?=$member avatar?>" width="30" alt="User
Avatar">
       <a href="<?=$ SERVER['SCRIPT NAME']?>?page=Profile&amp;action=view&amp;user=<?</pre>
=$member username?>" target=" self"><?=htmlentities($member username)?></a>
       <?=htmlentities($member email)?>
      <?= ($member lolid !=='\)? htmlentities($member lolid):'/'); ?>
       <?
              //If teamowner then show kick column
              if($ SESSION['loggedIN']==true && $ SESSION['team id']!=0){
                    if($team id == $ SESSION['team id'] && $team leader != $ SESSION['username']){
                            sis owner = 0:
                    }elseif($team id == $ SESSION['team id'] && $team leader == $ SESSION['username']) {
                           \sin = 1;
                    //if teamowner show kickbutton, no kick button for the teamowner
                    if($is owner ==1){?>
              <form method="post" action="<?=$ SERVER['SCRIPT NAME']?>?page=Teams&amp;action=view&teamid=<?=$team id?</pre>
>">
                           <? if ( $member username != $ SESSION['username']) { ?>
              <button type="submit" class="standardbutton" style="font-weight:bolder" name="BTN kick" onclick="return</pre>
confirm('Do you want to kick <?=$member username?> of your team?')" value="<?=$member username?>">X</button><input
type="hidden" value="<?=$team teamname?>" name="teamname" /><input type="hidden" value="<?=$member email?>" name="email"
/>
              <? } ?>
              </form>
              <?
              ?>
   <? }
?>
```

Huberty Tom 169/182

```
<? }elseif($check_team == 1 && isset($_POST['btn_leave'])) {
        echo"<h3 style='padding-left:5px'>You have left your team.</h3>";
    }else{
            echo"<h3 style='padding-left:5px'>The team you want to view does not exist,or has been deactivated!
</h3>";
    }
}
```

#### 4.2.2.28. /include/teams/edit.php

```
<?
if ($ GET['action'] == 'edit' && isset($ GET['teamid']) && $ SESSION['loggedIN'] == true && $ SESSION['team id'] ==
$ GET['teamid']) {
   $check user team owner q = mysql query("SELECT * FROM teams WHERE id team = " . $ GET['teamid'] . " AND fi username =
'" . $ SESSION['username'] . "'");
   $check user team owner = mysql num rows($check user team owner q);
   if ($check user team owner == 1) {
       $team editsql = "SELECT * FROM teams WHERE id team = '" . $ SESSION['team id'] . "' LIMIT 1";
       $team editguery = mysgl guery($team editsgl);
       $teamname = mysql result($team editquery, 0, 'teamname');
       $old teamname = $teamname;
       $team id = mysql result($team editquery, 0, 'id team');
       $team leader = mysql result($team editquery, 0, 'fi username');
       $team website = mysql result($team editquery, 0, 'website');
       $team descr = mysql result($team editquery, 0, 'description');
       $new logo = mysql result($team editquery, 0, 'logo');
       //Deactivate Team
       //Users fi team with the relative teamid will be set to 0
       if (isset($ POST['BTN delteam'])) {
           mysql query("UPDATE users SET fi team = 0 WHERE fi team = '" . $team id . """);
           mysql query("UPDATE teams SET fi username = '' , league = 0 WHERE id team = " . $team id . "");
           $ SESSION['teamid'] = 0;
       if (isset($ POST['BTN editteam'])) {
           $old teamname = $ POST['old teamname'];
           $team id = $ POST['team id'];
           $teamname = $ POST['teamname'];
```

Huberty Tom 170/182

```
$team descr = $ POST['descr'];
            $team leader = $ POST['team leader'];
            //CHECK Teamname
            if ($teamname !== $ POST['old teamname']) {
                $checkteam q = mysql query("SELECT * FROM teams WHERE teamname = '" . $teamname . "'");
               $checkteam = mysql num rows($checkteam q);
                if ($checkteam >= 1) {
                    $errorteamname = 1;
                    $teamname msq = 'Teamname already exists!';
            //CHECK TEAMLEADER
            if ($ POST['ch leader'] == 1) {
                $team leader = $ POST['sel leader'];
            //CHECK IF PASSWORDS ARE CORRECT
            if (($ POST['new password1'] || $ POST['new password2']) !== '') {
                pass change = 1;
                if ($ POST['new password1'] == $ POST['new password2']) {
                    $check pw = true;
                    $new password = sha1($ POST['new password1']);
                } else {
                    $check pw
                               = false;
                    $password msq = 'Both passwords have to be the same!';
            } else {
                pass change = 0;
            if ($errorteamname == 0 && $pass change == 1 && $check pw == true) {
               //CHECK NEW teams RIGHTS
               mysql query("UPDATE teams SET teamname='" . $teamname . "',fi username='" . $team leader . "',password='"
. $new password . "', website='" . $team website . "', description='" . $team descr . "' WHERE id team ='" . $team id .
""");
               $confirm edit = 1;
            } elseif ($errorteamname == 0 && $pass change == 0) {
               mysql_query("UPDATE teams SET teamname='" . $teamname . "',fi_username='" . $team leader . "',website='"
```

Huberty Tom 171/182

\$team website = \$ POST['website'];

```
. $team website . "', description='" . $team descr . "' WHERE id team = '" . $team id . "'");
                $confirm edit = 1;
            if (isset($ FILES['logo'])) {
                $change avatar = 1;
                $allowed
                              = array(
                    "gif".
                    "ipea",
                    "jpq",
                    "pnq"
                $tempname = explode(".", $ FILES['logo']['name']);
               $extension = end($tempname);
               if ((($ FILES["logo"]["type"] == "image/gif") || ($ FILES["logo"]["type"] == "image/jpeg") ||
($ FILES["logo"]["type"] == "image/jpg") || ($ FILES["logo"]["type"] == "image/pjpeg") || ($ FILES["logo"]["type"] ==
"image/x-png") || ($ FILES["logo"]["type"] == "image/png")) && ($ FILES["logo"]["size"] <= 204800) &&
in array($extension, $allowed)) {
                    // CHECK IF IMAGE IS SQUARE
                   list($width, $height) = getimagesize($ FILES['logo']['tmp name']);
                    if ($width == $height) {
                       $lookuplogo q = mysql query("SELECT logo FROM teams WHERE id team = '" . $ SESSION['team id'] .
""");
                        $lookuplogo = mysql result($lookuplogo q, 0, 'logo');
                       $old tempname = explode(".", $lookuplogo);
                        $old extension = end($old tempname);
                       if ($\subsetextriangle extension) {
                           unlink('./img/teams/' . $lookuplogo);
                       move uploaded file($ FILES["logo"]["tmp name"], "./img/teams/" . $ SESSION['team id'] . '.' .
$extension);
                       //UPDATE AVATAR IN DATABASE OF USER
                        $newlogo = $ SESSION['team id'] . '.' . $extension;
                       mysql query("UPDATE teams SET logo='" . $newlogo . "' WHERE id team = '" . $ SESSION['team id'] .
"""):
                    } else {
                        $errorlogo = 'Image need to be square(128x128,250x250,etc..).';
```

Huberty Tom 172/182

```
} else {
                 $errorlogo = 'Invalid File, see conditions.';
if ($ SESSION['loggedIN'] && !isset($ POST['BTN delteam'])) {
   if ($check user team owner == 1) {
?>
       <h3 style="font-weight:bold; width:100%; background:rgba(255, 255, 255, 0.5); ">Edit Team:</h3>
      <form method="post" action="<?= $ SERVER['SCRIPT NAME'] ?>?page=Teams&amp;action=edit&amp;teamid=<?=</pre>
$ SESSION['team id'] ?>" enctype="multipart/form-data">
       <button type="submit" class="standardbutton" style="width:auto;padding-left:3px;padding-right:3px;margin-</pre>
bottom: 3px; margin-right: 5px" name="BTN delteam" onclick="return confirm('Do you really want to delete your
team?')">Delete Team?</button>
   <br />
   <?php
      if ($confirm edit == 1) {
?>
   <h4 align="center" style="background:rgba(255,255,255,0.5);border-radius:4px;border:1px rgba(0,0,0.8) solid;margin-
bottom:4px;">The team has been updated.</h4>
   <?
>>
    //Logo 
     <img src="./img/teams/<?= $new logo ?>" width="100px" alt="Team Logo"/>
     <input type="file" name="logo" class="standardinput" accept="image/jpeg, image/png"
style="background:rgba(255,255,255,0.6);" />
       <?= $errorlogo ?>
     >
```

Huberty Tom 173/182

```
<td style="background:rgba(255,255,255,0.8);border:1px rgba(0,0,0,0.7) solid;border-
radius:2px;padding:2px;"><h5>Only jpeq,jpq,pnq and gif allowed. Must be under 200kbytes.</h5>
         \langle \mathbf{h5} \rangle Picture needs to be square (128 \times 128, 250 \times 250, \ldots) \cdot \langle \mathbf{h5} \rangle \langle \mathbf{td} \rangle
      //Name & amp; Leader
>
       Teamname: 
       <input type="text" name="old teamname" hidden="" value="<?= $old teamname ?>"/>
         <input type="text" name="team id" hidden="" value="<?= $team id ?>" />
         <input type="text" name="teamname" maxlength="20" pattern="^[A-Za-z0-9]{1,20}$" title="Only a-z,A-Z, ,0-9.</pre>
Minimum 1 character." value="<?= $teamname ?>" required="required" class="standardinput" />
       <?= $teamname msq ?>
     <t.r>
       Leader: 
       <input type="text" name="ch leader" value="0" hidden="" />
         <input type="text" name="team leader" id="show leader" readonly="readonly" value="<?= $team leader ?>"
class="standardinput" />
         <select size="1" name="sel leader" style="width:163px" class="standardinput" hidden="" class="standardinput">
         <?php
       $members sql = "SELECT * FROM users WHERE fi team = '" . $team id . "' AND id username NOT LIKE '" .
$ SESSION['username'] . "' ";
       $members result = mysql query($members sql, $con);
       $members rows = mysql num rows($members result);
       for ($i = 0; $i <= $members rows - 1; $i++) {
           $membername = mysql result($members result, $i, 'id username');
           echo "<option value='" . $membername . "'>" . $membername . "</option>";
?>
         </select>
         <button type="button" onclick="change leader();" class="standardbutton" style="width:150px;margin-</pre>
right:0;margin-top:0;" id="change">Change</button>
```

Huberty Tom 174/182

```
 //Password 
    Password:
      <input pattern=".{7,}" title="7 characters minimum." type="password" name="new password1"
class="standardinput" />
       <?= $password msq ?>
      <t.r>
      <td style="background:rqba(255,255,255,0.8); border:1px rqba(0,0,0,0.7) solid; border-radius:2px; padding:2px; "
colspan="2"><h5>Leave empty, if you don't want to change your current password.</h5>
    >
      Repeat Password:
     <input pattern=".{7,}" title="7 characters minimum." type="password" name="new password2"
class="standardinput" />
    <td style="background:rgba(255,255,255,0.8); border:1px rgba(0,0,0.7) solid; border-radius:2px; padding:2px; "
colspan="2"><h5>Re-Enter password, if you want to change your current password.</h5>
     //Information 
   Website: 
<input type="text" name="website" value="<?=htmlspecialchars($team website,ENT QUOTES)?>"class="standardinput"/>
     <t.r>
      Description: 
      <textarea name="descr" style="max-width: 590px;min-width:250px;min-height: 200px;font-family:Calibri Light;"
placeholder="Write a little description about your team."><?=htmlspecialchars($team descr,ENT QUOTAS) ?>
</textarea>
```

Huberty Tom 175/182

# 4.2.2.29. include/teams/create.php

```
//Initialisation of variables needed.
$new teamname = '';
$new website = '';
$new descr = '';
$team created = 0;
if (isset($ POST['BTN createteam'])) {
   $new teamname
                         = mysql real escape string($ POST['teamname']);
                       = mysql real escape string($ POST['website']);
   $new website
                         = mysql real escape string($ POST['descr']);
   $new descr
   //CHECK teamname
   $new teamname nospace = str replace(' ', '', $new teamname);
                         = mysql query("SELECT * FROM teams WHERE teamname = '" . $new teamname . "'");
   $checkteam q1
    $checkteam1
                         = mysql num rows ($checkteam q1);
                         = mysql query("SELECT * FROM teams");
   $check allTeams
    $check numTeams
                         = mysql num rows($check allTeams);
```

Huberty Tom 176/182

```
Śi
                         = 0:
    $checkteam2
                    = 0;
    while ($i < $check numTeams && $checkteam2 == 0) {</pre>
       if (strtolower(str replace(' ', '', mysql result($check allTeams, $i, 'teamname'))) == strtolower($new teamname))
           checkteam2 = 1;
       if (strtolower(str replace(' ', '', mysql result($check allTeams, $i, 'teamname')))) ==
strtolower($new teamname nospace)) {
           $checkteam2 = 1;
       $i++;
   if ($checkteam1 !== 0 || $checkteam2 !== 0) {
       $errorteamname = 1;
       $teamname msg = 'Teamname already exists!';
    //CHECK IF PASSWORDS ARE CORRECT
    //PASSWORD
   if ($ POST['new password1'] == $ POST['new password2']) {
        $check pw = true;
       $new password = shal($ POST['new password1']);
   } else {
        $check pw
                   = false;
        $password msq = 'Both passwords have to be the same!';
   //CHECK IF EVERYTHING IS VALIDATE AND EXECUTE QUERY
   if ($errorteamname == 0 && $check pw == true) {
        $team created = 1;
       mysql query("INSERT INTO teams(teamname, fi username, password, website, logo, description) VALUES ('".
$new teamname . "','" . $ SESSION['username'] . "', " . $new password . "', " . $new website . "', 'standard.png', " .
$new descr . "')");
                          = "SELECT * FROM teams WHERE teamname = '" . $new teamname . "' LIMIT 1";
        $id teamsql
       $id teamquery = mysql query($id teamsql, $con);
       $id team = mysql result($id teamquery, 0, 'id team');
        $ SESSION['team id'] = $id team;
       mysql query("UPDATE users SET fi team = '" . $id team . "' WHERE id username = '" . $ SESSION['username'] . "'");
```

Huberty Tom 177/182

```
}
if (isset($ SESSION['username'])) {
   if ($ SESSION['team id'] == 0) {
2>
              <h3 style="font-weight:bold; width:100%; background:rgba(255,255,0.5); ">Create Team:</h3>
              <form method="post" action="<?= $ SERVER['SCRIPT NAME'] ?>?page=Teams&amp;action=create">
       >
                     Teamname: 
                     <input type="text" name="teamname" maxlength="20" pattern="^[A-Za-z0-9]{1,20}$" title="Only
a-z, A-Z, , 0-9. Minimum 1 character." value="<?= $new teamname ?>" required="required" class="standardinput" />
                     <?= $teamname msg ?>
              >
                     Website: 
                     <input type="text" name="website" value="<?= $new website ?>" class="standardinput"
autocomplete="off" />
                     >
                     Password:
                     <input pattern=".{7,}" title="7 characters minimum." type="password" name="new password1"</pre>
class="standardinput" autocomplete="off" required="required" />
                     <?= $password msq ?>
                     >
                     Repeat Password:
                     <input pattern=".{7,}" title="7 characters minimum." type="password" name="new password2"</pre>
class="standardinput" required="required" />
              >
                     Description: 
                     <textarea name="descr" style="max-width: 590px;min-width:250px;min-height: 200px;font-
family: Calibri Light;"
                     placeholder="Write a little description about your team.">
<?=htmlspecialchars($new descr,ENT QUOTES) ?></textarea>
```

Huberty Tom 178/182

```
>
                     <button type="submit" name="BTN createteam" value="Create"</pre>
class="standardbutton">Create Team</button>
              </form>
 <?
   } elseif ($team created == 1) {
       echo "<h3 style='padding-left:5px'>Your team has been created!<a href='" . $ SERVER['SCRIPT NAME'] . "?</pre>
page=Teams' class='actionbutton'>Back to the teams</a></h3>";
   } else {
       echo "<h3 style='padding-left:5px'>You have to leave your current team to join a new one!</h3>";
} else {
   echo "<h3 style='padding-left:5px'>You have to be logged in to create a team.</h3>";
?>
```

# 4.2.2.30. /include/teams/join.php

```
//JOIN TEAM START

if (isset($_POST['BTN_join'])) {
    //TEAM EXISTS?
    $join_teamname = $_POST['team_name'];
    $join_password = shal($_POST['team_password']);
    $checkteam_q = mysql_query("SELECT * FROM teams WHERE teamname = '" . $join_teamname . "'");
    $checkteam = mysql_num_rows($checkteam_q);
    //echo $checkteam;
    if ($checkteam == 0) {
        $teamname_msg = "Team doesn't exists!";
    }
}
```

Huberty Tom 179/182

```
//RIGHT PASSWORD?
   if ($checkteam !== 0) {
       $team password = mysql result($checkteam q, 0, 'password');
                     = mysql result($checkteam q, 0, 'id team');
       if ($join password == $team password) {
           mysql query("UPDATE users SET fi team='" . $team id . "' WHERE id username = '" . $ SESSION['username'] .
""");
           $joined team = mysql result($checkteam q, 0, 'teamname');
           $team join = true;
       } else {
           $teampassword msg = "Wrong password!";
//JOIN TEAM END
>>
<h3 style="font-weight:bold; width:100%; background:rgba(255,255,0.5); ">Join Team:</h3>
if ($team join == false) {
?>
       <form method="post" action="<?= $ SERVER['SCRIPT NAME'] ?>?page=Teams&amp;action=join">
       <fieldset style="border:none;" >
               <input type="hidden" name="team id" value="<?= $check user team ?>" />
               >
                              Teamname:
                              <input type="text" autocomplete="off" class="standardinput" name="team name"
maxlength="20" pattern="^[A-Za-z0-9] {1,20}$" title="Only a-z,A-Z, ,0-9. Minimum 1 character." value="<?= $join teamname
?>" required="required"/>
                              <?= $teamname msq ?>
                      >
                              Join-Password:
                              <input type="password" autocomplete="off" class="standardinput" name="team password"</pre>
pattern=".{7,}" title="7 characters minimum." required="required" />
                              <?= $teampassword msg ?>
```

Huberty Tom 180/182

```
>
                             </
                             <button type="submit" class="standardbutton" name="BTN join">Join!</button>
                      </fieldset>
       </form>
<?
} elseif ($team join == true) {
   $ SESSION['team id'] = $team id;
?>
       You have successfully joined the team <b>
       <?= $joined team ?>
       </b><br />
       <a href="<?= $ SERVER['SCRIPT NAME'] ?>?page=Teams" class="actionbutton">Back to Teams</a>
<?
```

# 4.2.3 Javascript

## 4.2.3.1. /include/bg set.php

Huberty Tom 181/182

```
//document.getElementsByTagName("head").item(0).replaceChild(newlink, oldlink);
}

function checkCSS(cname)
{
    var name = cname + "=";
    var cookie_array = document.cookie.split(';');
    for(var i=1; i<=cookie_array.length; i++)
    {
        var c = cookie_array[i].trim();
        if (c.indexOf(name) == 0) {

        document.getElementsByTagName('link').item(0).setAttribute("href",'./stylesheets/'+c.substring(name.length,c.length) +'.css');
        };
        alert(substring(name.length,c.length));
    }
}
</script>
```

Huberty Tom 182/182