SEMITRANS® 10

IGBT4 Modules

SKM1000GB17E4

Features*

- Symmetrical current sharing
- Low-inductive module design
- High mechanical robustness
- UL recognized, file no. E63532

Typical Applications

- Motor Drives
- UPS Systems
- Solar Inverters

Remarks

Recommended T_{jop} = -40 ... +150°C
I_{DC} ≤ 1000A for $T_{Terminal}$ = 100°C



GB

Absolute Maximum Ratings				
Symbol	**Conditions**		**Values**	**Unit**
IGBT				
V_{CES}	T_j = 25 °C		1700	V
I_C	T_j = 175 °C	T_c = 25 °C	1300	A
		T_c = 100 °C	850	A
I_{Cnom}			1000	A
I_{CRM}			2000	A
V_{GES}			-20 ... 20	V
t_{psc}	V_{CC} = 1000 V V_{GE} ≤ 15 V V_{CES} ≤ 1700 V	T_j = 150 °C	10	µs
T_j			-40 ... 175	°C
Inverse diode				
V_{RRM}	T_j = 25 °C		1700	V
I_F	T_j = 175 °C	T_c = 25 °C	1427	A
		T_c = 100 °C	890	A
I_{FRM}			2000	A
I_{FSM}	t_p = 10 ms, sin 180°, T_j = 25 °C		6240	A
T_j			-40 ... 175	°C
Module				
$I_{t(RMS)}$			1000	A
T_{stg}			-40 ... 150	°C
V_{isol}	AC sinus 50 Hz, t = 1 min		4000	V

Characteristics						
Symbol	**Conditions**		**min.**	**typ.**	**max.**	**Unit**
IGBT						
$V_{CE(sat)}$	I_C = 1000 A V_{GE} = 15 V chiplevel	T_j = 25 °C		1.99	2.31	V
		T_j = 150 °C		2.44	2.77	V
V_{CE0}	chiplevel	T_j = 25 °C		1.10	1.20	V
		T_j = 150 °C		1.00	1.10	V
r_{CE}	V_{GE} = 15 V chiplevel	T_j = 25 °C		0.89	1.11	mΩ
		T_j = 150 °C		1.44	1.67	mΩ
$V_{GE(th)}$	V_{GE}=V_{CE}, I_C = 36 mA		5.2	5.8	6.4	V
I_{CES}	V_{GE} = 0 V, V_{CE} = 1700 V, T_j = 25 °C				5	mA
C_{ies}	V_{CE} = 25 V V_{GE} = 0 V	f = 1 MHz		70.8		nF
C_{oes}		f = 1 MHz		2.58		nF
C_{res}		f = 1 MHz		2.28		nF
Q_G	V_{GE} = +15V / -15 V			7200		nC
R_{Gint}	T_j = 25 °C			1.5		Ω
$t_{d(on)}$	V_{CC} = 900 V I_C = 1000 A V_{GE} = +15/-15 V $R_{G\,on}$ = 1.2 Ω $R_{G\,off}$ = 1.2 Ω di/dt_{on} = 8.2 kA/µs di/dt_{off} = 4.7 kA/µs dv/dt = 3800 V/µs L_s = 25 nH	T_j = 150 °C		730		ns
t_r		T_j = 150 °C		115		ns
E_{on}		T_j = 150 °C		450		mJ
$t_{d(off)}$		T_j = 150 °C		990		ns
t_f		T_j = 150 °C		175		ns
E_{off}		T_j = 150 °C		370		mJ
$R_{th(j-c)}$	per IGBT				0.034	K/W
$R_{th(c-s)}$	per IGBT (λ_{grease}=0.81 W/(m*K))			0.016		K/W
$R_{th(c-s)}$	per IGBT, pre-applied phase change material			0.013		K/W

SEMITRANS® 10

IGBT4 Modules

SKM1000GB17E4

Features*

- Symmetrical current sharing
- Low-inductive module design
- High mechanical robustness
- UL recognized, file no. E63532

Typical Applications

- Motor Drives
- UPS Systems
- Solar Inverters

Remarks

Recommended T_{jop} = -40 ... +150°C
I_{DC} ≤ 1000A for $T_{Terminal}$ = 100°C



GB

Characteristics						
Symbol	**Conditions**		**min.**	**typ.**	**max.**	**Unit**
Inverse diode						
$V_F = V_{EC}$	I_F = 1000 A V_{GE} = 0 V chiplevel	T_j = 25 °C		1.78	2.12	V
		T_j = 150 °C		1.81	2.14	V
V_{F0}	chiplevel	T_j = 25 °C		1.32	1.56	V
		T_j = 150 °C		1.08	1.22	V
r_F	chiplevel	T_j = 25 °C		0.46	0.56	mΩ
		T_j = 150 °C		0.73	0.92	mΩ
I_{RRM}	I_F = 1000 A di/dt$_{off}$ = 8.38 kA/µs V_{GE} = -15 V V_{CC} = 900 V	T_j = 150 °C		800		A
Q_{rr}		T_j = 150 °C		360		µC
E_{rr}		T_j = 150 °C		200		mJ
$R_{th(j-c)}$	per diode				0.043	K/W
$R_{th(c-s)}$	per diode (λ_{grease}=0.81 W/(m*K))			0.017		K/W
$R_{th(c-s)}$	per diode, pre-applied phase change material			0.014		K/W
Module						
L_{CE}				10		nH
$R_{CC'+EE'}$	measured per switch, T_C = 25 °C			0.2		mΩ
$R_{th(c-s)1}$	calculated without thermal coupling (λ_{grease}=0.81 W/(m*K))			0.0041		K/W
$R_{th(c-s)2}$	including thermal coupling, T_s underneath module (λ_{grease}=0.81 W/(m*K))			0.007		K/W
$R_{th(c-s)2}$	including thermal coupling, T_s underneath module, pre-applied phase change material			-		K/W
M_s	to heat sink M5		4		6	Nm
M_t		to terminals M8	8		10	Nm
		to terminals M4	1.8		2.1	Nm
w					1250	g
Temperature Sensor						
R_{100}	T_c=100°C (R_{25}=5 kΩ)			493 ± 5%		Ω
$B_{100/125}$	$R_{(T)}=R_{100}\exp[B_{100/125}(1/T-1/T_{100})]$; T[K];			3550 ±2%		K



Fig. 1: Output characteristics IGBT (typical); I_C = f (V_{CE}); V_{GE} = 15V; (chiplevel)



Fig. 2: Output characteristics IGBT (typical); I_C = f (V_{CE}); T_j = 150 °C; (chiplevel)



Fig. 3: Switching losses IGBT (typical); E=f(I_C)



Fig. 4: Switching losses IGBT (typical); E=f(R_G)



Fig. 5: Transient thermal impedance IGBT



Fig. 6: RBSOA IGBT



Fig. 7: Forward charact. Diode (typical); $I_F=f(V_F)$; (chiplevel)



Fig. 8: Switching losses Diode (typical); $E=f(I_F)$



Fig. 9: Switching losses Diode (typical); $E=f(R_G)$



Fig. 10: Transient thermal impedance Diode



Fig. 11: RBSOA Diode



Fig. 12: NTC characteristics (typical)



Fig. 13: Typ. transfer characteristic



Fig. 14: Typ. gate charge characteristic



•Dimensions in mm
•General tolerances ±0,5mm

SEMITRANS 10



GB

This is an electrostatic discharge sensitive device (ESDS) due to international standard IEC 61340.

***IMPORTANT INFORMATION AND WARNINGS**

The specifications of SEMIKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMIKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMIKRON makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMIKRON reserves the right to make changes.