IPOSIM Steady-State Calculation Report

Report number: 787e634e-e0c6-4177-b650-0cdbfc8f215d

User: davide.bagnara@leitner.com Feb 3, 2026

Circuit & Control

Modulation algorithm	**SVPWM**
DC link voltage V_{DC}	**1070 V**
Output current I_{out}	**370 Arms**
Output frequency	**15.6 Hz**
Switching frequency	**4000 Hz**
Modulation index	**0.85**
Power factor cos(ϕ)	**0.8**
Output voltage V_{out}	**557 V**
Reactive power type	**Inductive load (lagging) V**



INDUSTRIAL MODULES

Three Phase - 2 Level

SWITCH

FF650R17IE4

IGBT parameters

V_{CEsat}	**2.35 V**
$E_{on} + E_{off}$	**503.00 mWs**
T_{vjmax}	**150.00 °C**
R_{thJC}	**0.04 K/W**
R_{thCH}	**0.01 K/W**

Diode parameters

V_F	**1.95 V**
E_{rec}	**135.00 mWs**
T_{vjmax}	**150.00 °C**
R_{thJC}	**0.07 K/W**
R_{thCH}	**0.03 K/W**

System parameters

Slew-rate gate control	**Deactivated**
Switch Q1: R_{Gon}	**1.80 Ω**
Switch Q1: R_{Goff}	**2.70 Ω**

Cooling conditions

Heatsink model	**User defined heatsink**
Ambient temperature T_a	**40.00 °C**

Heatsink parameters

$R_{th,h}$ [K/W]	$\tau_{th,h}$ [s]
0.036	1
0	1
0	1
0	1
0	1

	MAXIMUM JUNCTION TEMPERATURE	CONDUCTION LOSSES	SWITCHING LOSSES	TOTAL LOSSES
SWITCH Q1	138.70 °C	242.10 W	610.20 W	852.30 W
DIODE D1	116.10 °C	57.70 W	195.70 W	253.40 W

System Electrical

System Voltage



Device Electrical

Device Q1 Voltage and Current



Device Thermal

Device Q1 Temperature Ripple



Legal Disclaimer

The information given in this Simulation tool shall in no event be regarded as a guarantee of conditions, characteristics or results. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

If you experience any problems in the use of the program or have doubts in the exactness of results don't hesitate to contact our support team via the feedback function of the tool.