

# IPOSIM Steady-State Calculation Report


Report number: 7d721091-98cb-47cb-9d17-50e4ca88516a [🔗](#)

User: davide.bagnara@leitner.com

Feb 3, 2026

## Circuit & Control

Modulation algorithm	SVPWM
DC link voltage $V_{DC}$	1070 V
Output current $I_{out}$	370 Arms
Output frequency	15.6 Hz
Switching frequency	4000 Hz
Modulation index	0.85
Power factor $\cos(\phi)$	0.8
Output voltage $V_{out}$	557 V
Reactive power type	Inductive load (lagging) V



Three Phase - 2 Level

SWITCH  
**FF1200R17IP5**

### IGBT parameters

$V_{CEsat}$	2.14 V
$E_{on} + E_{off}$	797.90 mWs
$T_{vjmax}$	175.00 °C
$R_{thJC}$	0.02 K/W
$R_{thCH}$	0.02 K/W

### Diode parameters

$V_F$	1.74 V
$E_{rec}$	244.00 mWs
$T_{vjmax}$	175.00 °C
$R_{thJC}$	0.04 K/W
$R_{thCH}$	0.02 K/W

### System parameters

Slew-rate gate control	Deactivated
Switch Q1: $R_{Gon}$	1.20 Ω
Switch Q1: $R_{Goff}$	1.20 Ω

### Cooling conditions


Heatsink model	User defined heatsink	
Ambient temperature $T_a$	40.00 °C	
Heatsink parameters	$R_{th,h}$ [K/W]	$\tau_{th,h}$ [s]
	0.036	1
	0	1
	0	1
	0	1
	0	1



	SWITCH Q1	129.40 °C	171.30 W	699.20 W	870.50 W
	DIODE D1	100.90 °C	43.70 W	188.20 W	231.90 W
MAXIMUM JUNCTION TEMPERATURE			CONDUCTION LOSSES		SWITCHING LOSSES
					TOTAL LOSSES

## System Electrical


### System Voltage






## Device Electrical

### Device Q1 Voltage and Current



## Device Thermal

### Device Q1 Temperature Ripple





### Legal Disclaimer

The information given in this Simulation tool shall in no event be regarded as a guarantee of conditions, characteristics or results. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

If you experience any problems in the use of the program or have doubts in the exactness of results don't hesitate to contact our support team via the feedback function of the tool.

© 1999 - 2026 Infineon Technologies AG