

---

# HW 9 – Parse Trees, Ambiguous Grammars, LR and Recursive Descent Parsing

CS 421 – Spring 2014

Revision 1.0

**Assigned** Thursday, April 03, 2014

**Due** Sunday, April 14, 2013, 11:59 PM

---

## 1 Change Log

1.0 Initial Release.

## 2 Turn-In Procedure

This assignment is named `hw9`. Using your favorite tool(s), you should put your solution in a file named `hw9-solution.pdf`. Your answers to the following questions are to be submitted using the `svn` repository as described in the section **Instruction for Solving and Submitting Assignments on the web-page**: <http://courses.engr.illinois.edu/cs421/sp2014/mps/index.html>

## 3 Objectives and Background

The purpose of this HW is to test your understanding of

- How to create a parse tree for a given string with a given grammar
- How to disambiguate a grammar
- How to write a recursive descent parser for an LL(1) grammar

Another purpose of HW9 is to provide you with experience answering non-programming written questions of the kind you may experience on the second midterm and final.

**Caution:** It is strongly advised that you know how to do these problems before the second midterm.

## 4 Problems

1. (23 points) Consider the following grammar over the alphabet  $\{if, then, else, +, x, y, z, (, )\}$ :

$$\begin{aligned} \langle \text{exp} \rangle &::= \langle \text{var} \rangle \mid \text{if } \langle \text{exp} \rangle \text{ then } \langle \text{exp} \rangle \text{ else } \langle \text{exp} \rangle \mid \langle \text{exp} \rangle + \langle \text{exp} \rangle \mid (\langle \text{exp} \rangle) \\ \langle \text{var} \rangle &::= x \mid y \mid z \end{aligned}$$

- (9 points) Show that the above grammar is ambiguous by showing at least three distinct parse trees for the string "if x then x else x + y + z"
- (9 points) Write a new grammar accepting the same language that is unambiguous, and such that addition  $\langle \text{exp} \rangle + \langle \text{exp} \rangle$  has higher precedence than conditional *if*  $\langle \text{exp} \rangle$  *then*  $\langle \text{exp} \rangle$  *else*  $\langle \text{exp} \rangle$ , and such that addition associates to the left.

c. (5 points) Give the parse tree for "if x then x else x + y + z" using the grammar you gave in the previous part of this problem.

2. (17 points) Given the following grammar over nonterminal  $\langle m \rangle$ ,  $\langle e \rangle$  and  $\langle t \rangle$ , and terminals  $z$ ,  $o$ ,  $l$ ,  $r$ ,  $p$  and  $\text{eof}$ , with start symbol  $\langle m \rangle$ :

$P_0 : \langle m \rangle ::= \langle e \rangle \text{ eof}$   
 $P_1 : \langle e \rangle ::= \langle t \rangle$   
 $P_2 : \langle e \rangle ::= \langle t \rangle p \langle e \rangle$   
 $P_3 : \langle t \rangle ::= z$   
 $P_4 : \langle t \rangle ::= o$   
 $P_5 : \langle t \rangle ::= l \langle e \rangle r$

and Action and Goto tables generated by YACC for the above grammar:

State	Action						Goto		
	$z$	$o$	$l$	$r$	$p$	$[\text{eof}]$	$\langle m \rangle$	$\langle e \rangle$	$\langle t \rangle$
st1	s3	s4	s5	err	err	err		st2	st7
st2	err	err	err	err	err	a			
st3	r3	r3	r3	r3	r3	r3			
st4	r4	r4	r4	r4	r4	r4			
st5	s3	s4	s5	err	err	err		st8	st7
st6	err	err	err	err	err	a			
st7	err	err	err	r1	s9	r1			
st8	err	err	err	s10	err	err			
st9	s3	s4	s5	err	err	err		st11	st7
st10	r5	r5	r5	r5	r5	r5			
st11	r2	r2	r2	r2	r2	r2			

where  $\text{sti}$  is state  $i$ ,  $\text{si}$  abbreviates **shift**  $i$ ,  $\text{ri}$  abbreviates **reduce**  $i$ , **a** abbreviates **accept** and  $[\text{eof}]$  means we have reached the end of input, describe how the string  $lzp\text{or}[\text{eof}]$  would be parsed with an LR parser using these productions and tables by filling in the table on the next page. I have given you the first 5 cells in the first two rows to get you started. You will need to add more rows.

Stack	Current String	Action to be taken
Empty	$lzp\text{or}[\text{eof}]$	Initialize stack, go to state 1
st1	$lzp\text{or}[\text{eof}]$	