

XLINK

UNIT-I

XLink

- XLink is used to create hyperlinks within XML documents
- Any element in an XML document can behave as a link
- With XLink, the links can be defined outside the linked files
- XLink is a W3C Standard

HTML Hyperlinks Vs XLink

- HTML Hyperlinks
 - require the use of the anchor element (<a>)
 - Need someone to click them to navigate to the specified location
- XLink
 - Allows a link to another document to be specified through any element in an XML document
 - More complex links are supported

XLink Attributes

- `xlink:type` - specifies xlink types
- `xlink:href` - specifies info' need to locate desired resource
- `xlink:role` / `xlink:arcrole` - describes function of link between the current resource and another
- `xlink:title` - describes the meaning of the link between the resources
- `xlink:show` - Specifies where to open the link
- `xlink:actuate` - specifies when to load the linked resource
- `xlink:label` - specifies name for a target resource
- `xlink:from` - Identifies a starting resource
- `xlink:to` - Identifies an ending resource

Attribute - xlink:type (simple)

- **simple** - A simple link defines a one-way connection between two resources (similar to HTML links)

- Example

```
<novel>
```

```
  <title>The Wonderful Wizard of Oz</title>
```

```
  <author>L. Frank Baum</author>
```

```
  <year>1900</year> </novel>
```

```
<novel xmlns:xlink="http://www.w3.org/1999/xlink"
  xlink:type = "simple"
```

```
  xlink:href = "ftp://archive.org/pub/etext/etext93/wizoz10.txt">
```

```
  <title>The Wonderful Wizard of Oz</title>
```

```
  <author>L. Frank Baum</author>
```

```
  <year>1900</year>
```

```
</novel>
```

Attribute - xlink:type (Extended)

- Extended – describes a collection of resources and a collection of paths between those resources
 - Each path connects exactly two resources
 - Any individual resource may be connected:
 - to one of the other resources / two of the other resources / zero of the other resources / all of the other resources / any subset of the other resources in the collection
 - It may even be connected back to itself
 - An extended link is a directed labeled graph in which the paths are arcs, the documents are vertices, and the URIs are labels

Attribute xlink:type (Locator)

- Locator - creates a link that points to another resource
 - Each locator element has an **xlink:type** = locator and an **xlink:href** = URI for the resource it locates
 - Locators represent remote resources that are not part of the document (generally URI) and used with extended link

```
<novel xlink:type = "extended">
<title>The Wonderful Wizard of Oz</title>
<author>L. Frank Baum</author>
<year>1900</year>
<edition xlink:type="locator" xlink:href="urn:isbn:0688069444"
  xlink:label="ISBN0688069444" />
<edition xlink:type="locator" xlink:href="urn:isbn:0192839306"
  xlink:label="ISBN0192839306" />
<edition xlink:type="locator" xlink:href="urn:isbn:0700609857"
  xlink:label="ISBN0700609857" />
</novel>
```

xlink:type attribute Contd...

- Arc - Paths between resources are called *arcs*
 - creates links with multiple resources and various traversal paths
 - Each arc element should have an **xlink:from** attribute and an **xlink:to** attribute (a name matching the value of the xlink:label attribute)
 - xlink:from – label identifying source link
 - xlink:to - label identifying source link
- Example continued in next slide

xlink:type arc Example

```
<series xlink:type="extended" xmlns:xlink="http://www.w3.org/1999/xlink">
  <author>L. Frank Baum</author>
  <novel xlink:type="locator" xlink:label="oz1"
    xlink:href="ftp://archive.org/pub/etext/etext93/wizoz10.txt">
    <title>The Wonderful Wizard of Oz</title>
    <year>1900</year>
  </novel>
  <novel xlink:type="locator" xlink:label="oz2"
    xlink:href="ftp://archive.org/pub/etext/etext93/ozland10.txt">
    <title>The Marvelous Land of Oz</title>
    <year>1904</year>
  </novel>

  <next xlink:type="arc" xlink:from="oz1" xlink:to="oz2" />
  <previous xlink:type="arc" xlink:from="oz2" xlink:to="oz1" />
</series>
```

Local Resources

- Resource - Extended links can also contain local resources in (i.e. data is contained inside the extended link element)
- Each such resource is represented by a *resource element*

Example:

```
<author xlink:type="resource" xlink:label="baum">L. Frank Baum</author>
```

- To establish links from this local resource to all the books, add these three arc elements:

```
<book xlink:type="arc" xlink:from="baum" xlink:to="oz1" />
```

```
<book xlink:type="arc" xlink:from="baum" xlink:to="oz2" />
```

```
<book xlink:type="arc" xlink:from="baum" xlink:to="oz3" />
```

- To move in the other direction, you'd simply reverse the values of the `xlink:from` and `xlink:to` attributes.

Attribute - xlink:show

- xlink:show attribute
 - optional, has five possible values
 - suggest where to open the link (display)
 - new - Open and show target resource in a new window
 - replace - Show target resource replacing the current document
 - embed - Embed target resource resource in the current document at the location of the link element
 - Other - behavior is may be specified by other nonstandard markup that a particular application understands.
 - none - Specify no behavior

Example:

```
<book title="XQuery Kick Start">
  <description
    xlink:type="simple"
    xlink:href="/images/XQuery.gif"
    xlink:show="new">
    XQuery Kick Start delivers a concise introduction
    to the XQuery standard.....
  </description>
</book>
```

Attribute – xlink:actuate

- **xlink:actuate**
- optional xlink:actuate attribute, has four possible values
- suggest what action should the link follow
- onLoad - the resource should be loaded and shown when the document loads
- onRequest - the resource is not read or shown before the link is clicked
- other - is determined by other markup in the document not specified by XLink.
- none - No details are available
- Example:

```
<image xlink:type="simple" xlink:actuate="onLoad"  
xlink:show="embed"  
xlink:href="http://www.turing.org.uk/turing/pi1/bus.jpg"  
width="152" height="345" />
```