


Symmetric Encryption

- Also referred to as conventional encryption or single-key encryption
- Was the only type of encryption in use prior to the development of public-key encryption in the 1970s
- Remains by far the most widely used of the two types of encryption



Basic Terminology

- Plaintext
 - The original message
- Ciphertext
 - The coded message
- Enciphering or encryption
 - Process of converting from plaintext to ciphertext
- Deciphering or decryption
 - Restoring the plaintext from the ciphertext
- Cryptography
 - Study of encryption
- Cryptographic system or cipher
 - Schemes used for encryption
- Cryptanalysis
 - Techniques used for deciphering a message without any knowledge of the enciphering details
- Cryptology
 - Areas of cryptography and cryptanalysis together

Contd...

- two requirements for secure use of conventional encryption:
 - strong encryption algorithm
 - Sender and receiver must have obtained copies of the secret key.
 - impractical to decrypt a message on the basis of the ciphertext plus knowledge of the encryption/decryption algorithm. do not need to keep the algorithm secret; we need to keep only the key secret – Low cost chip implementation.

Simplified Model of Symmetric Encryption




Figure 2.1 Simplified Model of Symmetric Encryption

Model of Symmetric Cryptosystem





Figure 2.2 Model of Symmetric Cryptosystem

Cryptographic Systems

- Characterized along three independent dimensions:



Cryptanalysis and Brute-Force Attack

Cryptanalysis

- Attack relies on the nature of the algorithm plus some knowledge of the general characteristics of the plaintext
- Attack exploits the characteristics of the algorithm to attempt to deduce a specific plaintext or to deduce the key being used

Brute-force attack


- Attacker tries every possible key on a piece of ciphertext until an intelligible translation into plaintext is obtained
- On average, half of all possible keys must be tried to achieve success

Type of Attack	Known to Cryptanalyst
Ciphertext Only	<ul style="list-style-type: none"> • Encryption algorithm • Ciphertext
Known Plaintext	<ul style="list-style-type: none"> • Encryption algorithm • Ciphertext • One or more plaintext-ciphertext pairs formed with the secret key
Chosen Plaintext	<ul style="list-style-type: none"> • Encryption algorithm • Ciphertext • Plaintext message chosen by cryptanalyst, together with its corresponding ciphertext generated with the secret key
Chosen Ciphertext	<ul style="list-style-type: none"> • Encryption algorithm • Ciphertext • Ciphertext chosen by cryptanalyst, together with its corresponding decrypted plaintext generated with the secret key
Chosen Text	<ul style="list-style-type: none"> • Encryption algorithm • Ciphertext • Plaintext message chosen by cryptanalyst, together with its corresponding ciphertext generated with the secret key • Ciphertext chosen by cryptanalyst, together with its corresponding decrypted plaintext generated with the secret key

Table 2.1
Types of
Attacks
on
Encrypted
Messages


Encryption Scheme Security

- Unconditionally secure
 - No matter how much time an opponent has, it is impossible for him or her to decrypt the ciphertext simply because the required information is not there
- Computationally secure
 - The cost of breaking the cipher exceeds the value of the encrypted information
 - The time required to break the cipher exceeds the useful lifetime of the information




Brute-Force Attack

Involves trying every possible key until an intelligible translation of the ciphertext into plaintext is obtained



On average, half of all possible keys must be tried to achieve success



To supplement the brute-force approach, some degree of knowledge about the expected plaintext is needed, and some means of automatically distinguishing plaintext from garble is also needed

Substitution Technique

- Is one in which the letters of plaintext are replaced by other letters or by numbers or symbols
- If the plaintext is viewed as a sequence of bits, then substitution involves replacing plaintext bit patterns with ciphertext bit patterns





Caesar Cipher



- Simplest and earliest known use of a substitution cipher
- Used by Julius Caesar
- Involves replacing each letter of the alphabet with the letter standing three places further down the alphabet
- Alphabet is wrapped around so that the letter following Z is A

plain: meet me after the toga party

cipher: PHHW PH DIWHU WKH WRJD SDUWB

Caesar Cipher Algorithm

- Can define transformation as:

a	b	c	d	e	f	g	h	i	j	k	l	m	n	o	p	q	r	s	t	u	v	w	x	y	z
D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	A	B	C

- Mathematically give each letter a number

a	b	c	d	e	f	g	h	i	j	k	l	m	n	o	p	q	r	s	t	u	v	w	x	y	z
0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25

- Algorithm can be expressed as:

$$c = E(3, p) = (p + 3) \bmod (26)$$

- A shift may be of any amount, so that the general Caesar algorithm is:

$$C = E(k, p) = (p + k) \bmod 26$$

- Where k takes on a value in the range 1 to 25; the decryption algorithm is simply:

$$p = D(k, C) = (C - k) \bmod 26$$

Brute-Force Cryptanalysis of Caesar Cipher

(This chart can be found on
page 35 in the textbook)

KEY	PHHW	PH	DIWHU	WKH	WRJD	SDUWB
1	oggv	og	chvgt	vjg	vqic	rctva
2	nffu	nf	bgufs	uif	uphb	qbsuz
3	meet	me	after	the	toga	party
4	ldds	ld	zesdq	sgd	snfz	ozqsx
5	kccr	kc	ydrpc	rfc	rmey	nyprw
6	jbbq	jb	xcqbo	qeb	qldx	mxoqv
7	iaap	ia	wbpan	pda	pkcw	lwnpu
8	hzzo	hz	vaozm	ocz	objv	kvmot
9	gyyn	gy	uznyl	nby	niau	julns
10	fxxm	fx	tymxk	max	mhzt	itkmr
11	ewwl	ew	sxlwj	lzw	lgys	hsjlg
12	dvvk	dv	rwkvi	kyv	kfxr	grikp
13	cuuj	cu	qvjuh	jxu	jewq	fghjo
14	btti	bt	puitg	iwt	idvp	epgin
15	assh	as	othsf	hvs	hcuo	dofhm
16	zrrg	zr	nsgr	gur	gbtn	cnegl
17	yqqf	yq	mrfqd	ftq	fasm	bmdfk
18	xppe	xp	lqepc	esp	ezrl	alcej
19	wood	wo	kpdob	dro	dyqk	zkbdi
20	vnnc	vn	jocna	cqn	cxpj	yjach
21	ummb	um	inbmz	bpm	bwoi	xizbg
22	tlla	tl	hmaly	aol	avnh	whyaf
23	skkz	sk	glzcx	znk	zumg	vgxze
24	rjyy	rj	fkyjw	ymj	ytlf	ufwyd
25	qiix	qi	ejxiv	xli	xske	tevxc

Figure 2.3 Brute-Force Cryptanalysis of Caesar Cipher

Sample of Compressed Text

~+Wu"- Ω-O)S4(=†, e-Ωträu.-î 0~Z-
Û#2Ô#Åæð æ=q7,Ωn-@3NÔÛ æz'Y-f=î[±Ô_ èΩ,<NO~t«"xâ Åæè03Å
x)05k°Å
_yî ^ΔÉ] ,= J/'iTê&1 'c<uΩ-
ÅD(G WÄC~y_I0ÄN PÔ1<îÛ†ç],=,~î^uNπ~="L~9OgfiO~&ES ~S 0Ô5":
^E!SQqèvo" ú\,S>h<-*6ø†%x'"|fió#~"myt~ZNP<,fi Åj Å0_~Zû-
Ω~Ô~6ay(%,ΩBó ,I π+Ái~ú02ç8y'O-
2Änßi /0~"ΠK~*P0π,ú4^'JΣ~0~ÔZî~Y~YΩmY> Ω+eð/'<Kf_~*+~"S0~
B Z0K~Q8yú/.!0nîzaS/)>0Q ú

Figure 2.4 Sample of Compressed Text

Monoalphabetic Cipher

- Permutation
 - Of a finite set of elements S is an ordered sequence of all the elements of S , with each element appearing exactly once
- If the “cipher” line can be any permutation of the 26 alphabetic characters, then there are $26!$ or greater than 4×10^{26} possible keys
 - This is 10 orders of magnitude greater than the key space for DES
 - Approach is referred to as a *monoalphabetic substitution cipher* because a single cipher alphabet is used per message





Figure 2.5 Relative Frequency of Letters in English Text


Monoalphabetic Ciphers

- Easy to break because they reflect the frequency data of the original alphabet
- Countermeasure is to provide multiple substitutes (homophones) for a single letter

- Digram
 - Two-letter combination
 - Most common is *th*



- Trigram
 - Three-letter combination
 - Most frequent is *the*



Playfair Cipher

- Best-known multiple-letter encryption cipher
- Treats digrams in the plaintext as single units and translates these units into ciphertext digrams
- Based on the use of a 5 x 5 matrix of letters constructed using a keyword
- Invented by British scientist Sir Charles Wheatstone in 1854
- Used as the standard field system by the British Army in World War I and the U.S. Army and other Allied forces during World War II

Playfair Key Matrix

- Fill in letters of keyword (minus duplicates) from left to right and from top to bottom, then fill in the remainder of the matrix with the remaining letters in alphabetic order
- Using the keyword MONARCHY:

M	O	N	A	R
C	H	Y	B	D
E	F	G	I/J	K
L	P	Q	S	T
U	V	W	X	Z




Figure 2.6 Relative Frequency of Occurrence of Letters

Examples

- _____ is the most common method used to conceal small blocks of data, such as encryption keys and hash function values, which are used in digital signatures.
- A) Symmetric encryption B) Data integrity algorithms
- C) Asymmetric encryption D) Authentication protocols

- A common technique for masking contents of messages or other information traffic so that opponents can not extract the information from the message is _____ .

- A) integrity B) encryption
- C) analysis D) masquerade

- _____ involves the passive capture of a data unit and its subsequent retransmission to produce an unauthorized effect.

- A) Disruption B) Replay
- C) Service denial D) Masquerade

-

-

- The three concepts that form what is often referred to as the CIA triad are _____. These three concepts embody the fundamental security objectives for both data and for information and computing services.
- A) confidentiality, integrity and availability
- B) communication, integrity and authentication
- C) confidentiality, integrity, access control
- D) communication, information and authenticity
-

- A loss of _____ is the unauthorized disclosure of information.

- A) authenticity B) confidentiality
- C) reliability D) integrity

- Verifying that users are who they say they are and that each input arriving at the system came from a trusted source is _____ .

- A) authenticity B) credibility
- C) accountability D) integrity
-

- A _____ level breach of security could cause a significant degradation in mission capability to an extent and duration that the organization is able to perform its primary functions, but the effectiveness of the functions is significantly reduced.
- | | |
|-----------------|-------------|
| A) catastrophic | B) moderate |
| C) low | D) high |

- A _____ is any action that compromises the security of information owned by an organization.

- A) security attack

B) security service

- C) security alert mechanism

D) security

- A _____ takes place when one entity pretends to be a different entity.

- A) replay

- B) masquerade

- C) service denial

- D) passive attack

- _____ is the protection of transmitted data from passive attacks.

- A) Access control

- B) Data control

- C) Nonrepudiation

- D) Confidentiality

- A(n) _____ service is one that protects a system to ensure its availability and addresses the security concerns raised by denial- of- service attacks.

- A) replay
- B) availability
- C) masquerade
- D) integrity
-

- _____ threats exploit service flaws in computers to inhibit use by legitimate users.

- A) Information access B) Reliability
- C) Passive D) Service

- A(n) _____ is a potential for violation of security, which exists when there is a circumstance, capability, action or event that could breach security and cause harm.

- A) threat
- B) attack
- C) risk
- D) attack vector
-

- The protection of the information that might be derived from observation of traffic flows is _____ .

- A) connectionless confidentiality B) connection confidentiality
- C) traffic- flow confidentiality D) selective-field confidentiality

-

- Data appended to, or a cryptographic transformation of, a data unit that allows a recipient of the data unit to prove the source and integrity of the data unit and protect against forgery is a(n) _____ .

- A) security audit trail B) digital signature

- C) encipherment D) authentication exchange

-

- A _____ is any process, or a device incorporating such a process, that is designed to detect, prevent, or recover from a security attack. Examples are encryption algorithms, digital signatures and authentication protocols.
- An _____ attack attempts to alter system resources or affect their operation.

- A loss of _____ is the disruption of access to or use of information or an information system.
- A loss of _____ is the unauthorized modification or destruction of information.
- A _____ attack attempts to learn or make use of information from the system but does not affect system resources.

- The _____ service is concerned with assuring the recipient that the message is from the source that it claims to be from.
- Viruses and worms are two examples of _____ attacks.
- . _____ is the use of a trusted third party to assure certain properties of a data exchange.

Hill Cipher

- Developed by the mathematician Lester Hill in 1929
- Strength is that it completely hides single-letter frequencies
 - The use of a larger matrix hides more frequency information
 - A 3×3 Hill cipher hides not only single-letter but also two-letter frequency information
- Strong against a ciphertext-only attack but easily broken with a known plaintext attack

Contd...

$$\mathbf{A} = \begin{pmatrix} 5 & 8 \\ 17 & 3 \end{pmatrix} \quad \mathbf{A}^{-1} \bmod 26 = \begin{pmatrix} 9 & 2 \\ 1 & 15 \end{pmatrix}$$

$$\begin{aligned} \mathbf{A}\mathbf{A}^{-1} &= \begin{pmatrix} (5 \times 9) + (8 \times 1) & (5 \times 2) + (8 \times 15) \\ (17 \times 9) + (3 \times 1) & (17 \times 2) + (3 \times 15) \end{pmatrix} \\ &= \begin{pmatrix} 53 & 130 \\ 156 & 79 \end{pmatrix} \bmod 26 = \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix} \end{aligned}$$

Contd...

$$(c_1 \ c_2 \ c_3) = (p_1 \ p_2 \ p_3) \begin{pmatrix} k_{11} & k_{12} & k_{13} \\ k_{21} & k_{22} & k_{23} \\ k_{31} & k_{32} & k_{33} \end{pmatrix} \bmod 26$$

$$c_1 = (k_{11}p_1 + k_{21}p_2 + k_{31}p_3) \bmod 26$$

$$c_2 = (k_{12}p_1 + k_{22}p_2 + k_{32}p_3) \bmod 26$$

$$c_3 = (k_{13}p_1 + k_{23}p_2 + k_{33}p_3) \bmod 26$$

$$\mathbf{C} = \mathbf{PK} \bmod 26$$

- Paymoremoney = plaintext

$$\mathbf{K} = \begin{pmatrix} 17 & 17 & 5 \\ 21 & 18 & 21 \\ 2 & 2 & 19 \end{pmatrix}$$

- Pay = (15 0 24)
- $C = (15 \ 0 \ 24) * K \bmod 26$

Contd...

$$\mathbf{K}^{-1} = \begin{pmatrix} 4 & 9 & 15 \\ 15 & 17 & 6 \\ 24 & 0 & 17 \end{pmatrix}$$

$$\mathbf{C} = \mathbf{E}(\mathbf{K}, \mathbf{P}) = \mathbf{PK} \bmod 26$$

$$\mathbf{P} = \mathbf{D}(\mathbf{K}, \mathbf{C}) = \mathbf{CK}^{-1} \bmod 26 = \mathbf{PKK}^{-1} = \mathbf{P}$$

Hill cipher is strong against a ciphertext-only attack, it is easily broken with a known plaintext attack.

Polyalphabetic Ciphers

- Polyalphabetic substitution cipher
 - Improves on the simple monoalphabetic technique by using different monoalphabetic substitutions as one proceeds through the plaintext message

All these techniques have the following features in common:

- A set of related monoalphabetic substitution rules is used
- A key determines which particular rule is chosen for a given transformation

Vigenère Cipher

- Best known and one of the simplest polyalphabetic substitution ciphers
- In this scheme the set of related monoalphabetic substitution rules consists of the 26 Caesar ciphers with shifts of 0 through 25
- Each cipher is denoted by a key letter which is the ciphertext letter that substitutes for the plaintext letter a

Example of Vigenère Cipher

- To encrypt a message, a key is needed that is as long as the message
- Usually, the key is a repeating keyword
- For example, if the keyword is *deceptive*, the message “we are discovered save yourself” is encrypted as:

key: deceptivedeceptivedeceptive

plaintext: wearediscoveredsaveyourself

ciphertext: ZICVTWQNGRZGVTWAVZHCQYGLMGJ

Contd...

$$\begin{aligned} C &= C_0, C_1, C_2, \dots, C_{n-1} = E(K, P) = E[(k_0, k_1, k_2, \dots, k_{m-1}), (p_0, p_1, p_2, \dots, p_{n-1})] \\ &= (p_0 + k_0) \bmod 26, (p_1 + k_1) \bmod 26, \dots, (p_{m-1} + k_{m-1}) \bmod 26, \\ &\quad (p_m + k_0) \bmod 26, (p_{m+1} + k_1) \bmod 26, \dots, (p_{2m-1} + k_{m-1}) \bmod 26, \dots \end{aligned}$$

$$C_i = (p_i + k_{i \bmod m}) \bmod 26$$

$$p_i = (C_i - k_{i \bmod m}) \bmod 26$$

key:	<i>deceptivedeceptivedeceptive</i>
plaintext:	wearediscoveredsaveyourself
ciphertext:	ZICVTWQNGRZGVTWAVZHCQYGLMGJ

Contd...

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
A	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
B	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	A
C	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	A	B
D	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	A	B	C
E	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	A	B	C	D
F	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	A	B	C	D	E
G	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	A	B	C	D	E	F
H	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	A	B	C	D	E	F	G
I	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	A	B	C	D	E	F	G	H
J	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	A	B	C	D	E	F	G	H	I
K	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	A	B	C	D	E	F	G	H	I	J
L	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	A	B	C	D	E	F	G	H	I	J	K
M	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	A	B	C	D	E	F	G	H	I	J	K	L
N	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	A	B	C	D	E	F	G	H	I	J	K	L	M
O	O	P	Q	R	S	T	U	V	W	X	Y	Z	A	B	C	D	E	F	G	H	I	J	K	L	M	N
P	P	Q	R	S	T	U	V	W	X	Y	Z	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
Q	Q	R	S	T	U	V	W	X	Y	Z	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P
R	R	S	T	U	V	W	X	Y	Z	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q
S	S	T	U	V	W	X	Y	Z	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R
T	T	U	V	W	X	Y	Z	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S
U	U	V	W	X	Y	Z	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T
V	V	W	X	Y	Z	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U
W	W	X	Y	Z	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V
X	X	Y	Z	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W
Y	Y	Z	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X
Z	Z	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y

- To decrypt, pick a letter in the ciphertext and its corresponding letter in the keyword, use the keyword letter to find the corresponding row, and the letter heading of the column that contains the ciphertext letter is the needed plaintext letter.

Vigenère Autokey System

- A keyword is concatenated with the plaintext itself to provide a running key

- Example:

key: deceptivewearediscoveredsav

plaintext: wearediscoveredsaveyourself

ciphertext: ZICVTWQNGKZEIIGASXSTSLVWLA

- Even this scheme is vulnerable to cryptanalysis
 - Because the key and the plaintext share the same frequency distribution of letters, a statistical technique can be applied

Vernam Cipher




Figure 2.7 Vernam Cipher

$$c_i = p_i \oplus k_i$$

where

p_i = i th binary digit of plaintext

k_i = i th binary digit of key

c_i = i th binary digit of ciphertext

\oplus = exclusive-or (XOR) operation

$$p_i = c_i \oplus k_i$$

One-Time Pad

- Improvement to Vernam cipher proposed by an Army Signal Corp officer, Joseph Mauborgne
- Use a random key that is as long as the message so that the key need not be repeated
- Key is used to encrypt and decrypt a single message and then is discarded
- Each new message requires a new key of the same length as the new message
- Scheme is unbreakable
 - Produces random output that bears no statistical relationship to the plaintext
 - Because the ciphertext contains no information whatsoever about the plaintext, there is simply no way to break the code



- 27 characters including space.

- Cipher text = `ANKYODKYUREPFJBYOJDSPLREYIUNOFDOIUERFPLUYTS`

```
ciphertext: ANKYODKYUREPFJBYOJDSPLREYIUNOFDOIUERFPLUYTS
key:        pxlmvmsydozufyrvzwc tnlebnecvgdupahfzzlmnyih
plaintext:  mr mustard with the candlestick in the hall
```

```
ciphertext: ANKYODKYUREPFJBYOJDSPLREYIUNOFDOIUERFPLUYTS
key:        pftgpmiydgaxgoufhkl11lmhsqdgogtewbqfgyovuhwt
plaintext:  miss scarlet with the knife in the library
```


Difficulties

- The one-time pad offers complete security but, in practice, has two fundamental difficulties:
 - There is the practical problem of making large quantities of random keys
 - Any heavily used system might require millions of random characters on a regular basis
 - Mammoth key distribution problem
 - For every message to be sent, a key of equal length is needed by both sender and receiver
- Because of these difficulties, the one-time pad is of limited utility
 - Useful primarily for low-bandwidth channels requiring very high security
- The one-time pad is the only cryptosystem that exhibits *perfect secrecy* (see Appendix F)

Rail Fence Cipher


- Simplest transposition cipher
- Plaintext is written down as a sequence of diagonals and then read off as a sequence of rows
- To encipher the message “meet me after the toga party” with a rail fence of depth 2, we would write:

m e m a t r h t g p r y

e t e f e t e o a a t

Encrypted message is:

MEMATRHTGPRYETEFETEOAAT



Row Transposition Cipher

- Is a more complex transposition
- Write the message in a rectangle, row by row, and read the message off, column by column, but permute the order of the columns
 - The order of the columns then becomes the key to the algorithm

Key: 4 3 1 2 5 6 7

Plaintext: a t t a c k p

o s t p o n e

d u n t i l t

w o a m x y z

Ciphertext: TTNAAPTMTSUOAODWCOIXKNLYPETZ

Contd...

- t t n a 4,3,1,2,5,6,7
- a p t m
- T s u o
- A o d w
- C o i x
- K n l y
- P e t z

Rotor Machines




Figure 2.8 Three-Rotor Machine With Wiring Represented by Numbered Contacts

Steganography

3rd March

Dear George,

Greetings to all at Oxford. Many thanks for your letter and for the Summer examination package. All Entry Forms and Fees Forms should be ready for final despatch to the Syndicate by Friday 20th or at the very latest, I'm told, by the 21st. Admin has improved here, though there's room for improvement still; just give us all two or three more years and we'll really show you! Please don't let those wretched 16+ proposals destroy your basic O and A pattern. Certainly this sort of change, if implemented immediately, would bring chaos.

Sincerely yours,

Figure 2.9 A Puzzle for Inspector Morse
(from *The Silent World of Nicholas Quinn*, by Colin Dexter)

Other Steganography Techniques



- Character marking
 - Selected letters of printed or typewritten text are over-written in pencil
 - The marks are ordinarily not visible unless the paper is held at an angle to bright light
- Invisible ink
 - A number of substances can be used for writing but leave no visible trace until heat or some chemical is applied to the paper
- Pin punctures
 - Small pin punctures on selected letters are ordinarily not visible unless the paper is held up in front of a light
- Typewriter correction ribbon
 - Used between lines typed with a black ribbon, the results of typing with the correction tape are visible only under a strong light

Summary

- Symmetric Cipher Model
 - Cryptography
 - Cryptanalysis and Brute-Force Attack
- Transposition techniques
- Rotor machines



- Substitution techniques
 - Caesar cipher
 - Monoalphabetic ciphers
 - Playfair cipher
 - Hill cipher
 - Polyalphabetic ciphers
 - One-time pad
- Steganography