

Key Concepts & Measures in SNA

Global Structure of Networks



- A Social network can be represented as a graph $G = (V, E)$
- V - finite set of vertices
- E - finite set of edges such that $E \subseteq V \times V$

$$M := (m_{i,j})_{n \times n} \text{ where } n = |V|, m_{i,j} = \begin{cases} 1 & |(v_i, v_j) \in E \\ 0 & \text{otherwise} \end{cases}$$

- For weighted (valued) graphs, its characteristic matrix is defined as

$$m_{i,j} = \begin{cases} w(e) & |(v_i, v_j) \in E \\ 0 & \text{otherwise} \end{cases}$$


Social Network represented as Graph



	v_1	v_2	v_3	v_4
v_1	0	1	1	0
v_2	1	0	1	0
v_3	1	1	0	1
v_4	0	0	1	0

Contd...

- Major breakthrough in SNA - American psychologist Stanley Milgram proposed the structure of social networks
- Milgram observation – “no matter where we live, the world around us seems to be *small*”
- He showed that on average Americans are no more than six steps apart from each other (*six degrees of separation*)




Contd...

- *characteristic path length* - size of the average shortest path of the network (*called by milgram*)
- Geodesic (shortest path between two vertices v_s and v_t) - *a path that begins at the vertex v_s and ends in the vertex v_t and contains the least possible number of vertices*
- Longest geodesic in the graph is called the diameter of the graph (maximum number of steps required between any 2 nodes)
- average shortest path - average of the length of the geodesics between all pairs of vertices in the graph
- Impossible for unconnected graph

Contd...

- Certain structures does not have small world property (2D lattice model) [characteristic path length of network size 'n' - $\frac{2}{3} * \sqrt{n}$]



The 2D lattice model of networks (left). By connecting the nodes on the opposite borders of the lattice we get a toroidal lattice (right).


Clustering

- Friends are likely to know each other as well and tend to socialize in groups
- Other than that, other friends know each other because we introduced them to each other
- Clustering for a single vertex =

Actual number of edges between neighbors of a vertex

Possible number of possible edges between neighbors

(no. of triangles A is involved wrt ones it could be involved in)




- **averaging clustering over all vertices -> clustering coefficient**
- *clustering coefficient = 0 (for a tree as there are no triads)*
- *It would never be the case that our friends are friends with each other*

Random Graph Model

- Proposed by Hungarian mathematicians Erdős and Rényi
- A random graph can be generated by taking a set of vertices with no edges connecting them
- Subsequently, edges are added by picking pairs of nodes with equal probability
- This way we create a graph where each pair of vertices will be connected with an equal probability
- higher probability—results in random graphs with small characteristic path length and most likely exhibit some **clustering**


Random Graphs



$p = 0.1$



$p = 0.25$



$p = 0.5$

Contd...

Random Graphs



What does this mean?

BIG “IF”!!!

- If connections between people can be modeled as a random graph, then...
 - Because the average person easily knows more than one person ($k \gg 1$),
 - We live in a “small world” where within a few links, we are connected to anyone in the world.
 - Erdős and Renyi computed average path length between connected nodes to be:

$$\frac{\ln N}{\ln k}$$

Contd...

- ER random graphs are generative models – center point interest in knowing the process of growing complex networks in physics
- Researchers study the emergence of complex global structures from systems that are defined solely through elementary interactions

Alpha Model Networks



- In 1999, mathematicians Steven Strogatz and Duncan Watts presented alpha-model of networks
- Number of mutual friends shared by any two nodes determines the likelihood of a new tie
- Parameter alpha (number of friends) influence on the probability of a tie
- Alpha model generates graphs with small path lengths and relative large clustering coefficients

Beta Network Model

- alpha-model later simplified by authors so-called beta-model
- It achieves same results through less intuitive process
- It is Generative, one-dimensional toroidal lattice
- Every node connected to its neighbors and also its neighbors neighbors
- A random edge rewired keeping one end of edge fixed and other end rewired to another randomly selected node
- This process repeated until every link rewired with a probability of beta
- choosing beta appropriately, it can generate small path lengths and relatively large clustering coefficients network

Contd...


Rewired



Scale free Networks

- alpha and beta models fail to recreate scale-free characteristic of degree distribution
- Degree distribution of networks - diagram showing how many nodes in the network have a certain number of neighbors (degrees)
- In toroidal lattice, all nodes have an equal number of neighbors
- In alpha and beta models and random graphs shows normal distribution
- However, in real social networks, the higher the degree least likely to occur

Contd...



The degree distribution of a real world scale-free network (upper part) and the degree distribution of a random network of the same size (lower part)

Contd...

- steepness of the distribution shows - majority of nodes have much fewer connections except few *hubs of the network*
- *Barabasi discovered that exact correlation is a power law - i.e. $p(d) = d^{-k}$, where $k > 0$ is a parameter of the distribution*
- He also gave a generative model to reproduce it

Contd...

- Barabási started with a single node and add nodes in every step
- when adding new nodes it is linked to the node to an already existing node
- probability of linking determined by how many edges the node already has (the rich get richer)
- a node that has already attracted more edges will have larger probability to attract connections in subsequent rounds
- Barabási showed that the resulting networks - have short characteristic path lengths, a large clustering coefficient and a degree distribution that approaches a power law