Mapping Data Warehouse to Multiprocessor Architecture



Relational Database Technology for Data Warehouse

- The data warehouse environment is pursuing two goals:
 - Speed-up-ability to execute the same request on the any amount of data in less time
 - Scale-up ability to obtain the same performance even if database size increases.
- Parallel hardware architectures are based on Multiprocessor architectures designed as a shared memory model (SMPs) shared-disk model, or a distributed-memory model (MPPs) and clusters of uniprocessors



Types of Parallelism

- Interquery parallelism: Different threads (or process) handle multiple requests at the same time. Successfully implemented on the SMP systems.
- Intraquery parallelism Decomposes the serial SQL query into lower-level operations such as scan, join, sort, and aggregation operations and they are executed concurrently in parallel.
- Intraquery parallelism can be done in either of two ways:



Types of Parallelism

- Horizontal parallelism: Database is partitioned across multiple disks, and parallel processing occurs within a specific task (table scan) that is performed concurrently on different sets of data.
- Vertical parallelism All complex query operations are executed in parallel in a pipeline fashion.
 - An output from on tasks (e.g., scan) becomes are input into another task (e.g., join) as soon as records become available



Types of DBMS parallelism

Response Time Serial **RDBMS** Vertical Parallelism (Query Decomposition) **Horizontal Parallelism Parallel RDBMS** (Data Partitioning) Case 3 Case 2 Case 1 Case 4

Data Partitioning

- It is a key requirement for effective parallel execution of database operations.
- Spreads data from database tables across multiple disks so that
 I/O operations such as read and write can be performed in parallel.
- Two types random and intelligent partitioning.
- Random partitioning: It includes random data striping across multiple disks on a single server.
- Another option for random partitioning is round-robin
 partitioning in which each new record is placed on the next disk
 assigned to the database.
- The effectiveness of round-robin partitioning is reduced depending upon the data distribution and aueru selectivitu

Data Partitioning – Intelligent partitioning

DBMS knows where a specific record is located and does not waste time searching for it across all disks.

- Hash partitioning: A hash algorithm is used to calculate the partition number (hash value) based on the value of the portioning key for each row.
- Key range partitioning: Rows are placed and located in the partitions according to the value of the partitioning key (all rows with the key value from A to K are in partition 1, L to T are in partition 2 etc.).



Data Partitioning

- Schema partitioning: An entire table is placed on one disk, another table is placed on a different disk, etc. This is useful for small reference tables that are more effectively used when replicated in each partition rather than spread across partitions.
- *User-defined partitioning:* This is a partitioning method that allows a table to be partitioned on the basis of a user-defined expression.



Database Architectures for Parallel Processing

- 1. Shared-memory architecture- SMP (Symmetric Multiprocessors)
- 2. Shared-disk architecture
- 3. Shared-nothing architecture
- 4. Combined architecture



Shared-memory architecture - SMP (Symmetric Multiprocessors)


- Shared memory or Shared everything style is the traditional approach to implementing an RDBMS or SMP hardware.
- A single RDBMS server can potentially utilize all processors, access all memory and access the entire database thus providing the user with a consistent single system image.
- Multiple database components executing SQL statements communicate with each other by exchanging messages and data via the shared memory.
- Scalability can be achieved through process-based multitasking or threadbased multitasking.

Shared-memory architecture - SMP (Symmetric Multiprocessors)

- Advantage: Threads provide better resource utilization and faster context switching.
- Disadvantage: Threads tightly coupled with OS and may limit RDBMS portability



Shared-memory architecture - SMP (Symmetric Multiprocessors)





Shared-disk architecture

- Implements the concept of shared ownership of the entire database between RDBMS servers, each of which is running on a node of the distributed memory system.
- Each RDBMS server can read, write, update, and delete records from the same shared database.
- Implemented by using distributed lock manager (DLM).
- Disadvantages: "Pinging problem": All nodes are reading and updating the same data, the RDBMS and its DLM will have to spend a lot of resources synchronizing multiple buffer pools.
- It may have to handle significant message traffic in a highly utilized RDBMS environment.


Shared-disk architecture

Advantages:

- It reduces performance bottlenecks resulting from data skew and can significantly increase system availability.
- It eliminates the memory access bottleneck typical of large SMP systems, and helps reduce DBMS dependency on data partitioning.



Shared-disk architecture






Shared-nothing architecture

- Data is partitioned across all disks and the DBMS is partitioned across multiple coservers which resides in individual nodes of the parallel system.
- Each processor has its own memory and disk, and communicates with other processors by exchanging messages and data over the interconnection network.
- Offer near-linear scalability.

Disadvantages:

- It is most difficult to implement.
- It requires a new programming paradigm, new OS, new compilers and new programming languages

Shared-nothing architecture



Combined architecture

Combined hardware architecture could be a cluster of SMP nodes.

Combined parallel DBMS architecture should support intersever parallelism of distributed memory MPPs and intraserver parallelism of SMP nodes.



Parallel DBMS Vendors

- Oracle
- Informix
- IBM
- Sybase
- Microsoft



Oracle

Oracle supports parallel database processing with its add-on oracle parallel server option(OPS) and parallel query option(PQO).

Architecture

- Virtual shared-disc capability
- Process-based approach
- · Facilitate the inter query parallelism
- PQO supports parallel operations such as index build, database load, backup, and recovery

Data partitioning

- It supports random striping of data across multiple disks.
- · Oracle supports dynamic data repartitioning

Oracle

Parallel operations

- · Generates a parallel plan
- The oracle PQO query coordinator breaks the query into sub queries
- Parallelize the creation of indexes, database load, backup, and recovery
- PQO supports both horizontal and vertical parallelism



Informix

Architecture

- Support shared-memory, shared-disk, and shared-nothing models.
- It is thread based architecture.

Data partitioning

- Round-robin, schema, charts, key range, and user-defined partitioning methods.
- · Both data and index can be partitioned

Parallel Operations

· Executes queries in parallel.



Client/Server database product-DB2 parallel Edition

Architecture

- DB2 PE is a shared-nothing architecture in which all data is partitioned across processor nodes.
- Each node is aware of the other nodes and how the data is partitioned

Data partitioning

- · Allow a table to span multiple nodes.
- The master system catalog for each database is stored on one node and cached on every other node.

Parallel operations

· All database operations are fully parallelized

Sybase

Sybase has implemented its parallel DBMS functionality in a parallel product called DYBASE MPP.

Architecture

- It is a shared-nothing systems that partitions data across multiple SQL servers and supports both function shipping and data repartitions.
- Open server application that operates on top of existing SQL servers.
- All the knowledge about the environment, data partitions, and parallel query execution is maintained by SYBASE MPP software.



Sybase

SYBASE MPP consists of specialized servers.

- Data server, the smaller executable unit of parallelism that consists of SQL server, split server (performs joins across nodes), and control server (coordination of execution and communication)
- DBA server handles optimization, DDL statements, security and global systems catalog.
- Administrative server, a graphical user interface for managing SYBASE MPP.

Data partitioning.

Supports hash, key range, and schema partitioning, indexes partitioning.

Parallel operations: All SQL statements and utilities in parallel across SQL servers

Microsoft

SQL server architecture is shared-everything design optimized for SMP systems. SQL server is tightly integrated with the NT operating systems threads

