FastAPI Conf, Amsterdam / October 2026

Constrained Optimism

Samuel Colvin · Pydantic

whoami - Samuel Colvin

- Creator of **Pydantic** (the validation layer under FastAPI), Founder & CEO of **Pydantic Labs**

Pydantic Today

Open source

FREE – WHAT YOU BUILD WITH

Pydantic Validation
Contracts for data, 1 billion downloads a month

Pydantic AI
Production grade agent framework

Pydantic Monty
Python sandbox for code written by agents, starts in 1ms

Pydantic Logfire

COMMERCIAL – WHERE YOU RUN IT


AI Observability
Traces, evals and prompt management for agents

Infra Observability
Logs, metrics and traces for the whole application

AI Gateway
One endpoint, every model

Sandboxes soon
Hosted code execution, built on Monty

What Pydantic does, in five steps



That's the day job. This talk is about something else.

How I think about building software now.

It's a theory. I'm not certain it's right today, let alone tomorrow.

Software development is a constrained, non-convex optimization problem.

What does that mean?

> *Software development is a constrained, non-convex optimization problem.*

Optimization

There are metrics and you want them better: speed, compatibility, memory, signups.

The agent is the optimizer. Stochastic, tireless, not picky about how.

Constrained

Some things must stay true whatever the metric says: the spec, security, no `unsafe`.

Gates, not weights. The optimizer never gets to trade them.


Non-convex

There is no single downhill path. Plenty of places "work" but aren't good, and the optimizer will stop in one.

Someone has to poke it.


My job moved from finding **x** to choosing **f** and **g**. Review is one of the **g**'s.

Visual slop metaphor



Yes, the bowl is a convex *function*. No, I don't know why mathematicians called it that either. The dips make it non-convex, and the dips are where the agent stops. The hatched areas are the constraints: the ball never goes in, however good the slope looks.

But we never reach perfect, the descent is indefinite



So what does the developer actually do?

Set up the problem for the agent to solve.

The challenge

1

Pick one or two metrics

What gets better. If there seem to be ten, combine them into one composite score.

`p50 latency` `CPython compat %` `bytes allocated`

2

Define hard constraints

What must never break. Deterministic where you can, AI review where you can't.

`cargo test` `pyright --strict` `clippy -D warnings` `review agent`

3

Close the feedback loop

The agent reads the result itself: no human copying errors between windows.

`gh run view` `compiler errors` `CodSpeed MCP` `Logfire MCP`

jiter

Fast JSON parser in Rust, used inside Pydantic. **4.1x faster than `serde_json`.**

Optimize

Parse speed

Constraints

Correctly parse JSON

Errors match `serde_json`

Feature set, e.g. float, decimal or str output for floats


Memory limits

No extra unsafe code

I restarted development by writing the test corpus, not the code.

jiter: how the agent gets feedback

Metrics



CodSpeed runs on every PR. MCP server for CodSpeed gives the agent access to the context. Don't be a meat proxy.

Constraints

- **Clippy**, pedantic group denied, also on wasm with no SIMD
- **Unit tests** under `cargo careful`, which catches undefined behaviour
- **Corpus tests**: ~3,300 documents, same answer as serde_json
- **Fuzzing** against serde_json, five minutes per target
- **Python tests** on every supported version
- **Builds** on the minimum Rust version and on the latest dependencies

Monty

A Python interpreter in Rust for running the code agents write. **Starts in under 1 ms.**

Optimize

CPython compatibility

Startup and runtime speed

Memory

Constraints

No way out of the sandbox

Resource limits always hold

No `unsafe`

Monty: how the agent gets feedback

Metrics

```
x = {}
x.get(1, 2, 3)
# Raise=TypeError('get expected at most 2 arguments, got 3')
```


- **~700 Python scripts** run with Monty and CPython, guaranteeing exactly matching behaviour
- **CodSpeed** on every PR

Constraints

- **Masses of unit tests**
- **Bounty program**: hackmonty.com, $20k reward
- `unsafe_code = "deny"`
- **miri**
- **Reference-counting build**
- **3 review agents**: Cubic, Macroscope, Veria Labs

Logfire

AI + Infra observability, evals, AI Gateway



Logfire

AI + Infra observability, evals, AI Gateway

Optimize

Business: a Pareto frontier across signup success, engagement, new feature usage and data sent

Engineering: query performance, ingest latency

Constraints

Tenant isolation

Alerts must fire

Ingest uptime


Logfire Example

Our MCP server lets coding agents query Logfire directly with SQL and do (almost) **everything**. This lets our customers use Logfire as a metric or a constraint.

The constraints are obvious (security, isolation). The metrics are harder to define:

- Speed to achieve a goal (we can't measure token count)
- Valid SQL %

We get feedback by including an `intent` field in MCP tools.



What this means for your FastAPI service

The objective

Whatever your product metric is: p99 latency, conversion, cost per request. **One** of them; threshold the rest.

Write it down as one sentence. If you can't, the agent is optimizing something you didn't choose.

The constraints

- **Types**: Pydantic models and the OpenAPI schema, the one constraint that holds everywhere, not just where you tested
- **Tests**: the behaviour your clients depend on
- **A latency budget**: a gate in CI, not a hope
- **Lint and formatting**: cheap, deterministic, no judgment needed

Tomorrow: audit your "requirements". Which are enforced by something a machine runs, and which are merely hoped for?

Where the metaphor breaks

- **Constraints are sampled, not proven.** CI checks points, not the region. Types and proofs are the exception, and the main reason to stay strict about typing.
- **The optimizer can read the constraints.** A solver can't lobby you to relax a bound; an agent will edit the test. Fences need tamper-protection: branch protection, "never xfail", a human approval, credentials it doesn't have.
- **The real objective is a proxy.** Signups, revenue, "ease of use" aren't measurable until deployed. Goodhart's law applies to you, not just the model.

Why I'm optimistic

Defining and maintaining the fences on an endless slope is a harder, more complex and more valuable job than typing out the code ever was.

Not a software factory. I still write code, and my review is often the most important constraint. But the person who formulates the problem is worth more today than the person who wrote the code was a year ago.

Thank you



pydantic.dev/contact

`@samuelcolvin` · `@pydantic`