

Data Drift:

How to Uncover Changes in Your ML Model's Input Data

Emeli Dral
CTO Evidently AI

About me




- Co-founder & CTO Evidently AI, open-source ML monitoring
- Ex Chief Data Scientist at Yandex Data Factory and Mechanica AI
- Co-founder of Data Mining in Action, largest offline data science course in Russia
- Co-author of two Coursera specializations in data science with > 100K students
- Lecturer at Harbour.Space University, GSOM MBA

50+ Industrial applications of machine learning




ML models degrade and need monitoring


Model accuracy



Model accuracy



Standard ML monitoring: measuring the performance



Model quality or error:
precision, recall, log-loss, MAE, etc...




Business or product metrics:
purchases, clicks, views, etc...

Standard ML monitoring is not always enough!



Feedback or ground truth is delayed



Many segments with different quality




The target function is volatile (quality varies)



Past performance does not guarantee future results

How to tackle it? Early monitoring

- Data quality: any issues with quality and integrity
- Data drift: changes in the input feature distributions
- Output drift: change in the models predictions




Data Quality: with no expectations

Missing cells	10 (6%)
Constant features	12 (7,5%)
Empty features	1 (0,6%)
Almost constant	12 (7,5%)
Almost empty	0 (0%)

Even if we do not have reference data:

- missing values (or almost missing!)
- constant features (or almost constant!)
- correlations (high correlation between feature and target, feature pairs, etc.)
- range violations (based on the feature context, e.g. negative age)

Data Quality: if we have expectations



Based on training data or past batch:

- expected data quality (e.g. 80% non-constant)
- data distribution type (e.g. normality)
- descriptive statistics: averages, median, quantiles, min-max for individual features
 - point estimation as a simple solution
 - statistical test to get confidence interval

Example from the Evidently OSS library

39
Tests

30
Success

0
Warning

9
Fail

0
Error

By test type

Number of Rows

HIDE

❗ Number of Rows

The number of rows is 34687. The test threshold is eq=1.42e+04 ± 1.42e+03.

Number of Columns

SHOW

Column Types

SHOW

The Share of Missing Values in a Column

SHOW

Share of Out-of-Range Values


SHOW

Share of Out-of-List Values


SHOW

Mean Value Stability

SHOW




Test against expectations



Explore changes

Data Drift: compare feature distributions




Data can drift without performance decay. But if the **key features** change, this can be an issue!

It is important to define:

- Optimal statistical tests, distance metrics or rules
- Reasonable confidence for statistical tests
- Alert conditions based on feature importance and the share of the drifting features

Prediction Drift: compare output distributions

Target Drift: detected, p_value=0.002266



How do we define that data has drifted?



Drift detection: parametric tests

EXAMPLES OF PARAMETRIC TESTS

One-sample:

- Z-test & T-test for mean ($\mu = \mu_0$)
- One proportion Z-test ($p = p_0$)

Two-samples:

- Two-proportions Z-test
- Two-samples Z-test T-test for means (normally distributed samples)

SOME CONSIDERATIONS:

- Require different tests for different features
- More sensitive to drift than non-parametric tests
- Hard to fine-tune if you have a lot of features

Makes sense if you have a small number of interpretable features and critical use cases (e.g., in healthcare).

Drift detection: non-parametric tests

EXAMPLES OF NON-PARAMETRIC TESTS

- Kolmogorov–Smirnov test:
 - the equality of distributions for continuous data
- K-sample Anderson–Darling tests:
 - can several collections of observations be modelled as coming from a single population?
- Pearson's chi-squared test:
 - the equality of distributions for categorical data
- Fisher's/Barnard's exact test for small samples

SOME CONSIDERATIONS:

- Can use heuristics to choose tests based on the feature type, e.g. numerical, categorical, binary
- Less sensitive to drift than parametric tests

Drift detection: distance-based approaches


EXAMPLES OF METHODS

- Wasserstein distance:
 - distance between probability distributions; shows how much effort it takes to turn one distribution into another
- Jensen-Shannon divergence:
 - distance between probability distributions; based on Kullback-Leibler divergence, but it is always finite and symmetric
- Population Stability Index (PSI):
 - reflects the relative size of a drift for numand cat features
- Domain classification:
 - applicable for different data types, including unstructured and multinomial data; ML-model based

SOME CONSIDERATIONS:

- Roughly any metric that shows difference/similarity between distributions can be used as a drift detection method
- Often it makes more sense to pick an interpretable metric rather than a statistical test

Example from the Evidently OSS library



For small datasets (<1000):

- Numerical features: [two-sample Kolmogorov-Smirnov test](#).
- Categorical features, [chi-squared test](#).
- Binary categorical features: the proportion difference test for independent samples based on Z-score.

Example from the Evidently OSS library

CURRENT: CHARACTERISTIC WORDS		REFERENCE: CHARACTERISTIC WORDS
disappointed	VS	feminine
money		dressed
poorly		elegant
returning		hi
unraveled		little
cheap		issues
completely		pleated

For text data:

- Content drift: domain classifier for text features
- Text descriptors drift: distribution shift in text characteristics


Drift detection: large datasets

If we have a lot of objects and/or a lot features, tests can be “too sensitive”.

Practical solutions:

- Sampling (“pick” representative observations)
- Bucketing (“aggregate” all observations)

NOTE: statistics was made to work with samples!




Drift detection: non-batch models

Descriptive statistics and quality:

- calculate metrics continuously or even incrementally

Statistical tests on a continuous data stream:

- pick a window function (e.g. moving windows with or without moving reference)



How to choose metrics and tests?

Option 1: go with defaults

- Pick a reasonable statistical test as a heuristic (e.g. K-S for numerical features)
- Start monitoring
- Adjust based on false alarms and your sensitivity

Option 2: experiment

Use past data to pick the most suitable test and drift conditions

Example of the experiment design:

- Pick a stable period when no drift
- Define candidate statistical tests
- Apply all tests and pick the one with the highest sensitivity (lowest p-value) that does not detect drift.
- If you have known past drift periods, make sure the test catches them.
- You can experiment with tests, confidence threshold, window size, sampling and bucketing parameters


Nuanced interpretations of drift

Data Drift: **detected**. Prediction drift: **not detected**.



Positive interpretation:

- Important features did not change.
- Model is robust enough to survive drift.
- No need to intervene.



Negative scenario:

- Important features changed.
- Model should have reacted, but did not. It does not extrapolate well.
- We need to intervene.

Nuanced interpretations of drift

Data Drift: **detected**. Prediction drift: **detected**.



Positive interpretation:

- Important features changed.
- Model reacts and extrapolates well (e.g. prices lower > higher sales)
- No need to intervene.



Negative scenario:

- Important features changed.
- Model behavior is unreasonable.
- We need to intervene.

Drift Detected, what is next?



Data Quality:

- run before acting on the model predictions
- solve data quality issues if detected!

Prediction and Data Drift:

- interpret it: sometimes drift is OK if the real world changed!
- (label new data), and retrain the model
- calibrate or rebuild the model
- switch to an alternative process (fallback, rules, manual)
- change business logic or model post-processing (higher decision threshold, exclude certain segments, etc.)

Questions?

Emeli Dral

CTO Evidently AI

emeli@evidentlyai.com

Evidently on GitHub:

<https://github.com/evidentlyai/evidently>