

# activAnalyzer: An R Shiny app to analyse ActiGraph accelerometer data and to implement the use of the PROactive Physical Activity in COPD instruments

05 July 2022

## Statement of need

ActiGraph devices (ActiGraph LLC, Pensacola, FL) have been the most used accelerometers in scientific literature to measure physical activity (Bassett et al. 2015; Migueles et al. 2017). These devices, along with their software companion ActiLife (ActiGraph LLC, Pensacola, FL), allow to get movement data expressed in either *activity counts* or *G-force* units. Activity counts represent the amount of acceleration produced over a given epoch of time at the wearing position of the device. While analytic methods based on G-force data are developing, using activity counts to assess physical activity and sedentary behaviours remains common (Migueles et al. 2017). Interestingly, ActiGraph devices have been validated to implement the framework related to the use of the PROactive Physical Activity in COPD (chronic obstructive pulmonary disease) instruments (Dobbels et al. 2014; Gimeno-Santos et al. 2015; Garcia-Aymerich et al. 2021). Such a framework requires combining scores relating to answers of questionnaire items and scores relating to accelerometer metrics obtained from a week of measurement.

Due to the large size of data files to analyse when using accelerometry and due to the relative complexity of the implementation of some algorithms, a simple spreadsheet does not appear to be a feasible tool to complete all the accelerometer data analysis workflow from the same place. The ‘Full’ version of ActiLife software allows completing all the general steps of the data analysis workflow with activity counts but the cost of this ActiLife version may prevent teaching a wide audience to implement such a workflow and may also prevent working with large teams on recorded data (‘Lite’ versions of ActiLife software, that are at a lower cost than ‘Full’ versions, allow device initialisation and data downloading only). Moreover, there is no solution in ActiLife software to fully implement the PROactive framework for COPD patients described above.

Other ways than ActiLife software to analyse activity counts include using programming languages. R (R Core Team 2022) and Python (Python Software Foundation 2022) have been programming languages commonly used by scientists to build tools aiming at fostering physical activity data analysis. In R, the ‘accelerometry’ and ‘nhanesaccel’ packages by Van Domelen and Pittard (2014), the ‘actigraph.sleep’ package by Petkova (2021), and the ‘pawacc’ package by Geraci (2017), provide several functions to perform analyses of interest with activity counts. In Python, the ‘pyActigraphy’ library by Hammad and Reyt (2020) also allows, among various other features, to handle ActiGraph activity counts. While useful for research settings, these resources may be of a little interest for other settings where people have no programming skills, because they do not propose a GUI (graphical user interface) to help people who do not code and who have no time to learn this skill. Beyond the lack of a free and simple interface to analyse ActiGraph activity counts data, there is, to our knowledge, no app that allows an easy implementation of the PROactive framework with COPD patients that would be based on an analysis of ActiGraph activity counts. This is why we have developed the ‘activAnalyzer’ app. For now, a first main interest of this app is to allow teaching large groups of students or professionals, who have no programming skills, to analyse activity counts for assessing physical behaviour. A second main interest is to allow an easy implementation of the PROactive framework with COPD patients when working with an ActiGraph accelerometer, this by clinicians, healthcare providers and/or researchers, either in clinical routine or in research setting.

## Functionality and purpose of the software

‘activAnalyzer’ is an app built as a package using R programming language. The app can be used in three different ways as explained elsewhere (<https://pydemull.github.io/activAnalyzer/>), including (i) a standalone desktop application for Windows machines only thanks to the DesktopDeployR framework developed by Lee Pang; (ii) using R and RStudio software along with the CRAN version of the ‘activAnalyzer’ package (v1.0.4) or its development version from GitHub; (iii) using a shinyapps.io platform. If used with R and RStudio, the app will require the installation of the TinyTeX distribution to generate .pdf reports, as explained on the app website.

When the user opens the app, they has to deal with four ordered sections. The first section allows the user to complete information related to the measurement setup (patient’s characteristics, device position, etc.). In the second section, the user must upload an .agd data file (.agd’ being the extension of the initial file generated by ActiLife software when the user wants to work with activity counts data). Then, the user has to configure the app to detect nonwear time. The results from this first analysis can be visualised by the user, as shown in Figure 1.




Figure 1: Example of analysis for nonwear time detection.

In a third section, the user has to select an equation to estimate energy expenditure and values to define cut-points in counts/min. Cut-points are the values below or above which one can be classified as being in sedentary behaviour or in light, moderate, or vigorous physical activity. Once the user has completed the configuration for intensity analysis, they can run analysis. Then, the user can see a figure showing time spent in the different categories of activity intensity (Figure 2), a table showing the results of the measurement for each day (Figure 3), and tables with daily means and daily medians, respectively, showing metrics summarised from valid days (e.g., Figure 4 for means).

Once analysis is finished, the user can generate a report of the measurement, download .csv files containing data produced by the app, or go to the questionnaires related to the PROactive framework. This last part consists of completing the chosen questionnaire, and downloading a report once analysis is completed.




Figure 2: Example of analysis for intensity of physical behaviour.

|   | date       | wear_time | total_counts_axis1 | total_counts_vm | axis1_per_min | vm_per_min | total_steps | total_kcal |
|---|------------|-----------|--------------------|-----------------|---------------|------------|-------------|------------|
| 1 | 2021-04-07 | 720       | 359125             | 721645.8        | 498.78        | 1002.29    | 14056       | 2090.04    |
| 2 | 2021-04-08 | 811       | 495257             | 946481.6        | 610.67        | 1167.06    | 14595       | 2273.94    |
| 3 | 2021-04-09 | 718       | 1222315            | 1945733.9       | 1702.39       | 2709.94    | 21635       | 3273.24    |
| 4 | 2021-04-10 | 770       | 320847             | 806592.1        | 416.68        | 1047.52    | 13744       | 2128.08    |
| 5 | 2021-04-11 | 820       | 167999             | 431269.6        | 204.88        | 525.94     | 10315       | 1780.67    |
| 6 | 2021-04-12 | 0         | 0                  | 0.0             | NA            | NA         | 0           | 1544.40    |

Figure 3: Example of table of results with the metrics for each day (first columns).

|   | valid_days | wear_time | total_counts_axis1 | total_counts_vm | axis1_per_min | vm_per_min | total_steps | total_kcal |
|---|------------|-----------|--------------------|-----------------|---------------|------------|-------------|------------|
| 1 | 5          | 767.8     | 513108.6           | 970344.61       | 686.68        | 1290.55    | 14869       | 2309.19    |

Figure 4: Example of table of results with the means of the metrics from valid days (first columns).

## Acknowledgements

The authors thank Florian Congnard and Bénédicte Noury-Desveaux for their valuable feedbacks. The authors also thank Sebastien Chastin and Ulf Ekelund for giving time to provide their point of view on some of the figures the app can generate for the reports and that use data they published. Of note, the final decision regarding the use of the concerned figures and their design are only from the authors of the present work.

## References

- Bassett, David R., Richard P. Troiano, James J. McClain, and Dana L. Wolff. 2015. “Accelerometer-Based Physical Activity: Total Volume Per Day and Standardized Measures.” *Medicine & Science in Sports & Exercise* 47 (4): 833–38. <https://doi.org/10.1249/MSS.0000000000000468>.
- Dobbels, Fabienne, Corina de Jong, Ellen Drost, Janneke Elberse, Chrysoula Feridou, Laura Jacobs, Roberto Rabinovich, et al. 2014. “The PROactive Innovative Conceptual Framework on Physical Activity.” *Eur Respir J* 44 (5): 1223–33. <https://doi.org/10.1183/09031936.00004814>.
- Garcia-Aymerich, Judith, Milo A Puhan, Solange Corriol-Rohou, Corina de Jong, Heleen Demeyer, Fabienne Dobbels, Damijan Erzen, et al. 2021. “Validity and Responsiveness of the Daily- and Clinical Visit-PROactive Physical Activity in COPD (D-PPAC and C-PPAC) Instruments.” *Thorax* 76 (3): 228–38. <https://doi.org/10.1136/thoraxjnl-2020-214554>.
- Geraci, Marco. 2017. *Pawacc: Physical Activity with Accelerometers* (version 1.2.2). <https://CRAN.R-project.org/package=pawacc>.
- Gimeno-Santos, Elena, Yegini Raste, Heleen Demeyer, Zafeiris Louvaris, Corina de Jong, Roberto A. Rabinovich, Nicholas S. Hopkinson, et al. 2015. “The PROactive Instruments to Measure Physical Activity in Patients with Chronic Obstructive Pulmonary Disease.” *Eur Respir J* 46 (4): 988–1000. <https://doi.org/10.1183/09031936.00183014>.
- Hammad, Grégory, and Mathilde Reyt. 2020. *pyActigraphy* (version 1.0). <https://github.com/ghammad/pyActigraphy>.
- Migueles, Jairo H., Cristina Cadenas-Sanchez, Ulf Ekelund, Christine Delisle Nyström, Jose Mora-Gonzalez, Marie Löf, Idoia Labayen, Jonatan R. Ruiz, and Francisco B. Ortega. 2017. “Accelerometer Data Collection and Processing Criteria to Assess Physical Activity and Other Outcomes: A Systematic Review and Practical Considerations.” *Sports Med* 47 (9): 1821–45. <https://doi.org/10.1007/s40279-017-0716-0>.
- Petkova, Desislava. 2021. *Actigraph.sleepr: Detect Periods of Sleep and Non-Wear from 'ActiGraph' Data* (version 0.2.0). <https://github.com/dipetkov/actigraph.sleepr>.
- Python Software Foundation. 2022. *Python*. <https://www.python.org/>.
- R Core Team. 2022. *R: A Language and Environment for Statistical Computing*. *R Foundation for Statistical Computing, Vienna, Austria*. <https://www.R-project.org/>.
- Van Domelen, Dane, and W. Stephen Pittard. 2014. “Flexible R Functions for Processing Accelerometer Data, with Emphasis on NHANES 2003-2006.” *The R Journal* 6 (2): 52. <https://doi.org/10.32614/RJ-2014-024>.