

# CS 186 Discussion 10

Recovery

# Logistics

- Homework 5 due 11/24
- HKN Course Surveys 11/30
- Midterm 3 on 12/02

# Recovery

- Logging enables atomicity and durability
- Works tightly with buffer pool and lock manager
- Strict 2PL

# Steal / No-Force

- **Steal** - okay to evict dirty pages
  - Watch out for:
  - Log Info:
- **No-Force** - can delay disk writes
  - Watch out for:
  - Log Info:

# Steal / No-Force

- **Steal** - okay to evict dirty pages
  - Watch out for: **Atomicity** (xact doesn't commit)
  - Log Info: **UNDO**
- **No-Force** - can delay disk writes
  - Watch out for:
  - Log Info:

# Steal / No-Force

- **Steal** - okay to evict dirty pages
  - Watch out for: **Atomicity** (xact doesn't commit)
  - Log Info: **UNDO**
- **No-Force** - can delay disk writes
  - Watch out for: **Durability** (commit lost to crash)
  - Log Info: **REDO**

# Homework 5 Demo

# Steal / No-Force

- **Steal** - okay to evict dirty pages
- **No-Force** - can delay disk writes
- So when are:
  - Updates persisted to disk?
  - Update records written?



# Steal / No-Force

- **Steal** - okay to evict dirty pages
- **No-Force** - can delay disk writes
- So when are:
  - Updates persisted to disk? **on eviction (or earlier)**
  - Update records written?
    - In the homework: **before commit or eviction**
    - In ARIES: **whenever you update**

# ARIES Logging

- Log Sequence Numbers (increasing “timestamps”)
- **pageLSN** - each page, most recent update LSN
- Record Types:
  - Update, Commit, Abort
  - Checkpoint
  - CLR (an undo)
  - End (done committing/aborting)

# ARIES Logging

- Transaction Table
  - Tracks active xacts
  - **lastLSN** - most recent LSN written by xact
- Dirty Page Table
  - Tracks dirty pages in buffer
  - **recLSN** - first record that dirtied page
- **flushedLSN** - max LSN flushed so far

# ARIES - Commit

1. Write commit record
2. Flush log to disk
3. Write end record

# ARIES - Abort


1. Write abort record
2. Rollback - fix buffer pool page with before image
  - Write CLR records per undo, update pageLSN
  - Redo CLR's if you crash
3. Write end record

# ARIES - Checkpoint

- Faster recovery! Store most recent checkpoint
- Checkpoint record stores current xact table + DPT
- No need to force dirty pages to disk (recLSN)


# ARIES - Recovery

- If we crash:
  - What do we need to restore?
- What do we need to undo?



# ARIES - Recovery


- If we crash:
  - What do we need to restore?
    - Anything that committed
  - What do we need to undo?
    - Anything that aborted
    - or... didn't finish





# ARIES - Recovery

- **Analysis** / REDO / UNDO
  - Need to know which xacts started/committed/aborted after checkpoint
  - xact table = loser xacts
    - Remove xact if END
    - Add xact if anything else
  - Add new pages to DPT for updates (+ **recLSN**)



# Worksheet - Analysis

LSN	Record
90	update: T1 writes P3
100	end checkpoint
110	update: T2 writes P3
120	T2 commit
130	update: T4 writes P1
140	T2 end
150	T4 abort
160	update: T5 writes P2
180	CLR: undo T4 LSN 130

Transaction	lastLSN	Status
T1	70	Running
T2	60	Running
T3	30	Running
T4	50	Running

PageID	recLSN
P5	50
P1	40

# Worksheet - Analysis

LSN	Record
90	update: T1 writes P3
100	end checkpoint
110	update: T2 writes P3
120	T2 commit
130	update: T4 writes P1
140	T2 end
150	T4 abort
160	update: T5 writes P2
180	CLR: undo T4 LSN 130

Transaction	lastLSN	Status
T1	90	Running
T2	60	Running
T3	30	Running
T4	50	Running

PageID	recLSN
P5	50
P1	40
P3	90

# Worksheet - Analysis

LSN	Record
90	update: T1 writes P3
100	end checkpoint
110	update: T2 writes P3
120	T2 commit
130	update: T4 writes P1
140	T2 end
150	T4 abort
160	update: T5 writes P2
180	CLR: undo T4 LSN 130

Transaction	lastLSN	Status
T1	90	Running
T2	110	Running
T3	30	Running
T4	50	Running

PageID	recLSN
P5	50
P1	40
P3	90

# Worksheet - Analysis

LSN	Record
90	update: T1 writes P3
100	end checkpoint
110	update: T2 writes P3
120	T2 commit
130	update: T4 writes P1
140	T2 end
150	T4 abort
160	update: T5 writes P2
180	CLR: undo T4 LSN 130

Transaction	lastLSN	Status
T1	90	Running
T2	110	Committed
T3	30	Running
T4	50	Running

PageID	recLSN
P5	50
P1	40
P3	90

# Worksheet - Analysis

LSN	Record
90	update: T1 writes P3
100	end checkpoint
110	update: T2 writes P3
120	T2 commit
130	update: T4 writes P1
140	T2 end
150	T4 abort
160	update: T5 writes P2
180	CLR: undo T4 LSN 130

Transaction	lastLSN	Status
T1	90	Running
T2	110	Running
T3	30	Running
T4	130	Running

PageID	recLSN
P5	50
P1	40
P3	90

# Worksheet - Analysis

LSN	Record
90	update: T1 writes P3
100	end checkpoint
110	update: T2 writes P3
120	T2 commit
130	update: T4 writes P1
140	T2 end
150	T4 abort
160	update: T5 writes P2
180	CLR: undo T4 LSN 130

Transaction	lastLSN	Status
T1	90	Running
T3	30	Running
T4	130	Running

PageID	recLSN
P5	50
P1	40
P3	90

# Worksheet - Analysis

LSN	Record
90	update: T1 writes P3
100	end checkpoint
110	update: T2 writes P3
120	T2 commit
130	update: T4 writes P1
140	T2 end
150	T4 abort
160	update: T5 writes P2
180	CLR: undo T4 LSN 130

Transaction	lastLSN	Status
T1	90	Running
T3	30	Running
T4	130	Aborting

PageID	recLSN
P5	50
P1	40
P3	90



# Worksheet - Analysis

LSN	Record
90	update: T1 writes P3
100	end checkpoint
110	update: T2 writes P3
120	T2 commit
130	update: T4 writes P1
140	T2 end
150	T4 abort
160	update: T5 writes P2
180	CLR: undo T4 LSN 130

Transaction	lastLSN	Status
T1	90	Running
T5	160	Running
T3	30	Running
T4	130	Aborting

PageID	recLSN
P5	50
P1	40
P3	90
P2	160

# Worksheet - Analysis


LSN	Record
90	update: T1 writes P3
100	end checkpoint
110	update: T2 writes P3
120	T2 commit
130	update: T4 writes P1
140	T2 end
150	T4 abort
160	update: T5 writes P2
180	CLR: undo T4 LSN 130

Transaction	lastLSN	Status
T1	90	Running
T5	160	Running
T3	30	Running
T4	180	Aborting

PageID	recLSN
P5	50
P1	40
P3	90
P2	160

# ARIES - Recovery

- Analysis / **REDO** / UNDO
  - Redo everything from min recLSN, unless:
    - page not in DPT
    - recLSN of page > LSN
    - pageLSN  $\geq$  LSN
  - Redo with after-image
  - Update pageLSNs



# Worksheet - REDO

LSN	Record
40	update: T4 writes P1
50	update: T4 writes P5
60	update: T2 writes P5
70	update: T1 writes P2
80	begin checkpoint
90	update: T1 writes P3
100	end checkpoint
110	update: T2 writes P3
120	T2 commit
130	update: T4 writes P1
140	T2 end
150	T4 abort
160	update: T5 writes P2
180	CLR: undo T4 LSN 130

Skip redo if:

- page not in DPT
- recLSN of page > LSN
- pageLSN  $\geq$  LSN

PageID	recLSN
P5	50
P1	40
P3	90
P2	160

# Worksheet - REDO

LSN	Record
40	update: T4 writes P1
50	update: T4 writes P5
60	update: T2 writes P5
70	update: T1 writes P2
80	begin checkpoint
90	update: T1 writes P3
100	end checkpoint
110	update: T2 writes P3
120	T2 commit
130	update: T4 writes P1
140	T2 end
150	T4 abort
160	update: T5 writes P2
180	CLR: undo T4 LSN 130

Skip redo if:

- page not in DPT
- recLSN of page > LSN
- pageLSN  $\geq$  LSN

PageID	recLSN
P5	50
P1	40
P3	90
P2	160

# Worksheet - 2ab

Transaction	lastLSN	Status

PageID	recLSN

# Worksheet - 2ab

Transaction	lastLSN	Status
T3	70	Running
T2	80	Aborting

PageID	recLSN

# Worksheet - 2ab


Transaction	lastLSN	Status
T3	70	Running
T2	80	Aborting

PageID	recLSN
P1	10
P2	70
P3	20
P4	40



# ARIES - Recovery

- Analysis / REDO / **UNDO**
  - Undo everything in xact table -> abort these xacts
- Performance optimization:
  - Repeat with decreasing LSN, until table empty
  - Undo updates and continue writing CLR's



# Worksheet - UNDO

Xact	lastLSN	Status
T3	70	Running
T2	80	Aborting

- Start from max lastLSN, work backwards
- ToUndo = {70, 80}
  - prevLSN of 80?

PageID	recLSN
P1	10
P2	70
P3	20
P4	40

# Worksheet - UNDO

Xact	lastLSN	Status
T3	70	Running
T2	80	Aborting

- Start from max lastLSN, work backwards
- ToUndo = {50, 70}

PageID	recLSN
P1	10
P2	70
P3	20
P4	40

# Worksheet - UNDO

Xact	lastLSN	Status
T3	70	Running
T2	80	Aborting

- Start from max lastLSN, work backwards
- ToUndo = {**40**, 50}

PageID	recLSN
P1	10
P2	70
P3	20
P4	40

LSN	Record
100	CLR: T3 LSN = 70; undoNextLSN = 40

# Worksheet - UNDO

Xact	lastLSN	Status
T3	70	Running
T2	80	Aborting

- Start from max lastLSN, work backwards
- ToUndo = {**20**, 40}

PageID	recLSN
P1	10
P2	70
P3	20
P4	40

LSN	Record
100	CLR: T3 LSN = 70; undoNextLSN = 40
110	CLR: T2 LSN = 50; undoNextLSN = 20

# Worksheet - UNDO

Xact	lastLSN	Status
T3	70	Running
T2	80	Aborting

- Start from max lastLSN, work backwards
- ToUndo = {20}

PageID	recLSN
P1	10
P2	70
P3	20
P4	40

LSN	Record
100	CLR: T3 LSN = 70; undoNextLSN = 40
110	CLR: T2 LSN = 50; undoNextLSN = 20
120	CLR: T3 LSN = 40; undoNextLSN = null
130	T3 end

# Worksheet - UNDO

Xact	lastLSN	Status
T3	70	Running
T2	80	Aborting

- Start from max lastLSN, work backwards
- ToUndo = {}

PageID	recLSN
P1	10
P2	70
P3	20
P4	40

LSN	Record
100	CLR: T3 LSN = 70; undoNextLSN = 40
110	CLR: T2 LSN = 50; undoNextLSN = 20
120	CLR: T3 LSN = 40; undoNextLSN = null
130	T3 end
140	CLR: T2 LSN = 20; undoNextLSN = null
150	T2 end