

=====

aiKart AGENT MANIFEST GUIDE

Specification for the "Try Me Now" Sandbox

Version 1.0 (Draft)

=====

STATUS

This document specifies the manifest format your agent must follow to support aiKart's in-house "Try Me Now" sandbox feature. This is a SPECIFICATION for an upcoming capability – publish your manifest now so your listing is ready the moment sandbox execution goes live on aiKart.

1. WHAT IS "TRY ME NOW"?

"Try Me Now" lets a buyer run your agent directly from its aiKart listing, without leaving the site and without you handling the request yourself. aiKart starts a fresh, isolated, on-demand container from your published image, feeds it the buyer's inputs, captures the output, and shuts the container down. Nothing persists between runs.

2. THE MANIFEST FILE

Upload one YAML file describing your agent. This is the file you attach in the "Try / Run My Agent" step of the listing wizard.

```
apiVersion: aikart.dev/v1
kind: AgentManifest

metadata:
  name: my-agent-name           # lowercase, hyphenated, unique to you
  displayName: "My Agent"
  description: "One-line description of what this agent does"

runtime:
  type: docker                  # only "docker" is supported today
  image: "docker.io/yourorg/agent:1.0.0" # publicly pullable image
  command: ["python", "run.py"] # optional – overrides the image CMD

resources:
  cpu: 1                        # vCPUs requested (max 2)
  memoryMb: 2048                # memory in MB (max 4096)
  timeoutSeconds: 120           # hard wall-clock limit (max 280)

inputs:
  - name: topic
    label: "Topic"
    type: text                   # text|textarea|number|boolean|select
    required: true
  - name: tone
    label: "Tone"
    type: select
    required: false
    options: ["Formal", "Casual", "Playful"]
    default: "Formal"

output:
  format: markdown              # markdown | text | json | html

security:
```

```
networkEgress: none # none | allowlist
# egressAllowlist: ["api.your-llm-provider.com"]
```

3. FIELD REFERENCE

metadata.name	Unique slug identifying your agent. Lowercase, hyphens only.
metadata.displayName	Human-readable name shown to buyers.
metadata.description	One-line summary.
runtime.type	Currently must be "docker".
runtime.image	A PUBLICLY pullable image reference (Docker Hub, GHCR, etc). Private registries requiring credentials are not supported at this time.
runtime.command	Optional. Overrides your image's default CMD.
resources.cpu	Requested vCPUs. Hard cap: 2
resources.memoryMb	Requested memory (MB). Hard cap: 4096
resources.timeoutSeconds	Max run time. Hard cap: 280
	Manifests requesting more than the caps above will be rejected at review.
inputs[]	The form fields shown to the buyer before running your agent. Each entry needs: - name - the field's identifier - label - shown to the buyer - type - text textarea number boolean select - required - true false - options - required when type is "select" - default - optional default value
output.format	How your agent's result should be rendered to the buyer: - markdown - rendered as formatted text - text - shown as plain text - json - shown as formatted JSON - html - rendered in a sandboxed iframe (no scripts, no cookies, no same-origin access)
security.networkEgress	"none" (default, recommended) blocks all outbound network access from the container. "allowlist" permits only the domains you list under egressAllowlist – useful if your agent calls an LLM API. Allowlisted domains are subject to review before your listing is approved.

4. RUNTIME CONTRACT – HOW INPUT AND OUTPUT FLOW

INPUT

When a run starts, aiKart writes the buyer's answers as a single JSON object to:

/aikart/input.json

The same JSON string is also exposed via the environment variable:

AIKART_INPUT

Use whichever is more convenient for your stack. Example payload for the manifest above:

```
{ "topic": "renewable energy", "tone": "Casual" }
```

OUTPUT

Before your process exits, write the result as JSON to:

`/aikart/output.json`

with this exact shape:

```
{ "format": "markdown", "response": "<your agent's output>" }
```

"format" should match (or be a subset of) what you declared under `output.format` in the manifest.

EXIT CODE

Exit `0` on success. Any non-zero exit is treated as a failure; the buyer sees a generic error message (your logs/stderr are never shown to buyers).

STORAGE

Fully ephemeral. Nothing written inside the container persists after the run completes – do not rely on any local state between runs.

5. A MINIMAL WORKING EXAMPLE

Manifest:

```
apiVersion: aikart.dev/v1
```

```
kind: AgentManifest
```

```
metadata:
```

```
  name: haiku-writer
```

```
  displayName: "Haiku Writer"
```

```
  description: "Writes a haiku about any topic"
```

```
runtime:
```

```
  type: docker
```

```
  image: "docker.io/yourorg/haiku-writer:1.0.0"
```

```
resources:
```

```
  cpu: 1
```

```
  memoryMb: 512
```

```
  timeoutSeconds: 30
```

```
inputs:
```

```
  - name: topic
```

```
    label: "Topic"
```

```
    type: text
```

```
    required: true
```

```
output:
```

```
  format: text
```

```
security:
```

```
  networkEgress: none
```

Your container's job, in pseudocode:

```
input = read_json("/aikart/input.json")
```

```
result = generate_haiku(input["topic"])
```

```
write_json("/aikart/output.json", { "format": "text", "response": result })
```

```
exit(0)
```

6. WHERE TO SUBMIT

In the aiKart listing wizard, go to the "Try / Run My Agent" step, choose "Yes, enable it", and upload your manifest as a `.yaml` or `.yml` file. Our team reviews the manifest (resource limits, any requested network egress) as part of your listing's approval.

7. VERSIONING

This is v1 of the format (apiVersion: aikart.dev/v1). Future versions will be backward compatible where possible; breaking changes will use a new apiVersion.

=====
Questions? Contact your aiKart account team.
=====