Information requirements
(air-to-air air conditioners)

Model(s): GMV-160WL/C-X							
Outdoor side heat exchanger of air conditioner	air						
Indoor side heat exchanger of air conditioner	air						
Type	compressor driven vapour compression						
If applicable: driver of compressor	electric motor						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated cooling capacity	$P_{rated,c}$	16.00	kW	Seasonal space cooling energy efficiency	$\eta_{s,c}$	275.4	%
Declared cooling capacity for part load at given outdoor temperatures T_j and indoor 27°/19 °C (dry/wet bulb)				Declared energy efficiency ratio for part load at given outdoor temperatures T_j			
T_j = + 35 °C	Pdc	16.00	kW	T_j = + 35 °C	EER_d	2.90	-
T_j = + 30 °C	Pdc	11.45	kW	T_j = + 30 °C	EER_d	5.00	-
T_j = + 25 °C	Pdc	7.30	kW	T_j = + 25 °C	EER_d	9.30	-
T_j = + 20 °C	Pdc	3.30	kW	T_j = + 20 °C	EER_d	20.00	-
Degradation co-efficient for air conditioners(*)	C_{dc}	0.25	—				-
Power consumption in modes other than 'active mode'							
Off mode	P_{OFF}	0.048	kW	Crankcase heater mode	P_{CK}	0.048	kW
Thermostat-off mode	P_{TO}	0.010	kW	Standby mode	P_{SB}	0.048	kW
Other items							
Capacity control	variable			For air-to-air air conditioner: air flow rate, outdoor measured	—	6600	m^3/h
Sound power level, outdoor	L_{WA}	75.00	dB				
If engine driven: Emissions of nitrogen oxides	NOx(**)	-	mg/kWh fuel input GCV				
GWP of the refrigerant	2088		kg CO_2 eq (100 years)				
Contact details: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070				Name of manufacturer: GREE ELECTRIC APPLIANCES,INC. OF ZHUHAI			
(*) If C_{dc} is not determined by measurement then the default degradation coefficient air conditioners shall be 0,25. (**) From 26 September 2018. Where information relates to multi-split air conditioners, the test result and performance data may be obtained on the basis of the performance of the outdoor unit, with a combination of indoor unit(s) recommended by the manufacturer or importer.							

Information requirements
(heat pump)

Model(s): GMV-160WL/C-X							
Outdoor side heat exchanger of heat pump	air						
Indoor side heat exchanger of heat pump	air						
Indication if the heater is equipped with a supplementary heater	no						
If applicable: driver of compressor	electric motor						
Parameters declared for	Average climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heating capacity	$P_{rated,h}$	16.00	kW	Seasonal space heating energy efficiency	$\eta_{s,h}$	158.6	%
Declared heating capacity for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance for part load at given outdoor temperatures Tj			
T_j = – 7 °C	Pdh	9.90	kW	T_j = – 7 °C	COP_d	2.60	-
T_j = + 2 °C	Pdh	6.00	kW	T_j = + 2 °C	COP_d	3.50	-
T_j = + 7 °C	Pdh	4.00	kW	T_j = + 7 °C	COP_d	6.50	-
T_j = + 12 °C	Pdh	4.00	kW	T_j = + 12 °C	COP_d	8.50	-
T_{biv} = bivalent temperature	Pdh	9.90	kW	T_{biv} = bivalent temperature	COP_d	2.60	-
T_{OL} = operation limit	Pdh	11.70	kW	T_{OL} = operation limit	COP_d	2.25	-
Tj = – 15 °C (if TOL < – 20 °C)	Pdh	-	kW	Tj = – 15 °C (if TOL < – 20 °C)	COP_d	-	-
Bivalent temperature	T_{biv}	-7.00	°C	Operation limit temperature	T_{ol}	-10.00	°C
Degradation co-efficient heat pumps(**)	C_{dh}	0.25	—				
Power consumption in modes other than 'active mode'				Supplementary heater			
Off mode	P_{OFF}	0.048	kW	Back-up heating capacity (*)	elbu	0	kW
Thermostat-off mode	P_{TO}	0.053	kW	Type of energy input	Electric		
Crankcase heater mode	P_{CK}	0.048	kW	Standby mode	P_{SB}	0.048	kW
Other items							
Capacity control	variable			air flow rate, outdoor measured	—	6600	m^3/h
Sound power level, indoor/outdoor measured	L_{WA}	-/76.00	dB				
Emissions of nitrogen oxides (if applicable)	NOx(***)	-	mg/kWh input GCV	Rated brine or water flow rate, outdoor side heat exchanger	—	-	m^3/h
GWP of the refrigerant	2088		kg CO_2 eq (100 years)				
Contact details: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070				Name of manufacturer: GREE ELECTRIC APPLIANCES,INC. OF ZHUHAI			

(*)
(**) If Cdh is not determined by measurement then the default degradation coefficient of heat pumps shall be 0,25.
(***) From 26 September 2018.
Where information relates to multi-split heat pumps, the test result and performance data may be obtained on the basis of the performance of the outdoor unit, with a combination of indoor unit(s) recommended by the manufacturer or importer.

Information requirements
(heat pump)

Model(s): GMV-160WL/C-X							
Outdoor side heat exchanger of heat pump	air						
Indoor side heat exchanger of heat pump	air						
Indication if the heater is equipped with a supplementary heater	no						
If applicable: driver of compressor	electric motor						
Parameters declared for	Warmer climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heating capacity	$P_{rated,h}$	16.00	kW	Seasonal space heating energy efficiency	$\eta_{s,h}$	232.5	%
Declared heating capacity for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance for part load at given outdoor temperatures Tj			
T_j = – 7 °C	Pdh	-	kW	T_j = – 7 °C	COP_d	-	-
T_j = + 2 °C	Pdh	12.5	kW	T_j = + 2 °C	COP_d	2.8	-
T_j = + 7 °C	Pdh	7.9	kW	T_j = + 7 °C	COP_d	5.8	-
T_j = + 12 °C	Pdh	3.4	kW	T_j = + 12 °C	COP_d	7.5	-
T_{biv} = bivalent temperature	Pdh	12.5	kW	T_{biv} = bivalent temperature	COP_d	2.8	-
T_{OL} = operation limit	Pdh	12.5	kW	T_{OL} = operation limit	COP_d	2.8	-
Tj = – 15 °C (if TOL < – 20 °C)	Pdh	-	kW	Tj = – 15 °C (if TOL < – 20 °C)	COP_d	-	-
Bivalent temperature	T_{biv}	2.00	°C	Operation limit temperature	T_{ol}	2.00	°C
Degradation co-efficient heat pumps(**)	C_{dh}	0.25	—				
Power consumption in modes other than 'active mode'				Supplementary heater			
Off mode	P_{OFF}	0.048	kW	Back-up heating capacity (*)	elbu	0	kW
Thermostat-off mode	P_{TO}	0.053	kW	Type of energy input	Electric		
Crankcase heater mode	P_{CK}	0.048	kW	Standby mode	P_{SB}	0.048	kW
Other items							
Capacity control	variable			air flow rate, outdoor measured	—	6600	m^3/h
Sound power level, indoor/outdoor measured	L_{WA}	-/76.00	dB				
Emissions of nitrogen oxides (if applicable)	NOx(***)	-	mg/kWh input GCV	Rated brine or water flow rate, outdoor side heat exchanger	—	-	m^3/h
GWP of the refrigerant	2088		kg CO_2 eq (100 years)				
Contact details: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070				Name of manufacturer: GREE ELECTRIC APPLIANCES,INC. OF ZHUHAI			

(*)
(**) If Cdh is not determined by measurement then the default degradation coefficient of heat pumps shall be 0,25.
(***) From 26 September 2018.
Where information relates to multi-split heat pumps, the test result and performance data may be obtained on the basis of the performance of the outdoor unit, with a combination of indoor unit(s) recommended by the manufacturer or importer.