

HIS Integration Document Template — [Hospital Name]

[Hospital Name] - HIS Integration Document

i Instructions for filling this template: Replace all [bracketed placeholders] with actual values. Use inline comments (/Comment) next to fields to indicate handling rules (see legend below). Delete any API section that is NOT applicable (or mark it N/A). Every field in request/response samples must have an inline comment explaining its source.

- [\[Hospital Name\] - HIS Integration Document](#)
- [1. Overview](#)
 - [Integration Type Descriptions](#)
 - [Slot Ownership](#)
- [2. Authentication](#)
 - [If Dynamic Auth \(OAuth2 / Session Token\):](#)
- [3. Base URL](#)
- [4. Inline Comment Legend](#)
- [5. API Specifications](#)
 - [5.1 Get Slots API \(Fetch Doctor Availability from HIS\)](#)
 - [5.2 Get Bulk Slots API \(Multi-day Slot Fetch\)](#)
 - [5.3 Create Appointment API \(Push Booking to HIS\)](#)
 - [Gender Mapping \(if HIS expects specific values\):](#)
 - [5.4 Cancel Appointment API](#)
 - [5.5 Reschedule Appointment API](#)
 - [5.6 Appointment Status API \(Polling from HIS\)](#)
 - [Status Mapping \(REQUIRED - list ALL possible status values from HIS\):](#)
 - [5.7 Bulk Appointment Status API \(Multiple Appointments per Call\)](#)
 - [5.8 Fetch UHID API](#)
 - [5.9 Hold Appointment Slot API \(Two-step Booking\)](#)
 - [5.10 Register Patient API](#)
 - [5.11 Create Lead API](#)
 - [5.12 Fetch Follow-up Appointments API](#)
 - [5.13 Validate Mobile API](#)
- [6. Default/Fallback Values](#)
- [7. Terminal Statuses](#)
- [8. Static/Constant Values](#)
- [9. Per-Clinic Dynamic Fields](#)
- [10. Additional Notes](#)
- [11. Contacts](#)
- [Appendix: Postman Collection](#)
- [Checklist Before Submission](#)

1. Overview

Field	Value
Hospital Name	[e.g. True Hospitals]
Establishment ID	[Practo establishment ID, e.g. 2080431]
Slug	[Practo slug URL]
HIS System Name	[e.g. TrueHMS, eHospital, Akhil HIS]
Integration Type	[Choose: Full Shadow / Practo Slots + HIS Push / One-way Push Only]

Integration Type Descriptions

- **Full Shadow:** Practo syncs slots FROM HIS AND pushes bookings TO HIS (both directions)
- **Practo Slots + HIS Push:** Practo owns slots; only pushes confirmed appointments and polls status from HIS (no slot API)
- **One-way Push Only:** Only push appointments to HIS, no status polling back

Slot Ownership

Question	Answer
Who is the source of truth for slots?	[Practo / HIS]
Does HIS provide a slot availability API?	[Yes / No]
Does HIS provide a bulk (multi-day) slot API?	[Yes / No]

2. Authentication

Field	Value
Auth Type	[Choose: Static API Key / OAuth2/Bearer Token / Session Token / None]

Header Name	[e.g. X-API-Key , Authorization , x-thms-api-key]
Header Value Format	[e.g. <api_key_value> , Bearer <token>]
API Key/Credentials	[Contact person or actual test key]
Is auth per-clinic or global?	[Per-clinic / Global]

If Dynamic Auth (OAuth2 / Session Token):

Field	Value
Token Endpoint	[e.g. POST /auth/token]
Token Request Body	(see sample below)
Token Response Field	[e.g. access_token , sessionId]
Token Expiry (seconds)	[e.g. 3600]
Token Template	[e.g. Bearer {token}]
Cache Token?	[Yes / No]
Fetch Token Inline (per-request) or Background (cron)?	[Inline / Background]

```

1 //
2 // Token Request Sample (if dynamic auth)
3 POST /auth/token
4 Content-Type: application/json
5
6 {
7   "username": "[username]",
8   "password": "[password]",
9   "grant_type": "client_credentials"
10 }
11

```

```

1 //
2 // Token Response Sample
3 {
4   "access_token": "eyJhbGciOiJIUzI1NiIs... ",
5   "expires_in": 3600,
6   "token_type": "Bearer"
7 }

```

3. Base URL

Environment	URL
Production	[e.g. https://api.truehospitals.com]

4. Inline Comment Legend

Use these comment patterns next to fields in request/response samples below. The automation uses these to determine how each field is handled:

Comment Pattern	Meaning	Example
/Constant or /send this as X	Always send this exact fixed value	"mode": "IN_CLINIC" /Constant
/we can send dummy or /dummy value	Use a placeholder when real data unavailable	"dob": "1990-01-01" /we can send dummy date of birth
/send X if not present or /If not we should send X	Use real data when available, fallback to X	"email": "a@b.com" /If not we should send true@example.com
/Patient name (Mandatory)	Map from patient record, required field	"name": "John" /Patient name (Mandatory)
/Practo field_name	Map from a specific Practo data field	"id": "123" /Practo appointment_id

/Practice city or /Doctor name etc.	Map from practice/doctor metadata	"address": "Delhi" /Practice city
(no comment)	Needs clarification - add a comment!	

5. API Specifications

 Fill out ONLY the APIs that the HIS provides. Delete or mark N/A for APIs not available.

5.1 Get Slots API (Fetch Doctor Availability from HIS)

 Skip this section entirely if Practo owns slots (Integration Type = "Practo Slots + HIS Push")

Field	Value
Available?	[Yes / No / N/A - Practo owns slots]
HTTP Method	[GET / POST]
Endpoint	[e.g. /api/slots]
Request Content-Type	[e.g. application/json]
Date Format	[e.g. YYYY-MM-DD , DD-MM-YYYY HH:MM:SS , epoch_ms]
Timezone	[e.g. Asia/Kolkata , UTC]
Does response include unavailable slots?	[Yes (needs availability filter) / No (only available)]
If yes, which field indicates availability?	[e.g. status = "OPEN" , is_available = 1]
Are times in UTC?	[Yes / No]
Are times in Unix milliseconds?	[Yes / No]

Request Headers:

```
1 Content-Type: application/json
2 [Auth-Header]: [value]
3
```

Request Sample:

```
1 //
2 // For POST:
3 {
4   "doctor_id": "DOC001",           /HMS doctor code
5   "date": "2026-04-15",           /Appointment date
6   "clinic_code": "CLINIC001"      /HMS clinic code
7 }
8
```

```
1 //
2 // For GET with query params:
3 // GET /api/slots?doctor_id=DOC001&date=2026-04-15&location=CLINIC001
4 // url_params: doctor_id = hms_doctor_code, date = date, location =
5 //               hms_clinic_code
```

Response Sample (Success):

```
1 {
2   "data": {
3     "timeslots": [
4       {
5         "slotTime": "09:00",        /start_time - appointment start
6         time
7         "slotId": "SLOT001",        /id - unique slot identifier
8         "sessionId": "SES01",       /session_id - session identifier
9         (if applicable)
10        "slotNumber": 1,             /slot_number - slot sequence number
11        (if applicable)
12        "duration": 15,              /duration - slot duration in
13        minutes
14        "status": "OPEN",            /is_available - availability
15        indicator
16        "endTime": "09:15"          /end_time - slot end time (if
17        available)
18      }
19    ]
20  }
21 }
```

Response Sample (Error):

```
1 {
2   "error": "Doctor not found",
3   "code": 404
4 }
5
```

5.2 Get Bulk Slots API (Multi-day Slot Fetch)

 Only fill if HIS supports fetching slots for multiple days in a single call

Field	Value
-------	-------

Available?	[Yes / No]
HTTP Method	[GET / POST]
Endpoint	[e.g. /api/bulk-slots]
Max days per request	[e.g. 7]

Request Sample:

```

1 {
2   "doctor_id": "DOC001",           /HMS doctor code
3   "from_date": "2026-04-15",      /Start date
4   "to_date": "2026-04-21",        /End date
5   "clinic_code": "CLINIC001"      /HMS clinic code
6 }
7

```

Response Sample:

```

1 {
2   "slots": {
3     "2026-04-15": [ { "slotTime": "09:00", "status": "OPEN" } ],
4     "2026-04-16": [ { "slotTime": "10:00", "status": "OPEN" } ]
5   }
6 }
7

```

5.3 Create Appointment API (Push Booking to HIS)

Field	Value
Available?	[Yes - required for all integrations]
HTTP Method	[POST / PUT]
Endpoint	[e.g. /api/appointments/confirmed]
Request Content-Type	[e.g. application/json , application/xml]
Date/Time Format	[e.g. ISO 8601: 2026-04- 15T10:30:00+05:30]
DOB Format	[e.g. YYYY-MM-DD , DD/MM/YYYY]

Requires slot data from get_slots?	[Yes (need session_id/slot_number) / No (just send time)]
Is there a hold-then-confirm flow?	[Yes (see Hold Slot API) / No]
Booking ID values that indicate failure	[e.g. " 0 ", "", null — or None]

Request Headers:

```

1 Content-Type: application/json
2 [Auth-Header]: [value]
3

```

Request Sample:

```

1 {
2   "hospitalId": "eb35f2a4-xxxx",           /Constant - hospital
   identifier
3   "practoAppointmentId": "PRACTO_APPT_123", /Practo appointment_id
4   "patient": {
5     "name": "Amit Kumar",                 /Patient name
   (Mandatory)
6     "phone": "9999999999",               /Patient phone number
   (Mandatory)
7     "dob": "1990-02-14",                 /we can send dummy date
   of birth
8     "gender": "Other",                   /send this as Other
9     "email": "amit@example.com",         /we need to send the
   email if present in our DB. If not we should send true@example.com
10    "address": "Gurgaon"                 /Practice city
11  },
12  "appointment": {
13    "scheduledAt": "2026-04-15T10:30:00+05:30", /Appointment slot time
   (ISO 8601)
14    "doctorName": "Dr. Devender",         /Practo Doctor name
15    "specialisation": "Orthopedics",       /Doctor specialisation
16    "reason": "Other",                    /Constant
17    "notes": "Confirmed via Practo",       /Constant
18    "mode": "IN_CLINIC"                   /Constant
19  }
20 }
21

```

Gender Mapping (if HIS expects specific values):

Practo Gender	HIS Value
male	[e.g. Male , M , MALE]
female	[e.g. Female , F , FEMALE]
others (default)	[e.g. Other , 0 , OTHERS]

If HIS always expects a fixed gender value regardless of patient data, note: "Always send [value]".

Response Sample (Success):

```
1 {
2   "message": "Appointment created successfully",
3   "data": {
4     "bookingId": "HMS-APT-001",      /booking_id - HIS appointment
identifier
5     "uhid": "UHID12345",            /uhid - patient UHID (if
generated)
6     "visitId": "VISIT001",          /visit_id - visit identifier (if
applicable)
7     "status": "CONFIRMED"           /status - appointment status
8   }
9 }
10
```

Response Sample (Error):

```
1 {
2   "message": "Appointment creation failed",
3   "error": "Slot not available",
4   "code": 400
5 }
6
```

5.4 Cancel Appointment API

Field	Value
Available?	[Yes / No — if No, Practo handles cancellation locally]
HTTP Method	[POST / PUT / DELETE]
Endpoint	[e.g. /api/appointments/cancel]
Identifies appointment by	[HMS booking ID / Practo appointment ID]

Request Sample:

```
1 {
2   "bookingId": "HMS-APT-001",      /HMS booking ID from create response
3   "reason": "Patient Cancelled",    /Constant OR /Cancellation reason
4   "cancelledBy": "patient"          /Constant
5 }
6
```

Response Sample:

```
1 {
```

```

2  "message": "Appointment cancelled successfully",
3  "status": "CANCELLED"
4  }
5

```

5.5 Reschedule Appointment API

Field	Value
Available?	[Yes / No — if No, system uses cancel + create]
HTTP Method	[POST / PUT]
Endpoint	[e.g. /api/appointments/reschedule]
Requires new slot data?	[Yes / No]

Request Sample:

```

1  {
2    "bookingId": "HMS-APT-001",           /Current HMS booking ID
3    "newScheduledAt": "2026-04-16T11:00:00+05:30", /New appointment time
4    "newDoctorId": "DOC001",             /HMS doctor code (if
doctor can change)
5    "reason": "Patient requested"         /Reschedule reason
6  }
7

```

Response Sample:

```

1  {
2    "message": "Appointment rescheduled",
3    "data": {
4      "newBookingId": "HMS-APT-002",    /booking_id - new HIS appointment
identifier
5      "status": "RESCHEDULED"
6    }
7  }
8

```

5.6 Appointment Status API (Polling from HIS)

Field	Value
Available?	[Yes / No]
HTTP Method	[GET / POST]

Endpoint	[e.g. /api/appointments/status]
Identifies appointment by	[HMS booking ID / Practo appointment ID]
Returns UHID in response?	[Yes / No]
Batch size per Lambda call	[e.g. 50]

Request Sample:

```

1 //
2 // For GET with query params:
3 GET /api/appointments/status?practoAppointmentId=PRACTO_APPT_123
4 // Query param: practoAppointmentId = Practo appointment_id
5
6
7 //
8 // For POST:
9 {
10   "bookingId": "HMS-APT-001"           /HMS booking ID
11 }
12

```

Request Headers:

```

1 [Auth-Header]: [value]
2

```

Response Sample:

```

1 {
2   "message": "OK",
3   "data": {
4     "practoAppointmentId": "PRACTO_APPT_123",
5     "thmsAppointmentId": "a90070cd-xxxx", /booking_id - HIS internal
6     ID
7     "uhid": "TRRU26324", /uhid - patient UHID
8     "visitId": "OPDTRRU263241", /visit_id - visit
9     identifier
10    "status": "RECEIVED", /appointment_status
11    "billing": null
12  }
13 }
14

```

Status Mapping (REQUIRED - list ALL possible status values from HIS):

HIS Status Value	Meaning	Practo Status
[e.g. RECEIVED]	[Appointment received by HIS]	[e.g. Checked In]

[e.g. CONFIRMED]	[Appointment confirmed]	[e.g. Checked In]
[e.g. COMPLETED]	[Visit completed]	[Checked Out]
[e.g. CANCELLED]	[Appointment cancelled]	[Cancelled]
[e.g. NO_SHOW]	[Patient didn't show up]	[No Show]
[e.g. RESCHEDULED]	[Appointment rescheduled]	[Rescheduled]

Valid Practo statuses: `Checked In` , `Checked Out` , `Cancelled` , `No Show` , `Rescheduled` .
IMPORTANT: Every status value that appears in sample responses **MUST** be listed here, even transitional ones.

5.7 Bulk Appointment Status API (Multiple Appointments per Call)

 Only fill if HIS supports polling status for multiple appointments in one call

Field	Value
Available?	[Yes / No]
HTTP Method	[GET / POST]
Endpoint	[e.g. <code>/api/appointments/bulk-status</code>]
Accepts list of booking IDs?	[Yes / No — if No, filters by date]

Request Sample:

```

1 {
2   "clinic_code": "CLINIC001",           /HMS clinic code
3   "date": "2026-04-15",                /Date to query
4   "bookingIds": ["HMS-001", "HMS-002"] /HMS booking IDs (if ID-
  based)
5 }
6
```

Response Sample:

```

1 {
2   "appointments": [
3     {
4       "bookingId": "HMS-001",           /booking_id

```

```

5     "status": "COMPLETED",           /appointment_status
6     "uhid": "UHID001"                 /uhid
7   }
8 ]
9 }
10

```

5.8 Fetch UHID API

 Skip if UHID is returned in the Status API response (Section 5.6) — note this in the table below

Field	Value
Available?	[Yes / No / N/A - UHID from status API]
HTTP Method	[GET / POST]
Endpoint	[e.g. <code>/api/patients/uhid</code>]
Lookup Method	[phone_number / booking_id / date / date_range]
UHID values to ignore	[e.g. " -- ", " 0 ", "" — or None]

Request Sample:

```

1 //
2 // By phone number:
3 GET /api/patients?phone=9999999999
4

```

```

1 //
2 // By booking ID:
3 GET /api/patients?bookingId=HMS-APT-001
4

```

```

1 //
2 // By date range:
3 GET /api/patients?from=2026-04-01&to=2026-04-30&clinic=CLINIC001
4

```

Response Sample:

```

1 //
2 // Single UHID:
3 {
4   "uhid": "UHID12345"
5 }
6

```

```

1 //
2 // UHID list (multiple patients/appointments):
3 {

```

```

4  "data": [
5    {
6      "bookingId": "HMS-APT-001",    /booking_id
7      "uhid": "UHID12345"          /uhid
8    }
9  ]
10 }
11

```

5.9 Hold Appointment Slot API (Two-step Booking)

Only fill if the HIS requires holding a slot before confirming the appointment

Field	Value
Available?	[Yes / No]
HTTP Method	[POST]
Endpoint	[e.g. /api/appointments/hold]
Requires slot data?	[Yes / No]

Request Sample:

```

1  {
2    "doctorId": "DOC001",           /HMS doctor code
3    "slotTime": "09:00",           /Slot start time
4    "clinicCode": "CLINIC001"      /HMS clinic code
5  }
6

```

Response Sample:

```

1  {
2    "transactionId": "HOLD-001",    /booking_id - passed to create
appointment
3    "message": "Slot held successfully"
4  }
5

```

5.10 Register Patient API

Only fill if the HIS requires patient registration before appointment creation

Field	Value
Available?	[Yes / No]
HTTP Method	[POST]
Endpoint	[e.g. /api/patients/register]

Request Sample:

```
1 {  
2   "name": "Amit Kumar",           /Patient name  
3   "phone": "9999999999",         /Patient phone  
4   "dob": "1990-02-14",          /Patient DOB  
5   "gender": "Male"               /Patient gender  
6 }  
7
```

Response Sample:

```
1 {  
2   "uhid": "UHID12345",           /uhid - generated patient ID  
3   "message": "Patient registered"  
4 }  
5
```

5.11 Create Lead API

 Only fill if the HIS requires a separate lead creation call after appointment booking

Field	Value
Available?	[Yes / No]
HTTP Method	[POST]
Endpoint	[e.g. /api/leads/create]

Request/Response samples follow same format as above.

5.12 Fetch Follow-up Appointments API

 Only fill if the HIS provides an API to fetch follow-up appointments by UHID

Field	Value
Available?	[Yes / No]
HTTP Method	[GET / POST]
Endpoint	[e.g. /api/followups]

Request/Response samples follow same format as above.

5.13 Validate Mobile API

 Only fill if the HIS provides patient lookup by mobile number

Field	Value
Available?	[Yes / No]
HTTP Method	[GET / POST]
Endpoint	[e.g. <code>/api/patients/validate</code>]

Request/Response samples follow same format as above.

6. Default/Fallback Values

List fallback values for optional patient fields. These are used when the patient record in Practo is missing data.

Field	Fallback Value	Notes
Patient Email	[e.g. <code>true@example.com</code>]	[Used when patient has no email in Practo]
Patient DOB	[e.g. <code>1987-01-01</code>]	[Dummy DOB for patients without DOB]
Patient Gender	[e.g. <code>Other</code>]	[Default gender when not available]
Patient Last Name	[e.g. <code>.</code>]	[When API requires last name but patient has single name]
Patient Age	[e.g. <code>30</code>]	[Default age when DOB not available]

7. Terminal Statuses

List the HIS status values that mean an appointment lifecycle is complete (no further polling needed).

Terminal Status	Meaning
-----------------	---------

[e.g. Completed]	[Visit finished]
[e.g. Cancelled]	[Appointment cancelled]
[e.g. No Show]	[Patient didn't arrive]

8. Static/Constant Values

List any fields that must always be sent with a fixed value, regardless of patient/appointment data.

API	Field	Fixed Value	Notes
[e.g. Create Appointment]	[e.g. hospitalId]	[e.g. eb35f2a4-xxxx]	[Hospital identifier]
[e.g. Create Appointment]	[e.g. mode]	[e.g. IN_CLINIC]	[Always in-clinic]
[e.g. Create Appointment]	[e.g. reason]	[e.g. Other]	[Default reason]

9. Per-Clinic Dynamic Fields

List fields whose values change per clinic/practice and must be configured in the admin panel (NOT hardcoded in config).

Field	Where Used	Example Value	How to Obtain
[e.g. API Key]	[Auth header]	[e.g. abc-123-xyz]	[Contact hospital IT]
[e.g. Hospital ID]	[Create appointment body]	[e.g. eb35f2a4-xxxx]	[Provided during onboarding]
[e.g. HMS Doctor Code]	[All APIs]	[e.g. D0C001]	[Doctor mapping sheet]
[e.g. HMS Clinic Code]	[All APIs]	[e.g. CLINIC001]	[Clinic mapping sheet]

10. Additional Notes

- [e.g. API is idempotent on `practoAppointmentId` - duplicate calls won't create duplicate appointments]
 - [e.g. UHID is only generated for new patients; returning patients keep existing UHID]
 - [e.g. Rate limiting: max 100 requests/minute]
 - [e.g. Staging environment requires VPN access]
-

11. Contacts

Role	Name	Contact
Hospital IT / API Support	[Name]	[Email/Phone]
Practo Product Owner	[Name]	[Slack/Email]
Practo Engineering	[Name]	[Slack/Email]

Appendix: Postman Collection

Attach or link the Postman collection if available: `[filename].postman_collection.json`

Checklist Before Submission

- ☐ All available APIs have complete request AND response samples
- ☐ Every field in request samples has an inline comment (/comment)
- ☐ Status mapping table is complete with ALL possible HIS status values
- ☐ Authentication details are specified (type, header, key source)
- ☐ Gender mapping is specified (if HIS expects specific values)
- ☐ Default/fallback values are listed for optional fields
- ☐ Static/constant values are listed separately
- ☐ Base URL is provided for at least one environment
- ☐ Terminal statuses are defined for polling stop conditions
- ☐ Per-clinic dynamic fields are identified