Daimon on Azure — Coke IT install kit

Pilot: one AKS node, ACR Basic and Azure OpenAI (AOAI); PostgreSQL, session workspaces, MCP server and scheduler run in the cluster. Teams is off by default. Full operator instructions: AKS recipe.

Before starting: use a dedicated resource group and budget; Azure CLI logged into the target subscription, Helm 3.19+, kubectl, Python 3, git; reviewed `azure-selfhost` checkout. Resource-group Owner, or Contributor plus ACR role-assignment rights, is required; subscription admin registers **Microsoft.ContainerService, Microsoft.ContainerRegistry, Microsoft.CognitiveServices, Microsoft.Compute, Microsoft.Network, Microsoft.Storage**. Cluster-admin access and approval for the harness PodSecurity exception are required. Confirm Dsv6 CPU quota/capacity for one **Standard_D2s_v6** node (pilot minimum); **Standard_D4s_v6** is recommended for production. AKS system pools reject B-series. Use **eastus2 (US Data Zone)** or an approved EU Data Zone region; obtain a supported AOAI deployment (**gpt-5.4-mini**, DataZoneStandard) and regional model quota. Existing AOAI is reused; set its account/deployment names below. Processing stays within the selected US/EU zone, not necessarily one region. AOAI local authentication is required for this API-key install; disabling it requires a reviewed identity proxy.

Install: run from the repository root in one shell. Replace globally unique ACR/AOAI names; use the existing AOAI account's resource group when reusing it. Keep the generated `AKS_STATE` directory private: it contains keys. Never enable shell tracing.

```
export RG=daimon-selfhost LOCATION=eastus2
export ACR=daimoncoke12345 AKS=daimon-coke AOAI=daimon-coke-12345
export AOAI_DEPLOYMENT=gpt-5.4-mini; export TAG=$(git rev-parse HEAD)
export AKS_STATE=$(mktemp -d)
bash deploy/helm/daimon-selfhost/scripts/aks.sh bootstrap
bash deploy/helm/daimon-selfhost/scripts/aks.sh install
bash deploy/helm/daimon-selfhost/scripts/aks.sh probe
```

Builds/pushes both images, mirrors PostgreSQL, creates AKS/network/disks/public IP, and creates AOAI if absent. Helm installs Secrets, in-cluster TLS, policies and persistent volumes; waits for migrations and Ready pods. **Probe is a paid preflight:** two short **gpt-5.4-mini** turns write a file, then read it back; model tokens are billed. For registration, application turns and egress checks, follow Register and run; sample billing rates are TEST rates.

Cost: observed D2s_v6 compute ≈ **US$2.30/day per node** (two ≈ $4.60/day), plus AOAI usage, ACR Basic/storage/builds, disks, public IP and network traffic. AKS Free control-plane tier has no SLA; nodes are billed. Confirm your region/contract and set budget alerts before installing; these observations are not a quote.

Security: database, ledger and workspaces stay in your tenant; inference goes to your Azure OpenAI deployment. MCP and harness use verified in-cluster HTTPS with a chart-generated CA; keys use Kubernetes Secrets and protected operator files. Default-deny host/harness egress permits DNS and required same-release services; harness AOAI HTTPS is pinned to endpoint IPv4 /32s. Recheck pins when DNS changes. No Anthropic or OpenAI.com calls are allowed. Validate enforcement with the recipe's egress checks. Sessions share a kernel: trusted tenant only, no per-session VM boundary. One node has no HA; bundled PostgreSQL has no automatic backup or PITR.

Reset (irreversible): confirm backups or accept loss of all tenants, database, ledger, sessions and workspaces. Teardown deletes the release, namespace, both PVCs, AKS and managed node resource group; verifies its deletion; retains billable ACR/images, AOAI/deployment and protected operator state. Reinstall targets 30 minutes, not measured.

```
bash deploy/helm/daimon-selfhost/scripts/aks.sh teardown
```

Remove everything: deletes the dedicated group, budget, ACR and AOAI (even reused). Verify no node/data-disk group, disks or IPs remain before saying billing has stopped.

```
bash deploy/helm/daimon-selfhost/scripts/aks.sh remove
rm -r "$AKS_STATE"
```