PyMC Labs

Daimon on Azure — Coke IT install kit

Pilot: one AKS node, ACR Basic and Azure OpenAI (AOAI); PostgreSQL, workspaces, MCP and scheduler run in the cluster. Teams is off. Repository, reviewed `azure-selfhost` branch; full AKS recipe.

Before starting: use a DEDICATED Daimon resource group and budget, never a shared AOAI group. Reuse AOAI only if already in this dedicated group; otherwise create new. The helper cannot reuse AOAI from another group. Removal deletes everything in `RG`. Azure CLI must support az acr run; subscription policy must allow ACR Tasks. Helm 3.19+, kubectl, Python 3 and git are required; no local Docker/buildx is needed. RG Owner, or Contributor plus ACR role-assignment rights; cluster-admin is required. A subscription admin registers **Microsoft.ContainerService, Microsoft.ContainerRegistry, Microsoft.CognitiveServices, Microsoft.Compute, Microsoft.Network, Microsoft.Storage**. Approve privileged PodSecurity for the whole `daimon` namespace, not only the harness. Confirm Dsv6 CPU quota/capacity: **Standard_D2s_v6** pilot minimum, **Standard_D4s_v6** recommended for production; no B-series system pools. Use **eastus2 (US Data Zone)** or approved EU Data Zone; obtain **gpt-5.4-mini**, DataZoneStandard deployment/quota. Inference stays in that US/EU zone, not necessarily one region. AOAI local auth is required for this API-key path; disabling it requires a reviewed identity proxy.

Install: from the repository root, one shell; replace globally unique ACR/AOAI names. Keep `AKS_STATE` private (contains keys); retain it for reinstall. No shell tracing.

```
export RG=daimon-selfhost LOCATION=eastus2
export ACR=daimoncoke12345 AKS=daimon-coke AOAI=daimon-coke-12345
export AOAI_DEPLOYMENT=gpt-5.4-mini
export AKS_STATE=$(mktemp -d)
bash deploy/helm/daimon-selfhost/scripts/aks.sh bootstrap
bash deploy/helm/daimon-selfhost/scripts/aks.sh install
bash deploy/helm/daimon-selfhost/scripts/aks.sh probe
```

Bootstrap saves its image tag in `AKS_STATE`; uploads source to ACR Tasks. Remote BuildKit builds/pushes both images (build timeout: 2 hours), mirrors PostgreSQL, creates AKS/network/disks/public IP and AOAI if absent. Build pulls pinned Docker Hub frontend **docker/dockerfile:1.7.0**. Helm installs Secrets, TLS, policies, PVCs; waits for migrations/Ready pods. **Probe is paid:** two short **gpt-5.4-mini** turns write then read a file; tokens are billed. **App admission stays off until Register and run**; follow its registration, application turns and egress checks. Sample billing rates are TEST rates.

Cost: observed node compute ≈ **US$2.30/day (~$70/month)**. Plan **$100–170/month** for one pilot including disks/network/ACR, plus model tokens/builds/egress; unverified planning range, not a quote. Confirm region/contract and budgets. AKS Free has no SLA.

Security trade-offs: public AKS API and public AOAI endpoint (no Private Endpoint), public-IP node egress; Docker Hub pulls/imports (Postgres, curl probe, BuildKit frontend). Kubernetes Secrets/local key files replace Key Vault. The whole namespace permits privileged PodSecurity. Sessions share a kernel: trusted tenant only, no per-session VM. One node has no HA; bundled PG has no automatic backups/PITR. Data stays in your tenant; inference uses AOAI. MCP/harness use verified chart-CA HTTPS. Default-deny egress pins AOAI IPv4 /32s; refresh when DNS changes. Validate recipe egress checks: no Anthropic/OpenAI.com.

Reset (irreversible): confirm backups or accept loss of all tenants, ledger, sessions and workspaces. Teardown deletes release, namespace, both PVCs/data, AKS and managed node RG; verifies deletion. Retains billable ACR/images, AOAI/deployment and protected state. Reinstall independently measured: about **7 minutes from cluster create to first reply**; follow the recipe's register/turn steps after reinstall to restore application access.

```
bash deploy/helm/daimon-selfhost/scripts/aks.sh teardown
time bash deploy/helm/daimon-selfhost/scripts/aks.sh reinstall
```

Remove everything: deletes all of `RG`, including budget, AKS, ACR and reused AOAI. Verify no node/data-disk RG, disks or IPs remain before saying billing has stopped.

```
bash deploy/helm/daimon-selfhost/scripts/aks.sh remove
rm -r "$AKS_STATE"
```