

---

# **AIMBAT Documentation**

***Release 0.1.2***

**Lay Kuan Loh, Xiaoting Lou, & Suzan van der Lee**

May 22, 2014



## CONTENTS

<b>1</b>	<b>Introduction</b>	<b>3</b>
<b>2</b>	<b>Installing Dependencies</b>	<b>5</b>
2.1	Getting your operating system . . . . .	5
2.2	Installing Python . . . . .	5
2.3	Python Dependencies . . . . .	5
<b>3</b>	<b>Installing AIMBAT</b>	<b>7</b>
3.1	Getting the Packages . . . . .	7
<b>4</b>	<b>Standing Order for Data (SOD)</b>	<b>9</b>
4.1	Installing SOD . . . . .	9
4.2	Downloading Data with SOD . . . . .	10
<b>5</b>	<b>Analyzing Data</b>	<b>13</b>
5.1	Seismic Analysis Code (SAC) . . . . .	13
<b>6</b>	<b>Picking Travel Times</b>	<b>15</b>
<b>7</b>	<b>Indices and tables</b>	<b>17</b>



Contents:



## **INTRODUCTION**

AIMBAT (Automated and Interactive Measurement of Body wave Arrival Times) is an open-source software package for efficiently measuring teleseismic body wave arrival times for large seismic arrays [LouVanderleeLloyd2013-SeismologicalResearchLetters]. It is based on a widely used method called MCCC (Multi-Channel Cross-Correlation) [VandecarCrosson1990-BulletinSeismologicalSocietyOfAmerica]. The package is automated in the sense of initially aligning seismograms for MCCC which is achieved by an ICCS (Iterative Cross Correlation and Stack) algorithm. Meanwhile, a GUI (graphical user interface) is built to perform seismogram quality control interactively. Therefore, user processing time is reduced while valuable input from a user's expertise is retained. As a byproduct, SAC [GoldsteinDodgeFirpo2003-InternationalGeophysics] plotting and phase picking functionalities are replicated and enhanced.

Modules and scripts included in the AIMBAT package were developed using [Python programming language](#) and its open-source modules on the Mac OS X platform since 2009. The original MCCC [VandecarCrosson1990-BulletinSeismologicalSocietyOfAmerica] code was transcribed into Python. The GUI of AIMBAT was inspired and initiated at the [2009 EarthScope USArray Data Processing and Analysis Short Course](#). AIMBAT runs on Mac OS X, Linux/Unix and Windows thanks to the platform-independent feature of Python. It has been tested on Mac OS 10.6.8 and 10.7 and Fedora 16.

The AIMBAT software package is distributed under the [GNU General Public License Version 3 \(GPLv3\)](#) as published by the Free Software Foundation.





## INSTALLING DEPENDENCIES

### 2.1 Getting your operating system

You may need to know .. image:: installing-images/system\_preferences.png

### 2.2 Installing Python

Shaowei Lin suggested Enthought Canopy to install all the Python packages easily. If you download the free version of Enthought Canopy, it gives you everything you need for installing AIMBAT properly. If you do not want to use Enthought Canopy, read the rest of this section to use Macports or Pip.

### 2.3 Python Dependencies

- Numpy
- Scipy
- Matplotlib
- iPython (optional)



## INSTALLING AIMBAT

### 3.1 Getting the Packages

AIMBAT is released as a sub-package of `pysmo` in the name of `pysmo.aimbat` along with another sub-package `pysmo.sac`. The latest releases of `pysmo.sac` and `pysmo.aimbat` are available for download at the [official project webpage](#) and [Github](#).

The packages should be installed into the Python site-packages directory. To find out where that is, in the python console, do:

```
import site;
site.getsitepackages()
```

Whatever is output there, lets call it `<pkg-install-dir>`. You can choose to install AIMBAT either locally or globally, depending on whether you want all users of the computer to have access to it.

Make a directory called `pysmo`, and place the `sac` and `aimbat` directories there.

Now that we know the location of the site-packages direction, `cd` into it. Call the path to it `<pkg-install-dir>`. Notice that in this case, the site-packages has been installed for all users on the computer, not just the current user's home directory.

Put the two Python packages inside the directory.




## STANDING ORDER FOR DATA (SOD)

### 4.1 Installing SOD


First, download [SOD](#).

Once you have gotten the folder for SOD, put it somewhere where you won't touch it too much. What I did was put the SOD folder in my home directory, though other places are acceptable as well, as long as its not too easy to delete it by accident.

A screenshot of a macOS terminal window titled "lkloh — bash — 80x24". The terminal shows a user at "LKS-MacBook-Pro" with a prompt "sod lkloh\$". They enter "cd" and then "ls". The output of "ls" is a three-column list of files and directories: AI-Intro, Cascades-2014, Cascades-BigFiles, Cascades-Fall-2013, Cascades-SESUR-2012, Desktop, Documents, Downloads, Dropbox, Library, Movies, Music, Pictures, Public, classify, pysmo, and sod-3.2.3. The prompt returns to "LKS-MacBook-Pro:~ lkloh\$".

```
LKS-MacBook-Pro:sod lkloh$ cd
LKS-MacBook-Pro:~ lkloh$ ls
AI-Intro           Documents          Pictures
Cascades-2014      Downloads         Public
Cascades-BigFiles  Dropbox           classify
Cascades-Fall-2013 Library           pysmo
Cascades-SESUR-2012 Movies            sod-3.2.3
Desktop           Music
LKS-MacBook-Pro:~ lkloh$
```

Once you have it there, get the path to the sod folder's bin and put it in your path folder.



Inside my home directory's bash profile (you get the by typing `cd`), you put the path to `sod-3.2.3/bin` by adding in either the `bash` or `bash_profile` or `profile` files:

## 4.2 Downloading Data with SOD

**Authors** Trevor Bollmann

1. Create a sod recipe and place it in the folder that you would like the data to download to.

- `sod -f <recipename>.xml`

2. Run verb "sodcut.sh" to cut the seismogram around phase wanted

- check model within `cutevseis.sh`
- run using `sodcut.sh <name>`
- watch `sdir` = processed seismograms
- Run over the entire downloaded directory (the files sod downloaded)

3. Run `sodpkl.sh` (converts `.sac` files to python pickles)

- run using `sodpkl.sh [options] <directory>`
- output will automatically be zipped
- run in DATA directory

4. Run `ttpick.py` (does travel time picking with plotting)

- can use `iccs.py` but it does not have plotting capabilities
- run using `ttpick.py [options] <pkl.gz file>`
- do this one event at a time
- use `sacp2` to look at the stacking of the seismograms
- you can sort the seismograms using the `-s` flag

5. **run *getsta.py* (creates a *loc.sta* file)**

- *getsta.py [options] <pkl.gz.files>*

6. **Run EITHER of these:**

- **FIRST CHOICE**

- run *mccc2delay.py* (converts mccc delays to actual delays) by doing *mccc2delay.py [option] <.mcp.files>*

- **run *getdelay.py* (creates a delay file) by doing *getdelay.py [options] <\*.px>***

- Can possibly use *doplotsta.sh*, plots all of the events and their station delays

- Run *evmcdelay.sh*

- **SECOND CHOICE**

- verb "ttcheck.py" to compare the delay times of the p and s waves. Should form a nice cloud with the mean value in line with the cloud.

7. **If you need to remove a station from an event you can use verb "pklsel.py"**

- Run using verb "pklsel.py [pkl file] -d [stnm]" to remove one station
- Only works for one event at a time

8. **If you need to filter the data to be able to pick use verb "evsacbp.sh"**

- run using verb "evsacbp.sh [pkl file] bp1 bp2"
- Automatically uses two corners
- run in the whole downloaded directory (the one with the sac directory)





## ANALYZING DATA

### 5.1 Seismic Analysis Code (SAC)

SAC is used.



## PICKING TRAVEL TIMES

Hello, World! I love picking travel times manually!



## INDICES AND TABLES

- *genindex*
- *modindex*
- *search*