



35. 5

Dimensions:

LxWxH:120x60x35.5 (mm)

Model	INPUT	OUTPUT
GF65I-US1250 GF65I-US1543 GF65I-US1640 GF65I-US1836 GF65I-US1934 GF65I-US2032 GF65I-US2427	90-264VAC (50-60HZ)	12V 5.0A 15V 4.3A 16V 4.0A 18V 3.6A 19V 3.4A 20V 3.25A 24V 2.7A

SWITCHING AC ADAPTER

GF65 I - USTYPE

DESCRPTION:

- 65W AC/DC Adapter
- Universal Input
- Desktop Type (IEC 320 C14)
- Power Saving < 0.5 W

MEET SAFETY:

CB, PSE, UL, cUL, FCC, CE, CEC

GENERAL SPECIFICATIONS:

Maximum Output Power: 65W Input Voltage: 90~264VAC 47Hz~63Hz Input Frequency: **Inp Input Current:** 1.35A Leakage Current(max): 0.75mA Efficiency: 80% Ripple Noise(max): 240mVp-p Line Regulation: $\pm 1\%$ Load Regulation: $\pm 5\%$ Hold-Up Time: 10**ms Over Voltage Protection:** 120% **Over Current Protection:** 120%~200% **Operating Temperature:** 0~40℃ **Operating Relative Humidity:** 20~95%RH **Storage Temperature:** -20~80℃ Storage Humidity: 20~95%RH

Withstand voltage: 3KVAC/min
Weight: 300g

Cable type: UL2468 16AWG or 18AWG

GO FORWARD ENTERPRISE CORP.

Head Office:

NO.328, Siangyang Road, Fongyan City, Taichung County 420, Taiwan R.O.C

TEL:04-2529-2612 FAX:04-2529-2614

 $\hbox{E-mail:sevice} @ go forward.com.tw / sales @ go forward.com.tw \\$

http://www.goforward.tw/jp