

Standard Interconnection Application

Persons interested in applying for the interconnection of a distributed energy resource (DER) to the Utility's distribution system through the Fast Track Process or Study Process are to fill out this interconnection application. The interconnection application is to be filled out completely by the Applicant or as noted in each section of the application. **A non-refundable application fee will be drafted from the Member's account at the time of application submittal.** The Utility will contact the Applicant within 10 business days once the interconnection application and the corresponding processing fee is submitted to the Utility. The Utility will then notify the Applicant of the completeness of their application. If the application is deemed incomplete by the Utility, the Utility will provide the Applicant with a list of missing information. The Applicant will then have 10 business days to provide the Utility with this information or request an extension, otherwise the application will be deemed incomplete and the Applicant will lose their place in the queue. Sections that are noted with * are required to be filled out.

Checklist for Submission to Utility

The items below shall be included with submittal of the interconnection application to the Utility. Failure to include all items will deem the interconnection application incomplete.

	Included
One-line diagram: <ul style="list-style-type: none">This one-line diagram must be signed and stamped by a professional engineer licensed in Minnesota if the DER is uncertified greater than 20 kW AC or if certified system is over 250 kW.Details required on one-line diagram specified at the end of the Standard Interconnection Application.	<input type="checkbox"/> Yes
Schematic drawings for all protection and control circuits, relay current circuits, relay potential circuits, and alarm/monitoring circuits.	<input type="checkbox"/> Yes
Inverter specification sheet(s) (if applicable).	<input type="checkbox"/> Yes
Documentation that describes and details the operation of protection and control schemes.	<input type="checkbox"/> Yes
Documentation showing site control.	<input type="checkbox"/> Yes
Aerial map showing DER system layout including major roadways and true north.	<input type="checkbox"/> Yes

Non-refundable processing fee schedule.

Fast Track Process: (respective application fee will be charged to the Member's account)

- \$100 + \$1/kW for certified systems
- \$100 + \$2/kW for non-certified systems

Study Process: (check payment to Connexus Energy)

- \$1,000 + \$2/kW down payment. Additional study fees may apply.

<u>Possible Additional Documentation</u> <ul style="list-style-type: none"> • If the DER export capacity is limited, include information material explaining the limiting capabilities. • If energy storage is included with the proposed DER system, include the Energy Storage Application. 		
General*		
Select review process: <input type="checkbox"/> Fast Track Process <input type="checkbox"/> Study Process		
Application is for:	<input type="checkbox"/> New DER	<input type="checkbox"/> Capacity addition or material modification to existing DER
If capacity addition or material modification to existing facility, please describe:		
DER will be used for what reason? (Check all that apply):		
<input type="checkbox"/> Net Metering <input type="checkbox"/> Supply Power to Interconnection Customer <input type="checkbox"/> Supply Power to Area EPS		
Installed DER system cost (before incentives):		\$
Interconnection Customer*		
Full name (must match the name of the existing service account):		
Account number:		Meter number:
Mailing address:		
City:	State:	Zip code:
Email:		Telephone Number:

**Indicates section must be completed.*

Application Agent*	
Is the Interconnection Customer using an Application Agent for this application?	<input type="checkbox"/> Yes <input type="checkbox"/> No
<i>If Interconnection Customer is not using an Application Agent, please proceed to the next section.</i>	
Application Agent:	
Company name:	
Email:	Telephone Number:
DER Information*	
Estimated installation date:	
Location (if different from mailing address of Interconnection Customer):	
Will the proposed DER system be interconnected to an existing electric service?	<input type="checkbox"/> Yes <input type="checkbox"/> No
Is the DER a single unit or multiple units?	<input type="checkbox"/> Single <input type="checkbox"/> Multiple
DER type (<i>check all that apply</i>):	
<input type="checkbox"/> Solar Photovoltaic	<input type="checkbox"/> Wind
<input type="checkbox"/> Combined Heat and Power	<input type="checkbox"/> Energy Storage
<input type="checkbox"/> Solar Thermal	<input type="checkbox"/> Other (please specify)
<i>DER systems with energy storage must also submit the Energy Storage Application to the Utility.</i>	
Total number of DER's to be interconnected pursuant to this interconnection application:	
Phase configuration of DER(s):	<input type="checkbox"/> Single-Phase <input type="checkbox"/> Three-Phase
Type of generator:	<input type="checkbox"/> Inverter <input type="checkbox"/> Synchronous <input type="checkbox"/> Induction
Aggregate DER capacity (the sum of nameplate capacity of all generation and storage devices at the point of common coupling):	
kW_{ac}	kVA_{ac}

* Indicates section must be completed.

Export Capacity Limitation*	
Is the export capability of the DER limited?	<input type="checkbox"/> Yes <input type="checkbox"/> No
<i>If the DER export capacity is limited, complete the following sections and include information material explaining the limiting capabilities.</i>	
Maximum physical export capacity requested.	kW_{ac}
If Yes, please provide additional details describing method of export limitation:	
Load Information*	
Interconnection Customer's or customer-sited load:	kW_{ac}
Typical reactive load (if known):	
Equipment Certification*	
Is the DER equipment certified?	<input type="checkbox"/> Yes <input type="checkbox"/> No
<i>Please list all IEEE Standard 1547 certified equipment below. Include all certified equipment manufacturer specification sheets with the Standard Interconnection Application submission.</i>	
Equipment type	Certifying entity
1	
2	
3	
4	

Prime Mover*

Please indicate the prime mover:

- | | | |
|---|---------------------------------------|---|
| <input type="checkbox"/> Solar Photovoltaic | <input type="checkbox"/> Microturbine | <input type="checkbox"/> Fuel Cell |
| <input type="checkbox"/> Reciprocating Engine | <input type="checkbox"/> Gas Turbine | <input type="checkbox"/> Other (please specify) |

Is the prime mover compatible with certified protection equipment package?	<input type="checkbox"/> Yes <input type="checkbox"/> No
--	--

DER manufacturer:

Model name & number:

Version:

List of adjustable set points for protection equipment or software:

Summer name plate rating: kW_{ac}

Winter name plate rating: kVA_{ac}

Rated power factor:

Leading:

Lagging:

A completed power system load flow data sheet must be supplied with the Standard Interconnection Application.

Only appropriate sections beyond this point until the signature page are to be completed.

DER Characteristic Data (for Inverter-Based Machines)

Max design fault contribution current:

Is your response to the previous field an instantaneous or RMS measurement?

☐ Instantaneous ☐ RMS

Harmonic characteristics:

Start-up requirements:

DER Characteristic Data (for Synchronous Machines)	
RPM at rated frequency:	Neutral grounding resistor:
Direct axis synchronous reactance, X_d :	Zero sequence reactance, X_0 :
Direct axis transient reactance, X'_d :	KVA base:
Direct axis subtransient reactance, X''_d :	Field volts:
Negative sequence reactance, X_2 :	Field amperes:
Please provide the appropriate IEEE model block diagram of excitation system, governing system, and power system stabilizer (PSS) in accordance with the regional reliability council criteria. A PSS may be determined to be required by applicable studies. A copy of the manufacturer's block diagram may not be submitted.	
DER Characteristic Data (for Induction Machines)	
RPM at rated frequency:	Neutral grounding resistor:
Motoring power (kW):	Exciting current:
Heating time constant:	Temperature rise:
Rotor resistance, R_r :	Frame size:
Stator resistance, R_s :	Design letter:
Stator reactance, X_s :	Reactive power required in Vars (no load):
Rotor reactance, X_r :	Reactive power required In Vars (full ;oad):
Magnetizing reactance, X_m :	Total rotating inertia, H:
Short circuit reactance, X''_d :	

Interconnection Facilities Information			
Will a transformer be used between the DER and the point of common coupling?			<input type="checkbox"/> Yes <input type="checkbox"/> No
Will the transformer be provided by the Interconnection Customer? If yes, please fill in the fields below.			<input type="checkbox"/> Yes <input type="checkbox"/> No
Proposed location of protective interface equipment on property:			
Transformer data (for Interconnection Customer-Owned transformer)			
What is the phase configuration of the transformer?			<input type="checkbox"/> Single-phase <input type="checkbox"/> Three-phase
Size (kVA):	Transformer impedance (%):		On kVA base:
Transformer volts: (primary)	Delta:	Wye:	Wye grounded:
Transformer volts: (secondary)	Delta:	Wye:	Wye grounded:
Transformer volts: (tertiary)	Delta:	Wye:	Wye grounded:
Transformer Fuse Data (or Interconnection Customer-Owned fuse)			
Manufacturer:	Type:	Size:	Speed:
Interconnecting Circuit Breaker (for Interconnection Customer-Owned circuit breaker)			
Manufacturer:		Type:	
Load rating (in amps):	Interrupting rating (in amps):	Trip speed (cycles):	
Interconnection Protective Relays (for microprocessor controlled relays)			
Set point function	Minimum	Maximum	

Interconnection Protective Relays (for relays with discrete components)			
Manufacturer:	Type:	Style/Catalog No.:	Proposed setting:
Manufacturer:	Type:	Style/Catalog No.:	Proposed setting:
Manufacturer:	Type:	Style/Catalog No.:	Proposed setting:
Manufacturer:	Type:	Style/Catalog No.:	Proposed setting:
Manufacturer:	Type:	Style/Catalog No.:	Proposed setting:
Current Transformer Data:			
Manufacturer:	Type:	Accuracy class:	Proposed ratio connection:
Manufacturer:	Type:	Accuracy class:	Proposed ratio connection:
Potential Transformer Data:			
Manufacturer:	Type:	Accuracy class:	Proposed ratio connection:
Manufacturer:	Type:	Accuracy Class:	Proposed ratio connection:

Interconnection Agreement*

Proposed DER interconnections that are also deemed qualifying facilities less than 40 kW AC under Minnesota Statute 216B.164 are eligible to sign the Utility's Uniform Contract for Cogeneration and Small Power Production Facilities. Included in this agreement are payment terms for excess power generated by the proposed DER system the Utility may purchase. In lieu of the Utility's Uniform Contract for Cogeneration and Small Power Production Facilities, the Interconnection Customer may choose to instead sign the Utility's Distribution Interconnection Agreement.

The Interconnection Customer requests an Interconnection Agreement to be executed in lieu of the Utility's Uniform Contract for Cogeneration and Small Power Production Facilities.

☐ Yes ☐ No

Disclaimers – Must be completed by Interconnection Customer*

	Initials
The Interconnection Customer has opportunities to request a timeline extension during the interconnection process. Failure by the Interconnection Customer to meet or request an extension for a timeline outlined in the interconnection process could result in a withdrawn queue position and the need to re-apply.	
Propose DER interconnection to the Utility's distribution submitted under the fast track process may be moved into the study process if engineering screens are failed during the Standard Interconnection Application review.	

Application Signature – Must be completed by Interconnection Customer*

I designate the individual or company listed as my Application Agent to serve as my agent for the purpose of coordinating with the Area EPS Operators on my behalf throughout the interconnection process.

Initials

I hereby certify that, to the best of my knowledge, the information provided in this application is true, and that I have appropriate site control in conformance with the interconnection process. I agree to abide by the terms and conditions of the interconnection process and will inform the Utility if the proposed DER system changes from the details listed in this Application. I accept the respective application processing fee charge to my utility account.

Applicant Signature:

Date:

Please print clearly or type and return completed along with any additional documentation.

Information Required on One-Line Diagram

A Standard Interconnection Application must include a site electrical one-line diagram showing the configuration of all distributed energy resource equipment, current and potential circuits, and protection and control schemes. The one-line diagram shall include:

- Applicant name
- Member account number
- Installer name and contact information
- Address where DER system will be installed — must match application address.
 - Be sure to list the address for the protective interface equipment if the protective interface equipment is located at a different address than the DER system.
- Correct positions of all equipment, including but not limited to panels, inverter, and DC/AC disconnect. Include distances between equipment, and any labeling found on equipment. Indicate new equipment.
- Method of interconnection. We will need to know where the connection is (ie. line side of main breaker in the service panel, junction box between the main service panel and meter, in the meter socket on the member side of the meter) and what piece of equipment is being used (ie. splicing taps, double lug in the meter socket, multi-tap lugs).
- Note indicating: 24/7 unescorted access for utility crews and equipment. Visible, lockable, readily accessible and labeled AC Disconnect located within 10' of utility meter.
- Review the Connexus Energy TSM for more information

This one-line diagram must be signed and stamped by a Minnesota licensed professional engineer if the distributed energy resource is larger than 20 kW (if uncertified) and 250 kW (if certified.)