

Py-Concurrency Issues

The first day of PyConES 2026 went perfectly. The welcome program printed without a single bug, the opening keynote started right on time, and everyone already has their badge hanging from the official lanyard.

But now comes the real challenge of the conference: **the schedule grid**.

There are five parallel rooms. And it's not like there are only a few options, no. Just in one Saturday afternoon slot, you'd have to choose between "Lazy imports and the art of interpreter procrastination," "Odyssey: From Contributor to Maintainer," "Can AI Build an Integration on Its Own? The Good, the Bad, and the Ugly," "Untangling the Web: Alternative Protocols with Python," "Tachyon: Python 3.15's Sampling Profiler is Faster Than Your Code," and "What Comes After Rust in the Python Ecosystem?" — and that's not even counting the other forty-something talks happening the rest of the weekend.

You want to see them all. Physically, you can't: if two talks overlap even by a minute, you have to pick one. And as a good pythonista, you're not going to decide "by eye" — you're going to write code to solve it.

Someone from the staff approaches you, looking a bit anxious:

—"Hey, you're the one who codes, right? We need to know, for the conference stats, what's the **maximum number of talks a single person could attend** today, without any of them overlapping."

You open your editor. You already know what's coming.

Problem Statement

You are given the schedule of all the talks for one day of PyConES: for each talk, its **start** and **end** time (in minutes since the start of the day, as integers).

A person can attend a talk only if it doesn't overlap with any other talk they've already decided to attend. Two talks are considered to **overlap** if one starts before the other ends (if a talk ends exactly when another one starts, they can be chained back-to-back — that is not considered an overlap).

Write a Python program that calculates the **maximum number of talks** a person can attend that day.

Input Format

- The first line contains an integer **n**, the number of talks.

- Each of the following n lines contains two integers $start$ and end , separated by a space, indicating the start and end minute of that talk.

Constraints

```
1 ≤ n ≤ 10^5  
0 ≤ start < end ≤ 10^4
```

Output Format

A single integer: the maximum number of non-overlapping talks that can be attended.

Sample Input 0

```
6  
0 30  
25 60  
40 70  
50 90  
80 100  
90 120
```

Sample Output 0

```
4
```

Explanation 0

One optimal selection is: $(0, 30)$, $(40, 70)$, $(80, 100)$, $(90, 120) \rightarrow 4$ non-overlapping talks. No combination allows attending 5 or more talks.