```
entry:
%0 = add i32 %W, 2, !dbg !23
%1 = add i32 %H, 2, !dbg !23
%2 = mul nsw i32 %CI, %N, !dbg !23
%3 = mul nsw i32 %2, %1, !dbg !23
%4 = mul nsw i32 %3, %0, !dbg !23
%5 = sext i32 %4 to i64, !dbg !23
%6 = shl nuw nsw i64 %5, 2, !dbg !23
%7 = load ptr, ptr @__TVMBackendAllocWorkspace, align 8, !dbg !23, !tbaa !24
%pad_temp = tail call ptr %7(i32 1, i32 %dev_id, i64 %6, i32 2, i32 32),
... !dbg !23
call void @llvm.assume(i1 true) [ "align"(ptr %pad_temp, i64 64) ], !dbg !23
%8 = icmp eq ptr %pad_temp, null, !dbg !23
br i1 %8, label %common.ret, label %for_begin_i0.preheader, !dbg !23, !prof
... !28
```

```
for_begin_i0.preheader:
%9 = icmp sgt i32 %N, 0, !dbg !23
br i1 %9, label %for_begin_i1.preheader.lr.ph, label %for_end_nn, !dbg !23,
... !prof !30
```

```
for_begin_i1.preheader.lr.ph:
%10 = icmp slt i32 %CI, 1
%invariant.gep = getelementptr i8, ptr %A, i64 -4
%11 = icmp slt i32 %W, -1
%12 = icmp slt i32 %H, -1
%or.cond.not196 = select i1 %10, i1 true, i1 %12
%brmerge = select i1 %or.cond.not196, i1 true, i1 %11
br i1 %brmerge, label %for_begin_ff.preheader.lr.ph, label
... %for_begin_i1.preheader.us.us.us.preheader, !prof !31
```

```
for_begin_i1.preheader.us.us.us.preheader:
%13 = mul i32 %0, %CI
%14 = mul i32 %13, %1
%15 = mul i32 %0, %1
%smax = tail call i32 @llvm.smax.i32(i32 %0, i32 1), !dbg !23
%16 = zext nneg i32 %smax to i64, !dbg !23
%17 = shl nuw nsw i64 %16, 2, !dbg !23
%18 = sext i32 %W to i64, !dbg !23
%19 = sext i32 %H to i64, !dbg !23
%20 = sext i32 %0 to i64, !dbg !23
%smax121 = tail call i32 @llvm.smax.i32(i32 %1, i32 1), !dbg !23
%21 = sext i32 %1 to i64, !dbg !23
%22 = zext nneg i32 %CI to i64, !dbg !23
%wide.trip.count132 = zext nneg i32 %N to i64, !dbg !23
%wide.trip.count127 = zext nneg i32 %CI to i64
%wide.trip.count122 = zext nneg i32 %smax121 to i64
%exitcond.peel.not = icmp ugt i32 %W, 2147483645
%23 = add nsw i64 %16, -1, !dbg !23
%xtraiter = and i64 %23, 1
%24 = icmp eq i32 %W, 0
%unroll_iter = and i64 %23, -2
%lcmp.mod.not = icmp eq i64 %xtraiter, 0
br label %for_begin_i1.preheader.us.us.us, !dbg !23
```

```
for_begin_i1.preheader.us.us.us:
%indvars.iv129 = phi i64 [ 0, %for_begin_i1.preheader.us.us.us.preheader
... ], [ %indvars.iv.next130,
... %for_begin_i1.for_end_i1_crit_edge.split.us.split.us.us.us ]
%25 = trunc nuw nsw i64 %indvars.iv129 to i32
%26 = mul i32 %14, %25
%27 = mul nuw nsw i64 %indvars.iv129, %22
br label %for_begin_i2.preheader.us.us.us.us, !dbg !23
```

```
for_begin_i2.preheader.us.us.us.us:
%indvars.iv124 = phi i64 [ %indvars.iv.next125,
... %for_begin_i2.for_end_i2_crit_edge.split.us.us.us.us.us.us ], [ 0,
... %for_begin_i1.preheader.us.us.us ]
%28 = trunc nuw nsw i64 %indvars.iv124 to i32
%29 = mul i32 %15, %28
%30 = add i32 %26, %29
%31 = add nuw nsw i64 %indvars.iv124, %27
%32 = trunc i64 %31 to i32
%33 = mul i32 %32, %H
%34 = add i32 %33, -1
%35 = mul nsw i64 %31, %21
br label %for_begin_i3.preheader.us.us.us.us.us.us, !dbg !23
```

```
for_begin_i3.preheader.us.us.us.us.us.us:
%indvars.iv118 = phi i64 [ %indvars.iv.next119,
... %for_begin_i3.for_end_i3_crit_edge.us.us.us.us.us.us ], [ 0,
... %for_begin_i2.preheader.us.us.us.us ]
%36 = trunc nuw nsw i64 %indvars.iv118 to i32
%37 = icmp sle i64 %indvars.iv118, %19
%38 = icmp ne i64 %indvars.iv118, 0
%39 = and i1 %38, %37
%40 = add nsw i64 %indvars.iv118, %35
%41 = mul nsw i64 %40, %20
%.fr.us.us.us.us.us.us = freeze i1 %39
br i1 %.fr.us.us.us.us.us.us, label %if_end3.us.us.us.us.us.us.peel, label
... %for_body_i3.us.us.us.us.us.us.preheader
```

```
if_end3.us.us.us.us.us.us.peel:
%46 = getelementptr inbounds float, ptr %pad_temp, i64 %41, !dbg !23
store float 0.000000e+00, ptr %46, align 4, !dbg !23, !tbaa !35
br i1 %exitcond.peel.not, label
... %for_begin_i3.for_end_i3_crit_edge.us.us.us.us.us.us, label
... %for_body_i3.us13.us.us.us.us.us.us.peel.next, !dbg !23, !prof !37
```

```
for_body_i3.us.us.us.us.us.us.preheader:
%42 = mul i32 %0, %36
%43 = add i32 %30, %42
%44 = sext i32 %43 to i64
%45 = shl nsw i64 %44, 2
%scevgep = getelementptr i8, ptr %pad_temp, i64 %45
tail call void @llvm.memset.p0.i64(ptr noundef nonnull align 4
... dereferenceable(1) %scevgep, i8 0, i64 %17, i1 false), !dbg !23, !tbaa !35
br label %for_begin_i3.for_end_i3_crit_edge.us.us.us.us.us.us, !dbg !23
```

```
for_body_i3.us13.us.us.us.us.us.us.peel.next:
%47 = add i32 %34, %36
%48 = mul nsw i32 %47, %W
%49 = sext i32 %48 to i64, !dbg !23
%invariant.gep171 = getelementptr float, ptr %invariant.gep, i64 %49, !dbg
... !23
%invariant.gep172 = getelementptr float, ptr %pad_temp, i64 %41, !dbg !23
br i1 %24, label
... %for_begin_i3.for_end_i3_crit_edge.us.us.us.us.us.us.loopexit.unr-lcssa,
... label %for_body_i3.us13.us.us.us.us.us.us, !dbg !23, !prof !38
```

```
for_body_i3.us13.us.us.us.us.us.us:
%indvars.iv = phi i64 [ %indvars.iv.next.1, %if_end3.us.us.us.us.us.us.us.1
... ], [ 1, %for_body_i3.us13.us.us.us.us.us.us.peel.next ]
%niter = phi i64 [ %niter.next.1, %if_end3.us.us.us.us.us.us.us.1 ], [ 0,
... %for_body_i3.us13.us.us.us.us.us.us.peel.next ]
%.not169 = icmp sgt i64 %indvars.iv, %18, !dbg !23
br i1 %.not169, label %if_end3.us.us.us.us.us.us.us, label
... %if_then2.us.us.us.us.us.us.us, !dbg !23
```

```
if_then2.us.us.us.us.us.us.us:
%gep = getelementptr float, ptr %invariant.gep171, i64 %indvars.iv, !dbg
... !23
%50 = load float, ptr %gep, align 4, !dbg !23, !tbaa !39
br label %if_end3.us.us.us.us.us.us.us, !dbg !23
```

```
if_end3.us.us.us.us.us.us.us:
%51 = phi float [ %50, %if_then2.us.us.us.us.us.us.us ], [ 0.000000e+00,
... %for_body_i3.us13.us.us.us.us.us.us ], !dbg !23
%gep173 = getelementptr float, ptr %invariant.gep172, i64 %indvars.iv, !dbg
... !23
store float %51, ptr %gep173, align 4, !dbg !23, !tbaa !35
%indvars.iv.next = add nuw nsw i64 %indvars.iv, 1, !dbg !23
%.not169.1.not = icmp slt i64 %indvars.iv, %18, !dbg !23
br i1 %.not169.1.not, label %if_then2.us.us.us.us.us.us.us.1, label
... %if_end3.us.us.us.us.us.us.us.1, !dbg !23
```

```
if_then2.us.us.us.us.us.us.us.1:
%gep.1 = getelementptr float, ptr %invariant.gep171, i64 %indvars.iv.next,
... !dbg !23
%52 = load float, ptr %gep.1, align 4, !dbg !23, !tbaa !39
br label %if_end3.us.us.us.us.us.us.us.1, !dbg !23
```

```
if_end3.us.us.us.us.us.us.us.1:
%53 = phi float [ %52, %if_then2.us.us.us.us.us.us.us.1 ], [ 0.000000e+00,
... %if_end3.us.us.us.us.us.us.us ], !dbg !23
%gep173.1 = getelementptr float, ptr %invariant.gep172, i64
... %indvars.iv.next, !dbg !23
store float %53, ptr %gep173.1, align 4, !dbg !23, !tbaa !35
%indvars.iv.next.1 = add nuw nsw i64 %indvars.iv, 2, !dbg !23
%niter.next.1 = add i64 %niter, 2, !dbg !23
%niter.ncmp.1 = icmp eq i64 %niter.next.1, %unroll_iter, !dbg !23
br i1 %niter.ncmp.1, label
... %for_begin_i3.for_end_i3_crit_edge.us.us.us.us.us.us.loopexit.unr-lcssa,
... label %for_body_i3.us13.us.us.us.us.us.us, !dbg !23, !prof !41, !llvm.loop !42
```

```
for_begin_i3.for_end_i3_crit_edge.us.us.us.us.us.us.loopexit.unr-lcssa:
%indvars.iv.unr = phi i64 [ 1, %for_body_i3.us13.us.us.us.us.us.us.peel.next
... ], [ %indvars.iv.next.1, %if_end3.us.us.us.us.us.us.us.1 ]
br i1 %lcmp.mod.not, label
... %for_begin_i3.for_end_i3_crit_edge.us.us.us.us.us.us, label
... %for_body_i3.us13.us.us.us.us.us.us.epil, !dbg !23, !prof !44
```

```
for_body_i3.us13.us.us.us.us.us.us.epil:
%.not169.epil = icmp sgt i64 %indvars.iv.unr, %18, !dbg !23
br i1 %.not169.epil, label %if_end3.us.us.us.us.us.us.us.epil, label
... %if_then2.us.us.us.us.us.us.us.epil, !dbg !23
```

```
if_then2.us.us.us.us.us.us.us.epil:
%gep.epil = getelementptr float, ptr %invariant.gep171, i64
... %indvars.iv.unr, !dbg !23
%54 = load float, ptr %gep.epil, align 4, !dbg !23, !tbaa !39
br label %if_end3.us.us.us.us.us.us.us.epil, !dbg !23
```

```
if_end3.us.us.us.us.us.us.us.epil:
%55 = phi float [ %54, %if_then2.us.us.us.us.us.us.us.epil ], [ 0.000000e+00,
... %for_body_i3.us13.us.us.us.us.us.us.epil ], !dbg !23
%gep173.epil = getelementptr float, ptr %invariant.gep172, i64
... %indvars.iv.unr, !dbg !23
store float %55, ptr %gep173.epil, align 4, !dbg !23, !tbaa !35
br label %for_begin_i3.for_end_i3_crit_edge.us.us.us.us.us.us, !dbg !23
```

```
for_begin_i3.for_end_i3_crit_edge.us.us.us.us.us.us:
%indvars.iv.next119 = add nuw nsw i64 %indvars.iv118, 1, !dbg !23
%exitcond123.not = icmp eq i64 %indvars.iv.next119, %wide.trip.count122,
... !dbg !23
br i1 %exitcond123.not, label
... %for_begin_i2.for_end_i2_crit_edge.split.us.us.us.us.us.us, label
... %for_begin_i3.preheader.us.us.us.us.us.us, !dbg !23, !prof !37
```

```
for_begin_i2.for_end_i2_crit_edge.split.us.us.us.us.us.us:
%indvars.iv.next125 = add nuw nsw i64 %indvars.iv124, 1, !dbg !23
%exitcond128.not = icmp eq i64 %indvars.iv.next125, %wide.trip.count127,
... !dbg !23
br i1 %exitcond128.not, label
... %for_begin_i1.for_end_i1_crit_edge.split.us.split.us.us.us, label
... %for_begin_i2.preheader.us.us.us.us, !dbg !23, !prof !37
```

```
for_begin_i1.for_end_i1_crit_edge.split.us.split.us.us.us:
%indvars.iv.next130 = add nuw nsw i64 %indvars.iv129, 1, !dbg !23
%exitcond133.not = icmp eq i64 %indvars.iv.next130, %wide.trip.count132,
... !dbg !23
br i1 %exitcond133.not, label %for_begin_nn.preheader, label
... %for_begin_i1.preheader.us.us.us, !dbg !23, !prof !37
```

```
for_begin_nn.preheader:
br i1 %9, label %for_begin_ff.preheader.lr.ph, label %for_end_nn, !dbg
... !23, !prof !46
```

```
for_begin_ff.preheader.lr.ph:
%56 = icmp slt i32 %CO, 1
%57 = add i32 %H, 3
%58 = sub i32 %57, %KH
%59 = add i32 %W, 3
%60 = sub i32 %59, %KW
%61 = icmp slt i32 %60, 1
%62 = icmp slt i32 %CI, 1
%63 = icmp slt i32 %KH, 1
%64 = icmp slt i32 %KW, 1
%65 = icmp slt i32 %58, 1
%or.cond184.not199 = select i1 %56, i1 true, i1 %65
%brmerge186 = select i1 %or.cond184.not199, i1 true, i1 %61
%brmerge188 = select i1 %brmerge186, i1 true, i1 %62
%brmerge190 = select i1 %brmerge188, i1 true, i1 %63
%brmerge192 = select i1 %brmerge190, i1 true, i1 %64
br i1 %brmerge192, label %for_end_nn, label
... %for_begin_ff.preheader.us.us.us.us.us.us.preheader, !prof !47
```

```
for_begin_ff.preheader.us.us.us.us.us.us.preheader:
%66 = sext i32 %0 to i64, !dbg !23
%67 = zext nneg i32 %KW to i64, !dbg !23
%68 = sext i32 %1 to i64, !dbg !23
%69 = zext nneg i32 %KH to i64, !dbg !23
%70 = zext nneg i32 %60 to i64, !dbg !23
%71 = zext nneg i32 %58 to i64, !dbg !23
%72 = zext nneg i32 %CI to i64, !dbg !23
%73 = zext nneg i32 %CO to i64, !dbg !23
%wide.trip.count167 = zext nneg i32 %N to i64, !dbg !23
%wide.trip.count162 = zext nneg i32 %CO to i64
%wide.trip.count157 = zext nneg i32 %58 to i64
%wide.trip.count152 = zext nneg i32 %60 to i64
%wide.trip.count147 = zext nneg i32 %CI to i64
%wide.trip.count142 = zext nneg i32 %KH to i64
%wide.trip.count137 = zext nneg i32 %KW to i64
%xtraiter200 = and i64 %wide.trip.count137, 1
%74 = icmp eq i32 %KW, 1
%unroll_iter203 = and i64 %wide.trip.count137, 2147483646
%lcmp.mod201.not = icmp eq i64 %xtraiter200, 0
br label %for_begin_ff.preheader.us.us.us.us.us.us, !dbg !23
```

```
for_begin_ff.preheader.us.us.us.us.us.us:
%indvars.iv164 = phi i64 [ 0,
... %for_begin_ff.preheader.us.us.us.us.us.us.preheader ], [ %indvars.iv.next165,
...
... %for_begin_ff.for_end_ff_crit_edge.split.us.split.us.split.us.split.us.split.u
...s.us.us.us.us.us.us ]
%75 = mul nuw nsw i64 %indvars.iv164, %73
%76 = mul nuw nsw i64 %indvars.iv164, %72
br label %for_body_ff.us.us.us.us.us.us.us.us.us.us.us, !dbg !23
```

```
for_body_ff.us.us.us.us.us.us.us.us.us.us.us:
%indvars.iv159 = phi i64 [ %indvars.iv.next160,
... %for_begin_yy.for_end_yy_crit_edge.split.us.split.us.split.us.split.us.us.us.u
...s.us.us.us.us.us.us.us.us ], [ 0, %for_begin_ff.preheader.us.us.us.us.us.us ]
%77 = add nuw nsw i64 %indvars.iv159, %75
%78 = mul nuw nsw i64 %77, %71
%79 = mul nuw nsw i64 %indvars.iv159, %72
br label %for_body_yy.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us, !dbg !23
```

```
for_body_yy.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us:
%indvars.iv154 = phi i64 [ %indvars.iv.next155,
... %for_begin_xx.for_end_xx_crit_edge.split.us.split.us.split.us.us.us.us.us.us.u
...s.us.us.us.us.us.us.us.us.us ], [ 0,
... %for_body_ff.us.us.us.us.us.us.us.us.us.us.us ]
%80 = add nuw nsw i64 %indvars.iv154, %78
%81 = mul nuw nsw i64 %80, %70
%invariant.gep181 = getelementptr inbounds float, ptr %conv2d_nchw, i64 %81,
... !dbg !23
br label
... %for_begin_rc.preheader.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us,
... !dbg !23
```

```
for_begin_rc.preheader.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us:
%indvars.iv149 = phi i64 [ %indvars.iv.next150,
... %for_begin_rc.for_end_rc_crit_edge.split.us.split.us.us.us.us.us.us.us.us.us.u
...s.us.us.us.us.us.us.us.us.us ], [ 0,
... %for_body_yy.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us ]
%gep182 = getelementptr inbounds float, ptr %invariant.gep181, i64
... %indvars.iv149
%invariant.gep176 = getelementptr float, ptr %pad_temp, i64 %indvars.iv149
%.promoted = load float, ptr %gep182, align 4, !tbaa !52
br label
... %for_begin_ry.preheader.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.
...us.us, !dbg !23
```

```
for_begin_ry.preheader.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.
...us:
%.lcssa.lcssa180 = phi float [ %.lcssa,
... %for_begin_ry.for_end_ry_crit_edge.split.us.us.us.us.us.us.us.us.us.us.us.us.u
...s.us.us.us.us.us.us.us.us ], [ %.promoted,
... %for_begin_rc.preheader.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us
... ]
%indvars.iv144 = phi i64 [ %indvars.iv.next145,
... %for_begin_ry.for_end_ry_crit_edge.split.us.us.us.us.us.us.us.us.us.us.us.us.u
...s.us.us.us.us.us.us.us.us ], [ 0,
... %for_begin_rc.preheader.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us
... ]
%82 = add nuw nsw i64 %indvars.iv144, %76
%83 = mul nsw i64 %82, %68
%84 = add nsw i64 %83, %indvars.iv154
%85 = add nuw nsw i64 %indvars.iv144, %79
%86 = mul nuw nsw i64 %85, %69
br label
... %for_begin_rx.preheader.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.
...us.us.us, !dbg !23
```

```
for_begin_rx.preheader.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.
...us.us:
%.lcssa179 = phi float [ %.lcssa,
... %for_begin_rx.for_end_rx_crit_edge.us.us.us.us.us.us.us.us.us.us.us.us.us.us.u
...s.us.us.us.us.us.us ], [ %.lcssa.lcssa180,
... %for_begin_ry.preheader.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.
...us.us ]
%indvars.iv139 = phi i64 [ %indvars.iv.next140,
... %for_begin_rx.for_end_rx_crit_edge.us.us.us.us.us.us.us.us.us.us.us.us.us.us.u
...s.us.us.us.us.us.us ], [ 0,
... %for_begin_ry.preheader.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.
...us.us ]
%87 = or i64 %indvars.iv139, %indvars.iv144
%88 = add nsw i64 %84, %indvars.iv139
%89 = mul nsw i64 %88, %66
%90 = add nuw nsw i64 %indvars.iv139, %86
%91 = mul nuw nsw i64 %90, %67
%gep177 = getelementptr float, ptr %invariant.gep176, i64 %89
%invariant.gep174 = getelementptr inbounds float, ptr %W1, i64 %91, !dbg !23
br i1 %74, label
... %for_begin_rx.for_end_rx_crit_edge.us.us.us.us.us.us.us.us.us.us.us.us.us.us.u
...s.us.us.us.us.us.us.unr-lcssa, label
... %for_body_rx.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us,
... !dbg !23, !prof !38
```

```
for_body_rx.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us:
%92 = phi float [ %103,
... %for_body_rx.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us
... ], [ %.lcssa179,
... %for_begin_rx.preheader.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.
...us.us.us ]
%indvars.iv134 = phi i64 [ %indvars.iv.next135.1,
... %for_body_rx.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us
... ], [ 0,
... %for_begin_rx.preheader.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.
...us.us.us ]
%niter204 = phi i64 [ %niter204.next.1,
... %for_body_rx.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us
... ], [ 0,
... %for_begin_rx.preheader.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.
...us.us.us ]
%93 = or i64 %87, %indvars.iv134, !dbg !23
%94 = and i64 %93, 4294967295, !dbg !23
%95 = icmp eq i64 %94, 0, !dbg !23
%.193 = select i1 %95, float 0.000000e+00, float %92, !dbg !23, !prof !28
%96 = getelementptr float, ptr %gep177, i64 %indvars.iv134, !dbg !23
%97 = load float, ptr %96, align 4, !dbg !23, !tbaa !35
%gep175 = getelementptr inbounds float, ptr %invariant.gep174, i64
... %indvars.iv134, !dbg !23
%98 = load float, ptr %gep175, align 4, !dbg !23, !tbaa !56
%99 = tail call float @llvm.fmuladd.f32(float %97, float %98, float %.193),
... !dbg !23
%indvars.iv.next135 = or disjoint i64 %indvars.iv134, 1, !dbg !23
%100 = getelementptr float, ptr %gep177, i64 %indvars.iv.next135, !dbg !23
%101 = load float, ptr %100, align 4, !dbg !23, !tbaa !35
%gep175.1 = getelementptr inbounds float, ptr %invariant.gep174, i64
... %indvars.iv.next135, !dbg !23
%102 = load float, ptr %gep175.1, align 4, !dbg !23, !tbaa !56
%103 = tail call float @llvm.fmuladd.f32(float %101, float %102, float %99),
... !dbg !23
%indvars.iv.next135.1 = add nuw nsw i64 %indvars.iv134, 2, !dbg !23
%niter204.next.1 = add i64 %niter204, 2, !dbg !23
%niter204.ncmp.1 = icmp eq i64 %niter204.next.1, %unroll_iter203, !dbg !23
br i1 %niter204.ncmp.1, label
... %for_begin_rx.for_end_rx_crit_edge.us.us.us.us.us.us.us.us.us.us.us.us.us.us.u
...s.us.us.us.us.us.us.unr-lcssa, label
... %for_body_rx.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us,
... !dbg !23, !prof !41
```

```
for_begin_rx.for_end_rx_crit_edge.us.us.us.us.us.us.us.us.us.us.us.us.us.us.u
...s.us.us.us.us.us.us.unr-lcssa:
%.lcssa.ph = phi float [ poison,
... %for_begin_rx.preheader.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.
...us.us.us ], [ %103,
... %for_body_rx.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us ]
%.unr = phi float [ %.lcssa179,
... %for_begin_rx.preheader.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.
...us.us.us ], [ %103,
... %for_body_rx.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us ]
%indvars.iv134.unr = phi i64 [ 0,
... %for_begin_rx.preheader.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.
...us.us.us ], [ %indvars.iv.next135.1,
... %for_body_rx.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us ]
br i1 %lcmp.mod201.not, label
... %for_begin_rx.for_end_rx_crit_edge.us.us.us.us.us.us.us.us.us.us.us.us.us.us.u
...s.us.us.us.us.us.us, label
... %for_body_rx.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.ep
...il, !dbg !23, !prof !44
```

```
for_body_rx.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.epil:
%104 = or i64 %87, %indvars.iv134.unr, !dbg !23
%105 = and i64 %104, 4294967295, !dbg !23
%106 = icmp eq i64 %105, 0, !dbg !23
%.193.epil = select i1 %106, float 0.000000e+00, float %.unr, !dbg !23,
... !prof !28
%107 = getelementptr float, ptr %gep177, i64 %indvars.iv134.unr, !dbg !23
%108 = load float, ptr %107, align 4, !dbg !23, !tbaa !35
%gep175.epil = getelementptr inbounds float, ptr %invariant.gep174, i64
... %indvars.iv134.unr, !dbg !23
%109 = load float, ptr %gep175.epil, align 4, !dbg !23, !tbaa !56
%110 = tail call float @llvm.fmuladd.f32(float %108, float %109, float
... %.193.epil), !dbg !23
br label
... %for_begin_rx.for_end_rx_crit_edge.us.us.us.us.us.us.us.us.us.us.us.us.us.us.u
...s.us.us.us.us.us.us, !dbg !23
```

```
for_begin_rx.for_end_rx_crit_edge.us.us.us.us.us.us.us.us.us.us.us.us.us.us.u
...s.us.us.us.us.us.us:
%.lcssa = phi float [ %.lcssa.ph,
... %for_begin_rx.for_end_rx_crit_edge.us.us.us.us.us.us.us.us.us.us.us.us.us.us.u
...s.us.us.us.us.us.us.unr-lcssa ], [ %110,
... %for_body_rx.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.ep
...il ], !dbg !23
%indvars.iv.next140 = add nuw nsw i64 %indvars.iv139, 1, !dbg !23
%exitcond143.not = icmp eq i64 %indvars.iv.next140, %wide.trip.count142,
... !dbg !23
br i1 %exitcond143.not, label
... %for_begin_ry.for_end_ry_crit_edge.split.us.us.us.us.us.us.us.us.us.us.us.us.u
...s.us.us.us.us.us.us.us.us, label
... %for_begin_rx.preheader.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.
...us.us.us, !dbg !23, !prof !37
```

```
for_begin_ry.for_end_ry_crit_edge.split.us.us.us.us.us.us.us.us.us.us.us.us.u
...s.us.us.us.us.us.us.us:
%indvars.iv.next145 = add nuw nsw i64 %indvars.iv144, 1, !dbg !23
%exitcond148.not = icmp eq i64 %indvars.iv.next145, %wide.trip.count147,
... !dbg !23
br i1 %exitcond148.not, label
... %for_begin_rc.for_end_rc_crit_edge.split.us.split.us.us.us.us.us.us.us.us.us.u
...s.us.us.us.us.us.us.us.us.us, label
... %for_begin_ry.preheader.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.
...us.us, !dbg !23, !prof !37
```

```
for_begin_rc.for_end_rc_crit_edge.split.us.split.us.us.us.us.us.us.us.us.us.u
...s.us.us.us.us.us.us.us.us:
store float %.lcssa, ptr %gep182, align 4, !tbaa !52
%indvars.iv.next150 = add nuw nsw i64 %indvars.iv149, 1, !dbg !23
%exitcond153.not = icmp eq i64 %indvars.iv.next150, %wide.trip.count152,
... !dbg !23
br i1 %exitcond153.not, label
... %for_begin_xx.for_end_xx_crit_edge.split.us.split.us.split.us.us.us.us.us.us.u
...s.us.us.us.us.us.us.us.us.us, label
... %for_begin_rc.preheader.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us,
... !dbg !23, !prof !37
```

```
for_begin_xx.for_end_xx_crit_edge.split.us.split.us.split.us.us.us.us.us.us.u
...s.us.us.us.us.us.us.us.us:
%indvars.iv.next155 = add nuw nsw i64 %indvars.iv154, 1, !dbg !23
%exitcond158.not = icmp eq i64 %indvars.iv.next155, %wide.trip.count157,
... !dbg !23
br i1 %exitcond158.not, label
... %for_begin_yy.for_end_yy_crit_edge.split.us.split.us.split.us.split.us.us.us.u
...s.us.us.us.us.us.us.us.us, label
... %for_body_yy.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us.us, !dbg !23, !prof !37
```

```
for_begin_yy.for_end_yy_crit_edge.split.us.split.us.split.us.split.us.us.us.u
...s.us.us.us.us.us.us.us:
%indvars.iv.next160 = add nuw nsw i64 %indvars.iv159, 1, !dbg !23
%exitcond163.not = icmp eq i64 %indvars.iv.next160, %wide.trip.count162,
... !dbg !23
br i1 %exitcond163.not, label
... %for_begin_ff.for_end_ff_crit_edge.split.us.split.us.split.us.split.us.split.u
...s.us.us.us.us.us.us, label %for_body_ff.us.us.us.us.us.us.us.us.us.us.us, !dbg
... !23, !prof !37
```

```
for_begin_ff.for_end_ff_crit_edge.split.us.split.us.split.us.split.us.split.us.u
...s.us.us.us.us.us:
%indvars.iv.next165 = add nuw nsw i64 %indvars.iv164, 1, !dbg !23
%exitcond168.not = icmp eq i64 %indvars.iv.next165, %wide.trip.count167,
... !dbg !23
br i1 %exitcond168.not, label %for_end_nn, label
... %for_begin_ff.preheader.us.us.us.us.us.us, !dbg !23, !prof !37
```

```
for_end_nn:
%111 = load ptr, ptr @__TVMBackendFreeWorkspace, align 8, !dbg !23, !tbaa
... !24
%112 = tail call i32 %111(i32 1, i32 %dev_id, ptr nonnull %pad_temp), !dbg
... !23
%.not = icmp ne i32 %112, 0, !dbg !23
%. = sext i1 %.not to i32, !dbg !23
br label %common.ret, !dbg !23
```

```
common.ret:
%common.ret.op = phi i32 [ -1, %entry ], [ %., %for_end_nn ]
ret i32 %common.ret.op, !dbg !23
```

CFG for 'conv_compute_' function