

The background of the slide is a complex network diagram. It consists of numerous nodes, represented by circles of various sizes and colors (grey, white, yellow, green, blue, orange, purple, pink), connected by thin grey lines. Some nodes are highlighted with larger, colored circles (yellow, green, blue, orange, purple, pink) and are surrounded by smaller nodes, suggesting hubs or clusters within the network. The overall structure is a dense, interconnected web of nodes and edges.

Lecture 7 · Random Networks I

Networks, Crowds and Markets

Today's Lecture

1. Wrapping-up centrality measures: PageRank and HITS.
2. Random graphs, Erdős–Rényi model.
3. Probability recap: binomial and Poisson distribution.

Recall: PageRank

Note

We define random walk on a directed graph in a natural way. The walk can only follow the direction of arrows.

Algebraically more complicated as A_G is not symmetric and the eigenvalues are complex.

- Web graph = directed network of pages and hyperlinks.
- Eigenvector centrality does not work directly in directed graphs with sinks or disconnected components.
- PageRank modifies the random walk with teleportation:

$$P_\alpha = \alpha P + (1 - \alpha) \frac{1}{N} \mathbf{1}\mathbf{1}^T,$$

where P is the transition matrix of the web, $\alpha \in (0, 1)$.

- Stationary distribution of P_α = PageRank vector.

Beyond PageRank: The HITS Algorithm


Goal: Identify both *authorities* and *hubs* in a directed network.

- A good **hub** points to many good **authorities**.
- A good **authority** is pointed to by many good **hubs**.

Beyond PageRank: The HITS Algorithm

Goal: Identify both *authorities* and *hubs* in a directed network.


- A good **hub** points to many good **authorities**.
- A good **authority** is pointed to by many good **hubs**.



Beyond PageRank: The HITS Algorithm

Goal: Identify both *authorities* and *hubs* in a directed network.

- A good **hub** points to many good **authorities**.
- A good **authority** is pointed to by many good **hubs**.



Context:

- Introduced by Jon Kleinberg (1999).
- Used originally to rank web pages within a *topic query*.
- Query-dependent — unlike PageRank, which is global.

Mathematics of HITS

Let A be the adjacency matrix ($A_{ij} = 1$ if $i \rightarrow j$).

Each node i has: **authority score** a_i , **hub score** h_i .

Mathematics of HITS

Let A be the adjacency matrix ($A_{ij} = 1$ if $i \rightarrow j$).

Each node i has: **authority score** a_i , **hub score** h_i .

They satisfy the mutual reinforcement relations:

$$\begin{cases} h \propto Aa, & \text{(hubs get votes from authorities)} \\ a \propto A^T h, & \text{(authorities get votes from hubs)} \end{cases}$$

Mathematics of HITS

Let A be the adjacency matrix ($A_{ij} = 1$ if $i \rightarrow j$).

Each node i has: **authority score** a_i , **hub score** h_i .

They satisfy the mutual reinforcement relations:

$$\begin{cases} h \propto Aa, & (\text{hubs get votes from authorities}) \\ a \propto A^\top h, & (\text{authorities get votes from hubs}) \end{cases}$$

Combining gives:

$$a \propto A^\top Aa, \quad h \propto AA^\top h.$$

Mathematics of HITS

Let A be the adjacency matrix ($A_{ij} = 1$ if $i \rightarrow j$).

Each node i has: **authority score** a_i , **hub score** h_i .

They satisfy the mutual reinforcement relations:

$$\begin{cases} h \propto Aa, & (\text{hubs get votes from authorities}) \\ a \propto A^\top h, & (\text{authorities get votes from hubs}) \end{cases}$$

Combining gives:

$$a \propto A^\top Aa, \quad h \propto AA^\top h.$$


- Take a and h to be **dominant eigenvectors** of $A^\top A$ and AA^\top .
- In the iterative HITS algorithm, a and h are renormalized at each step, so the proportionality becomes equality after scaling.
- Equivalent viewpoint: HITS computes the first left and right singular vectors of A .

Example: Hubs and Authorities in a Small Web

Adjacency matrix:

$$A = \begin{pmatrix} 0 & 1 & 1 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \\ 0 & 0 & 0 & 0 \end{pmatrix}$$

Graph representation:



Example: Hubs and Authorities in a Small Web


Adjacency matrix:

$$A = \begin{pmatrix} 0 & 1 & 1 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \\ 0 & 0 & 0 & 0 \end{pmatrix}$$

Iterative algorithm:

1. Initialize $a_i = h_i = 1$.
2. Repeat $a \leftarrow A^\top h$, normalize; $h \leftarrow Aa$, normalize.

Graph representation:




Example: Hubs and Authorities in a Small Web

Adjacency matrix:

$$A = \begin{pmatrix} 0 & 1 & 1 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \\ 0 & 0 & 0 & 0 \end{pmatrix}$$

Graph representation:



Iterative algorithm:

1. Initialize $a_i = h_i = 1$.
2. Repeat $a \leftarrow A^\top h$, normalize; $h \leftarrow Aa$, normalize.

Python demo:


```
import networkx as nx
G = nx.DiGraph()
G.add_edges_from([(1,2),(1,3),(2,3),(3,4)])
hubs, auth = nx.hits(G)
```

Example: Hubs and Authorities in a Small Web

Adjacency matrix:

$$A = \begin{pmatrix} 0 & 1 & 1 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \\ 0 & 0 & 0 & 0 \end{pmatrix}$$

Graph representation:



Iterative algorithm:

1. Initialize $a_i = h_i = 1$.
2. Repeat $a \leftarrow A^\top h$, normalize; $h \leftarrow Aa$, normalize.

Python demo:

```
import networkx as nx
G = nx.DiGraph()
G.add_edges_from([(1,2),(1,3),(2,3),(3,4)])
hubs, auth = nx.hits(G)
```

Interpretation:

- Node 1 \rightarrow strong hub (points to many).
- Node 4 \rightarrow strong authority (pointed to by many).

Random graphs and Erdős–Rényi model

Why random graphs?

Real networks (social, economic, financial) are noisy and constantly evolving. We need a simple *baseline model* to compare against.

Definition (Erdős–Rényi (ER) model)


$G(N, p)$: a random graph on N nodes where each of the $\binom{N}{2}$ possible edges appears independently with probability p .

Why random graphs?

Real networks (social, economic, financial) are noisy and constantly evolving. We need a simple *baseline model* to compare against.

Definition (Erdős–Rényi (ER) model)

$G(N, p)$: a random graph on N nodes where each of the $\binom{N}{2}$ possible edges appears independently with probability p .



Paul Erdős (1913 - 1996)



Alfréd Rényi (1921-1970)

Erdős and Rényi (1959–60) launched the probabilistic study of graphs.

$G(N, p)$ Model

Take $N = 4$ then the graph can have up to six edges. Each with distribution $\text{Bern}(p)$:



12



13



14



23



24



34

$$\mathbb{P}(\text{graph with edges } 12, 13, 14, 23, 24, 34) = p^2(1 - p)^4$$

If $p = \frac{1}{2}$, each graph appears with the same probability $\frac{1}{2^6} = \frac{1}{64}$.

Probability recap: Binomial

Definition

If $X \sim \text{Bin}(n, p)$ then

$$\mathbb{P}(X = k) = \binom{n}{k} p^k (1 - p)^{n-k}, \quad \mathbb{E}[X] = np, \quad \text{Var}(X) = np(1 - p).$$

Useful characterization: $X = \sum_{i=1}^n Z_i$ with independent $Z_i \sim \text{Bern}(p)$.

In the ER graph $G(N, p)$:

- Number of edges:

$$L \sim \text{Bin}\left(\binom{N}{2}, p\right).$$

- Degree of a fixed vertex v :

$$\deg(v) \sim \text{Bin}(N - 1, p).$$

Probability recap: Binomial

Definition

If $X \sim \text{Bin}(n, p)$ then

$$\mathbb{P}(X = k) = \binom{n}{k} p^k (1 - p)^{n-k}, \quad \mathbb{E}[X] = np, \quad \text{Var}(X) = np(1 - p).$$

Useful characterization: $X = \sum_{i=1}^n Z_i$ with independent $Z_i \sim \text{Bern}(p)$.

In the ER graph $G(N, p)$:

- Number of edges:

$$L \sim \text{Bin}\left(\binom{N}{2}, p\right).$$

- Degree of a fixed vertex v :

$$\deg(v) \sim \text{Bin}(N - 1, p).$$

Probability recap: Poisson (as Binomial limit)

Theorem

If $X_n \sim \text{Bin}(n, p_n)$ with $n \rightarrow \infty$ and $np_n \rightarrow \lambda > 0$, then

$$X_n \longrightarrow X \sim \text{Pois}(\lambda), \quad \mathbb{P}(X = k) = \frac{\lambda^k}{k!} e^{-\lambda}.$$

The approximation $\text{Bin}(n, p) \approx \text{Pois}(\lambda)$ for $\lambda = np$ is particularly good if p is small.

Example (Quick check)

For $n = 2000$, $p = 0.003$, $\lambda = np = 6$. Compare $\mathbb{P}(X = 0)$: Binomial $= (1 - p)^{2000} \approx 0.00245$ vs. Poisson $e^{-6} \approx 0.00248$ (very close).

Degree distribution in $G(N, p)$

If $p = \lambda/(N - 1)$, then, for any $v \in V$,

$$\deg(v) \sim \text{Bin}(N - 1, p) \approx \text{Pois}(\lambda).$$

- Mean degree: $\mathbb{E}[\deg(v)] = (N - 1)p$.
- $\mathbb{P}(\deg(v) = k) \approx \frac{\lambda^k}{k!} e^{-\lambda}$.

Note

This gives closed forms for expectations; Poisson is a great approximation when N is large and p small.