



UNC
GREENSBORO

CS 405/605 Data Science

Dr. Qianqian Tong

Course Schedule

Week 13: April 3 topic: Random Forest

April 5 topic: Validation

Project stage IV and V released, and the ddl will be April 28.

Week 14: April 10 topic: PCA

April 12 topic: Clustering-Kmeans

Week 15: April 17 topic: Visualization

April 19 topic: Visualization

HW3 will be released, and the ddl will be April 28.

Week 16: April 24 Project Presentation (4 groups, each will have 15-20 min)

April 26 Project Presentation (4 groups, each will have 15-20 min)

All reports and homework must be submitted by April 28, and graded by the final week.

K-means Clustering

Clustering:

- What is clustering?
- Types of clustering
- Clustering algorithm ----- k-means
- How can you do this efficiently?

K-means Clustering

Clustering:

- What is clustering?

K-means Clustering

Clustering:

Task 1 : Group These Set of Document into 3 Groups based on meaning

Doc1 : Health , Medicine, Doctor

Doc 2 : Machine Learning, Computer

Doc 3 : Environment, Planet

Doc 4 : Pollution, Climate Crisis

Doc 5 : Covid, Health , Doctor

K-means Clustering

Clustering:

Task 1 : Group These Set of Document into 3 Groups.

Doc1 : Health , Medicine, Doctor

Doc 2 : Machine Learning, Computer

Doc 3 : Environment, Planet

Doc 4 : Pollution, Climate Crisis

Doc 5 : Covid, Health , Doctor

K-means Clustering

Clustering:

Task 1 : Group These Set of Document into 3 Groups.

Doc1 : Health , Medicine, Doctor

Doc 5 : Covid, Health , Doctor

Doc 3 : Environment,
Planet

Doc 4 : Pollution, Climate
Crisis


Doc 2 : Machine
Learning, Computer

K-means Clustering

Clustering:

- What is clustering?

Finding groups of objects such that the objects in a group will be similar (or related) to one another and different from (or unrelated to) the objects in other groups.



K-means Clustering

Clustering:

- What is clustering?

Finding groups of objects such that the objects in a group will be similar (or related) to one another and different from (or unrelated to) the objects in other groups.

	<i>Supervised Learning</i>	<i>Unsupervised Learning</i>
<i>Discrete</i>	classification or categorization	clustering
<i>Continuous</i>	regression	dimensionality reduction

K-means Clustering

Clustering:


- Types of clustering
 - A *clustering* is a set of clusters
 - Important distinction between *hierarchical* and *partitional* sets of clusters
 - Hierarchical clustering
 - A set of nested clusters organized as a hierarchical Tree
 - Partitional Clustering
 - A division data objects into non-overlapping subsets (clusters) such that each data object is in exactly one subset

K-means Clustering


Clustering:

- Types of clustering

Hierarchical clustering



Nested Clusters




Dendrogram

K-means Clustering


Clustering:

- Types of clustering

Partitional Clustering



Original Points




A Partitional Clustering

K-means Clustering



Clustering:

- Types of clustering


Partitional Clustering




How many clusters?





Six Clusters




Notion of a Cluster can be Ambiguous!



Two Clusters



Four Clusters



K-means Clustering

Clustering:

- *Clustering Algorithms*
 - *K-means and its variants*
 - *Hierarchical clustering*
 - *Density-based clustering*
 - *Spectral clustering*


K-means Clustering

Clustering:

- *Clustering Algorithms*

- *K-means*

1. Ask user how many clusters they'd like. (e.g. $k=5$)




K-means Clustering

Clustering:

- *Clustering Algorithms*

- *K-means*

1. Ask user how many clusters they'd like. (e.g. $k=5$)
2. Randomly guess k cluster Center locations




K-means Clustering

Clustering:

- *Clustering Algorithms*

- *K-means*

1. Ask user how many clusters they'd like. (e.g. $k=5$)
2. Randomly guess k cluster Center locations
3. Each datapoint finds out which Center it's closest to.
(Thus each Center "owns" a set of datapoints)




K-means Clustering

Clustering:

- *Clustering Algorithms*

- *K-means*

1. Ask user how many clusters they'd like. (e.g. $k=5$)
2. Randomly guess k cluster Center locations
3. Each datapoint finds out which Center it's closest to.
4. Each Center finds the centroid of the points it owns




K-means Clustering

Clustering:

- *Clustering Algorithms*

- *K-means*

1. Ask user how many clusters they'd like. (e.g. $k=5$)
2. Randomly guess k cluster Center locations
3. Each datapoint finds out which Center it's closest to.
4. Each Center finds the centroid of the points it owns
5.and jumps there
6.Repeat until terminated!



K-means Clustering

Clustering:

- *Clustering Algorithms*

- *K-means*

-
- 1: Select K points as the initial centroids.
 - 2: **repeat**
 - 3: Form K clusters by assigning all points to the closest centroid.
 - 4: Recompute the centroid of each cluster.
 - 5: **until** The centroids don't change
-

K-means Clustering

Clustering:

- *Clustering Algorithms*
 - *K-means*
 1. *Partitional clustering approach*
 2. *Each cluster is associated with a centroid (center point)*
 3. *Each point is assigned to the cluster with the closest centroid*
 4. *Number of clusters, K , must be specified*
 5. *The basic algorithm is very simple*

K-means Clustering

Clustering:

- *Clustering Algorithms*
 - *K-means*
 - Strengths
 - Simple iterative method
 - User provides “K”
 - Weaknesses
 - Often too simple → bad results
 - Difficult to guess the correct “K”

K-means Clustering

Details:

- ❑ *Initial centroids are often chosen randomly.*
 - *Clusters produced vary from one run to another.*
- ❑ *The centroid is (typically) the mean of the points in the cluster.*
- ❑ *'Closeness' is measured by Euclidean distance, cosine similarity, correlation, etc.*
- ❑ Iterate:
 - Calculate distance from objects to cluster centroids.
 - Assign objects to closest cluster
 - Recalculate new centroids
- ❑ Stop based on convergence criteria
 - No change in clusters
 - Max iterations
- ❑ *Complexity is $O(n * K * I * d)$*
 - n = number of points, K = number of clusters,*
 - I = number of iterations, d = number of attributes*

K-means Clustering


Objective function in K-means

Sum of Squared Errors (SSE)

$$SSE = \sum_{i=1}^K \sum_{x \in C_i} dist^2(m_i, x)$$




x is a data point in cluster C_i and m_i is the centroid of cluster C_i

Convergence Curve



K-means Clustering


Determine numbers of clusters



Choose the one with the smallest SSE

K-means Clustering

Determine numbers of clusters



K-means Clustering

How can you do this efficiently?

- Idea 1: Be careful about where you start
- Idea 2: Do many runs of k-means, each from a different random start configuration
- Many other ideas floating around.

K-means Clustering

How can you do this efficiently?

- Idea 1: Be careful about where you start
- Idea 2: Do multiple runs of k-means, each from a different starting point

Neat trick:

- Manually place the first center on top of randomly chosen datapoint.
Place second center on datapoint that's as far away as possible from first center
:
Place j 'th center on datapoint that's as far away as possible from the closest of Centers 1 through $j-1$
:

Codes available on github:

<https://github.com/q-tong/CS405-605-Data-Science/blob/main/lecture/4.%20Clustering-KMeans.ipynb>