x86-64 Integer Registers

%rax	%eax	%r8	%r8d
%rbx	%ebx	%r9	%r9d
%rcx	%есх	%r10	%r10d
%rdx	%edx	%r11	%r11d
%rsi	%esi	%r12	%r12d
%rdi	%edi	%r13	%r13d
%rsp	%esp	%r14	%r14d
%rbp	%ebp	%r15	%r15d

Can reference low-order 4 bytes (also low-order 1 & 2 bytes)

Complete Memory Addressing Modes

Most General Form

D(Rb,Ri,S) Mem[Reg[Rb]+S*Reg[Ri]+D]

D: Constant "displacement" 1, 2, or 4 bytes

Rb: Base register: Any of 16 integer registers

Ri: Index register: Any, except for %rsp

S: Scale: 1, 2, 4, or 8 (why these numbers?)

Special Cases

(Rb,Ri) Mem[Reg[Rb]+Reg[Ri]]

D(Rb,Ri) Mem[Reg[Rb]+Reg[Ri]+D]

(Rb,Ri,S) Mem[Reg[Rb]+S*Reg[Ri]]

Address Computation Instruction

■ leaq Src, Dst

- Src is address mode expression
- Set Dst to address denoted by expression

Uses

- Computing addresses without a memory reference
 - E.g., translation of p = &x[i];
- Computing arithmetic expressions of the form x + k*y
 - k = 1, 2, 4, or 8

Example

```
long m12(long x)
{
   return x*12;
}
```

Converted to ASM by compiler:

```
leaq (%rdi,%rdi,2), %rax # t <- x+x*2
salq $2, %rax # return t<<2</pre>
```

Some Arithmetic Operations

Two Operand Instructions:

Format	Computation		
addq	Src,Dest	Dest = Dest + Src	
subq	Src,Dest	Dest = Dest – Src	
imulq	Src,Dest	Dest = Dest * Src	
salq	Src,Dest	Dest = Dest << Src	Also called shiq
sarq	Src,Dest	Dest = Dest >> Src	Arithmetic
shrq	Src,Dest	Dest = Dest >> Src	Logical
xorq	Src,Dest	Dest = Dest ^ Src	
andq	Src,Dest	Dest = Dest & Src	
orq	Src,Dest	Dest = Dest Src	

- Watch out for argument order!
- No distinction between signed and unsigned int (why?)

Some Arithmetic Operations

One Operand Instructions

```
incq Dest Dest = Dest + 1

decq Dest Dest = Dest - 1

negq Dest Dest = -Dest

notq Dest Dest = \sim Dest
```

See book for more instructions

Condition Codes (Explicit Setting: Compare)

- Explicit Setting by Compare Instruction
 - •cmpq Src2, Src1
 - **cmpq b**, **a** like computing **a**-**b** without setting destination
 - **CF set** if carry out from most significant bit (used for unsigned comparisons)
 - "ZF set if a == b
 - "SF set if (a-b) < 0 (as signed)</pre>
 - ■OF set if two's-complement (signed) overflow
 (a>0 && b<0 && (a-b)<0) | | (a<0 && b>0 && (a-b)>0)

Condition Codes (Explicit Setting: Test)

- Explicit Setting by Test instruction
 - testq Src2, Src1
 - •testq b,a like computing a&b without setting destination
 - Sets condition codes based on value of Src1 & Src2
 - Useful to have one of the operands be a mask
 - "ZF set when a&b == 0
 - ■SF set when a&b < 0

Jumping

■ jX Instructions


Jump to different part of code depending on condition codes

jX	Condition	Description
jmp	1	Unconditional
je	ZF	Equal / Zero
jne	~ZF	Not Equal / Not Zero
js	SF	Negative
jns	~SF	Nonnegative
jg	~(SF^OF)&~ZF	Greater (Signed)
jge	~(SF^OF)	Greater or Equal (Signed)
jl	(SF^OF)	Less (Signed)
jle	(SF^OF) ZF	Less or Equal (Signed)
ja	~CF&~ZF	Above (unsigned)
jb	CF	Below (unsigned)

x86-64 Linux Register Usage #1

■ %rax

- Return value
- Also caller-saved
- Can be modified by procedure
- %rdi, ..., %r9
 - Arguments
 - Also caller-saved
 - Can be modified by procedure
- %r10, %r11
 - Caller-saved
 - Can be modified by procedure



x86-64 Linux Register Usage #2

- %rbx, %r12, %r13, %r14
 - Callee-saved
 - Callee must save & restore
- %rbp
 - Callee-saved
 - Callee must save & restore
 - May be used as frame pointer
 - Can mix & match

■ %rsp

- Special form of callee save
- Restored to original value upon exit from procedure

