

Congestion-Approximators from the Bottom Up

Jason Li (CMU)
Joint with Satish Rao (Berkeley),
Di Wang (Google)

Max-Flow Problem

Given undirected (uncapacitated) graph
 $G=(V,E)$ and vector b in \mathbb{R}^V with $\sum b_v = 0$
want net flow b_v at each vertex v

Max-Flow Problem

Given undirected (uncapacitated) graph
 $G=(V,E)$ and vector b in \mathbb{R}^V with $\sum b_v = 0$

s-t max-flow: $b = \mathbf{1}_s - \mathbf{1}_t = \begin{bmatrix} +1 \\ 0 \\ \vdots \\ -1 \end{bmatrix}_{\begin{matrix} s \\ t \end{matrix}}$

Max-Flow Problem

Given undirected (uncapacitated) graph
 $G=(V,E)$ and vector b in \mathbb{R}^V with $\sum b_v = 0$

s-t max-flow: $b = \mathbf{1}_s - \mathbf{1}_t = \begin{bmatrix} +1 \\ 0 \\ \vdots \\ -1 \end{bmatrix}_{\begin{matrix} s \\ t \end{matrix}}$

Minimize congestion


= max amount of flow sent along any edge

Max-Flow Problem

Given undirected (uncapacitated) graph
 $G=(V,E)$ and vector b in \mathbb{R}^V with $\sum b_v = 0$

s-t max-flow: $b = \mathbf{1}_s - \mathbf{1}_t =$

$$\begin{bmatrix} +1 \\ 0 \\ \vdots \\ -1 \end{bmatrix} \begin{matrix} s \\ t \end{matrix}$$



$$b = \mathbf{1}_s - \mathbf{1}_t$$


Minimize congestion

= max amount of flow sent along any edge

Max-Flow Problem

Given undirected (uncapacitated) graph
 $G=(V,E)$ and vector b in \mathbb{R}^V with $\sum b_v = 0$

$$s-t \text{ max-flow: } b = \mathbf{1}_s - \mathbf{1}_t = \begin{bmatrix} +1 \\ 0 \\ \vdots \\ -1 \end{bmatrix}_{\mathbb{R}^V}$$



$$b = \mathbf{1}_s - \mathbf{1}_t$$

congestion = $1/3$

Minimize congestion

= max amount of flow sent along any edge


Flow/Cut Duality

Given a subset of vertices S , consider

$$\frac{|\partial S|}{|b(S)|} \leftarrow \frac{\text{size of boundary}}{|\sum_{v \in S} b_v|}$$

Flow/Cut Duality


Given a subset of vertices S , consider



$$\frac{\partial S}{|b(S)|} \leftarrow \text{size of boundary}$$
$$|b(S)| \leftarrow \left| \sum_{v \in S} b_v \right|$$

Flow/Cut Duality

Given a subset of vertices S , consider




$$\frac{\partial S}{|b(S)|} \leftarrow \sum_{v \in S} b_v$$

$\frac{\partial S}{|b(S)|} \leftarrow$ size of boundary
 $\sum_{v \in S} b_v$

Flow/Cut Duality

Given a subset of vertices S , consider




$$\frac{\partial S}{|b(S)|} \leftarrow \text{size of boundary}$$
$$|b(S)| \leftarrow \left| \sum_{v \in S} b_v \right|$$

$$\partial S = 2$$

$$|b(S)| = 2$$

Flow/Cut Duality

Given a subset of vertices S , consider



$$\frac{|\partial S|}{|\mathbf{b}(S)|} \leftarrow |\sum_{v \in S} \mathbf{b}_v|$$

net $|\mathbf{b}(S)|=2$ flow must

$$|\partial S|=2$$

go across $|\partial S|=2$ edges

$$|\mathbf{b}(S)|=2$$

\rightarrow any flow has congestion ≥ 1

Flow/Cut Duality

For any S ($b(S) \neq 0$), congestion $\geq \frac{|\partial S|}{|b(S)|}$

Flow/Cut Duality

For any S ($b(S) \neq 0$), congestion $\geq \frac{|\partial S|}{|b(S)|}$

Flow/Cut Duality: congestion = $\max_{S \subseteq V} \frac{|\partial S|}{|b(S)|}$

Flow/Cut Duality

For any S ($b(S) \neq 0$), congestion $\geq \frac{|\partial S|}{|b(S)|}$

Flow/Cut Duality: congestion $= \max_{S \subseteq V} \frac{|\partial S|}{|b(S)|}$

Congestion Approximator:

family \mathcal{C} of subsets S s.t.

congestion $\leq \alpha \cdot \max_{\substack{S \in \mathcal{C} \\ \text{quality}}} \frac{|\partial S|}{|b(S)|}$

Flow/Cut Duality

For any S ($b(S) \neq 0$), congestion $\geq \frac{|\partial S|}{|b(S)|}$

Flow/Cut Duality: congestion $= \max_{S \subseteq V} \frac{|\partial S|}{|b(S)|}$

Congestion Approximator:

family \mathcal{C} of subsets S s.t.

congestion $\leq \alpha \cdot \max_{\substack{S \in \mathcal{C} \\ \text{quality}}} \frac{|\partial S|}{|b(S)|}$ for **all** demands b $(b(V)=0)$

Approximate Max-Flow

[Sherman '13, '17] Given polylog-quality congestion approximator, can solve $(1+\varepsilon)$ -approximate congestion in $\tilde{O}(m/\varepsilon)$ with $\tilde{O}(\hat{m})$ representation size

Approximate Max-Flow

[Sherman '13, '17] Given polylog-quality congestion approximator, can solve $(1+\varepsilon)$ -approximate congestion in $\tilde{O}(m/\varepsilon)$ with $\tilde{O}(\hat{m})$ representation size

[Räcke, Shah, Taubig '14] Can compute polylog-quality congestion approximator by computing $(1+1/\text{polylog})$ -approximate max-flow on instances of total size $\tilde{O}(m)$

Approximate Max-Flow

[Sherman '13, '17] Given polylog-quality congestion approximator, can solve $(1+\varepsilon)$ -approximate congestion in $\tilde{O}(m/\varepsilon)$ with $\tilde{O}(\hat{m})$ representation size

[Räcke, Shah, Taubig '14] Can compute polylog-quality congestion approximator by computing $(1+1/\text{polylog})$ -approximate max-flow on instances of total size $\tilde{O}(m)$

Cyclic dependency! Resolved by [Peng '16] using recursive graph sparsification. Complicated algorithm

Approximate Max-Flow

[Sherman '13, '17] Given polylog-quality congestion approximator, can solve $(1+\varepsilon)$ -approximate congestion in $\tilde{O}(m/\varepsilon)$ with $\tilde{O}(\hat{m})$ representation size


[Räcke, Shah, Taubig '14] Can compute polylog-quality congestion approximator by computing $(1+1/\text{polylog})$ -approximate max-flow on instances of total size $\tilde{O}(m)$

Cyclic dependency! Resolved by [Peng '16] using recursive graph sparsification. Complicated algorithm

This work: polylog-quality congestion approximator without recursive max-flow

Our Congestion Approximator Construction


Theorem: Consider partitions P_1, P_2, \dots, P_L of V s.t.



Our Congestion Approximator Construction

Theorem: Consider partitions P_1, P_2, \dots, P_L of V s.t.

(1) $P_1 = \{\{v\} : v \in V\}$ is singletons and $P_L = \{V\}$ is single cluster



Our Congestion Approximator Construction


Theorem: Consider partitions P_1, P_2, \dots, P_L of V s.t.

(1) $P_1 = \{\{v\} : v \in V\}$ is singletons and $P_L = \{V\}$ is single cluster

(2) For each i and each cluster $C \in P_{i+1}$,

$\partial P_i \cap E[C] \cup \partial C$ "mixes" in $G[C]$

with congestion polylog



Our Congestion Approximator Construction


Theorem: Consider partitions P_1, P_2, \dots, P_L of V s.t.

(1) $P_1 = \{\{v\} : v \in V\}$ is singletons and $P_L = \{V\}$ is single cluster

(2) For each i and each cluster $C \in P_{i+1}$,

$\partial P_i \cap E[C] \cup \partial C$ "mixes" in $G[C]$

with congestion polylog



(3) For each i , there is a flow $\partial P_{i+1} \rightarrow \partial P_i$

with congestion polylog s.t.

each $e \in P_i$ sends 1 flow and

each $e \in P_{i+1}$ receives $\leq 1/2$ flow

Our Congestion Approximator Construction

Theorem: Consider partitions P_1, P_2, \dots, P_L of V s.t.

(1) $P_1 = \{\{v\} : v \in V\}$ is singletons and $P_L = \{V\}$ is single cluster

(2) For each i and each cluster $C \in P_{i+1}$,

$\partial P_i \cap E[C] \cup \partial C$ "mixes" in $G[C]$



with congestion polylog

(3) For each i , there is a flow $\partial P_{i+1} \rightarrow \partial P_i$

with congestion polylog s.t.

each $e \in P_i$ sends 1 flow and

each $e \in P_{i+1}$ receives $\leq 1/2$ flow



Our Congestion Approximator Construction

Theorem: Consider partitions P_1, P_2, \dots, P_L of V s.t.

(1) $P_1 = \{\{v\} : v \in V\}$ is singletons and $P_L = \{V\}$ is single cluster

(2) For each i and each cluster $C \in P_{i+1}$,

$\partial P_i \cap E[C] \cup \partial C$ "mixes" in $G[C]$



with congestion polylog

(3) For each i , there is a flow $\partial P_{i+1} \rightarrow \partial P_i$

with congestion polylog s.t.

each $e \in P_i$ sends 1 flow and

each $e \in P_{i+1}$ receives $\leq 1/2$ flow



Our Congestion Approximator Construction


Theorem: Consider partitions P_1, P_2, \dots, P_L of V s.t.

(1) $P_1 = \{\{v\} : v \in V\}$ is singletons and $P_L = \{V\}$ is single cluster

(2) For each i and each cluster $C \in P_{i+1}$,

$\partial P_i \cap E[C] \cup \partial C$ "mixes" in $G[C]$

with congestion Actual: slightly weaker polylog




(3) For each i , there is a flow $\partial P_{i+1} \rightarrow \partial P_i$

with congestion polylog s.t.

each $e \in P_i$ sends 1 flow and

each $e \in P_{i+1}$ receives $\leq 1/2$ flow



Our Congestion Approximator Construction


Theorem: Consider partitions P_1, P_2, \dots, P_L of V s.t.

(1) $P_1 = \{\{v\} : v \in V\}$ is singletons and $P_L = \{V\}$ is single cluster

(2) For each i and each cluster $C \in P_{i+1}$,

$\partial P_i \cap E[C] \cup \partial C$ "mixes" in $G[C]$ i=1

with congestion Actual: slightly weaker polylog




(3) For each i , there is a flow $\partial P_{i+1} \rightarrow \partial P_i$

with congestion polylog s.t.

each $e \in P_i$ sends 1 flow and

each $e \in P_{i+1}$ receives $\leq 1/2$ flow



Our Congestion Approximator Construction


Theorem: Consider partitions P_1, P_2, \dots, P_L of V s.t.

(1) $P_1 = \{\{v\} : v \in V\}$ is singletons and $P_L = \{V\}$ is single cluster

(2) For each i and each cluster $C \in P_{i+1}$,

$\partial P_i \cap E[C] \cup \partial C$ "mixes" in $G[C]$ with congestion polylog

Actual: slightly weaker




(3) For each i , there is a flow $\partial P_{i+1} \rightarrow \partial P_i$

with congestion polylog s.t.

each $e \in P_i$ sends 1 flow and

each $e \in P_{i+1}$ receives $\leq 1/2$ flow



Our Congestion Approximator Construction

Theorem: Consider partitions P_1, P_2, \dots, P_L of V s.t.

:

For each i , let $R_{\geq i}$ be the common refinement of partitions P_i, P_{i+1}, \dots, P_L


Then $\mathcal{C} = \bigcup_i R_{\geq i}$ is a congestion approximator with quality polylog.

Our Congestion Approximator Construction

Theorem: Consider partitions P_1, P_2, \dots, P_L of V s.t.

:

For each i , let $R_{\geq i}$ be the common refinement of partitions P_i, P_{i+1}, \dots, P_L



Then $\mathcal{C} = \bigcup_i R_{\geq i}$ is a congestion approximator with quality polylog.

Our Congestion Approximator Construction


Theorem: Consider partitions P_1, P_2, \dots, P_L of V s.t.

10

For each i , let $R_{\geq i}$ be the common refinement of partitions P_i, P_{i+1}, \dots, P_L

Then $\mathcal{C} = \cup_{i >= i} R_i$ is a congestion approximator with quality polylog .

$$C = \begin{pmatrix} 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \end{pmatrix} \in R_{\geq 1}$$



Constructing the Congestion Approximator

P_2 is an expander decomposition (doable)

Constructing the Congestion Approximator

P_2 is an expander decomposition (doable)

In general, use P_1, \dots, P_{i-1} to construct P_i

Constructing the Congestion Approximator

P_2 is an expander decomposition (doable)

In general, use P_1, \dots, P_{i-1} to construct P_i

Max-flow calls required, but use structure of P_1, \dots, P_{i-1} to build "pseudo"-congestion approximator sufficient for the specialized max-flow calls

Conclusion

**Bottom-up congestion approximator construction,
in contrast to top-down of [Räcke, Shah, Taubig '14]**

Conclusion

**Bottom-up congestion approximator construction,
in contrast to top-down of [Räcke, Shah, Taubig '14]**

No recursive max-flow required → cleaner algorithm

Conclusion

**Bottom-up congestion approximator construction,
in contrast to top-down of [Räcke, Shah, Taubig '14]**

No recursive max-flow required → cleaner algorithm

Number of polylog factors still high (unspecified).

Open question: reduce number of polylog factors?