

A 70-Vertex Lower Bound for Cubic Bipartite Counterexamples to the Erdos-Gyarfas Conjecture

Draft manuscript v0.2 - post-minor-revision - 17 August 2026

Abstract

The Erdos-Gyarfas conjecture asserts that every finite simple graph of minimum degree at least three contains a cycle whose length is a power of two. For cubic bipartite graphs, Tranquilli proved by certified exhaustive computation that every graph on at most 58 vertices contains a cycle of length 4, 8, or 16, giving a 60-vertex lower bound for a cubic bipartite counterexample. **We raise this lower bound from 60 to 70 by proving that every simple cubic bipartite graph on at most 68 vertices contains a C_4 , C_8 , or C_{16} .** The proof combines the theorem of O’Keefe and Wong that every cubic graph of girth 10 has at least 70 vertices with a triangle-rooted restricted-growth enumeration of linear symmetric v_3 -configurations on at most 34 points. We give a cap-independent coverage proof for the enumeration, prove the correctness of the C_8 and C_{16} pruning predicates, and exhaust both normalized triangle-rooted search trees at cap 34. The two searches contain 225,745 states and examine 28,199,959 candidate extensions in total, with zero completions. The finite exhaustion is accompanied by static certificate streams whose verifier reconstructs the complete proposal schedule and checks explicit local witnesses for rejected branches. The cap-34 depth-first search was also rebuilt and rerun directly from a fresh checkout of the immutable upstream source, reproducing the exact counters and decision-transcript hashes.

1 Introduction

The Erdos-Gyarfas conjecture asks whether every finite simple graph of minimum degree at least three contains a cycle whose length is a power of two [1]. The original minimum-degree-three problem remains open, but substantial progress is known in several complementary directions.

In general graphs, Verstraete proved the existence of sparse unavoidable sets of cycle lengths under a constant average-degree condition [4], and Liu and Montgomery later showed that sufficiently large average degree already forces a cycle whose length is a power of two [5]. The conjecture is also known for a growing collection of restricted classes. Gao and Shan proved the P_8 -free case [6], Hu and Shen extended this to P_{10} -free graphs [7], and Hegde, Sandeep and Shashank used computer assistance to reach P_{13} -free graphs [8]. Other positive results include 3-connected cubic planar graphs [9], claw-free classes [10], and diameter-two graphs [13].

The cubic setting has a separate computational and structural history. Markstrom used exhaustive computer search to show that any cubic counterexample must have at least 30 vertices [11]. Bensmail studied power-cycle spectra in cubic graphs, constructing arbitrarily large cubic graphs with no q -power cycles for every $q \geq 3$ and, for $q = 2$, arbitrarily large cubic graphs whose only power-of-two cycles have length 4, or only length 8 [12]. These results help place the present cubic-bipartite finite frontier in a broader structural context.

We now specialize to cubic bipartite graphs. Since every cycle in a bipartite graph has even length, a counterexample must in particular avoid C_4 , C_8 , and C_{16} . Tranquilli [3] recently

established by certified exhaustive computation that every simple cubic bipartite graph on at most 58 vertices contains at least one of these three cycles. Equivalently, any cubic bipartite counterexample has at least 60 vertices.

The present work retains the same incidence-geometric viewpoint but pushes the triangle-rooted search to a point cap of 34. A C_4 -free cubic bipartite graph is the Levi graph of a linear symmetric v_3 -configuration, and a C_6 becomes a Berge triangle. The key structural observation is that below 70 vertices a relevant connected cubic bipartite graph must contain a C_6 : if it did not, its girth would be at least 10; the girth-10 case is excluded below 70 by O'Keefe and Wong [2], and girth at least 12 is excluded by the cubic Moore bound. This reduces the problem to two normalized triangle-rooted search trees.

Theorem 1.1. Every simple cubic bipartite graph G with $|V(G)| \leq 68$ contains a simple cycle of length 4, 8, or 16.

Corollary 1.2. Any simple cubic bipartite counterexample to the Erdos-Gyarfas conjecture has at least 70 vertices.

No claim is made here about graphs on 70 or more vertices.

The computer-assisted proof is deliberately separated into three logically distinct tasks. First, every relevant target configuration must have a branch in one of the two restricted-growth search trees. Second, the cycle-detection predicates must not falsely prune such a branch. Third, the finite search trees must actually be exhausted. The static certificate is designed to make this final statement checkable independently of the original depth-first search.

2 Incidence configurations and Berge cycles

Let $G = (X, Y; E)$ be a connected cubic bipartite graph. Since

$$3|X| = |E| = 3|Y|,$$

we have $|X| = |Y| = v$.

Regard the elements of X as points. For each y in Y , take its neighborhood $N(y)$ as a block. Every block contains three points and every point belongs to three blocks. Thus one obtains a symmetric v_3 -incidence structure whose Levi graph is precisely G .

If G is C_4 -free, no two distinct blocks share two points, so the incidence structure is linear. In a linear incidence structure, a Berge cycle of length k corresponds to a simple cycle of length $2k$ in the Levi graph. In particular:

$$C_6 \leftrightarrow \text{Berge triangle}, C_8 \leftrightarrow \text{Berge 4-cycle}, C_{16} \leftrightarrow \text{Berge 8-cycle}.$$

3 A triangle is forced below 70 vertices

Lemma 3.1. Let H be a connected cubic bipartite graph with $|V(H)| < 70$. If H contains no C_4 and no C_8 , then H contains a C_6 .

Proof. Suppose, for contradiction, that H also contains no C_6 . Because H is bipartite, every cycle has even length, so the absence of cycles of lengths 4, 6 and 8 implies that the girth is at least 10.

If the girth is exactly 10, the theorem of O'Keefe and Wong [2] gives $|V(H)| \geq 70$, a contradiction.

It remains to exclude girth at least 12. Choose an edge uv . From each endpoint grow the nonbacktracking cubic tree away from the central edge uv , to depth 5. We claim that all vertices appearing in these two rooted trees are distinct.

First consider a collision within one rooted tree. Two distinct root-to-vertex paths of lengths $a, b \leq 5$ ending at the same vertex contain a cycle of length at most

$$a + b \leq 10,$$

contradicting girth at least 12. Next consider a collision between the two rooted trees. If a vertex reached at depth $a \leq 5$ from u coincides with a vertex reached at depth $b \leq 5$ from v , the two root paths together with the central edge contain a cycle of length at most

$$a + b + 1 \leq 11,$$

again contradicting girth at least 12. Hence the two depth-5 trees are disjoint and internally collision-free. Therefore

$$|V(H)| \geq 2(1 + 2 + 4 + 8 + 16 + 32) = 126,$$

again a contradiction. Thus H contains a C_6 .

Remark. Only the minimum-order statement $f(3,10) = 70$ is used from O'Keefe and Wong. No classification of the 70-vertex cubic girth-10 graphs is required.

4 The two normalized triangle roots

Let the target be a connected linear symmetric v_3 -configuration containing a Berge triangle. Relabel the three triangle points as 0, 1, 2. Under first-occurrence labeling the triangle blocks can be written

$$\{0,1,3\}, \{1,2,4\}, \{0,2,5\}.$$

Consider the third block through point 0. Linearity prevents it from containing 1, 2, 3 or 5. Among introduced labels, only 4 may therefore be reused. The third block through 0 is consequently either $\{0,4,6\}$ or $\{0,6,7\}$. Hence the two normalized roots are

$$R1 = \{\{0,1,3\}, \{1,2,4\}, \{0,2,5\}, \{0,4,6\}\},$$

$$R2 = \{\{0,1,3\}, \{1,2,4\}, \{0,2,5\}, \{0,6,7\}\}.$$

5 Restricted-growth enumeration

Fix a cap M . At every search state the introduced labels form an initial interval $0,1,\dots,m-1$. The search chooses the least introduced point p whose current degree is less than three. A new block through p is written $\{p,q,r\}$ with $p < q < r$.

First-occurrence labeling gives exactly three possible forms: old-old $\{p,q,r\}$ with $r < m$; old-new $\{p,q,m\}$; and new-new $\{p,m,m+1\}$. For fixed p , candidates are considered in lexicographic order of (q,r) . A candidate is rejected if it violates the degree bound, repeats a point pair, or creates a forbidden Berge 4- or 8-cycle.

The implementation uses both a point-label cap M and a block-count cap M ; completion is tested before the block-count cutoff.

5.1 Coverage

Proposition 5.1 (Restricted-growth coverage). Let $M \geq 8$. Let the target be a connected linear symmetric v_3 -configuration with $v \leq M$, containing a Berge triangle and no Berge cycle of length 4 or 8. Assume that the two cycle-rejection predicates are sound. Then one of the two rooted restricted-growth search trees with cap M contains a completed state isomorphic to the target.

Proof. Normalize a Berge triangle as in Section 4 and follow a branch consisting only of target blocks. At each stage let $0, \dots, m-1$ be the introduced target points, and let p be the least introduced point whose current degree is less than three. Maintain:

- (I1) every target block whose least point is smaller than p has already been inserted;
- (I2) among target blocks whose least point is p , the inserted blocks form a lexicographic initial segment;
- (I3) introduced target labels are precisely $0, \dots, m-1$, with new points labeled in first-occurrence order.

At the normalized root, point 0 is saturated and the least deficient point is $p = 1$. The root already contains $\{1, 2, 4\}$. The remaining target block through 1 cannot reuse 0 or 3, because $\{0, 1, 3\}$ already contains those pairs, and cannot reuse 2 or 4, because $\{1, 2, 4\}$ already contains those pairs. By linearity, if the remaining block is $\{1, q, r\}$ with $q < r$, then $q \geq 5$. Hence $(2, 4)$ precedes (q, r) lexicographically, establishing the nontrivial base case for (I2). The other invariants are immediate.

Assume the invariants at a later state. Since p is deficient, choose the lexicographically first missing target block with least point p , say $B = \{p, q, r\}$. No point smaller than p can occur in B , because every such introduced point is already saturated.

If both q and r are already introduced, the generator proposes the old-old block. If exactly one is new, first-occurrence labeling gives $\{p, q, m\}$. If both are new, it gives $\{p, m, m+1\}$. Thus the target block is always among the generated candidates.

Invariant (I2) prevents lexicographic pruning. The degree filter cannot reject a target block because the target is cubic, and the repeated-pair filter cannot reject it because the target is linear. Since the partial state together with B is a subconfiguration of the target and the target has no forbidden Berge 4- or 8-cycle, sound cycle predicates cannot reject B . The invariants are preserved after insertion, so induction produces a branch consisting entirely of target blocks.

If all currently introduced points were saturated while some target point remained unseen, the introduced points would support a nonempty proper union of Levi components, contradicting connectedness. Hence all target points are eventually introduced.

The point cap is safe because $v \leq M$ and first-occurrence labels never exceed $v-1$. The block cap is also safe: a symmetric v_3 -configuration has exactly v blocks. If $v < M$, completion occurs before the cap; if $v = M$, the M -th target block produces the complete configuration and completion is tested before the block-count cutoff. Thus the target reaches a completed state.

6 Correctness of the cycle-pruning predicates

The implementation uses two local predicates, `creates_C8` and `creates_C16`. They are called only after a candidate has passed the degree and repeated-pair tests, so the enlarged incidence structure remains linear. Proposition 5.1 needs only soundness, but both predicates are exact.

6.1 The C8 predicate

Lemma 6.1. For a structurally admissible candidate block t , `creates_C8( $t$ )` is true if and only if adding t creates a simple C_8 containing the new block vertex.

Proof. The predicate enumerates three pairwise distinct old blocks B_i, B_j, B_h and computes the four intersections $p_0 = t \text{ intersect } B_i, p_1 = B_i \text{ intersect } B_j, p_2 = B_j \text{ intersect } B_h$, and $p_3 = B_h \text{ intersect } t$. It accepts only when all four exist and are pairwise distinct. Then

$$T, p0, Bi, p1, Bj, p2, Bh, p3, T$$

is a simple 8-cycle. Conversely, any new simple 8-cycle containing the new block vertex T has exactly this form with three old block vertices, and the exhaustive ordered-block enumeration finds it.

6.2 Exact length-14 paths

Lemma 6.2. For two distinct old point vertices x and y , the helper routine `exact_path` succeeds if and only if the old Levi graph contains a simple path of exactly 14 edges from x to y .

Proof. Every recursive step follows one Levi incidence edge. The visited set contains both point and block vertices, so a successful branch cannot repeat a vertex. Success occurs only at depth 14 at the target, and reaching the target early is rejected. Conversely, the recursive neighbor enumeration can follow any given simple length-14 path; no vertex on such a path is blocked by the visited set and the target appears only at the final depth.

6.3 The C16 predicate

Lemma 6.3. For every structurally admissible candidate block t , `creates_C16(t)` is true if and only if adding t creates a simple C_{16} containing the new block vertex.

Proof. A candidate may contain one or two fresh points. A fresh point has no incident block in the old Levi graph, so it cannot be an endpoint of a positive-length old path. Likewise, if a new C_{16} containing the new block vertex T existed, neither of the two cycle edges incident with T could use a fresh point: deleting T would leave a length-14 old path starting at that fresh point, which is impossible. Therefore the two points of t used by any new C_{16} are necessarily old points, and Lemma 6.2 applies.

The predicate examines all three pairs of members of t . If two old members x, y are joined by a simple old path of length 14, adding the new block vertex T and the two incidence edges Tx, Ty closes that path into a simple 16-cycle. Conversely, deleting T from any new simple 16-cycle leaves a simple old path of length 14 between the two candidate points used by the cycle. The predicate examines that pair and succeeds. The third point of t may occur internally on the old path; then its edge to T is merely a chord and does not invalidate the simple cycle.

Lemmas 6.1 and 6.3 therefore establish the soundness assumption required by Proposition 5.1.

7 The cap-34 exhaustion

We now set the point-label and block-count cap to $M = 34$.

Root	States	Attempted	Structural	C8	C16	Completions
R1	23,143	2,972,750	180,011	1,424,785	1,344,812	0
R2	202,602	25,227,209	1,432,521	15,207,779	8,384,308	0
Total	225,745	28,199,959	1,612,532	16,632,564	9,729,120	0

Table 1. Cap-34 triangle-rooted search statistics.

For each root, attempted = structural + C8 + C16 + expanded and expanded = states - 1. These identities are consistency checks, not the exhaustion proof.

8 Static certification of the finite search

The certificate verifier reconstructs the restricted-growth proposal schedule from the current state instead of accepting a candidate list from the certificate generator. For every expected candidate, exactly one of four outcomes must be verified: structural rejection, rejection with a C_8 witness, rejection with a C_{16} witness, or acceptance and recursive verification of the resulting child.

A structural rejection is checked directly. A C_8 witness supplies three old block identifiers; the verifier reconstructs the four intersections and checks a genuine simple 8-cycle. A C_{16} witness supplies a pair of candidate points and seven old block identifiers; the verifier reconstructs an alternating simple path of length 14 and checks that the new block closes it into a simple 16-cycle. For an accepted candidate, the verifier constructs the child state itself and continues recursively. Thus an omitted branch is detectable: the verifier independently knows which candidate must be handled next.

Proposition 8.1 (Certificate exhaustion). Fix one of the two cap-34 rooted search trees. If the verifier accepts its complete certificate stream and reports zero solutions, then that search tree contains no completed state.

Proof. At every verified state the verifier independently reconstructs the complete ordered candidate list. For each candidate, either a directly checked structural or cycle witness closes the branch, or the verifier constructs and recursively checks the exact child. Hence every prescribed branch is either validly rejected or recursively exhausted. The cap makes the search tree finite. Every completed state encountered during this traversal is counted by the verifier. Therefore acceptance of the complete stream with zero solutions implies that the rooted search tree contains no completion.

Both cap-34 certificate streams are accepted and both report solutions 0.

The fixed compressed certificate SHA-256 digests are:

```
R1 dbc3b405bff9cadba5687e2eb8b6ba033255fc99d23b4bf7f49efc4d6e8b79a
R2 f8cd411dc6b26b5a703df811ad53c055d1e7ea75dbca2704a52bf0bbea911bd0
```

9 Proof of the main theorem

Proof of Theorem 1.1. Suppose that a simple cubic bipartite graph G with $|V(G)| \leq 68$ contains no cycle of length 4, 8, or 16. Choose any connected component H . Since G is cubic and bipartite, so is H , and $|V(H)| \leq 68 < 70$.

By Lemma 3.1, H contains a C_6 . Construct the incidence configuration whose Levi graph is H . Because H is C_4 -free, the configuration is linear; the C_6 becomes a Berge triangle; and the absence of C_8 and C_{16} means that it has no Berge 4- or 8-cycle. Since a connected cubic bipartite graph has equal bipartition sizes, this is a connected linear symmetric v_3 -configuration with $v \leq 34$.

By Lemmas 6.1 and 6.3, the cycle-rejection predicates satisfy the soundness hypothesis of Proposition 5.1. Hence Proposition 5.1 implies that a restricted-growth labeling of the target occurs as a completed state in one of the two cap-34 triangle-rooted search trees.

Proposition 8.1 and the two accepted certificate streams show that neither rooted tree contains a completed state. This contradiction proves the theorem.

Corollary 1.2 follows because a cubic bipartite graph has even order.

10 Reproducibility and provenance

The reference upstream implementation is the triangle-rooted search distributed with Tranquilli [3]. The source used for direct reproduction is anchored to the immutable commit

```
67adc92d31d5d1edfbd0a7b845dc232e31c412cd
```

A fresh Git checkout of this commit was independently obtained. The working tree was clean and the upstream SHA-256 manifest verification succeeded. The SHA-256 digest of the relevant upstream search source `triangle_root_universal_search.cpp` is

```
e778648bc3d5b0a19c860bec1371a542c464652693c2cbc4c2cd5ef05f314f41
```

The source was compiled directly from the fresh checkout with `-DSIDE=34`. The resulting computation reproduced all entries of Table 1 exactly and reproduced the decision-transcript hashes

```
R1 db548be2919a7f8a8b28c5ded67aa622779dd3e22192ee8a2a1e065f8c07b4c5
R2 c2e03a0f97ea3c649a5feaf4d4145b229da6f56aa31b8ebdb8b769b18848607
```

The static-certificate generator and verifier used here are project-specific additions rather than components of the upstream release. The complete certificate artifact was independently verified under Ubuntu 24.04 with GCC 13.3.0: the verification script checked the manifest, rebuilt the verifier, accepted both certificate streams with the exact expected counts, and terminated with zero solutions for both roots.

The packaged artifact SHA-256 is:

```
32558c65679736fb2ff75b67b2d75a85a2b7b91e6dde5d15b06c3a9b59f0d7de
```

Development repository (private at the time of this draft): <https://github.com/qacqac2/erdos-gyarfas-cubic-bipartite-70-bound>. The final public version will cite a fixed release and permanent archival DOI.

11 Trust boundary and AI assistance

11.1 Trust boundary

The static certificate substantially reduces the computation that must be trusted. The original DFS is not accepted merely because it prints a zero-solution count: the certificate verifier reconstructs the proposal schedule and checks local witnesses independently. Nevertheless, this is not a proof-assistant formalization. The conventional trusted computing base still includes the verifier source, the C++ implementation and compiler, the operating system and hardware used for verification, and SHA-256 for artifact identity. The finite exhaustion is therefore described as independently executable and certificate-checked, not as formally verified from first principles.

11.2 AI assistance

Generative AI tools were used during exploratory reasoning, literature review, source-code interpretation, proof auditing, adversarial review, artifact design, and manuscript drafting. AI-generated output is not used as an evidentiary substitute for the mathematical proof or the computational certificate. The theorem-supporting claims are reduced to explicit mathematical arguments, immutable source identity, reproducible computations, static certificate data, and independently executable verification. Responsibility for the mathematical statements, released artifact, and final manuscript rests with the human author.

12 Concluding remarks

The argument raises the lower bound for cubic bipartite counterexamples to the Erdos-Gyarfas conjecture from 60 to 70. The role of 70 is structural rather than merely computational. Below 70 vertices, the O'Keefe-Wong girth-10 theorem forces a C_6 once C_4 and C_8 are excluded, making the two triangle-rooted search trees complete throughout the present range.

At order 70 this forcing argument no longer applies: cubic graphs of girth 10 exist at that order. The present proof therefore deliberately makes no statement about the 70-vertex case or beyond. Further progress would require additional structure for the girth-10 regime or a different exhaustive-search framework.

References

- [1] P. Erdos, Some old and new problems in various branches of combinatorics, *Discrete Mathematics* 165-166 (1997), 227-231.
- [2] M. O'Keefe and P. K. Wong, A smallest graph of girth 10 and valency 3, *Journal of Combinatorial Theory, Series B* 29 (1980), 91-105.
- [3] J. Tranquilli, A 60-Vertex Lower Bound for Cubic Bipartite Counterexamples to the Erdos-Gyarfas Conjecture, arXiv:2608.02675 (2026).
- [4] J. Verstraete, Unavoidable cycle lengths in graphs, *Journal of Graph Theory* 49 (2005), 151-167.
- [5] H. Liu and R. Montgomery, A solution to Erdos and Hajnal's odd cycle problem, *Journal of the American Mathematical Society* 36(4) (2023), 1191-1234.
- [6] Y. Gao and S. Shan, Erdos-Gyarfas conjecture for P_8 -free graphs, *Graphs and Combinatorics* 38(6) (2022), Article 168.
- [7] Z. Hu and C. Shen, The Erdos-Gyarfas conjecture holds for P_{10} -free graphs, *Discrete Mathematics* 347(12) (2024), Article 114175.
- [8] A. S. Hegde, R. B. Sandeep and P. Shashank, Erdos-Gyarfas conjecture on graphs without long induced paths, arXiv:2410.22842 (2024; revised 2025).
- [9] C. C. Heckman and R. Kravovski, Erdos-Gyarfas conjecture for cubic planar graphs, *Electronic Journal of Combinatorics* 20(2) (2013), P7.
- [10] P. Salehi Nowbandegani, H. Esfandiari, M. H. Shirdareh Haghighi and K. Bibak, On the Erdos-Gyarfas conjecture in claw-free graphs, *Discussiones Mathematicae Graph Theory* 34(3) (2014), 635-640.
- [11] K. Markstrom, Extremal graphs for some problems on cycles in graphs, *Congressus Numerantium* 171 (2004), 179-192.
- [12] J. Bensmail, On q -power cycles in cubic graphs, *Discussiones Mathematicae Graph Theory* 37(1) (2017), 211-220. DOI 10.7151/dmgt.1926.
- [13] A. Carr, Cycles of Length 4 or 8 in Graphs with Diameter 2 and Minimum Degree at Least 3, arXiv:2508.19302 (2025; revised 2026).