

Bitcoin Early-Stage Mining Forensics: Core Implementation Fingerprint & Nonce Dispersion Analysis

Author: QAHTAN AL OUD | Contact: qahtanbins1@gmail.com

Target Dataset: First 28,652 Bitcoin Blocks (*blk00000*)

1. Executive Summary

This forensic investigation analyzes the cryptographic patterns, *scriptSig* prefixes, and *nonce* distribution across the earliest blocks of the Bitcoin blockchain. By isolating historical parameters from the genesis block up to block 28,647, this study maps operational signatures of early mining implementations to evaluate network decentralization and software homogeneity.

2. Methodology & Code Isolation

Using automated analysis scripts on raw block data, records were filtered to evaluate target prefixes and statistical deviations in nonce generation:

- **Total Blocks Analyzed:** 28,652 records.
- **Core Fingerprint Isolation:** Filtered for the persistent software signature prefix *04ffff001d01* (comprising length indicators, target bits, and ExtraNonce sizing).
- **Statistical Variance:** Computed the mean and standard deviation of nonce values across the cohort to measure behavioral and algorithmic randomness.

3. Key Findings & Empirical Results

- **Persistence of Core Implementation Fingerprint:** Exactly **5,590 blocks** (representing **19.51%** of the early sample) strictly matched the core prefix *04ffff001d01*. The height range of these matching blocks spans from **Block 0 to Block 28,647**, proving that this software variant was actively deployed throughout the entire foundational epoch.
- **Extreme Nonce Dispersion (98.41% Anomaly Rate):** The global nonce mean was calculated at *1,496,821,383.95* with a standard deviation reaching *1,359,514,876.57*. Outlier analysis revealed that **28,197 blocks (98.41%)** deviated heavily (>50 million points) from a unified sequential baseline. Within the isolated core footprint subset, the average nonce registered at *809,216,857.37* with a standard deviation of *1,109,482,327.69*.

4. Conclusion & Architectural Implications

The data provides definitive, empirical proof regarding the structure of the early Bitcoin network:

1. **Absence of Centralized Monotony:** The vast standard deviation and 98.41% outlier rate confirm that early mining did not operate via a single, synchronized, sequential linear counter.

2. **Multiple Independent Implementations:** The presence of a persistent core signature (~19.5%) combined with high variance across distributed blocks indicates that multiple independent miners or separate client instances were operating concurrently using localized or randomized hashing routines, reinforcing a decentralized multi-node footprint from inception.