



Digital Adventure Ride to the Future


7 – 18 January, 2024



Utrecht University




1




Classification and Algorithmic Fairness

Hakim Qahtan

Department of Information and Computing Sciences
Utrecht University





Utrecht University





2


Today

 Classification

 Model and Data Bias

 Fairness


 Utrecht University


 **wep**
ENRICHMENT
FOR ALL

3

3

Classification

 Utrecht University

 **wep**
ENRICHMENT
FOR ALL

4

Topics

- Classification
 - Train-Test Split
 - Classification Algorithms
 - Evaluation
- Evaluation




Utrecht University

5

5

Real World Examples

- Credit/loan approval
- Medical diagnosis
- Fraud detection
- Web page categorization
- Spam detection in emails
- Image classification
- Text sentiment




Utrecht University

6

6

How Classifiers Work?

- Classification is a supervised learning approach
 - Labeled dataset is needed
 - Features/Examples: X
 - Outcomes/Labels: Y
 - Learn the patterns
 - Use them to predict the labels



Classification techniques

- Include:
 - Logistic Regression
 - Learning from the neighbors
 - Decision tree-based methods
 - Support vector machines
 - Neural networks
 - Bayesian classification

Building a Classification Model



- Split the data into training and testing
- Train the classifier on the training data
- Select a set of performance measures
 - Accuracy, Balanced Accuracy, Precision, Recall, F-Score, ...
- Evaluate the classifier on the test set

NOTE: NEVER USE THE TEST SET FOR TRAINING!




Utrecht University

9

9

Train-Test Split



Utrecht University

10

10

Train-Test Split



- Problem
 - The training/testing set may not include examples from one of the classes
- Solution
 - Split with stratification
 - Ensures that each class is represented with approximately equal proportions in both subsets



Utrecht University

11

11

Classification – A Three-Step Process



- Model construction
 - describing a set of predetermined classes
- Model evaluation
 - testing if the model will perform well on unseen data
 - labels are available but not provided to the model (classifier)
- Model usage
 - for classifying future or unknown objects




Utrecht University

12

12

Model Construction




Utrecht University

13

13

Step (2): Evaluating the Model




Utrecht University

14

14

Step (3): Using the Model in Prediction



Utrecht University

15

15


Classification Techniques



Utrecht University

16

Logistic Regression



A sigmoid function that assumes values in the range $[0, 1]$

$$p(x) = \frac{e^{\beta_0 + \beta_1 x}}{1 + e^{\beta_0 + \beta_1 x}} = \frac{1}{1 + e^{-(\beta_0 + \beta_1 x)}}$$






Utrecht University

17

17

Decision Boundaries



Utrecht University

18

18

Nearest Neighbors Classifiers

Basic idea: if it walks like a duck, quacks like a duck, then it is probably a duck

The diagram illustrates the process of a Nearest Neighbors Classifier. On the left, a dashed red circle encloses five training records: two chickens and three ducks. On the right, a single duck is labeled 'Test Record'. Red arrows point from each of the five training records to the test record, with the label 'Compute Distance' above them. Blue arrows point from the three ducks in the training set to the test record, with the label 'Choose k of the "nearest" records' below them. The Utrecht University logo is in the bottom left, and a decorative pattern of colored dots is in the bottom right.

19

Nearest Neighbors Classifiers (Cont.)

The three diagrams show a 2D space with blue minus signs and red plus signs. A test point 'x' is marked with a red dashed circle around it. The first diagram shows the 1-nearest neighbor, the second shows the 2-nearest neighbors, and the third shows the 3-nearest neighbors. The Utrecht University logo is in the bottom left, and a decorative pattern of colored dots is in the bottom right.


1- nearest neighbor 2- nearest neighbors 3- nearest neighbors

20

Nearest Neighbors Classifiers (Cont.)



- Three requirements:
 - Set of records (training set)
 - Distance metric
 - The number of neighbors to be considered k
- Classifying unknown record x :
 - Compute the distance from x to the other training records
 - Identify the k -Nearest Neighbors ($kNN(x)$)
 - Use class labels of the kNN records to determine the class of x .. How?



Utrecht University


21

21

Decision Trees



- Outcome: Buys_computer
- Resulting tree:



age	income	student	credit rating	buys computer
<=30	high	no	fair	no
<=30	high	no	excellent	no
31...40	high	no	fair	yes
>40	medium	no	fair	yes
>40	low	yes	fair	yes
>40	low	yes	excellent	no
31...40	low	yes	excellent	yes
<=30	medium	no	fair	no
<=30	low	yes	fair	yes
>40	medium	yes	fair	yes
<=30	medium	yes	excellent	yes
31...40	medium	no	excellent	yes
31...40	high	yes	fair	yes
>40	medium	no	excellent	no




Utrecht University

22


22

Random Forests



23

Neural Network




$$w_j^{(k+1)} = w_j^{(k)} + \lambda (y_i - \hat{y}_i^{(k)}) x_{ij}$$

24


Support Vector Machines (SVM)



Find linear hyperplane (decision boundary) that will separate the data



One possible separators



Utrecht University


25

25


Support Vector Machines (SVM) (Cont.)



Another possible separator



Other possible separators



Utrecht University

26

26

Support Vector Machines (SVM) (Cont.)




Find the hyperplane that maximizes the margin

Better separator

Support Vectors

are the points that the margin is pushed up against



Utrecht University

27

27

Evaluation: Confusion Matrix



- Focus on the predictive capability of a model

Confusion Matrix:

	Predicted Label		
		Class = Y	Class = N
Actual Label	Class = Y	TP	FN
	Class = N	FP	TN

TP = True Positive
 FP = False Positive
 FN = False Negative
 TN = True Negative

- The basic used metric:

$$Accuracy = \frac{TP + TN}{TP + FN + FP + TN}$$



Utrecht University

28

28

Evaluation Measures



Measure	Formula
Accuracy (acc.)	$\frac{TP + TN}{TP + FP + TN + FN}$
Precision (P)	$\frac{TP}{TP + FP}$
Recall (R)	$\frac{TP}{TP + FN}$
F1-Score	$2 \frac{P \times R}{P + R}$
Sensitivity (TPR)	Recall (TPR)
Specificity (TNR)	$\frac{TN}{TN + FP}$
Balanced Accuracy (BA)	$\frac{\text{Sensitivity} + \text{Specificity}}{2}$



29

29

Accuracy




- Limitation of accuracy metric:
 - The problem of **unbalanced classes**
 - Consider a 2-class problem
 - Number of class 1 examples = 9990
 - Number of class 0 examples = 10
 - If the model predict everything as class 1
 - $Accuracy = \frac{9990}{10000} = 99.9\%$
- Accuracy is misleading because the classifier didn't predict any class 0 examples
- $Weighted Accuracy = \frac{w_1 TP + w_4 TN}{w_1 TP + w_2 FN + w_3 FP + w_4 TN}$



30

30


Example: Classifying hand-written digits



Utrecht University

31

31




Coding Time





Utrecht University


32


ENRICHMENT
FOR ALL

Coffee Break



 Utrecht University



33


ENRICHMENT
FOR ALL


Model and Data Bias

 Utrecht University



34

Unfair Algorithms – Apple Card



<https://www.bloomberg.com/opinion/articles/2019-11-11/is-the-apple-and-goldman-sachs-credit-card-sexist>,
<https://www.theguardian.com/technology/2019/nov/10/apple-card-issuer-investigated-after-claims-of-sexist-credit-checks>



Utrecht University

35

35

Who's Paid the Biggest Worker Abuse Fines? The Answer May Surprise You.

Big banks not only mistreat customers. They've also faced some of the heaviest fines for mistreating their employees.

RESEARCH & COMMENTARY
 JANUARY 25, 2019
 by Phil Mattera

Parent Companies with the Highest Disclosed Discrimination Penalties

Rank	Parent	Penalty Total	Cases
1	Bank of America	\$210,296,593	8
2	Coca-Cola	\$200,616,000	9
3	Novartis	\$183,000,000	2
4	Morgan Stanley	\$150,385,000	6
5	Abercrombie & Fitch	\$90,115,600	4
6	FedEx	\$80,035,138	15
7	Boeing	\$79,935,059	7
8	Verizon Communications	\$71,504,891	6
9	Wells Fargo	\$68,099,000	5
10	SoftBank (parent of Sprint)	\$62,852,756	3

<https://inequality.org/research/penalties-workplace-abuse/>



Utrecht University

36

36

Reasons

- Historical bias in the decision variable
- Limited / less informative features
- Biased data collection
- Imbalanced representation of different demographic groups




Utrecht University

37

37

Consequences

- One gets more than is needed
- Huge disparity is created



Utrecht University


38

38

What Should be Done?



- Equality: everyone benefits from the same support
- Equity: everyone gets the needed support
- Justice: remove the causes of inequity



Utrecht University

39

39

Algorithmic Fairness



Utrecht University

40

What do you think is fair?

“Fairness is the absence of any prejudice or favoritism towards an individual or a group based on their intrinsic or acquired traits in the decision-making context”



Utrecht University

41

41

Fairness Through Unawareness

- What if you do not even collect sensitive data?
 - Useful to have the sensitive features to check for fairness
- Removing the protected attributes does not always work
 - Proxy attributes




Utrecht University

42

42

Statistical Parity

- People of different groups should have the same probability of getting the positive outcome
- Disparate Impact Ratio
 - Base rate unprivileged / base rate privileged
 - Should be between 0.8 and 1.25





Utrecht University

43

43

Consistency

- An individual fairness measure
- Determines how similar the labels are for the similar instances in a dataset based on the k-neighbors of the instance
- This Metric: takes values between 0 and 1 with 1 is the optimal



Utrecht University

44

44

Bias Mitigation Algorithms


- Pre-Processing Algorithms
- In-Processing Algorithms
- Post-Processing Algorithms



Utrecht University

45

45



Coding Time





Utrecht University

46

Reading Material for Interested Students

- Introduction to Data Science, Ch 5.
[Supervised Learning](#)
- Data Mining: Concepts-and-Techniques
Ch 6. Classification

Acknowledgement: parts of the material were prepared by Xiangliang Zhang, Fenna Woudstra and Begum Hattatoglu



Utrecht University

47

47

Thank You



Utrecht University

48



Utrecht University

DISCLAIMER

The information in this presentation has been compiled with the utmost care,
but no rights can be derived from its contents.

© Utrecht University