

CT01 Model selection stability Table1

Candidate v0.1 • page 1 • 6 rows • not inserted in manuscript

Dataset / rule	Reference top model	Single-context agreement (95% CI)	Discordance (95% CI)	Paired bootstrap frequency q	5×3 budget agreement
OrganAMNIST / A (10×5; 4 models)	ResNet-18	0.620 [0.440, 0.800]	0.380 [0.200, 0.560]	0.9088	0.890
OrganAMNIST / B (10×5; 4 models)	ResNet-50	0.600 [0.400, 0.780]	0.400 [0.220, 0.600]	0.7825	0.587
SIPaKMeD / A (10×5; 4 models)	ResNet-18	0.520 [0.360, 0.740]	0.480 [0.260, 0.640]	0.8494	0.694
SIPaKMeD / B (10×5; 4 models)	ResNet-50	0.440 [0.380, 0.680]	0.560 [0.320, 0.620]	0.5377	0.204
ISIC2019 / A (10×3; 4 models)	ResNet-50	0.900 [0.733, 1.000]	0.100 [0.000, 0.267]	1.0000	1.000
MURA / A (10×3; 4 models)	ResNet-50	0.600 [0.300, 0.800]	0.400 [0.200, 0.700]	0.7687	0.571

The reference top model is defined by full-grid mean balanced accuracy (BA). Agreement/discordance intervals use 10,000 paired split-then-seed percentile resamples with the reference re-estimated per draw; discordance is 1 minus agreement. q is a point estimate from 10,000 paired crossed split–seed ranking resamples. The 5×3 column uses finite-grid agreement with a held-out five-split reference block, averaged over 252 oriented partitions; source images may overlap across splits. Original seed subsets come from five seeds; extension subsets from three.