Differentiate between supervised and unsupervised learning (2 marks)

Supervised and unsupervised learning are two fundamental paradigms in machine learning, distinguished by the presence or absence of labeled data.

Aspect	Supervised Learning	Unsupervised Learning
Data	Labeled (input-output pairs)	Unlabeled (input only)
Goal	Predict output for new inputs	Discover hidden patterns/structure
Output	Known target variable	No predefined target
Examples	Classification, regression	Clustering, dimensionality reduction
Algorithms	SVM, Decision Trees, Linear Regression	K-Means, PCA, DBSCAN
Evaluation	Accuracy, Precision, Recall	Silhouette score, cluster compactness

---

What is Reinforcement Learning? Explain the significance of reward and action in RL (2 marks)

Reinforcement Learning (RL) is a machine learning paradigm where an **agent** learns to make decisions by interacting with an **environment** to maximize cumulative **reward**

Significance of Reward:

- **Reward** is a scalar feedback signal indicating how good or bad an action was.
- It defines the **goal** of the agent; the agent aims to maximize total reward over time.
- Rewards can be **immediate** or **delayed**, shaping the learning trajectory.

Significance of Action:

- **Action** is the choice made by the agent at each state.
- It directly influences the next state and the reward received.
- The agent must balance **exploration** (trying new actions) and **exploitation** (using known good actions).


Explain linearly separable and non-linearly separable patterns with examples (2 marks)

Linearly Separable Patterns:

- Two classes can be separated by a single straight line (or hyperplane in higher dimensions).
- **Example:** AND gate : points (0,0), (0,1), (1,0) belong to class 0, and (1,1) belongs to class 1. A line (x + y = 1.5) separates them.

Non-Linearly Separable Patterns:

- No single straight line can separate the classes.
- **Example:** XOR gate : points (0,0), (1,1) belong to class 0, and (0,1), (1,0) belong to class 1. No straight line can separate them; a curved boundary is needed.



Discuss the applications of Machine Learning (2 marks)

Machine learning is applied across diverse domains to automate decision-making and extract insights.

1. **Healthcare** : Disease diagnosis, drug discovery, medical imaging analysis.
2. **Finance** : Credit scoring, fraud detection, algorithmic trading.
3. **E-commerce** : Product recommendations, customer segmentation, demand forecasting.
4. **Transportation** : Autonomous vehicles, traffic prediction, route optimization.
5. **Natural Language Processing** : Chatbots, sentiment analysis, machine translation.
6. **Cybersecurity** : Intrusion detection, malware classification.
7. **Agriculture** : Crop yield prediction, pest detection.

What is neural network architecture? Explain logistic sigmoid function with example (2 marks)

A **neural network architecture** is the structural design of interconnected artificial **neurons** (nodes) arranged in layers that process data, learn patterns, and make predictions.

1. Input Layer: Input layer accepts inputs in several formats provided by the programmer.
2. Hidden Layer: The hidden layer(s) is/are present between input and output layers. It performs all the calculations to find hidden features and patterns.
3. Output Layer: The input goes through a series of transformations using the hidden layer, which finally results in output that is conveyed using this layer.

The artificial neural network takes input and computes the weighted sum of the inputs and includes a bias. This computation is represented in the form of a transfer function.

Logistic Sigmoid Function Formula:

The logistic sigmoid function is a mathematical function that maps any real-valued number into a smooth, S-shaped curve with values strictly between 0 and 1.

$$\sigma(x) = \frac{1}{1 + e^{-x}}$$

$$Range : (0 - 1)$$

$$\sigma(2) = \frac{1}{1 + e^{-2}} \approx 0.88, \qquad \sigma(-2) = \frac{1}{1 + e^{2}} \approx 0.12$$

Properties:

- Smooth and differentiable.
- Outputs probabilities, useful for binary classification.

- Suffers from vanishing gradient for extreme inputs.

What are the important properties of activation functions used in neural networks? (2 marks)

Activation functions introduce non-linearity into neural networks, enabling them to learn complex mappings.

Properties:

1. **Non-linearity** : Essential for learning complex relationships.
2. **Differentiability** : Required for backpropagation and weight updates.
3. **Monotonicity** : Ensures consistent gradient direction.
4. **Bounded output** : Restricts activation values within a fixed, safe numerical range.
5. **Computational efficiency** : Ensures fast evaluation, reducing training time cost.
6. **Zero-centered** : Helps avoid zig-zagging during gradient descent (e.g., tanh).

Explain the basic McCulloch-Pitts neuron model with examples (2 marks)

The **McCulloch-Pitts (MP) neuron** is the earliest mathematical model of a neuron, proposed in 1943.

Components:

- **Inputs:** Binary (0 or 1).
- **Weights:** Excitatory (+1) or inhibitory (−1).
- **Threshold:** (\theta).
- **Output:** 1 if weighted sum ≥ (\theta), else 0.

Example: AND Gate

- Inputs: (x_1, x_2), weights: (w_1 = w_2 = 1), threshold (\theta = 2).
- Output: (y = 1) if (x_1 + x_2 \geq 2), else 0.
- Truth table: (0,0)→0, (0,1)→0, (1,0)→0, (1,1)→1.

Example: OR Gate

- Threshold (\theta = 1).
- Output: (y = 1) if (x_1 + x_2 \geq 1).

Differentiate between machine learning and deep learning. Applications of DL (2 marks)

Aspect	Machine Learning	Deep Learning
Feature extraction	Manual	Automatic
Data requirement	Smaller datasets	Large datasets
Hardware	CPU sufficient	Requires GPU/TPU
Training time	Shorter	Longer
Interpretability	Higher	Lower (black box)
Architecture	Shallow models	Deep neural networks

Applications of Deep Learning:

- **Computer Vision** : Image classification, object detection.
- **NLP** : Machine translation, sentiment analysis.
- **Speech Recognition** : Voice assistants, transcription.
- **Healthcare** : Medical imaging diagnosis.
- **Autonomous Vehicles** : Perception and decision-making.

What is meant by ensemble learning? What are the different types of ensemble classifiers? (2 marks)

Ensemble Learning combines multiple base models to produce a stronger, more accurate predictor than any single model.

Types of Ensemble Classifiers:

1. **Bagging** : Trains many models on random samples and combines their votes. (Random Forest)
2. **Boosting** : Trains models one after another, each fixing previous mistakes. (Gradient Boosting)
3. **Stacking** : Trains a meta-model to combine predictions of base models. (Stacked generalization)
4. **Voting** : Combines predictions by majority vote or average probability. (Hard voting, Soft voting)

Explain Accuracy, Precision, Recall, Specificity, and F1 Score (2 marks)

These metrics evaluate classification performance, especially on imbalanced data.

1. Accuracy: Overall correctness of the model

$$\text{Accuracy} = \frac{TP + TN}{TP + TN + FP + FN}$$

2. Precision: How many predicted positives were correct

$$\text{Precision} = \frac{TP}{TP + FP}$$

3. Recall (Sensitivity): Actual positives captured

$$\text{Recall} = \frac{TP}{TP + FN}$$

4. Specificity: Actual negatives captured

$$\text{Specificity} = \frac{TN}{TN + FP}$$

5. F1 Score: Harmonic mean of Precision and Recall

$$\text{F1 Score} = 2 \times \frac{\text{Precision} \times \text{Recall}}{\text{Precision} + \text{Recall}}$$

Explain the confusion matrix with examples (2 marks)

A **confusion matrix** is a table summarizing classification results against actual labels.

	Predicted Positive	**Predicted Negative**
Actual Positive	True Positive (TP)	False Negative (FN)
Actual Negative	False Positive (FP)	True Negative (TN)

Example: Fraud detection (F = fraud, N = no fraud)

- TP = 20 (fraud correctly detected)

- FN = 10 (fraud missed)
- FP = 10 (false alarms)
- TN = 60 (correctly classified non-fraud)

What are autoencoders? Discuss types of autoencoders. List applications (2 marks)

Autoencoders are neural networks trained to reconstruct their input at the output layer, learning a compressed representation in the bottleneck layer.

Types:

1. **Undercomplete Autoencoder** : Bottleneck smaller than input; learns compact features.
2. **Sparse Autoencoder** : Adds sparsity penalty to hidden units.
3. **Denoising Autoencoder** : Trained to reconstruct clean input from noisy version.
4. **Variational Autoencoder (VAE)** : Learns probabilistic latent space.
5. **Contractive Autoencoder** : Penalizes sensitivity to input perturbations.

Applications:

- Dimensionality reduction
- Image denoising
- Anomaly detection
- Feature extraction
- Recommendation systems

Summary: Autoencoders are versatile unsupervised models for representation learning.

Explain RNN and its uses in NLP (2 marks)

Recurrent Neural Networks (RNNs) are neural networks designed for sequential data, where connections between nodes form a directed graph along a temporal sequence.

Key Features:

- Maintains a **hidden state** that captures information from previous time steps.
- Shares weights across time steps.
- Suitable for variable-length sequences.

Uses in NLP:

- **Language Modeling** : Predicting next word.
- **Machine Translation** : Sequence-to-sequence mapping.
- **Sentiment Analysis** : Classifying text polarity.
- **Named Entity Recognition** : Tagging entities in text.
- **Text Generation** : Producing coherent text.

Limitation: Vanishing gradient problem for long sequences, addressed by LSTM and GRU.

Write a short note on trends in data science for Audio (2 marks)

Audio data science involves processing, analyzing, and modeling sound signals.

Trends:

1. **Speech Recognition** : Deep learning models (e.g., Transformers) for accurate transcription.
2. **Music Information Retrieval** : Genre classification, beat tracking, recommendation.
3. **Audio Surveillance** : Anomaly detection (e.g., gunshots, glass breaking).
4. **Voice Assistants** : NLP + audio for conversational AI.
5. **Emotion Recognition** : Detecting mood from speech.
6. **Audio Synthesis** : Generative models (e.g., WaveNet) for realistic speech/music.

Summary: Audio data science is advancing with deep learning, enabling richer human-computer interaction.

Explain Data Science for Multimodal applications (2 marks)

Multimodal Data Science integrates multiple data types (text, audio, image, video) to improve model performance and user experience.

Key Aspects:

- **Fusion Strategies** : Early (feature-level), late (decision-level), or hybrid fusion.
- **Cross-Modal Learning** : Aligning representations across modalities.
- **Applications:**
  - **Video Captioning** : Generating text from video.
  - **Sentiment Analysis** : Combining text and tone.
  - **Human-Computer Interaction** : Gesture + voice + gaze.
  - **Healthcare** : Combining imaging and clinical notes.

Result: Multimodal systems leverage complementary information, leading to more robust and context-aware applications.

Implement binary gates [OR, AND, NOR, XOR] using McCulloch-Pitts ANN (5 marks)

The McCulloch-Pitts neuron uses binary inputs, weights, and a threshold to produce binary output.

Given:

- Inputs: $(x_1, x_2 \in \{0, 1\})$
- Weights: (w_1, w_2)
- Threshold: θ
- Output: $(y = 1)$ if $\sum w_i x_i \geq \theta$, else 0.

OR Gate:

- Weights: $(w_1 = 1, w_2 = 1)$, $\theta = 1$
- Output: $(y = 1)$ if $(x_1 + x_2 \geq 1)$

(x_1)	(x_2)	$(x_1 + x_2)$	(y)
0	0	0	0
0	1	1	1
1	0	1	1
1	1	2	1

AND Gate:

- Weights: (w_1 = 1, w_2 = 1), (\theta = 2)
- Output: (y = 1) if (x_1 + x_2 \geq 2)

(x_1)	(x_2)	(x_1 + x_2)	(y)
0	0	0	0
0	1	1	0
1	0	1	0
1	1	2	1


NOR Gate:

- Weights: (w_1 = -1, w_2 = -1), (\theta = 0)
- Output: (y = 1) if (-x_1 - x_2 \geq 0) (i.e., both inputs 0)

(x_1)	(x_2)	(-x_1 - x_2)	(y)
0	0	0	1
0	1	-1	0
1	0	-1	0
1	1	-2	0

XOR Gate:

- XOR is not linearly separable; a single MP neuron cannot implement it.
- **Solution:** Use a two-layer network:
  - Layer 1: (y_1 = \text{OR}(x_1, x_2)), (y_2 = \text{NAND}(x_1, x_2))
  - Layer 2: (y = \text{AND}(y_1, y_2))



Result: OR, AND, NOR are implementable with a single MP neuron; XOR requires a multi-layer network.

Explain all the activation functions with neat diagrams (5 marks)

Activation functions introduce non-linearity, enabling neural networks to learn complex patterns.

1. Sigmoid:

- (\sigma(x) = \frac{1}{1 + e^{-x}})
- Range: (0, 1)
- **Diagram:** S-shaped curve.

- **Use:** Binary classification output.

2. Tanh (Hyperbolic Tangent):

- (\tanh(x) = \frac{e^x - e^{-x}}{e^x + e^{-x}})
- Range: (−1, 1)
- **Diagram:** S-shaped, zero-centered.
- **Use:** Hidden layers.

3. ReLU (Rectified Linear Unit):

- (\text{ReLU}(x) = \max(0, x))
- Range: [0, ∞)
- **Diagram:** Flat for negative, linear for positive.
- **Use:** Most hidden layers.

4. Leaky ReLU:


- (\text{Leaky ReLU}(x) = \max(0.01x, x))
- Range: (−∞, ∞)
- **Diagram:** Small slope for negative.
- **Use:** Avoids dead neurons.

5. Softmax:

- (\text{Softmax}(x_i) = \frac{e^{x_i}}{\sum_j e^{x_j}})
- Range: (0, 1), sums to 1.
- **Use:** Multi-class classification output.

6. Linear:

- (f(x) = x)
- Range: (−∞, ∞)
- **Use:** Regression output.



Summary: Each activation function has unique properties; ReLU and its variants are preferred for deep networks due to computational efficiency and reduced vanishing gradient.

Explain Bagging and Boosting in detail (5 marks)

Bagging (Bootstrap Aggregating):

- **Concept:** Train multiple models on different bootstrap samples of the dataset.
- **Aggregation:** Majority vote (classification) or average (regression).
- **Goal:** Reduce variance.
- **Example:** Random Forest.
- **Steps:**
  1. Create (B) bootstrap samples.
  2. Train a base model on each.
  3. Aggregate predictions.

Boosting:

- **Concept:** Train models sequentially, each focusing on errors of the previous.
- **Aggregation:** Weighted sum of predictions.

- **Goal:** Reduce bias.
- **Example:** AdaBoost, Gradient Boosting.
- **Steps:**
  1. Train initial model.
  2. Increase weights of misclassified samples.
  3. Train next model on reweighted data.
  4. Repeat and combine.

Aspect	Bagging	Boosting
Training	Parallel	Sequential
Focus	Variance reduction	Bias reduction
Data sampling	Bootstrap	Reweighted
Overfitting	Less prone	More prone


Key Distinctions: Bagging builds independent models and combines them; boosting builds dependent models that correct each other's errors.

Explain LSTM in detail (5 marks)

Long Short-Term Memory (LSTM) is a type of RNN designed to overcome the vanishing gradient problem, enabling learning of long-term dependencies.

Components:

1. **Cell State ((C_t)):** Long-term memory.
2. **Forget Gate ((f_t)):** Decides what to discard from cell state.
   - (f*t = *sigma(W_f* *cdot [h*{t-1}, x_t] + b_f))
3. **Input Gate ((i_t)):** Decides what new information to store.
   - (i*t = *sigma(W_i* *cdot [h*{t-1}, x_t] + b_i))
   - (\tilde{C}*t = *tanh(W_C* *cdot [h*{t-1}, x_t] + b_C))
4. **Cell State Update:**
   - (C*t = f_t* *cdot C*{t-1} + i_t \cdot \tilde{C}_t)
5. **Output Gate ((o_t)):** Decides what to output.
   - (o*t = *sigma(W_o* *cdot [h*{t-1}, x_t] + b_o))
   - (h_t = o_t \cdot \tanh(C_t))




Applications: Machine translation, speech recognition, time-series prediction.

Result: LSTM selectively remembers or forgets information, making it effective for sequential data with long-range dependencies.

Draw and explain architecture of convolutional neural networks. Explain kernel and pooling (5 marks)

CNN Architecture:

- **Input Layer:** Raw image data.
- **Convolutional Layers:** Apply filters (kernels) to extract features.
- **Activation Layers:** Typically ReLU.
- **Pooling Layers:** Downsample feature maps.
- **Fully Connected Layers:** Perform classification.
- **Output Layer:** Softmax for probabilities.


Input Image
Convolution
ReLU
Pooling
Convolution
ReLU
Pooling
Flatten
Fully Connected
Output

Kernel (Filter):

- A small matrix (e.g., 3×3) slid over the input.
- Computes dot product to produce feature maps.
- Learns to detect edges, textures, patterns.

Pooling:

- Reduces spatial dimensions.
- **Max Pooling:** Takes maximum value in window.
- **Average Pooling:** Takes average.
- Reduces computation and controls overfitting.

Result: CNNs automatically learn hierarchical features, achieving state-of-the-art performance in image tasks.

Explain how different data modalities are integrated to improve user experience in multimodal systems with a real-time application (5 marks)


Multimodal Integration combines text, audio, image, and video to create richer, context-aware systems.

Fusion Strategies:

- **Early Fusion:** Combine raw features before model training.
- **Late Fusion:** Combine decisions from separate models.
- **Hybrid Fusion:** Intermediate combination.

Real-Time Application: Multimodal Virtual Assistant

- **Inputs:** Voice (audio), facial expression (video), text query.
- **Integration:**
  - Audio → Speech-to-text → NLP.
  - Video → Facial emotion recognition.
  - Text → Intent classification.
- **Fusion:** Late fusion of sentiment, intent, and emotion.
- **Output:** Personalized response (e.g., empathetic tone).



Result: Multimodal integration improves accuracy, robustness, and user satisfaction by leveraging complementary information.

If TP, FP, FN, TN are given, compute Accuracy, Precision, Error Rate, Sensitivity, Specificity, and F1 Score (5 marks)

Given:

- TP = 40, FP = 10, FN = 20, TN = 30

Calculations:

- **Accuracy:** $\frac{TP + TN}{TP + TN + FP + FN} = \frac{40 + 30}{100} = 0.70$
- **Precision:** $\frac{TP}{TP + FP} = \frac{40}{50} = 0.80$
- **Error Rate:** $1 - \text{Accuracy} = 0.30$
- **Sensitivity (Recall):** $\frac{TP}{TP + FN} = \frac{40}{60} = 0.667$
- **Specificity:** $\frac{TN}{TN + FP} = \frac{30}{40} = 0.75$
- **F1 Score:** $2 \times \frac{\text{Precision} \times \text{Recall}}{\text{Precision} + \text{Recall}} = 2 \times \frac{0.80 \times 0.667}{1.467} = 0.727$

Result:

- Accuracy = **0.70**
- Precision = **0.80**
- Error Rate = **0.30**
- Sensitivity = **0.667**
- Specificity = **0.75**
- F1 Score = **0.727**

Evaluate performance of Classifier 1 and Classifier 2 using confusion matrices (5 marks)

Classifier 1:

	F'	N'
F	20	10
N	10	60

- TP = 20, FN = 10, FP = 10, TN = 60
- **Accuracy:** (\frac{20 + 60}{100} = 0.80)
- **Precision:** (\frac{20}{30} = 0.667)
- **Recall:** (\frac{20}{30} = 0.667)
- **Specificity:** (\frac{60}{70} = 0.857)
- **F1 Score:** (2 \times \frac{0.667 \times 0.667}{1.334} = 0.667)

Classifier 2:

	F'	N'
F	0	15
N	5	80

- TP = 0, FN = 15, FP = 5, TN = 80
- **Accuracy:** (\frac{0 + 80}{100} = 0.80)
- **Precision:** (\frac{0}{5} = 0)
- **Recall:** (\frac{0}{15} = 0)
- **Specificity:** (\frac{80}{85} = 0.941)
- **F1 Score:** (0)

Metric	Classifier 1	Classifier 2
Accuracy	0.80	0.80
Precision	0.667	0
Recall	0.667	0
Specificity	0.857	0.941
F1 Score	0.667	0

Result: Classifier 1 is superior for fraud detection because it correctly identifies fraud cases (Recall = 0.667), while Classifier 2 fails to detect any fraud (Recall = 0), despite similar accuracy. This highlights the importance of using precision, recall, and F1 over accuracy alone on imbalanced data.