

Audit Log Integrity Verification

Date: 2026-04-10 **Source:** Production RDS (`denali-prod` , us-east-1) via ECS exec read-only query

Schema

Column	Type	Nullable	Default
id	uuid	NO	gen_random_uuid()
user_id	uuid	YES	null
action	text	NO	null
resource_type	text	YES	null
resource_id	text	YES	null
metadata	jsonb	YES	'{}'::jsonb
ip_address	text	YES	null
user_agent	text	YES	null
created_at	timestamptz	YES	now()

Foreign Key

constraint: audit_logs_user_id_fkey
definition: FOREIGN KEY (user_id) REFERENCES users(id) ON DELETE SET NULL

When a user deletes their account, their audit log rows are preserved with `user_id` set to `NULL` . The 6-year HIPAA retention guarantee holds. Rows are never cascade-deleted.

Indexes

Index	Definition
audit_logs_pkey	UNIQUE btree (id)
idx_audit_logs_user	btree (user_id, created_at DESC)
idx_audit_logs_action	btree (action, created_at DESC)

Row Statistics

Metric	Value
Total rows	100
Distinct users	6
Oldest entry	2026-02-27

Newest entry	2026-03-25
--------------	------------

Baseline Migration

The full production schema is documented in version control at `scripts/migrate-audit-logs-baseline.sql` (commit `3307903`). This file is idempotent (`CREATE TABLE IF NOT EXISTS`) and includes `REVOKE UPDATE, DELETE, TRUNCATE` statements for database-layer append-only enforcement.