



RDS Deployment Guide for Google Cloud (GCP)

Virtual Desktop Service

Toby vanRoojen
February 17, 2021

Table of Contents

RDS Deployment Guide for Google Cloud (GCP)	1
Overview	1
Deployment architecture	1
RDS basics	1
Guide scope	1
Create service account	2
Enable Google compute API	6
Create new VDS deployment	7
Create a new provisioning collection	18
Create new workspace	22

RDS Deployment Guide for Google Cloud (GCP)

Overview

This guide will provide the step by step instructions to create a Remote Desktop Service (RDS) deployment utilizing NetApp Virtual Desktop Service (VDS) in Google Cloud.

This Proof of Concept (POC) guide is designed to help you quickly deploy and configure RDS in your own test GCP Project.

Production deployments, especially into existing AD environments are very common however that process is not considered in this POC Guide. Complex POCs and production deployments should be initiated with the NetApp VDS Sales/Services teams and not performed in a self-service fashion.

This POC document will take you thru the entire RDS deployment and provide a brief tour of the major areas of post-deployment configuration available in the VDS platform. Once completed you'll have a fully deployed and functional RDS environment, complete with session hosts, applications and users. Optionally you'll have the option to configure automated application delivery, security groups, file share permissions, Cloud Backup, intelligent cost optimization. VDS deploys a set of best practice settings via GPO. Instructions on how to optionally disable those controls are also included, in the event your POC needs to have no security controls, similar to an unmanaged local device environment.

Deployment architecture



RDS basics

VDS deploys a fully functional RDS environment, with all necessary supporting services from scratch. This functionality can include:

- RDS gateway server(s)
- Web client access server(s)
- Domain controller server(s)
- RDS licensing service
- ThinPrint licensing service
- Filezilla FTPS server service

Guide scope

This guide walks you through the deployment of RDS using NetApp VDS technology from the perspective of a GCP and VDS administrator. You bring the GCP project with zero pre-configuration and this guide helps you setup RDS end-to-end.

Create service account


1. In GCP, navigate to (or search for) *IAM & Admin > Service Accounts*

The screenshot shows the Google Cloud Platform dashboard for the project "VDS Sandbox G6". The left sidebar is collapsed, showing options like Marketplace, Billing, APIs & Services, Support, IAM & Admin, Getting started, Security, Anthos, Compute, App Engine, Compute Engine, Kubernetes Engine, Cloud Functions, Cloud Run, VMware Engine, Storage, and Bigtable. The main content area is titled "Project info" and shows the project name "VDS Sandbox G6", Project ID "vds-sandbox-g6", and Project number "967069066092". Below this is a "Resources" section which says "This project has no resources". To the right, there's a "APIs" section with a chart showing "Requests (requests/sec)" over time from 9 AM to 9:45 AM, and a note that "No data is available for the selected time frame". On the far right, there are cards for "Google Cloud Platform status" (All services normal), "Billing" (Estimated charges USD 0.00 for Sep 1 - 29, 2020), "Monitoring" (Set up alerting policies, Create uptime checks, View all dashboards, Go to Monitoring), "Error Reporting" (No sign of any errors, Learn how to set up Error Reporting), and "News". A "DISMISS" button is at the top right of the status bar.


2. Click + CREATE SERVICE ACCOUNT

The screenshot shows the "Service accounts - IAM & Admin" page. The left sidebar is expanded, showing "IAM & Admin" selected, followed by "Service accounts", "CREATE SERVICE ACCOUNT" (which is highlighted in blue), and "DELETE". Below this is a list of IAM components: IAM, Identity & Organization, Policy Troubleshooter, Organization Policies, Quotas, and Service Accounts. Under "Service Accounts", there are sub-options: Labels, Settings, Privacy & Security, Identity-Aware Proxy, Roles, Audit Logs, Manage Resources, and Groups. At the bottom of the sidebar is a "Manage resources" link. The main content area is titled "Service accounts for project "VDS Sandbox G6"" and contains a note: "A service account represents a Google Cloud service identity, such as code running on Compute Engine VMs, App Engine apps, or systems running outside Google. [Learn more about service accounts](#). Organization policies can be used to secure service accounts and block risky service account features, such as automatic IAM Grants, key creation/upload, or the creation of service accounts entirely. [Learn more about service account organization policies](#)." There is also a "Filter table" section with columns: Email, Status, Name (with an upward arrow), Description, Key ID, Key creation date, and Actions. A message at the bottom says "No rows to display".


3. Enter a unique service account name, click *CREATE*. Make a note of the service account's email address which will be used in a later step.




4. Select the *Owner* role for the service account, click *CONTINUE*



5. No changes are necessary on the next page (*Grant users access to this service account(optional)*), click *DONE*




6. From the *Service accounts* page, click the action menu and select *Create key*



7. Select *P12*, click *CREATE*

The screenshot shows the Google Cloud Platform IAM & Admin Service accounts page. On the left, there's a sidebar with various navigation options like IAM, Identity & Organization, Policy Troubleshooter, Quotas, and Service Accounts. The Service Accounts section is currently selected. In the main area, it shows a table of service accounts for the project "VDS Sandbox G6". One account, "novavelocity", is listed with a status of "Active", name "novavelocity", description "VDS deploy for Toby", and "No keys". A modal dialog box is open over the table, titled "Create private key for 'novavelocity'". It contains instructions about downloading a private key file and selecting a key type (JSON or P12). The "P12" option is selected. At the bottom of the dialog are "CANCEL" and "CREATE" buttons, with "CREATE" being highlighted.

8. Download the .P12 file and save it to your computer. Leaved the *Private key password* unchanged.



The screenshot shows the Google Cloud Platform IAM & Admin Service Accounts page. A service account named 'novavelocity' is listed. A modal window is open, titled 'Private key saved to your computer', containing a warning message: 'vds-sandbox-g6-f3804ca3023f.p12 allows access to your cloud resources, so store it securely.' Below the warning is a text input field with the password 'notasecret'. A 'CLOSE' button is at the bottom right of the modal.

Enable Google compute API

1. In GCP, navigate to (or search for) *APIs & Services > Library*

The screenshot shows the Google Cloud Platform API Library page. A search bar at the top is set to 'Library'. The results list includes several APIs, with 'Compute Engine API' being one of them. Other APIs listed include RxNorm, Library of Integrated Network-Based Cellular Signatures (LINCS), Photos Library API, AbanteCart Certified by Bitnami, AISE PyTorch CPU Notebook, AISE PyTorch CPU Production, AISE PyTorch NVidia GPU Production, AISE TensorFlow CPU Notebook, AISE TensorFlow NVidia GPU Notebook, Caffe Python 3.6 Nvidia GPU Production, CanvasJS for Data Visualization & Analytics, Coppermine, and Custom Governance.

2. In the GCP API Library, navigate to (or search for) *Compute Engine API*, Click *ENABLE*

The screenshot shows the Google Cloud Platform API Library interface. A search bar at the top contains the query 'comput engine'. Below the search bar, a sidebar titled 'Filter by CATEGORY' lists various categories: Big data (1), Compute (5), Developer tools (1), Financial services (1), Google Cloud APIs (2), Networking (1), Storage (1), and Other (3). The main content area displays 10 results under the heading '10 results'. Each result is a card with a thumbnail icon, the API name, the provider (Google), and a brief description. The results include:

- Compute Engine API
- Compute Engine Instance Group Manager API
- App Engine Admin API
- Kubernetes Engine API
- Google App Engine Flexible Environment
- Compute Engine Instance Group Updater API
- Compute Engine Instance Groups API
- Web Security Scanner API


The URL in the browser address bar is <https://console.cloud.google.com/apis/library/compute.googleapis.com?q=comput%20engine&id=a08439d8-80d6-43f1-af2e-6878251f018d&project=vds-sandbox-g6&authuser=2>.

Create new VDS deployment


1. In VDS, navigate to *Deployments* and click *+ New Deployment*

The screenshot shows the NetApp Virtual Desktop Service (VDS) interface. The left sidebar has a tree view with 'NetApp' selected, followed by 'Virtual Desktop Service'. Under 'Virtual Desktop Service', the 'Deployments' node is expanded, showing sub-options: Workspaces, App Services, Service Board, Scripted Events, Admins, Reports, and SaaS Backup. The main content area has a header with a search bar and a user profile 'Toby vanRoojen'. Below the header, there is a message: '⚠ You have 5 deployment(s) which require manual intervention for completion'. A table lists the deployments with columns: Deployment, Code, Version, Infrastructure Platform, Clients, Connection, and Status. At the bottom right of the table, there are 'Refresh' and '+ New Deployment' buttons. The URL in the browser address bar is <https://preview.manage.cloudworkspace.com/#/deployments>.

2. Enter a name for the deployment



3. Select Google Cloud Platform



Infrastructure platform

1. Enter the *Project ID* and OAuth Email address. Upload the .P12 file from earlier in this guide and select the appropriate zone for this deployment. Click *Test* to confirm the entries are correct and the appropriate permissions have been set.



The OAuth email is the address of the service account created earlier in this guide.

New Deployment

Platform

Google Cloud Platform

Project ID: vds-sandbox-g6

OAuth Email: novelocity@vds-sandbox-g6.iam.gserviceaccount.com P12 Key File Select File 1 file imported

Zone: us-central1-a

Test Authentication Untested

Cancel Save & Close Continue

2. Once confirmed, click *Continue*

New Deployment

Platform

Google Cloud Platform

Project ID: vds-sandbox-g6

OAuth Email: box-g6.iam.gserviceaccount.com P12 Key File Select File 1 file imported

Zone: us-central1-a

Test Confirmed

Cancel Save & Close Continue

Accounts

Local VM accounts

1. Provide a password for the local Administrator account. Document this password for later use.
2. Provide a password for the SQL SA account. Document this password for later use.



Password complexity requires an 8 character minimum with 3 of the 4 following character types: uppercase, lowercase, number, special character

SMTP account

VDS can send email notifications via custom SMTP settings or the built-in SMTP service can be used by selecting *Automatic*.

1. Enter an email address to be used as the *From* address when email notification are sent by VDS. *no-reply@<your-domain>.com* is a common format.
2. Enter an email address where success reports should be directed.
3. Enter an email address where failure reports should be directed.

The screenshot shows the 'New Deployment' dialog box in the VDS interface. The 'Accounts' tab is selected. Under 'Local VM Admin', the 'Username' is set to 'Administrator' and the 'Password' is masked. Under 'SQL SA Password', the password is also masked. In the 'SMTP Account' section, the 'SMTP Configuration' is set to 'Automatic' (radio button selected). The 'From Address' is set to 'no-reply@GCP-VDS-Demo.com'. Below this, 'Report Success To Address' and 'Report Failure To Address' are both set to 'tobyvanroojen@netapp.com'. At the bottom of the dialog, there are 'Cancel', 'Save & Close', and 'Continue' buttons.

Level 3 technicians

Level 3 technician accounts (aka. *.tech accounts*) are domain-level accounts for VDS admins to use when performing administrative tasks on the VMs in the VDS environment. Additional accounts can be created on this step and/or later.

1. Enter the username and password for the Level 3 admin account(s). ".tech" will be appended to the user name you enter to help differentiate between end users and tech accounts. Document these credentials for later use.



The best practice is to define named accounts for all VDS admins that should have domain-level credentials to the environment. VDS admins without this type of account can still have VM-level admin access via the *Connect to server* functionality built into VDS.


Domains

Active directory

Enter the desired AD domain name.

Public domain

External access is secured via an SSL certificate. This can be customized with your own domain and a self-managed SSL certificate. Alternatively, selecting *Automatic* allows VDS to manage the SSL certificate including an automatic 90-day refresh of the certificate. When using automatic, each deployment uses a unique sub-domain of *cloudworkspace.app*.



Virtual machines

For RDS deployments the required components such as domain controllers, RDS brokers and RDS gateways need to be installed on platform server(s). In production these services should be run on dedicated and redundant virtual machines. For proof of concept deployments a single VM can be used to host all of these services.

Platform VM configuration

Single virtual machine

This is the recommended selection for POC deployments. In a Single virtual machine deployment the following roles are all hosted on a single VM:

- CW Manager
- HTML5 Gateway
- RDS Gateway
- Remote App
- FTPS Server (Optional)
- Domain Controller

The maximum advised user count for RDS use cases in this configuration is 100 users. Load balanced RDS/HTML5 gateways are not an option in this configuration, limiting the redundancy and options for increasing scale in the future.



If this environment is being designed for multi-tenancy, a Single virtual machine configuration is not supported.

Multiple servers

When splitting the VDS Platform into Multiple virtual machines the following roles are hosted on dedicated VMs:

- Remote Desktop Gateway

VDS Setup can be used to deploy and configure one or two RDS Gateways. These gateways relay the RDS user session from the open internet to the session host VMs within the deployment. RDS Gateways handle an important function, protecting RDS from direct attacks from the open internet and to encrypt all RDS traffic in/out of the environment. When two Remote Desktop Gateways are selected, VDS Setup deploys 2 VMs and configures them to load balance incoming RDS user sessions.

- HTML5 Gateway

VDS Setup can be used to deploy and configure one or two HTML5 Gateways. These gateways host the HTML5 services used by the *Connect to Server* feature in VDS and the web-based VDS Client (H5 Portal). When two HTML5 Portals are selected, VDS Setup deploys 2 VMs and configures them to load balance incoming HTML5 user sessions.



When using Multiple server option (even if users will only connect via the installed VDS Client) at least one HTML5 gateway is highly recommended to enable *Connect to Server* functionality from VDS.

- Gateway Scalability Notes

For RDS use cases, the maximum size of the environment can be scaled out with additional Gateway VMs, with each RDS or HTML5 Gateway supporting roughly 500 users. Additional Gateways can be added later with minimal NetApp professional services assistance

If this environment is being designed for multi-tenancy then the *Multiple servers* selection is required.

Service roles

- Cwmgr1

This VM is the NetApp VDS administrative VM. It runs the SQL Express database, helper utilities and other administrative services. In a *single server* deployment this VM can also host the other services but in a *multiple server* configuration those services are moved to different VMs.

- CWPortal1(2)

The first HTML5 gateway is named *CWPortal1*, the second is *CWPortal2*. One or two can be created at deployment. Additional servers can be added post-deployment for increased capacity (~500 connections per server).

- CWRDSGateway1(2)

The first RDS gateway is named *CWRDSGateway1*, the second is *CWRDSGateway2*. One or two can be created at deployment. Additional servers can be added post-deployment for increased capacity (~500 connections per server).

- Remote App

App Service is a dedicated collection for hosting RemotApp applications, but uses the RDS Gateways and

their RDWeb roles for routing end user session requests and hosting the RDWeb application subscription list. No VM dedicated vm is deployed for this service role.

- Domain Controllers

At deployment one or two domain controllers can be automatically built and configured to work with VDS.

The screenshot shows the 'New Deployment' interface. On the left, a sidebar lists 'Infrastructure Platform' sections: Accounts, Domains, Virtual Machines (selected), Network (with a green checkmark), Licensing, and Review & Provision. The main area is titled 'Additional services' with an unchecked 'Include FTP' checkbox. A large blue box highlights the 'Included services and VMs' section. This section contains a table:

Service	# of VMs
Cwmgr1	1
CWPortal1(2)	2 ▾
CWRDSSGateway1(2)	1 ▾
Remote App	1
Domain Controllers	1

Below the table is a dropdown labeled '# of Domain Controllers' set to '2'. At the bottom are 'Cancel', 'Save & Close', and 'Continue' buttons.

Operating system

Select the desired server operating system to be deployed for the platform servers.


Time zone

Select the desired timezone. The platform servers will be configured to this time and log files will reflect this timezone. End user session will still reflect their own timezone, regardless of this setting.

Additional services

FTP

VDS can optional install and configure Filezilla to run an FTPS server for moving data in and out of the environment. This technology is older and more modern data transfer methods (like Google Drive) are recommended.



Network

It is a best practice to isolate VMs to different subnets according to their purpose.

Define the network scope and add a /20 range.


VDS Setup detects and suggests a range that should prove successful. Per best practices, the subnet IP addresses must fall into a private IP address range.

These ranges are:

- 192.168.0.0 through 192.168.255.255
- 172.16.0.0 through 172.31.255.255
- 10.0.0.0 through 10.255.255.255

Review and adjust if needed, then click Validate to identify subnets for each of the following:

- Tenant: this is the range in which session host servers and database servers will reside
- Services: this is the range in which PaaS services like Cloud Volumes Service will reside
- Platform: this is the range in which Platform servers will reside
- Directory: this is the range in which AD servers will reside



Licensing

SPLA


Enter your SPLA number so VDS can configure the RDS licensing service for easier SPLA RDS CAL reporting. A temporary number (such as 12345) can be entered for a POC deployment but after a trial period (~120 days) the RDS sessions will stop connecting.

SPLA products

Enter the MAK license codes for any Office products licensed via SPLA to enable simplified SPLA reporting from within VDS reports.


ThinPrint

Choose to install the included ThinPrint licensing server and license to simplify end user printer redirection.



Review & provision

Once all steps have been completed, review the selections, then validate and provision the environment.



Next steps

The deployment automation process will now deploy a new RDS environment with the options you selected throughout the deployment wizard.

You'll receive multiple emails as the deployment completes. Once complete you'll have an environment ready for your first workspace. A workspace will contain the session hosts and data servers needed to support the end users. Come back to this guide to follow the next steps once the deployment automation completes in 1-2 hours.

Create a new provisioning collection

Provisioning collections is functionality in VDS that allows for the creation, customization and SysPrep of VM images. Once we get into the workplace deployment, we'll need an image to deploy and the following steps will guide you thru creating a VM image.

Follow these steps to create a basic image for deployment:

1. Navigate to *Deployments > Provisioning Collections*, click *Add*


The screenshot shows the 'Virtual Desktop Service' interface. On the left, there's a sidebar with links like Dashboard, Organizations, Deployments (which is selected), Workspaces, App Services, Service Board, Scripted Events, Admins, Reports, and SaaS Backup. The main content area has a title 'GCP Deploy Demo (fss)' and tabs for Overview, Resource Defaults, Backup Defaults, and Provisioning Collections (which is active). Below this is a table titled 'Provisioning Collections' with columns: Name, Type, Operating System, Servers, Apps, Min. Cache, Current Cache, and Status. There are three entries: 'BaseHostImage' (VDI, Windows Server 2016, 1 server, 0 apps, 0 cache, Available), 'Default PC' (Shared, Windows Server 2016, 1 server, 0 apps, 0 cache, Available), and 'GCP Deploy Demo' (Shared, Windows Server 2016, 1 server, 1 app, 0 cache, Available). An 'Add' button is located at the top right of the table. The URL in the browser is https://preview.manage.cloudworkspace.com/#/deployments/fss?view=choice-collections.

2. Enter a Name and Description. Choose *Type: Shared*.




You can choose Shared or VDI. Shared will support a session server plus (optionally) a business server for applications like a database. VDI is a single VM image for VMs that will be dedicated to individual users.

3. Click *Add* to define the type of server image to build.



4. Select TSData as the **server role**, the appropriate VM image (Server 2016 in this case) and the desired storage type. Click **Add Server**




5. Optionally select the applications that will be installed on this image.

- a. The list of applications available is populated from the App Library that can be accessed by clicking the admin name menu in the upper right corner, under the *Settings > App Catalog* page.


6. Click *Add Collection* and wait for the VM to be built. VDS will build a Vm that can be accessed and customized.
7. Once the VM build has completed, connect to the server and make the desired changes.
 - a. Once the status shows *Collection Validation*, click the collection name.


Name	Type	Operating System	Servers	Apps	Min. Cache	Current Cache	Status
GCP	VDI		1	0	0	0	Collection Validation
BaseImage	VDI		1	0	0	0	Available
Default PC	Shared	Windows Server 2016	1	0	0	0	Available
GCP Deploy Demo	Shared	Windows Server 2016	1	1	0	0	Available

- b. Then, click the *server template name*




- c. Finally, click the **Connect to Server** button to be connected and automatically logged into the VM with local admin credentials.





8. Once all customizations have been completed, click *Validate Collection* so VDS can sysprep and finalize the image. Once complete, the VM will be deleted and the image will be available for deployment from within VDS deployment wizards.



5


Create new workspace

A workspace is a collection of session hosts and data servers that support a group of users. A deployment can contain a single workspace (single-tenant) or multiple workspaces (multi-tenant).

Workspaces define the RDS server collection for a specific group. In this example, we will deploy a single collection to demonstrate the virtual desktop capability. However, the model can be extended to multiple workspaces/ RDS collections to support different groups and different locations within the same Active Directory domain space. Optionally, administrators can restrict access between the workspaces/collections to support use cases that require limited access to applications and data.


Client & settings

1. In NetApp VDS, navigate to *Workspaces* and click *+ New Workspace*



The screenshot shows the NetApp Virtual Desktop Service (VDS) web interface. The URL in the browser is https://preview.manage.cloudworkspace.com/#/workspaces. The page has a dark header with the NetApp logo and 'Virtual Desktop Service'. Below the header is a navigation bar with links for Dashboard, Organizations, Deployments, Workspaces (which is highlighted in blue), App Services, Service Board, Scripted Events, Admins, Reports, and SaaS Backup. To the right of the navigation bar are search, refresh, and user profile icons. The main content area has tabs for Workspaces, Code, Deployment, Users, and Status. A green button labeled '+ New Workspace' is located in the top right of the main content area. At the bottom left of the page, there is a copyright notice: © 2020 NetApp, Inc. Privacy / Terms of Use.

2. click *Add* to create a new client. The client details typically represent either the company information or the information for a specific location/department.



- Enter company details and select the deployment into which this workspace will be deployed.
- Data Drive:** Define the drive letter to be used for the company share mapped drive.
- User Home Drive:** Define the drive letter to be used for the individual's mapped drive.
- Additional Settings**

The following settings can be defined at deployment and/or selected post-deployment.

- Enable Remote App:* Remote app presents applications as streaming applications instead of (or in addition to) presenting a full remote desktop session.
- Enable App Locker:* VDS contains applications deployment and entitlement functionality, by default the system will show/hide applications to the end users. Enabling App Locker will enforce application access via a GPO safelist.
- Enable Workspace User Data Storage:* Determine if end users have a need to have data storage access in their virtual desktop. For RDS deployments, this setting should always be checked to enable data access for user profiles.
- Disable Printer Access:* VDS can block access to local printers.
- Permit Access to Task Manager:* VDS can enable/disable end user access to the Task Manager in Windows.
- Require Complex User Password:* Requiring complex passwords enables the native Windows Server complex password rules. It also disables the time-delayed automatic unlock of locked user accounts. Thus, when enabled, admin intervention is required when end users lock their accounts with multiple failed password attempts.
- Enable MFA for All Users:* VDS includes a no-cost email/SMS MFA service that can be used to secure end user and/or VDS admin account access. Enabling this will require all end users in this workspace authenticate with MFA to access their desktop and/or apps.

Choose applications


Select the Windows OS version and Provisioning collection created earlier in this guide.

Additional applications can be added at this point but for this POC we'll address application entitlement post-deployment.

The screenshot shows a web-based interface for creating a new workspace. The URL is https://preview.manage.cloudworkspace.com/#/workspaces. The main menu on the left includes options like Dashboard, Organizations, Deployments, Workspaces (which is selected), App Services, Service Board, Scripted Environments, Admins, Reports, and SaaS Backup. The central area is titled 'New Workspace' and has four tabs: Client & Settings, Choose Applications (which is active), Add Users, and Review & Provision. Under 'Choose Applications', there's a section for 'Select a Provisioning Collection' which shows 'Deployment' selected and 'Windows Server 2016' chosen from a dropdown. The 'Applications' section lists 'Included with collection' with 'Firefox' checked. The 'App Services' section states 'No App Services Available for the Selected Provisioning Collection.' At the bottom, there are 'Back', '(1) Applications Selected', 'View', 'Cancel', and 'Continue' buttons.


Add Users

Users can be added by selecting an existing AD security groups or individual users. In this POC guide we'll add users post-deployment.



Review & provision

On the final page, review the chosen options and click *Provision* to start the automated build of the RDS resources.





During the deployment process, logs are created and can be accessed under *Task History* near the bottom of the Deployment details page. Accessible by navigating to *VDS > Deployments > Deployment Name*

Next steps

The workplace automation process will now deploy a new RDS resources with the options you selected throughout the deployment wizard.

Once complete, there are several common workflows you'll follow to customize the typical RDS deployment.

- [Add Users](#)
- [End User Access](#)
- [Application Entitlement](#)
- [Cost Optimization](#)

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.