

AI 2002

Artificial Intelligence

Dr. Hashim Yasin

Terminologies


Visited (Open) List:

- ▶ The *set of all leaf nodes available for expansion* at any given point is called the open list, (may be referred as **frontier**).
- ▶ In general, a state is said to be visited if it has ever shown up in search a node.
- ▶ The intuition is that *we have visited* them, but *we have not generated its descendants*.


Expanded (Closed, Explored) List:

- ▶ *Algorithms that forget their history are doomed to repeat it.*
- ▶ The way to avoid exploring redundant paths is to remember where one has been.
- ▶ To do this, we design **explored set** (also known as the **closed list**), which remembers every expanded node.

Terminologies



Depth First Search



Breadth First Search

Terminologies

Partial search trees for finding a route from Arad to Bucharest.

- ❑ Nodes that have been **visited but not yet expanded** are outlined in **bold**;
- ❑ Nodes that have been **expanded are shaded**;
- ❑ Nodes that have **not been visited** are shown in faint dashed lines.


(a) The initial state



(b) After expanding Arad



(c) After expanding Sibiu




Depth-First Search

Depth-First Search (without-visited)

- ☐ Pick first element of Q
- ☐ Add path extensions **in front** to Q

	Q
1	(S)
2	(A S) (B S)
3	(C A S) (D A S) (B S)
4	(D A S) (B S)
5	(C D A S) (G D A S) (B S)
6	(G D A S) (B S)




- ☐ **Blue Color represents added paths**
- ☐ Path has been shown in **reversed order**, node state is the first entry.
 - ☐ Traversal = S, A, C, D, C, G
 - ☐ The Final path = S, A, D, G

Depth-First Search





- ❑ Pick first element of Q
- ❑ Add path extensions **in front** to Q

	Q	Visited	Expanded
1	(S)	S	S
2	(A S) (B S)	A, B, S	A, S
3	(C A S) (D A S) (B S)	C, D, B, A, S	C, A, S
4	(D A S) (B S)	C, D, B, A, S	D, C, A, S
5	(G D A S) (B S)	G, C, D, B, A, S	G, D, C, A, S





- ❑ **Blue Color represents added paths**
- ❑ Path has been shown in **reversed order**, node state is the first entry.
- ❑ **Traversal = S, A, C, D, G**
- ❑ **The Final path = S, A, D, G**

Depth-First Search













NB: C is not
visited again



Numbers indicate order pulled off of Q (expanded)

Dark blue fill = Visited and Expanded

Light gray fill = Visited



DFS Example 2

Depth-First Search

- ▶ Depth-first search always expands the ***deepest node***
- ▶ Implemented with a **last-in-first-out (LIFO)** strategy, also known as a **stack**.
- ▶ As an alternative to the ***Graph-Search-style*** implementation, depth-first search is implemented with a **recursive function** that calls itself on each of its children in turn.

Depth-First Search


Completeness:

- ▶ The graph-search version, which *avoids repeated states and redundant paths*, is **complete** in finite state spaces because it will eventually expand every node.
- ▶ The tree-search version, on the other hand, it is **not complete**.

Optimality:

- ▶ It doesn't guarantee the best solution.

Depth-First Search



A simplified road map of part of Romania.


(a) The initial state



(b) After expanding Arad



(c) After expanding Sibiu



Depth-First Search

It overcomes **time and space** complexities.

Time:

- ▶ $O(b^m)$: terrible if m (maximum length of the depth) is much larger than the size of the state space.
- ▶ *If solutions are dense, may be much faster than breadth-first.*

Space:

- ▶ $O(bm)$, i.e., linear space!
- ▶ A variant of depth-first search with **backtracking search** uses still less memory $O(m)$.

Comparison with BFS

Depth	Nodes	Time	Memory
2	110	.11 milliseconds	107 kilobytes
4	11,110	11 milliseconds	10.6 megabytes
6	10^6	1.1 seconds	1 gigabyte
8	10^8	2 minutes	103 gigabytes
10	10^{10}	3 hours	10 terabytes
12	10^{12}	13 days	1 petabyte
14	10^{14}	3.5 years	99 petabytes
16	10^{16}	350 years	10 exabytes

Time and memory requirements for breadth-first search. The numbers shown assume branching factor $b = 10$; 1 million nodes/second; 1000 bytes/node.

The depth-first search would require **156 kilobytes** instead of 10 Exabyte at depth $d = 16$, a factor of **7 trillion times less space**.

Depth-limited Search

Depth-limited Search

- ▶ The problem of depth first search can be alleviated by supplying depth-first search with a **pre-determined depth limit l** .

$$l < d$$

- ▶ Nodes at depth l are treated as if they have no successors.

Completeness:

- ▶ It may be incomplete if we choose $l < d$, that is, the shallowest **goal is beyond the depth limit l** .

Optimality:

- ▶ The depth-limited search may be non-optimal if we choose $l > d$.

Depth-limited Search

Time complexity: $O(b^l)$

Space complexity: $O(bl)$

- ▶ *Depth-first search can be viewed as a special case of depth-limited search with*

$$l = \infty$$

- ▶ Depth limited search can be based on knowledge of the problem.
 - For the most problems, however, **we will not know a good depth limit until** we have solved the problem.

Iterative Deepening Search

Iterative Deepening Search

- ▶ No selection of the best depth limit
- ▶ It tries all possible depth limits:
 - first 0, then 1, 2, and so on
- ▶ Combines the benefits of depth-first and breadth-first search,

```
function ITERATIVE-DEEPENING-SEARCH(problem) returns a solution
  inputs: problem, a problem
  for depth ← 0 to  $\infty$  do
    result ← DEPTH-LIMITED-SEARCH(problem, depth)
    if result  $\neq$  cutoff then return result
  end
```

The cutoff value indicates that there is no any solution within the depth limit.

Iterative Deepening Search





► $\ell = 0$:

Limit = 0



► $\ell = 1$:


Limit = 1



Iterative Deepening Search

► $\ell = 2$:


Limit = 2



Iterative Deepening Search

► $\ell = 3$:

Limit = 3



Iterative Deepening Search

Complete?? Yes if ***b*** is finite

Time?? $(d)b + (d-1)b^2 + \dots + (1)b^d = O(b^d)$

Space?? $O(bd)$

Optimal?? Yes, if step cost = 1

Can be modified to explore uniform-cost tree


IDS suitable for the problem

- having a large search space
- and the *depth of the solution is not known*

Real Life Example

Example ... DFS

- ❑ Finding a path in the given grid using DFS.
- ❑ The order of the actions are **up, left, right, then down**.
- ❑ Maintain the visited list to avoid looping.
- ❑ Number the square according to the traversal.



Reading Material

- ▶ **Artificial Intelligence, A Modern Approach**
Stuart J. Russell and Peter Norvig
 - Chapter 3.