



QATIP Intermediate AWS Lab8

Jenkins Terraform Pipelining

Contents

Lab Objectives.....	1
Teaching Points	1
Solution	2
Before you begin.....	2
Task1 Create a Jenkins EC2 instance.....	2
Task2 Create an S3 Bucket for Remote State	3
Task3 Configure Jenkins	3
Task4 Create a Github account and repository.....	4
Task5 Add AWS Credentials to Jenkins	9
Task6 Configure Pipeline Job.....	10
Task7 Verify pipeline run and explore Jenkins	11
Task8 Updating the transformation pipeline	12
Task9 (Time permitting). Configure Destroy Pipeline Job	15

Lab Objectives

In this lab you will:

- Deploy a network and an EC2 instance with Jenkins installed via a script.
- Configure an S3 remote backend
- Configure and test terraform pipelining using Jenkins to deploy, modify and destroy AWS resources

Teaching Points

This lab introduces the concept of Terraform pipelining with Jenkins, demonstrating how infrastructure as code (IaC) can be automated for consistent and repeatable deployments in AWS. You will gain hands-on

experience in setting up a Jenkins pipeline to execute Terraform configurations, allowing them to deploy, modify, and destroy AWS resources efficiently. By integrating Terraform with Jenkins, users can enforce version control, automate approvals, and implement CI/CD best practices for infrastructure management.

Key concepts covered include provisioning infrastructure with Terraform, configuring Jenkins to automate deployments, and managing Terraform state remotely using an S3 backend. Additionally, you will explore how Jenkins integrates with GitHub for source control, manage AWS credentials within Jenkins securely, and implement automated triggers using GitHub Webhooks. By the end of the lab, you should understand how to structure Terraform pipelines in Jenkins, troubleshoot deployment issues, and automate resource lifecycle management, ensuring scalable and reliable infrastructure provisioning in AWS.

Solution

Given the nature of this lab, there is no solution section. Please reach out to your instructor if you encounter any issues

Before you begin

1. Ensure you have completed Lab0 before attempting this lab.
2. In the IDE terminal pane, enter the following commands...
cd ~/environment/aws-tf-int/labs/08
3. This shifts your current working directory to labs/08. ***Ensure all IDE commands are executed in this directory***

Task1 Create a Jenkins EC2 instance

1. Examine the script files **create_ec2.sh** and **cleanup.sh** in labs/08. The first will create network resources and an EC2 instance in **us-west-2** into which Jenkins is installed. The second will be used to delete these resources at the end of the lab. Make the scripts executable...

```
chmod +x create_ec2.sh
```

```
chmod +x cleanup.sh
```

2. Run the create script

```
./create_ec2.sh
```

3. You can continue with the next task whilst the script runs.

4. Consider why these resources are being created manually and not using IaC.


Consider why these resources are being created manually and not using IaC.

Task2 Create an S3 Bucket for Remote State

1. Switch to the AWS Console.
2. Search for and then navigate to the **S3** service. Click on **Create bucket**
3. Ensure you are focussed on the **Oregon (us-west-2)** region
4. Name your bucket **jenkins-state-*<your-name>***. Every bucket name must be globally unique; therefore, you may get a message indicating that a bucket already exists with your chosen name. If so, then simply append a random number after your name. Record the name of this bucket.
5. Leaving all settings at their default values, scroll down and select **Create bucket**.

Task3 Configure Jenkins

1. Wait until the script to deploy Jenkins completes and then open Jenkins in a new browser tab using the url displayed in your IDE. (Your IP address and password will differ)



```
=====
Jenkins Deployment Complete
=====
Jenkins URL:
http://34.219.177.84:8080


Initial Admin Password:
85450d22f61c4a87808cea79f4c7c761
```

2. Copy and paste the admin password from the IDE into the **Unlock Jenkins** screen the click on Continue
3. Select **"Install suggested plugins"**
4. On the **"Create First Admin User"** screen; Select **"Skip and continue as admin"**
5. Click **"Save and Finish"** to complete the Jenkins configuration.
6. Click **"Start using Jenkins"**


Task4 Create a Github account and repository

Note: The process that follows was correct at time of writing. Github enrolment steps may change over time, so apply your own logic as you work through the process if it does not exactly match the steps that follow.


1. Sign up to Github using a personal email address that is not currently associated with Github...
 - a. Navigate to <https://github.com/>
 - b. Enter a personal email address and select "Sign up for Github"...




- c. Enter a password and a unique username of your choice..




- d. Record and save your chosen **username** and **password** in your session-info file for safekeeping.
- e. Complete the challenge to prove you are a human...



- f. An email will sent containing your launch code. Retrieve this and enter it..




g. You will then be prompted to log into github using your new account..




The image shows the GitHub sign-in page. At the top is the GitHub logo and the text "Sign in to GitHub". Below this is a blue notification box that says "Your account was created successfully. Please sign in to continue". The main form has two input fields: "Username or email address" with the value "testuser2697" and "Password" with masked characters. There is a "Forgot password?" link next to the password field. A green "Sign in" button is at the bottom of the form. Below the form is a link "Sign in with a passkey" and another link "New to GitHub? Create an account".

h. Complete the questionnaire...



The image shows a questionnaire form titled "This will help us guide you to the tools that are best suited for your projects." It asks "How would you describe yourself?" with radio button options: "Student", "Teacher", "Working developer", and "Other". It also asks "How many team members will be working with you?" with radio button options: "Just me", "2-5", "5-10", "10-20", "20-50", and "50+". A blue "Continue" button is at the bottom.


i. When asked to select a subscription, select **"Continue for free"**..



The image shows a button labeled "Continue for free" with a white background and a dark border.

2. Create a public repository ...

a. Click on New ...




The image shows the GitHub Dashboard. On the left, under "Create your first project", there is a green button labeled "Create repository" which is circled in orange. On the right, under "Home", there is a section "Start a new repository for testuser2697" with a form to create a new repository. The form has a "Repository name" field, radio buttons for "Public" and "Private" (with "Private" selected), and a green "Create a new repository" button. There are also links for "Start writing code", "Introduce yourself", and "Use tools of the trade".

- b. Enter a Repository name of your choice. Ensure **Public** is selected and check the **'Add a README file'** option. Then click on **Create repository...**


The screenshot shows the 'Create a new repository' page on GitHub. The 'Repository name' field is filled with 'jenkins-lab' and a green checkmark indicates it is available. The 'Owner' is 'testuser2697'. The 'Description (optional)' field is empty. The 'Public' radio button is selected. Under 'Initialize this repository with:', the 'Add a README file' checkbox is checked. The 'Add .gitignore' section shows 'None' selected. The 'Choose a license' section shows 'None' selected. A green 'Create repository' button is at the bottom right.

- c. Download the following files from **labs\08** to your local machine;
main.tf
Jenkinsfile


- d. Back in your repo; Click on **Add file, Upload file..**




- e. Select the **main.tf** and **Jenkinsfile** files you just downloaded
f. Click on Commit changes..



- g. The 2 files should now be listed..



h. Copy the URL of your repository to your clipboard..





i. Record this URL in your **session-info** file against **Repo-URL**

j. Click on the file **Jenkinsfile** and then click on the **edit** icon to open the file for editing...




k. On line 6, replace **{your github repo url here}**, including the braces, with your **Repo-URL** and then click on **Commit changes** twice...





l. Click on **main.tf** and then open it for edits...




- m. On line 6, replace **{your state bucket}**, including the braces, with the name of the bucket you created in Task1 (recorded earlier). This is where your statefile will be created when you initialize Terraform
- n. On line 13, replace **{yournamehere}**, including the braces, with your name followed by 2 random digits (to guarantee uniqueness). This will be the name of the bucket that Terraform will create when we run a Jenkins pipeline.
- o. Commit these changes as before. Example shown below, your bucket names will differ...

```
1 provider "aws" {
2   region = "us-east-1"
3 }
4 terraform {
5   backend "s3" {
6     bucket = "jenkins-state-mcg2697123456"
7     key    = "terraform.tfstate"
8     region = "us-east-1"
9     encrypt = true
10  }
11 }
12 resource "aws_s3_bucket" "example" {
13   bucket = "jenkins-test-bucket-mcg123456"
14 }
```


- p. Leave the Github tab open as we will return to it later.

Task5 Add AWS Credentials to Jenkins


1. In order to use Terraform on Jenkins to interact with AWS, we must supply it with credentials to use. In your **Jenkins** browser session; Navigate to **Manage Jenkins > Credentials**.
2. On the breadcrumb menu; click on the **Credentials** dropdown and then select **System ...**



3. Click on “**Global credentials (unrestricted)**”...



4. Click on “**Add Credentials**” then “**Username and Password**”
5. For Username: Enter the **Access key ID** generated for your lab user. This and the Secret Access key required next, can in the Portal lab startup instructions...



6. For Password: Enter the **Secret Access key** generated for your lab user
7. For ID: enter **aws_user**
8. Select “**Create**”

New credentials

Kind
Username with password

Scope ?
Global (Jenkins, nodes, items, all child items, etc)

Username ?
AKIAX7JSH46JHVQQS7M8

☐ Treat username as secret ?

Password ?
.....

ID ?
aws_user

Description ?

Create

Task6 Configure Pipeline Job

1. Select “+ New Item” from the Jenkins **dashboard**
2. Enter “**Terraform Pipeline**” as the item name
3. Select “**Pipeline**” as the item type
4. Click “**OK**”
5. On the **General** page displayed next, scroll down to the **Pipeline** section. Use the dropdown list to change the **Definition** from “**Pipeline script**” to “**Pipeline script from SCM**”
6. Select “**Git**” from the **SCM** dropdown list
7. In the **Repository URL**: Enter **your** Github repository URL, recorded in your session-info file as **Repo-URL**
8. In “**Branches to build**,” “**Branch Specifier**,” change from ***/master** to ***/main**

Pipeline

Definition
Pipeline script from SCM

SCM ?
Git

Repositories ?
Repository URL ?
https://github.com/qatip/jenkins-demo.git

Credentials ?
- none -


Add Repository

Branches to build ?
Branch Specifier (blank for 'any') ?
*/main

9. Click **"Save"**
10. Click **"Build Now"**

Task7 Verify pipeline run and explore Jenkins


1. In Jenkins, return to the Dashboard. A record of the pipeline will be displayed showing run success and failure. Refresh the page until a result of the pipeline run is displayed...




A screenshot of the Jenkins Pipeline table. The table has columns: S, W, Name, Last Success, Last Failure, and Last Duration. The first row shows a successful build for 'Terraform Pipeline' with a duration of 38 sec. A green play button icon is visible on the right side of the row.

S	W	Name	Last Success	Last Failure	Last Duration
✓	☀	Terraform Pipeline	1 min 30 sec #1	N/A	38 sec


2. Select the drop-down menu against **#1** and choose Pipeline Overview..




3. The stages of the pipeline are shown, with ticks (or crosses) indicating success or failure at that stage...



4. Spend a little time exploring the Jenkins interface, using the bread-crumb menu to navigate around, and finally return to the main Dashboard...



5. In the AWS console, navigate to the S3 service and verify the existence of your new storage bucket alongside the state bucket..




Task8 Updating the transformation pipeline


In a production environment, developers would now check-out the contents of the Github repo to their local machine, make updates to the terraform files and then check them back into the repo for approval. Once approved these changes would be merged with the current files and deployed by triggering a new pipeline run. This can be done manually in Jenkins or automatically using Webhooks, whereby Github notifies Jenkins of the changed files, and the pipeline run starts automatically to deploy these changes.

In this task we will modify the terraform files directly in Github before manually triggering a new pipeline run in Jenkins. We will then set up Webhooks to show how changes in Github can automatically trigger the pipeline run.


1. Return to your Github repository, logging back in if necessary.
2. Open **main.tf** for editing
3. Change the name of the bucket to be created by adding addition digits to the existing name. This will cause the original bucket to be deleted and a new one to be created. Commit this change..



4. Switch to Jenkins and click on the play icon to schedule a manual running of the pipeline..



5. The build Executor Status will show the progress of the run..




6. The success runs count should increase to #2 indicating successful manual running of the pipeline. (You may need to refresh the page)

7. Looking at the logs for the **Terraform Apply** phase we see that the old bucket was replaced as bucket names are immutable and cannot be changed...




8. Switch to your console and, in S3, verify the deletion of the old bucket and the creation of a new one, refreshing the display if necessary.


9. To configure automatic pipeline running; **In Jenkins**, configure the pipeline by first selecting it on the main dashboard and then choosing the **"Configure"** option..



10. Scroll down to the Build Triggers section, select “**Github hook trigger for GITScm polling**” and click on Save ...



11. **Switch to Github.** Select the **Settings** for your repo. Scroll down and select **Webhooks**. Click on **Add webhook** (you may be prompted to re-authenticate at this point)...



12. For **Payload URL**; enter **http://{Jenkins Public IP}:8080/github-webhook/** replacing **{Jenkins Public IP}** with the Public IP address of your Jenkins instance

13. For Content type; select **application/json**

14. Select to disable **SSL verification** for this lab environment.

15. Verify your settings as shown in example below (your IP will differ) before clicking on **Add webhook**..

Settings Recent Deliveries

We'll send a post request to the URL below with details of any subscribed events. You can also specify which data format you'd like to receive (JSON, x-www-form-urlencoded, etc). More information can be found in [our developer documentation](#).

Payload URL *

Content type *

Secret


SSL verification

☐ By default, we verify SSL certificates when delivering payloads.

☐ Enable SSL verification ☒ Disable (not recommended)

16. Make another change to the name of your bucket in **main.tf** and commit the changes (refer to steps 2 and 3 above if you need guidance)

17. Re-visit your Webhooks setting and you should see confirmation that there was a successful push of the changes to Jenkins...



18. Switch to Jenkins. Return to the Dashboard and check that there is now a record of a third successful running of the pipeline...

Dashboard >

+ New Item

Build History

Project Relationship

Check File Fingerprint

Manage Jenkins

My Views

All +

Add description


S	W	Name 1	Last Success	Last Failure	Last Duration
✓	☀	Terraform Pipeline	7 min 52 sec #3	N/A	35 sec

19. Switch to your AWS console, navigate to S3, refresh the display if necessary and verify the new bucket has been created.

Task9 (Time permitting). Configure Destroy Pipeline Job

1. Select “+ New Item” from the Jenkins **dashboard**

2. Use **"Terraform Pipeline Destroy"** as the item name
3. Select **"Pipeline"** as the item type
4. Click **"OK"**
5. On the **General** page displayed next, scroll down to the **Pipeline** section. Use the dropdown list to change the **Definition** from **"Pipeline script"** to **"Pipeline script from SCM"**
6. Select **"Git"** from the **SCM** dropdown list
7. In the **Repository URL:** Enter **your** Github repository URL, recorded in your session-info file as **Repo-URL**
8. In **"Branches to build," "Branch Specifier;"** change from ***/master** to ***/main**



Pipeline

Definition

Pipeline script from SCM

SCM ?

Git


Repositories ?

Repository URL ?

https://github.com/qatip/jenkins-demo.git

Credentials ?

- none -




Add Repository

Branches to build ?

Branch Specifier (blank for 'any') ?

*/main

9. Change the Script Path to **destroy/Jenkinsfile**




Script Path ?


destroy/Jenkinsfile

10. Save the new pipeline but do not build it yet
11. Switch to your Github account

12. Create a new empty Jenkinsfile in a new folder “destroy”...



Note: Entering **destroy/** will create the **destroy** folder




13. In your IDE, navigate to and to open **Jenkinsfile.txt** in your **labs/08/destroy** folder and copy the contents into your new github file. Then commit the changes..




14. Switch back to Jenkins and **Build** the pipeline

15. This Jenkinsfile mandates that approval must be granted for the deletion to proceed.

16. Click on the pipeline and under **Builds**, select the running Terraform Pipeline Destroy job and select **Console Output**..



17. The run is waiting for approval to continue...



18. Click on **Yes** to confirm the deletion

19. The destruction should now proceed. Switch to **S3** to verify the deletion of your test bucket.

20. Delete the Jenkins vm and its associated networking by running the following script in **labs/08**

cleanup.sh

***** Congratulations, you have completed this lab *****

*****Destroy your Github repository at your own discretion*****

Copyright

© 2026 QA Michael Coulling-Green. All rights reserved. These lab materials are provided as part of an authorised training course. Course attendees may reuse these materials for their own personal learning and reference outside of the training session. Unauthorised copying, redistribution, publication, or use of these materials to deliver training is prohibited without prior written permission from the author.