

## ✓ Handling duplicate, missing, or invalid data

### About the data

In this notebook, we will use daily weather data that was taken from the [National Centers for Environmental Information \(NCEI\) API](#) and altered to introduce many common problems faced when working with data.

Note: The NCEI is part of the National Oceanic and Atmospheric Administration (NOAA) and, as you can see from the URL for the API, this resource was created when the NCEI was called the NCDC. Should the URL for this resource change in the future, you can search for the NCEI weather API to find the updated one.

### Background on the data

Data meanings:

- PRCP : precipitation in millimeters
- SNOW : snowfall in millimeters
- SNWD : snow depth in millimeters
- TMAX : maximum daily temperature in Celsius
- TMIN : minimum daily temperature in Celsius
- TOBS : temperature at time of observation in Celsius
- WESF : water equivalent of snow in millimeters

Some important facts to get our bearings:

- According to the National Weather Service, the coldest temperature ever recorded in Central Park was -15°F (-26.1°C) on February 9, 1934: [source](#)
- The temperature of the Sun's photosphere is approximately 5,505°C: [source](#)

## ✓ Setup

We need to import `pandas` and read the long format data to get started:

```
1 import pandas as p
2
3 df = p.read_csv('/content/dirty_data.csv')
```

## ✓ Finding problematic data

A good first step is to look at some rows:

```
1 df.head()
```

	date	station	PRCP	SNOW	SNWD	TMAX	TMIN	TOBS	WESF	inc1er
0	2018-01-01T00:00:00	?	0.0	0.0	-inf	5505.0	-40.0	NaN	NaN	
1	2018-01-01T00:00:00	?	0.0	0.0	-inf	5505.0	-40.0	NaN	NaN	
2	2018-01-01T00:00:00	?	0.0	0.0	-inf	5505.0	-40.0	NaN	NaN	
3	2018-01-01T00:00:00	?	0.0	0.0	-inf	5505.0	-40.0	NaN	NaN	

Looking at summary statistics can reveal strange or missing values:

```
1 df.describe()
```

```
/usr/local/lib/python3.10/dist-packages/numpy/lib/function_base.py:4655: RuntimeWarni
diff_b_a = subtract(b, a)
```

	PRCP	SNOW	SNWD	TMAX	TMIN	TOBS	WESF
count	765.000000	577.000000	577.0	765.000000	765.000000	398.000000	11.000000
mean	5.360392	4.202773	NaN	2649.175294	-15.914379	8.632161	16.290909
std	10.002138	25.086077	NaN	2744.156281	24.242849	9.815054	9.489832
min	0.000000	0.000000	-inf	-11.700000	-40.000000	-16.100000	1.800000
25%	0.000000	0.000000	NaN	13.300000	-40.000000	0.150000	8.600000
50%	0.000000	0.000000	NaN	32.800000	-11.100000	8.300000	19.300000
75%	5.800000	0.000000	NaN	5505.000000	6.700000	18.300000	24.900000
max	61.700000	229.000000	inf	5505.000000	23.900000	26.100000	28.700000

The info() method can pinpoint missing values and wrong data types:

```
1 df.info()

<class 'pandas.core.frame.DataFrame'>
RangeIndex: 765 entries, 0 to 764
Data columns (total 10 columns):
#   Column                Non-Null Count  Dtype
---  -
0   date                  765 non-null   object
1   station               765 non-null   object
2   PRCP                  765 non-null   float64
3   SNOW                  577 non-null   float64
4   SNWD                  577 non-null   float64
5   TMAX                  765 non-null   float64
6   TMIN                  765 non-null   float64
7   TOBS                  398 non-null   float64
8   WESF                  11 non-null    float64
9   inclement_weather    408 non-null   object
dtypes: float64(7), object(3)
memory usage: 59.9+ KB
```

We can use pd.isnull() / pd.isna() or the isna() / isnull() method of the series to find nulls:

```
1 contain_nulls = df[
2     df.SNOW.isnull() | df.SNWD.isna()\
3     | p.isnull(df.TOBS) | p.isna(df.WESF)\
4     | df.inclement_weather.isna()
5 ]
6 contain_nulls.shape[0]

765

1 contain_nulls.head(10)
```

	date	station	PRCP	SNOW	SNWD	TMAX	TMIN	TOBS	WESF	incle
0	2018-01-01T00:00:00	?	0.0	0.0	-inf	5505.0	-40.0	NaN	NaN	
1	2018-01-01T00:00:00	?	0.0	0.0	-inf	5505.0	-40.0	NaN	NaN	
2	2018-01-01T00:00:00	?	0.0	0.0	-inf	5505.0	-40.0	NaN	NaN	
3	2018-01-02T00:00:00	GHCND:USC00280907	0.0	0.0	-inf	-8.3	-16.1	-12.2	NaN	
4	2018-01-03T00:00:00	GHCND:USC00280907	0.0	0.0	-inf	-4.4	-13.9	-13.3	NaN	
5	2018-01-03T00:00:00	GHCND:USC00280907	0.0	0.0	-inf	-4.4	-13.9	-13.3	NaN	
6	2018-01-03T00:00:00	GHCND:USC00280907	0.0	0.0	-inf	-4.4	-13.9	-13.3	NaN	

Note that we can't check if we have NaN like this:

```
1 df[df.inclement_weather == 'NaN'].shape[0]

0
```

This is because it is actually `np.nan`. However, notice this also doesn't work:

```
1 import numpy as ny
2 df[df.increment_weather == ny.nan].shape[0]

0
```

We have to use one of the methods discussed earlier for this to work:

```
1 df[df.increment_weather.isna()].shape[0]

357
```

We can find `-inf / inf` by comparing to `-np.inf / np.inf`:

```
1 df[df.SNWD.isin([-ny.inf, ny.inf])].shape[0]

577
```

Rather than do this for each column, we can write a function that will use a [dictionary comprehension](#) to check all the columns for us:

```
1 import numpy as ny
2
3 def get_inf_count(df):
4     """Find the number of inf/-inf values per column in the dataframe"""
5     return {
6         col : df[df[col].isin([ny.inf, -ny.inf])].shape[0] for col in df.columns
7     }
8
9 get_inf_count(df)

{'date': 0,
 'station': 0,
 'PRCP': 0,
 'SNOW': 0,
 'SNWD': 577,
 'TMAX': 0,
 'TMIN': 0,
 'TOBS': 0,
 'WESF': 0,
 'increment_weather': 0}
```

Before we can decide how to handle the infinite values of snow depth, we should look at the summary statistics for snowfall which form a big part in determining the snow depth:

```
1 p.DataFrame({
2     'ny.inf Snow Depth': df[df.SNWD == ny.inf].SNOW.describe(),
3     '-ny.inf Snow Depth': df[df.SNWD == -ny.inf].SNOW.describe()
4 }).T
```

	count	mean	std	min	25%	50%	75%	max
<b>ny.inf Snow Depth</b>	24.0	101.041667	74.498018	13.0	25.0	120.5	152.0	229.0
<b>-ny.inf Snow Depth</b>	553.0	0.000000	0.000000	0.0	0.0	0.0	0.0	0.0

Let's now look into the `date` and `station` columns. We saw the `?` for `station` earlier, so we know that was the other unique value. However, we see that some dates are present 8 times in the data and we only have 324 days meaning we are also missing days:

```
1 df.describe(include='object')
```

	date	station	increment_weather
<b>count</b>	765	765	408
<b>unique</b>	324	2	2
<b>top</b>	2018-07-05T00:00:00	GHCND:USC00280907	False
<b>freq</b>	8	398	384

We can use the `duplicated()` method to find duplicate rows:

```
1 df[df.duplicated()].shape[0]

284
```

The default for `keep` is `first` meaning it won't show the first row that the duplicated data was seen in; we can pass in `False` to see it though:

```
1 df[df.duplicated(keep=False)].shape[0]

482
```

We can also specify the columns to use:

```
1 df[df.duplicated(['date', 'station'])].shape[0]

284
```

Let's look at a few duplicates. Just in the few values we see here, we know that the top 4 are actually in the data 6 times because by default we aren't seeing their first occurrence:

```
1 df[df.duplicated()].head()
```

	date	station	PRCP	SNOW	SNWD	TMAX	TMIN	TOBS	WESF	incle
1	2018-01-01T00:00:00	?	0.0	0.0	-inf	5505.0	-40.0	NaN	NaN	
2	2018-01-01T00:00:00	?	0.0	0.0	-inf	5505.0	-40.0	NaN	NaN	
5	2018-01-03T00:00:00	GHCND:USC00280907	0.0	0.0	-inf	-4.4	-13.9	-13.3	NaN	
6	2018-01-03T00:00:00	GHCND:USC00280907	0.0	0.0	-inf	-4.4	-13.9	-13.3	NaN	

## ✓ Mitigating Issues

### Handling duplicated data

Since we know we have NY weather data and noticed we only had two entries for `station`, we may decide to drop the `station` column because we are only interested in the weather data. However, when dealing with duplicate data, we need to think of the ramifications of removing it. Notice we only have data for the `WESF` column when the station is `?`:

```
1 df[df.WESF.notna()].station.unique()

array(['?'], dtype=object)
```

If we determine it won't impact our analysis, we can use `drop_duplicates()` to remove them:

```
1 # save this information for later
2 station_qm_wesf = df[df.station == '?'].WESF
3
4 # sort ? to the bottom
5 df.sort_values('station', ascending=False, inplace=True)
6
7 # drop duplicates based on the date column keeping the first occurrence
8 # which will be the valid station if it has data
9 df_deduped = df.drop_duplicates('date').drop(
10     # remove the station column because we are done with it
11     # and WESF because we need to replace it later
12     columns=['station', 'WESF']
13 ).sort_values('date').assign( # sort by the date
14     # add back the WESF column which will be properly matched because of the index
15     WESF=station_qm_wesf
16 )
17
18 df_deduped.shape

(324, 9)
```

Check out the 4th row, we have `WESF` in the correct spot thanks to the index:

```
1 df_deduped.head()
```

	date	PRCP	SNOW	SNWD	TMAX	TMIN	TOBS	inclement_weather	WESF
0	2018-01-01T00:00:00	0.0	0.0	-inf	5505.0	-40.0	NaN	NaN	NaN
3	2018-01-02T00:00:00	0.0	0.0	-inf	-8.3	-16.1	-12.2	False	NaN
6	2018-01-03T00:00:00	0.0	0.0	-inf	-4.4	-13.9	-13.3	False	NaN
~	2018-01-	00.0	000.0	-inf	5505.0	-40.0	NaN	True	10.0

## ✓ Dealing with nulls

We could drop nulls, replace them with some arbitrary value, or impute them using the surrounding data. Each of these options may have ramifications, so we must choose wisely.

We can use `dropna()` to drop rows where any column has a null value. The default options leave us without data:

```
1 df_deduped.dropna().shape
(0, 9)
```

If we pass `how='all'`, we can choose to only drop rows where everything is null, but this removes nothing:

```
1 df_deduped.dropna(how='all').shape
(324, 9)
```

We can use just a subset of columns to determine what to drop with the `subset` argument:

```
1 df_deduped.dropna(
2     how='all', subset=['inclement_weather', 'SNOW', 'SNWD']
3 ).shape
(293, 9)
```

This can also be performed along columns, and we can also require a certain number of null values before we drop the data:

```
1 df_deduped.dropna(axis='columns', thresh=df_deduped.shape[0]*.75).columns
Index(['date', 'PRCP', 'SNOW', 'SNWD', 'TMAX', 'TMIN', 'TOBS',
      'inclement_weather'],
      dtype='object')
```

We can choose to fill in the null values instead with `fillna()`:

```
1 df_deduped.loc[:, 'WESF'].fillna(0, inplace=True)
2 df_deduped.head()
```

	date	PRCP	SNOW	SNWD	TMAX	TMIN	TOBS	inclement_weather	WESF
0	2018-01-01T00:00:00	0.0	0.0	-inf	5505.0	-40.0	NaN	NaN	0.0
3	2018-01-02T00:00:00	0.0	0.0	-inf	-8.3	-16.1	-12.2	False	0.0
6	2018-01-03T00:00:00	0.0	0.0	-inf	-4.4	-13.9	-13.3	False	0.0
~	2018-01-	00.0	000.0	-inf	5505.0	-40.0	NaN	True	10.0

At this point we have done every we can without distorting the data. We know that we are missing dates, but if we reindex, we don't know how to fill in the NaN data. With the weather data, we can't assume because it snowed one day that it will snow the next or that the temperature will be the same. For this reason, note that the next few examples are just for illustrative purposes only—just because we can do something doesn't mean we should.

That being said, let's try to address some of remaining issues with the temperature data. We know that when `TMAX` is the temperature of the Sun, it must be because there was no measured value, so let's replace it with `NaN` and then we will make an assumption that the temperature won't change drastically day-to-day. Note that this is actually a big assumption, but it will allow us to understand how `fillna()` works when we provide a strategy through the `method` parameter. We will also do this for `TMIN` which currently uses -40°C for its placeholder when we know that the coldest temperature ever recorded in NYC was -15°F (-26.1°C) on February 9, 1934.

The `fillna()` method gives us 2 options for the method parameter:

- 'ffill' to forward fill
- 'bfill' to back fill

Note that 'nearest' is missing because we are not reindexing.

Here, we will use 'ffill' to show how this works:

```
1 df_deduped.assign(
2     TMAX=lambda x: x.TMAX.replace(5505, np.nan).fillna(method='ffill'),
3     TMIN=lambda x: x.TMIN.replace(-40, np.nan).fillna(method='ffill')
4 ).head()
```

	date	PRCP	SNOW	SNWD	TMAX	TMIN	TOBS	inclement_weather	WESF
0	2018-01-01T00:00:00	0.0	0.0	-inf	NaN	NaN	NaN	NaN	0.0
3	2018-01-02T00:00:00	0.0	0.0	-inf	-8.3	-16.1	-12.2	False	0.0
6	2018-01-03T00:00:00	0.0	0.0	-inf	-4.4	-13.9	-13.3	False	0.0
~	2018-01-	0.0	0.0	-inf	-4.4	-13.9	-13.3	False	0.0

We can use `np.nan_to_num()` to turn `np.nan` into 0 and `-np.inf` / `np.inf` into large negative or positive finite numbers:

```
1 df_deduped.assign(
2     SNWD=lambda x: np.nan_to_num(x.SNWD)
3 ).head()
```

	date	PRCP	SNOW	SNWD	TMAX	TMIN	TOBS	inclement_weather	WESF
0	2018-01-01T00:00:00	0.0	0.0	-1.797693e+308	5505.0	-40.0	NaN	NaN	0
3	2018-01-02T00:00:00	0.0	0.0	-1.797693e+308	-8.3	-16.1	-12.2	False	0
6	2018-01-03T00:00:00	0.0	0.0	-1.797693e+308	-4.4	-13.9	-13.3	False	0
~	2018-01-	0.0	0.0	-1.797693e+308	-4.4	-13.9	-13.3	False	0

We can couple `fillna()` with other types of calculations for interpolation. Here we replace missing values of `TMAX` with the median of all `TMAX` values, `TMIN` with the median of all `TMIN` values, and `TOBS` to the average of the `TMAX` and `TMIN` values. Since we place `TOBS` last, we have access to the imputed values for `TMIN` and `TMAX` in the calculation. **WARNING: the text has a typo and fills in `TMAX` with `TMIN`'s median, the below is correct.:**

```
1 df_deduped.assign(
2     TMAX=lambda x: x.TMAX.replace(5505, np.nan).fillna(x.TMAX.median()),
3     TMIN=lambda x: x.TMIN.replace(-40, np.nan).fillna(x.TMIN.median()),
4     # average of TMAX and TMIN
5     TOBS=lambda x: x.TOBS.fillna((x.TMAX + x.TMIN) / 2)
6 ).head()
```

	date	PRCP	SNOW	SNWD	TMAX	TMIN	TOBS	inclement_weather	WESF
0	2018-01-01T00:00:00	0.0	0.0	-inf	22.8	0.0	11.4	NaN	0.0
3	2018-01-02T00:00:00	0.0	0.0	-inf	-8.3	-16.1	-12.2	False	0.0
6	2018-01-03T00:00:00	0.0	0.0	-inf	-4.4	-13.9	-13.3	False	0.0
~	2018-01-	0.0	0.0	-inf	-4.4	-13.9	-13.3	False	0.0

We can also use `apply()` for running the same calculation across columns. For example, let's fill all missing values with their rolling 7 day median of their values, setting the number of periods required for the calculation to 0 to ensure we don't introduce more extra NaN values. (Rolling calculations will be covered in [chapter 4](#).) We need to set the `date` column as the index so `apply()` doesn't try to take the rolling 7 day median of the date:

```

1 df_deduped.assign(
2     # make TMAX and TMIN NaN where appropriate
3     TMAX=lambda x: x.TMAX.replace(5505, ny.nan),
4     TMIN=lambda x: x.TMIN.replace(-40, ny.nan)
5 ).set_index('date').apply(
6     # rolling calculations will be covered in chapter 4, this is a rolling 7 day median
7     # we set min_periods (# of periods required for calculation) to 0 so we always get a result
8     lambda x: x.fillna(x.rolling(7, min_periods=0).median())
9 ).head(10)

```

	PRCP	SNOW	SNWD	TMAX	TMIN	TOBS	inclement_weather	WESF
date								
2018-01-01T00:00:00	0.0	0.0	-inf	NaN	NaN	NaN	NaN	0.0
2018-01-02T00:00:00	0.0	0.0	-inf	-8.30	-16.1	-12.20	False	0.0
2018-01-03T00:00:00	0.0	0.0	-inf	-4.40	-13.9	-13.30	False	0.0
2018-01-04T00:00:00	20.6	229.0	inf	-6.35	-15.0	-12.75	True	19.3
2018-01-05T00:00:00	14.2	127.0	inf	-4.40	-13.9	-13.90	True	0.0
2018-01-06T00:00:00	0.0	0.0	-inf	-10.00	-15.6	-15.00	False	0.0
2018-01-07T00:00:00	0.0	0.0	-inf	-11.70	-17.2	-16.10	False	0.0
2018-01-08T00:00:00	0.0	0.0	-inf	-7.80	-16.70	-8.30	False	0.0

The last strategy we could try is interpolation with the `interpolate()` method. We specify the `method` parameter with the interpolation strategy to use. There are many options, but we will stick with the default of `'linear'`, which will treat values as evenly spaced and place missing values in the middle of existing ones. We have some missing data, so we will reindex first. Look at January 9th, which we didn't have before—the values for `TMAX`, `TMIN`, and `TOBS` are the average of values the day prior (January 8th) and the day after (January 10th):

```

1 df_deduped.assign(
2     # make TMAX and TMIN NaN where appropriate
3     TMAX=lambda x: x.TMAX.replace(5505, ny.nan),
4     TMIN=lambda x: x.TMIN.replace(-40, ny.nan),
5     date=lambda x: p.to_datetime(x.date)
6 ).set_index('date').reindex(
7     p.date_range('2018-01-01', '2018-12-31', freq='D')
8 ).apply(
9     lambda x: x.interpolate()
10 ).head(10)

```



	PRCP	SNOW	SNWD	TMAX	TMIN	TOBS	inclement_weather	WESF
date								
2018-01-01	0.0	0.0	-inf	NaN	NaN	NaN	NaN	0.0
2018-01-02	0.0	0.0	-inf	-8.3	-16.10	-12.20	False	0.0
2018-01-03	0.0	0.0	-inf	-4.4	-13.90	-13.30	False	0.0
2018-01-04	20.6	229.0	inf	-4.4	-13.90	-13.60	True	19.3
2018-01-05	14.2	127.0	inf	-4.4	-13.90	-13.90	True	0.0
2018-01-06	0.0	0.0	-inf	-10.0	-15.60	-15.00	False	0.0
2018-01-07	0.0	0.0	-inf	-11.7	-17.20	-16.10	False	0.0
2018-01-08	0.0	0.0	-inf	-7.8	-16.70	-8.30	False	0.0
2018-01-09	0.0	0.0	-inf	-1.4	-12.25	-8.05	NaN	0.0
2018-01-10	0.0	0.0	-inf	5.0	-7.80	-7.80	False	0.0