

## ✓ Introduction to Seaborn

---

**Name:** Cuadra, Audrick Zander G.

**Section:** CPE22S3

**Date:** March 30, 2024

**Submitted to:** Engr. Roman Richard

---

## About the Data

In this notebook, we will be working with 2 datasets:

- Facebook's stock price throughout 2018 (obtained using the `stock_analysis` [package](#))
- Earthquake data from September 18, 2018 - October 13, 2018 (obtained from the US Geological Survey (USGS) using the [USGS API](#))

## Setup

```
1 %matplotlib inline
2 import matplotlib.pyplot as plt
3 import numpy as np
4 import seaborn as sns
5 import pandas as pd
6
7 fb = pd.read_csv(
8     '/content/fb_stock_prices_2018.csv', index_col='date', parse_dates=True
9 )
10
11 quakes = pd.read_csv('/content/earthquakes.csv')
```

## ✓ Categorical data

A [7.5 magnitude earthquake on September 28, 2018 near Palu, Indonesia caused a devastating tsunami afterwards](#). Let's take a look at some visualizations to understand what `magTypes` are used in Indonesia, the range of magnitudes there, and how many of the earthquakes are accompanied by a tsunami.

```

1 quakes.assign(
2     time=lambda x: p.to_datetime(x.time, unit='ms')
3 ).set_index('time').loc['2018-09-28'].query(
4     "parsed_place == 'Indonesia' and tsunami == 1 and mag == 7.5"
5 )

```

	mag	magType	place	tsunami	parsed_place
time					
2018-09-28 10:02:43.480	7.5	mw	78km N of Palu, Indonesia	1	Indonesia

## ✓ stripplot()


The `stripplot()` function helps us visualize categorical data on one axis and numerical data on the other. We also now have the option of coloring our points using a column of our data (with the `hue` parameter). Using a strip plot, we can see points for each earthquake that was measured with a given `magType` and what its magnitude was; however, it isn't too easy to see density of the points due to overlap

```

1 sns.stripplot(
2     x='magType',
3     y='mag',
4     hue='tsunami',
5     data=quakes.query('parsed_place == "Indonesia"')
6 )

```

&lt;Axes: xlabel='magType', ylabel='mag'&gt;




## ✓ swarmplot()

The bee swarm plot helps address this issue by keeping the points from overlapping. Notice how many more points we can see for the blue section of the `mb` `magType`:

```
1 sns.swarmplot(
2     x='magType',
3     y='mag',
4     hue='tsunami',
5     data=quakes.query('parsed_place == "Indonesia"')
6 )
```

```
<Axes: xlabel='magType', ylabel='mag'>
```

```
/usr/local/lib/python3.10/dist-packages/seaborn/categorical.py:3398: UserWarning: 10.2%  
warnings.warn(msg, UserWarning)
```




## ✓ Correlations and Heatmaps

heatmap()

An easier way to create correlation matrix is to use seaborn:

```
1 sbn.heatmap(  
2     fb.sort_index().assign(  
3     log_volume=ny.log(fb.volume),  
4     max_abs_change=fb.high - fb.low  
5 ).corr(),  
6     annot=True, center=0  
7 )
```

&lt;Axes: &gt;




## ✓ pairplot()

The pair plot is seaborn's answer to the scatter matrix we saw in the pandas subplotting notebook:

```
1 sbn.pairplot(fb)
```


<seaborn.axisgrid.PairGrid at 0x7e6526d19ba0>



Just as with `pandas` we can specify what to show along the diagonal; however, `seaborn` also allows us to color the data based on another column (or other data with the same shape):

```
1 sbn.pairplot(  
2     fb.assign(quarter=lambda x: x.index.quarter),  
3     diag_kind='kde',  
4     hue='quarter'  
5 )
```

&lt;seaborn.axisgrid.PairGrid at 0x7e64e93d2d10&gt;






## ✓ jointplot()

The joint plot allows us to visualize the relationship between two variables, like a scatter plot. However, we get the added benefit of being able to visualize their distributions at the same time (as a histogram or KDE). The default options give us a scatter plot in the center and histograms on the sides:

```
1 sbn.jointplot(  
2     x='volume',  
3     y='max_abs_change',  
4     data=fb.assign(  
5         volume=ny.log(fb.volume),  
6         max_abs_change=fb.high - fb.low  
7     )  
8 )
```


&lt;seaborn.axisgrid.JointGrid at 0x7e6527b66740&gt;



By changing the `kind` argument, we can change how the center of the plot is displayed. For example, we can pass `kind='hex'` for hexbins:

```
1 sbn.jointplot(  
2     x='volume',  
3     y='max_abs_change',  
4     kind='hex',  
5     data=fb.assign(  
6         volume=ny.log(fb.volume),  
7         max_abs_change=fb.high - fb.low  
8     )  
9 )
```

&lt;seaborn.axisgrid.JointGrid at 0x7e64e0104490&gt;




If we specify `kind='reg'` instead, we get a regression line in the center and KDEs on the sides:

```

1 sbn.jointplot(
2     x='volume',
3     y='max_abs_change',
4     kind='reg',
5     data=fb.assign(
6         volume=ny.log(fb.volume),
7         max_abs_change=fb.high - fb.low
8     )
9 )

```


<seaborn.axisgrid.JointGrid at 0x7e64dfe3bf10>



If we pass `kind='resid'`, we get the residuals from the aforementioned regression:

```
1 sbn.jointplot(
2     x='volume',
3     y='max_abs_change',
4     kind='resid',
5     data=fb.assign(
6         volume=ny.log(fb.volume),
7         max_abs_change=fb.high - fb.low
8     )
9 )
```


<seaborn.axisgrid.JointGrid at 0x7e64f0890550>



Finally, if we pass `kind='kde'`, we get a contour plot of the joint density estimate with KDEs along the sides:

```
1 sbn.jointplot(
2     x='volume',
3     y='max_abs_change',
4     kind='kde',
5     data=fb.assign(
6         volume=ny.log(fb.volume),
7         max_abs_change=fb.high - fb.low
8     )
9 )
```

<seaborn.axisgrid.JointGrid at 0x7e64e2eef190>



## ✓ Regression plots

We are going to use `seaborn` to visualize a linear regression between the log of the volume traded in Facebook stock and the maximum absolute daily change (daily high stock price - daily low stock price). To do so, we first need to isolate this data:

```
1 fb_reg_data = fb.assign(
2     volume=ny.log(fb.volume),
3     max_abs_change=fb.high - fb.low
4 ).iloc[:, -2:]
```

Since we want to visualize each column as the regressor, we need to look at permutations of their order. Permutations and combinations (among other things) are made easy in Python with

`itertools`, so let's import it:

```
1 import itertools
```

`itertools` gives us efficient iterators. Iterators are objects that we loop over, exhausting them. This is an iterator from `itertools`; notice how the second loop doesn't do anything:

```
1 iterator = itertools.repeat("I'm an iterator", 1)
2
3 for i in iterator:
4     print(f'-->{i}')
5 print('This printed once because the iterator has been exhausted')
6 for i in iterator:
7     print(f'-->{i}')

-->I'm an iterator
This printed once because the iterator has been exhausted
```

Iterables are objects that can be iterated over. When entering a loop, an iterator is made from the iterable to handle the iteration. Iterators are iterables, but not all iterables are iterators. A list is an iterable. If we turn that iterator into an iterable (a list in this case), the second loop runs

```
1 iterable = list(itertools.repeat("I'm an iterable", 1))
2
3 for i in iterable:
4     print(f'-->{i}')
5 print('This prints again because it\'s an iterable:')
6 for i in iterable:
7     print(f'-->{i}')


-->I'm an iterable
This prints again because it's an iterable:
-->I'm an iterable
```

The `reg_resid_plots()` function from the `reg_resid_plot.py` module in this folder uses `regplot()` and `residplot()` from `seaborn` along with `itertools` to plot the regression and residuals side-by-side:

```
1 import itertools
2 import matplotlib.pyplot as plt
3 import seaborn as sns
4
5 def reg_resid_plots(data):
6     """
7     Using seaborn, plot the regression and residuals
8     plots side-by-side for every permutation of 2 columns
9     in the data.
10    Parameters:
11    - data: A pandas DataFrame
12    Returns:
13    A matplotlib Figure object.
14    """
15    num_cols = data.shape[1]
16    permutation_count = num_cols * (num_cols - 1)
17    fig, ax = plt.subplots(permutation_count, 2, figsize=(15, 8))
18    for (x, y), axes, color in zip(
19        itertools.permutations(data.columns, 2),
20        ax,
21        itertools.cycle(['royalblue', 'darkorange']))
22    ):
23        for subplot, func in zip(axes, (sns.regplot, sns.residplot)):
24            func(x=x, y=y, data=data, ax=subplot, color=color)
25    plt.close()
26    return fig

1 reg_resid_plots(fb_reg_data)
```






We can use `lmplot()` to split our regression across subsets of our data. For example, we can perform a regression per quarter on the Facebook stock data:

```

1 sns.lmplot(
2     x='volume',
3     y='max_abs_change',
4     data=fb.assign(
5         volume=ny.log(fb.volume),
6         max_abs_change=fb.high - fb.low,
7         quarter=lambda x: x.index.quarter
8     ),
9     col='quarter'
10 )

```

<seaborn.axisgrid.FacetGrid at 0x7e64dfc6cc70>



## ✓ Distributions

Seaborn provides some new plot types for visualizing distributions in addition to its own versions of the plot types we discussed in chapter 5 ([in this notebook](#)).

### boxenplot()

The boxenplot is a box plot that shows additional quantiles:


```

1 sns.boxenplot(
2     x='magType', y='mag', data=quakes[['magType', 'mag']]
3 )
4 plt.suptitle('Comparing earthquake magnitude by magType')

```

```
Text(0.5, 0.98, 'Comparing earthquake magnitude by magType')
```

## Comparing earthquake magnitude by magType



## ✓ violinplot()

Box plots lose some information about the distribution, so we can use violin plots which combine box plots and KDEs:

```
1 fig, axes = mpl.subplots(figsize=(10, 5))
2 sns.violinplot(
3     x='magType', y='mag', data=quakes[['magType', 'mag']],
4     ax=axes, scale='width', # all violins have same width
5     palette=['midnightblue', 'red', 'brown', 'turquoise',
6             'black', 'palegoldenrod', 'purple', 'blue',
7             'cyan', 'green']
8 )
9 mpl.suptitle('Comparing earthquake magnitude by magType')
```

```
<ipython-input-27-56441e1ca9d1>:2: FutureWarning:
```


Passing `palette` without assigning `hue` is deprecated and will be removed in v0.14.0.

```
sns.violinplot(
<ipython-input-27-56441e1ca9d1>:2: FutureWarning:
```

The `scale` parameter has been renamed and will be removed in v0.15.0. Pass `density\_norm`

```
sns.violinplot(
Text(0.5, 0.98, 'Comparing earthquake magnitude by magType')
```

Comparing earthquake magnitude by magType



## ✓ Faceting

We can create subplots across subsets of our data by faceting. First, we create a `FacetGrid` specifying how to layout the plots (which categorical column goes along the rows and which one along the columns). Then, we call the `map()` method of the `FacetGrid` and pass in the plotting function we want to use (along with any additional arguments).

Let's make histograms showing the distribution of earthquake magnitude in California, Alaska, and Hawaii faceted by `magType` and `parse_places`:

```

1 g = sns.FacetGrid(
2     quakes[
3 (quakes.parsed_place.isin([
4 'California', 'Alaska', 'Hawaii'
5 ]))\
6 & (quakes.magType.isin(['ml', 'md']))
7 ],
8 row='magType',
9 col='parsed_place'
10 )
11 g = g.map(mpl.hist, 'mag')

```

