

## [0] ĐỌC CODE TRƯỚC (bắt buộc)

bash

```
find . -type f \( -name "*.js" -o -name "*.ts" \) | grep -v node_modules | sort
cat package.json
cat src/index.js 2>/dev/null || cat src/app.js 2>/dev/null || cat src/server.js
ls src/routes/ && cat src/routes/*.js 2>/dev/null | head -200
cat src/controllers/*.controller.js 2>/dev/null | head -200
cat src/config/db.js 2>/dev/null || cat src/database/connection.js
cat src/utlis/response.js 2>/dev/null || cat src/helpers/response.js
cat src/middlewares/auth.middleware.js 2>/dev/null || cat src/middlewares/auth.js
```

→ Ghi nhớ: framework, ORM/raw-query, response format, auth middleware, file naming convention.

## [1] CONVENTIONS (áp dụng toàn bộ)

- **Response:** {success:bool, data?, message?, pagination?}
- **Pagination:** params page(def:1) + limit(def:20) → {current\_page, per\_page, total\_items, total\_pages}
- **Auth:** Bearer JWT → req.user = {user\_id, roles:string[]}
- **Seller store:** SELECT store\_id FROM user\_stores WHERE user\_id=@uid AND store\_member\_role='OWNER' AND is\_active=1
- **Soft delete:** set deleted\_at=SYSUTCDATETIME() hoặc status='INACTIVE'
- **SQL Server:** dùng @param, OFFSET x ROWS FETCH NEXT y ROWS ONLY
- **Comment code:** tối thiểu — chỉ comment logic không tự giải thích được

## GROUP 11: Orders – Seller (38–41)

**Auth:** Seller | Lấy store\_id từ token | Verify order.store\_id = @seller\_store\_id

### 38 · List Store Orders GET /api/v1/seller/orders

Params: status?, page, limit

sql

```
SELECT o.order_id, o.order_code, o.order_status, o.total_amount, o.created_at,
       u.full_name AS customer_name
FROM orders o JOIN users u ON o.customer_id=u.user_id
WHERE o.store_id=@sid [AND o.order_status=@s]
ORDER BY o.created_at DESC
```

→ 200: {orders[], pagination}

### 39 · Get Store Order Detail **GET** /api/v1/seller/orders/:id

- Verify `order.store_id = @sid`
- JOIN: order\_items, users (customer), shipments (LEFT)

→ **200**: {...order, items[], customer{full\_name,phone}, shipment?} → **403** | **404**

### 40 · Update Order Status **PATCH** /api/v1/orders/:id/status

Body: {new\_status, change\_note?}

- Verify `order.store_id = @sid`
- Allowed transitions:

| current    | → new         |
|------------|---------------|
| PENDING    | CONFIRMED     |
| CONFIRMED  | PROCESSING    |
| PROCESSING | READY_TO_SHIP |

- Không cho Seller cancel hoặc nhảy status
- INSERT order\_status\_histories
- Nếu `new_status='READY_TO_SHIP'`: INSERT shipments (`order_id=@oid`, `status='PENDING_ASSIGNMENT'`)

→ **200**: {order\_id, order\_status} | **400** transition lỗi | **403** | **404**

### 41 · Get Order Status History **GET** /api/v1/orders/:id/history | Seller, Admin

- Seller: verify `order.store_id = @sid`; Admin: xem tất cả

sql

```
SELECT h.*, u.full_name AS changed_by_name
FROM order_status_histories h
LEFT JOIN users u ON h.changed_by_user_id=u.user_id
WHERE h.order_id=@id ORDER BY h.created_at ASC
```

→ **200**: {order\_id, history:[{previous\_status, new\_status, changed\_by\_name?, change\_note, created\_at}]}

#### CHECKLIST:

- [ ] Tất cả 4 route (38-41) đăng ký đúng index router.

- [ ] Auth middleware đúng role ('Seller' cho 38-40; 'Seller' hoặc 'Admin' cho 41).
- [ ] Phải xác minh đúng đơn hàng thuộc về cửa hàng của Seller đang request.
- [ ] Trạng thái chuyển đổi (Status transition) BẮT BUỘC tuân thủ chặt chẽ luồng (PENDING -> CONFIRMED -> PROCESSING -> READY\_TO\_SHIP) ở API 40.
- [ ] Tự động tạo shipment ở API 40 khi status là **READY\_TO\_SHIP**.
- [ ] Parameterized query.
- [ ] Response format nhất quán.