

[0] ĐỌC CODE TRƯỚC (bắt buộc)

bash

```
find . -type f \( -name "*.js" -o -name "*.ts" \) | grep -v node_modules | sort
cat package.json
cat src/index.js 2>/dev/null || cat src/app.js 2>/dev/null || cat src/server.js
ls src/routes/ && cat src/routes/*.js 2>/dev/null | head -200
cat src/controllers/*.controller.js 2>/dev/null | head -200
cat src/config/db.js 2>/dev/null || cat src/database/connection.js
cat src/utis/response.js 2>/dev/null || cat src/helpers/response.js
cat src/middlewares/auth.middleware.js 2>/dev/null || cat src/middlewares/auth.js
```

→ Ghi nhớ: framework, ORM/raw-query, response format, auth middleware, file naming convention.

[1] CONVENTIONS (áp dụng toàn bộ)

- **Response:** {success:bool, data?, message?, pagination?}
- **Pagination:** params page(def:1) + limit(def:20) → {current_page, per_page, total_items, total_pages}
- **Auth:** Bearer JWT → req.user = {user_id, roles:string[]}
- **Seller store:** SELECT store_id FROM user_stores WHERE user_id=@uid AND store_member_role='OWNER' AND is_active=1
- **Soft delete:** set deleted_at=SYSUTCDATETIME() hoặc status='INACTIVE'
- **SQL Server:** dùng @param, OFFSET x ROWS FETCH NEXT y ROWS ONLY
- **Comment code:** tối thiểu — chỉ comment logic không tự giải thích được

GROUP 15: Shipments (52–54)

52 · Track Shipment GET /api/v1/shipments/:orderId | Customer

- Verify order.customer_id = @uid

sql

```
SELECT s.shipment_id, s.tracking_code, s.shipment_status,
       s.assigned_at, s.picked_up_at, s.delivered_at, s.failed_reason
FROM shipments s JOIN orders o ON s.order_id=o.order_id
WHERE s.order_id=@oid AND o.customer_id=@uid
```

→ 200: shipment object → 404 chưa có shipment (đơn chưa READY_TO_SHIP)

53 · List Assigned Shipments GET /api/v1/shipper/shipments | Shipper

Params: `status?`, `page`, `limit`

sql

```
SELECT s.*, o.order_code, o.recipient_name, o.shipping_province
FROM shipments s JOIN orders o ON s.order_id=o.order_id
WHERE s.shipper_user_id=@uid [AND s.shipment_status=@s]
ORDER BY s.assigned_at DESC
```

→ **200**: {`shipments[]`, `pagination`}

54 · Update Shipment Status PATCH

`/api/v1/shipper/shipments/:id/status` | Shipper

Body: {`new_status`, `failed_reason?`}

- Verify `shipment.shipper_user_id = @uid`
- Allowed transitions:

current → **new**

ASSIGNED PICKED_UP

PICKED_UP SHIPPING

SHIPPING DELIVERED

SHIPPING DELIVERY_FAILED

- **DELIVERY_FAILED**: `failed_reason` bắt buộc
- Nếu **DELIVERED**: `UPDATE orders SET order_status='COMPLETED', completed_at=NOW() + INSERT status_history`
- Nếu **DELIVERY_FAILED**: `UPDATE orders SET order_status='DELIVERY_FAILED' + INSERT status_history`
- Cập nhật timestamp tương ứng: `picked_up_at`, `delivered_at`

→ **200**: {`shipment_id`, `shipment_status`} | **400** transition lỗi | **403** | **404**

CHECKLIST:

- [] Tất cả 3 route (52-54) đăng ký đúng router.
- [] Auth middleware: 'Customer' (52); 'Shipper' (53, 54).
- [] Status transition (Trạng thái chuyển đổi) ở Lô hàng (API 54) **BẮT BUỘC** tuân thủ luồng (ASSIGNED -> PICKED_UP -> SHIPPING -> DELIVERED/FAILED).
- [] Tự động cập nhật trạng thái của Bảng Đơn Hàng (Orders) dựa vào kết quả giao hàng (DELIVERED -> COMPLETED).
- [] Parameterized query.
- [] Response format nhất quán.

