

[0] ĐỌC CODE TRƯỚC (bắt buộc)

bash

```
find . -type f \( -name "*.js" -o -name "*.ts" \) | grep -v node_modules | sort
cat package.json
cat src/index.js 2>/dev/null || cat src/app.js 2>/dev/null || cat src/server.js
ls src/routes/ && cat src/routes/*.js 2>/dev/null | head -200
cat src/controllers/*.controller.js 2>/dev/null | head -200
cat src/config/db.js 2>/dev/null || cat src/database/connection.js
cat src/utis/response.js 2>/dev/null || cat src/helpers/response.js
cat src/middlewares/auth.middleware.js 2>/dev/null || cat src/middlewares/auth.js
```

→ Ghi nhớ: framework, ORM/raw-query, response format, auth middleware, file naming convention.

[1] CONVENTIONS (áp dụng toàn bộ)

- **Response:** {success:bool, data?, message?, pagination?}
- **Pagination:** params page(def:1) + limit(def:20) → {current_page, per_page, total_items, total_pages}
- **Auth:** Bearer JWT → req.user = {user_id, roles:string[]}
- **Seller store:** SELECT store_id FROM user_stores WHERE user_id=@uid AND store_member_role='OWNER' AND is_active=1
- **Soft delete:** set deleted_at=SYSDATETIME() hoặc status='INACTIVE'
- **SQL Server:** dùng @param, OFFSET x ROWS FETCH NEXT y ROWS ONLY
- **Comment code:** tối thiểu — chỉ comment logic không tự giải thích được

GROUP 8: Store (25–28)

25 · Get Store Info GET /api/v1/stores/:id | Public

sql

```
SELECT s.*, COUNT(p.product_id) AS product_count
FROM stores s
LEFT JOIN products p ON p.store_id=s.store_id AND p.status='ACTIVE' AND p.deleted_at IS NULL
WHERE s.store_id=@id AND s.status='ACTIVE' AND s.deleted_at IS NULL
GROUP BY s.store_id, ...
```

→ 200: {store_id, store_name, slug, logo_url, description, province, contact_phone, total_products, status} → 404

26 · Get My Store GET /api/v1/seller/store | Seller

sql

```
SELECT s.* FROM stores s
JOIN user_stores us ON us.store_id=s.store_id
WHERE us.user_id=@uid AND us.store_member_role='OWNER' AND us.is_active=1
```

→ **200**: full store object | **404** chưa tạo shop

27 · Create Store **POST** /api/v1/stores | Seller

Body: {store_name, description?, logo_url?, contact_email?, contact_phone?, address_line?, ward?, district?, province?}

- Check chưa có shop (query user_stores) → nếu có → **409**
- `store_code` = `SHOP-` + `nanoid(8).toUpperCase()`
- `slug` = `slugify(store_name)` + `-` + `nanoid(6)`
- `INSERT stores` → `INSERT user_stores (role='OWNER', is_active=1)`

→ **201**: store object | **409** "Bạn đã có shop"

28 · Update Store **PATCH** /api/v1/seller/store | Seller

Body (partial): {store_name?, description?, logo_url?, contact_email?, contact_phone?, address_line?, ward?, district?, province?}

- Partial update; đổi `store_name` → cập nhật slug

→ **200**: store object

CHECKLIST:

- [] Tất cả 4 route (25-28) đăng ký đúng index router.
- [] Auth middleware phân tách rõ: API 25 Công khai, API 26-28 role 'Seller'.
- [] Ràng buộc duy nhất: Mỗi người bán chỉ có tối đa 1 cửa hàng (API 27).
- [] Parameterized query (chống SQL Injection).
- [] Partial update: API 28 chỉ update những trường được gửi lên.
- [] Responseformat nhất quán.