



Evaluation of on-chip ADC installed on the X-ray SOI pixel detector

Hiroumi Matsuhashi
(University of Tokyo Bamba-lab M1)

Kouichi Hagino, Aya Bamba (UTokyo)

Ayaki Takeda, Masataka Yukumoto, Koji Mori, Yusuke Nishioka (Univ of Miyazaki)

Takeshi Tsuru, Mizuki Uenomachi, Tomonori Ikeda, Masamune Matsuda, Takuto Narita (Kyoto U)

Takaaki Tanaka(Konan Univ), Hiromasa Suzuki (ISAS/JAXA)

Ikuo Kurachi (D&S), Takayoshi Kohmura, Yusuke Uchida (TUS), Yasuo Arai (KEK)

QBI2023@Osaka University


Outline

- Introduction : Astronomy and Detector
- About XRPIX
 - . What is the XRPIX?
 - .XRPIX's current status
 - .Purpose of on-chip ADC
 - .Overview of on-chip ADC
- Evaluation
 - .Evaluation of on-chip ADC only
 - .Evaluation of XRPIX + on-chip ADC

Introduction : X-ray Astronomy and Detector

What can we see ?

X-ray Band : High Energy Star (Black Holes , Galaxy , Neutron Star ...)




Problem :

X-rays need to be observed from space




Observe X-rays using a satellite



img:jaxa

XRISM : X-ray satellite

<X-ray Detector>



1.Irradiation X-ray on Sensor layer

2.**Electron-hole** pairs occur at Sensor layer(Si)

3.Sense-nodes catch the hole
and evaluate Energy of X-ray

What is the XRPIX?

Aiming to be installed on a future X-ray satellite as X-ray Detector

X-Ray SOI-CMOS detector

- Combine CMOS circuits and high- ρ Si sensor with SOI technology

Each pixel has trigger function

- Read pixels above threshold


 fast readout time(<10 μ sec)

Energy resolution

- Require : $\Delta E < 300$ eV(@6.0 keV)


Thick Sensor Layer

- High detection efficiency for hard X-rays




XRPIX's current status

We've been researching and developing



From 計測システム研究会(武田彩希)より改変

XRPIX6E
FWHM~240 eV at 6.0 keV




KyotoU Harada

Sensor : Good spectral performance

Future task : Digitalization

Purpose of on-chip ADC

Previous XRPIX : Converts **analog signals** with external ADC




Problem : X-ray satellites require a large imaging area in a limited space

ADC mounted on XRPIX for compactness(**on-chip**)

Overview of on-chip ADC

We developed XRPIX with on-chip ADC
Then XRPIX can output digital signal



Summary of on-chip ADC
Type : Cyclic ADC
Number of bits : 14 bits
Voltage range : 0.4-1.5 V
Total Units : 16 units

Goal : Evaluate on-chip ADC performance

Evaluation Contents

Evaluation of on-chip ADC only

1. Integral non-linearity
2. Differential non-linearity
3. Noise

Evaluation of XRPIX+on-chip ADC


- 4.comparison on-chip ADC with external one.

Set Up : Evaluation of on-chip ADC


Input Ramp wave into ADC



Function Generator



Result1: Integral Non-Linearity



Input Ramp wave(100 mHz) into on-chip ADC


Ideal ADC steps one at a time

Actual ADC : Vertical **deviation occurs**

<Methods>

Fitted actual ADC outputs with **Straight line**
calculated residuals between the line and ADC outputs

<Result>




Residuals : 6 LSB(=**0.036 %**)

No effect level for resolution 300 eV



ADC Outputs
10

Result2:Differential Non-Linearity



Methods :



Histogram the number of AD outputs
Divide each histogram by the average



ADC's Requirement <0.5 LSB
Measurement : **0.4 LSB**
➡ Meets requirements

Result3:Evaluation of Noise


Methods : Inputs constant voltage into on-chip ADC




Noise width ~ 3 channel (=0.2 mV)
➡ Meets the requirements

Evaluation of XRPIX + on-chip ADC

Irradiated X-rays on XRPIX





Comparison on-chip ADC with external



➡ Successfully obtained spectra from on-chip ADC
investigate performance difference


Result4: Compared on-chip with external

FWHM of external ADC and on-chip ADC compared at each pixel



Result4: Compared on-chip with external

FWHM of external ADC and on-chip ADC compared at each pixel



Summary

<Objective>

XRPIX aims to be installed on a future X-ray satellite as detector

Its Sensor : Good spectral performance(previous work)

➡ Future task: **Digitalization**

Detector needs to be compact ➡ We developed **on-chip ADC**

<Result : Evaluation of on-chip ADC>

1. Integral Non-Linearity:**0.036 %**

2. Differential Non-Linearity:**0.4 LSB** (Requirement < 0.5 LSB)

3. Noise :**0.2 mV**

<Result : Irradiated X-Rays on XRPIX9>

We **successfully** obtained spectrum from on-chip ADC.

No crucial differences between on-chip and external